

Volume

#

R0593

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES
OF THE

INDEPENDENT RESURVEY OF

A PORTION OF THE SOUTH BOUNDARY.

AND THE

SURVEY OF A PORTION OF THE

SOUTH BOUNDARY AND OF SUBDIVISION,

TOWNSHIP 24 SOUTH, RANGE 24 EAST

RECEIVED
BUREAU OF LAND MGMT.
OFFICE

74 JUL 30 PM 12:57

Of the Salt Lake Meridian,

In the State of Utah

EXECUTED BY

Jerry L. Thomas Supervisory Cadastral Surveyor

Under special instructions dated September 22, 19 50, which provided for the surveys
included under Group Number 377, approved October 4, 1950
and assignment instructions dated April 11, 19 72.

Survey commenced April 21, 19 72

Survey completed June 30, 19 72

INDEX DIAGRAM

Township 24 South , Range 24 East ,

6	5	4	17 3	12 11 2	9 1
				10	8
7	8	9 20	16 10	11	7 12
18	17	19 16	15 15	14	5 13
19	20	21	14 22	23	24
30	29 23	28	14 27	26	25
31 4	22 32 3	21 33 2	13 34	35	36

CHAINS

T. 24 S., R. 24 E.

History of Surveys

Surveyed by Retr. or Resurveyed by

NORTH BOUNDARY

A11 C. F. Moore 1929

SOUTH BOUNDARY

E. 2½ miles	Frank E. Baxter	1894	
E. 2½ miles	James M. Lentz	1901	
E. 3 miles	Robert C. Yundt	1950	
W. 2¼ miles to W. C. of secs. 31 & 32	James M. Lentz	1901	

EAST BOUNDARY

S. 3 miles	Frank E. Baxter		
	1894		
S. 3 miles		C. F. Moore	1933-1939
N. 3 miles	C. F. Moore	1933-1939	

WEST BOUNDARY (Grand River Guide Meridian)

All E. Buettner 1880
S. 2 miles D. B. Clement 1915

SUBDIVISIONS

Secs. 24, 25, 35, & 36,
and protracted SE $\frac{1}{4}$ of
Secs. 26 & 34. Frank E. Baxter
1894
Secs. 24, 25, 35 & 36 Robert C. Yundt 1950

The following field notes are those of an independent resurvey of the south boundary of secs. 32 and 33, and the survey of the south boundary of sec. 31 and a portion of the subdivision of T. 24 S., R. 24 E., Salt Lake Meridian, Utah.

The independent resurvey and survey were executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, Special Instructions for Group 377, Utah, dated September 22, 1950, and Assignment Instructions, Group 377, Utah dated April 11, 1972.

The directions of the lines of this survey were determined by reference to true meridians established on line by altitude observations on the sun and hour angle observations on Polaris. The lines were carried forward by sustained angulation being supplemented by other numerous solar and polaris observations taken throughout the progress of the survey. All lines of this survey were run by direct method where accessible, and inaccessible lines were established by triangulation. Distances to topography on lines run by triangulation are approximately as scaled from U.S.G.S. topographic maps.

Township 24 South Ra

CHAINS

The geographic position for the southeast corner of sec. 33, T. 24 S., R. 24 E., is at Latitude 38° 40' 00" N. and Longitude 109° 16' 10" W., as scaled from U.S.G.S. quadrangle sheet Mt. Waas 3NE, Utah, dated 1954.

The magnetic declination was read at a number of stations throughout the township and the average of several readings was found to be 15° 00' East.

Independent Resurvey of a Portion
of the South Boundary,
T. 24 S., R. 24 E., Salt Lake Meridian, Utah

Superseding the Survey Executed by
J. M. Lentz, Deputy Surveyor, in 1901

Beginning at the cor. of secs. 33 and 34, on the S. bdy. of the Tp., marked by an iron post, 1 in. diam., firmly set, extending 6 ins. above the ground, and in a collar of stone, with brass cap mkd.

T24S R24E
S33| S34
S4
T25S
1950

from which

A pinon, 9 ins. diam., bears N. 3° E., 10 lks. dist., mkd. T24S R24E S34 BT.

There are no other suitable bearing trees within limits.

Thence

West, along the S. bdy. of sec. 33.

Over rough and broken land, through scattered pinon timber and a medium dense undergrowth; asc. 480 ft. over rocky NE. slope and vertical ledge; by triangulation.

- 10.00 E. rim of Fisher Mesa, bears N. and S.; end triangulation along mesa top.
- 10.40 Trail road, bears SW. and curves NW.; desc. 80 ft. over W. slope.
- 13.00 Bottom of draw, drains SW.; thence along S. slope.
- 21.10 Slope changes; desc. 30 ft. over W. slope.
- 24.20 Bottom of ravine, drains SW.; asc. 30 ft. over SE. slope.
- 39.00 Top of sandstone ledge, bears S. and curves NE.; desc. 10 ft. along gentle S. slope.
- 40.00 Point for the ¼ sec. cor. of sec. 33.

Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in

Independent Resurvey of a Portion
of the South Boundary,
T. 24 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS

the ground to bedrock, in a mound of stone, 5½ ft. base to top, with brass cap mkd.

T24S R24E
¼ S 33
1972

There are no suitable bearing trees within limits.

- 40.85 The ¼ sec. cor. of sec. 33, monumented with a sandstone, 36x18x14 ins., firmly set, projecting 20 ins. above the ground and mkd. with a cross (X) and a ¼ on the N. side, bears S. 7 lks. dist. I destroy this cor. in accordance with the Special Instructions.

Slope changes; desc. 30 ft. over SW. slope.

- 46.75 Top of small spur, slopes S.; desc. 70 ft. along gradual W. slope.

- 51.30 W. rim of Fisher Mesa, bears W. and SE.; desc. 30 ft. along rim of mesa.

- 80.00 Point for the cor. of secs. 32 and 33.

Set an iron post, 30 ins. long, 2½ ins. diam., over a cross (X) on solid sandstone, in a mound of stone, 5 ft. base to top, with brass cap mkd.

T24S R24E
S32|S33
1972

There are no suitable bearing trees within limits.

Land, rocky and broken.

Soil, rocky loam.

Timber, scattered pinon and juniper.

Undergrowth, scattered shadscale, weeds and grass.

West, along the S. bdy. of sec. 32.

Over rough and broken land, with scattered juniper and pinon timber, shadscale and grass undergrowth; along S. rim of Fisher Mesa.

- .50 Rim of mesa, bears N. 10° W. and E.; desc. 1200 ft. over vertical ledge and rocky W. slope; by triangulation.

- 28.00 Bottom of draw, drains S. 10° W.; asc. 320 ft. over rocky SE. slope; end of triangulation.

- 40.00 Point for the ¼ sec. cor. of sec. 32.

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.

T24S R24E
¼ S 32
1972

Asc. 240 ft. over rocky SE. slope.

- 55.00 Top of ascent, slopes S.; thence along steep S. slope.

Independent Resurvey of a Portion
of the South Boundary,
T. 24 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
62.00	Descent 640 ft. over steep SW. slope.
80.00	Point for the cor. of secs. 31 and 32.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T24S R24E <u>S31 S32</u> 1972 </div>
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of cor.
	Land, rough and broken. Soil, mostly rocky with some clay on W. portion. Timber, scattered juniper and pinon on E. portion. Undergrowth, scattered shadscale and grass.
Survey of a Portion of the South Boundary, T. 24 S., R. 24 E., Salt Lake Meridian, Utah	
	West, along the S. bdy. of sec. 31.
	Over broken land, with scattered juniper and pinon timber, and some scattered shadscale and grass; desc. 320 ft. over SW. slope.
23.00	Top of spur, projects SW.; desc. 180 ft. over NW. slope.
35.37	Intersect the Grand River Guide Meridian, E. bdy. of sec. 36, T. 24 S., R. 23 E.
	Point for the closing tp. cor. of Tps. 24 and 25 S., R. 24 E.
	Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 5 ft. base to top, with brass cap mkd.
	<div style="text-align: center;"> T 24 S R23E R24E S36 <u>S31 C</u> <u>S6 C</u> T 25 S 1972 </div>
	From this closing cor., the original cor. of Tps. 24 and 25 S., Rs. 23 and 24 E., bears S. 0° 12' E., 1.22 chs. dist.
	Destroy markings on the E. side of the cor. referring to R. 24 E. This cor. now functions as the cor. of Tps. 24 and 25 S., R. 23 E. only.
	Land, broken. Soil, clay and rocky loam. Timber, scattered juniper and pinon. Undergrowth, scattered shadscale and grass.

Survey of a Portion of the Subdivision,
T. 24 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	Survey of a Portion of the Subdivision, T. 24 S., R. 24 E., Salt Lake Meridian, Utah
	<p>From the cor. of secs. 13, 14, 23 and 24, monumented with an iron post, 1 in. diam., extending 10 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R24E</p> <p>S14 S13</p> <hr style="width: 50%; margin: 0 auto;"/> <p>S23 S24</p> <p>1950</p> </div> <p>N. 0° 01' W., bet. secs. 13 and 14.</p> <p>Over rough and broken land, with scattered juniper and pinon timber, and scattered shadscale, sagebrush and grass; asc. 640 ft. over SW. slope and sandstone ledge; by triangulation.</p> <p>16.00 S. rim of Sevenmile Mesa, bears E. and W.; desc. 240 ft. over broken N. slope, through thick juniper and pinon timber; end of triangulation.</p> <p>32.40 S. rim of canyon, bears NW. and SE.; desc. 240 ft. over NE. slope.</p> <p>40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 5 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R24E</p> <p>$\frac{1}{4}$</p> <p>S14 S13</p> <p>1972</p> </div> <p>There are no suitable bearing trees within limits.</p> <p>Desc. 20 ft. over NE. slope.</p> <p>42.00 Bottom of canyon, drains NW.; asc. 80 ft. over S. slope.</p> <p>46.50 W. rim of sandstone outcropping, bears SE. and N. 5° W.; along broken W. slope.</p> <p>51.00 Slope changes; desc. 250 ft. over NW. slope.</p> <p>66.00 Bottom of descent, slopes W.; asc. 40 ft. over SW. slope.</p> <p>73.00 Top of spur, slopes W.; desc. 60 ft. over NW. slope.</p> <p>80.00 Point for the cor. of secs. 11, 12, 13 and 14.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground to bedrock and in a mound of stone, 5 ft. base to top, with brass cap mkd.</p>

Survey of a Portion of the Subdivision,
T. 24 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS

T24S R24E
 $\frac{S11 | S12}{S14 | S13}$

1972

There are no suitable bearing trees within limits.

Land, broken.

Soil, exposed sandstone and rocky loam.

Timber, scrub juniper and pinon.

Undergrowth, scattered sagebrush, shadscale and grass.

From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, extending 8 ins. above ground, with brass cap mkd.

T24S
 R24E R25E
 $\frac{S12 | S7}{S13 | S18}$
 1933

from which

A pinon, 6 ins. diam., bears N. 65° E., 85 lks. dist., mkd. T24S R25E S7 BT.

A pinon, 10 ins. diam., bears S. 37° E., 43 lks. dist., mkd. T24S R25E S18 BT.

A juniper, 7 ins. diam., bears S. 40° W., 55 lks. dist., mkd. T24S R24E S13 BT.

A juniper, 12 ins. diam., bears N. 39° W., 57 lks. dist., mkd. T24S R24E S12 BT.

S. 89° 51' W., bet. secs. 12 and 13.

Over broken land, with thick juniper and pinon timber, and scattered shadscale, sagebrush and grass; along N. slope.

- 5.00 Slope changes; desc. 80 ft. over NW. slope.
- 16.00 Bottom of small canyon, drains NE.; asc. 160 ft. over NE. slope.
- 24.00 Slope changes; along N. slope.
- 29.05 Dirt road, bears NE. and SW.; enter sparsely scattered timber.
- 40.24 Point for the $\frac{1}{4}$ sec. cor. of secs. 12 and 13.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground, to bedrock, in a mound of stone, 5 ft. base to top, with brass cap mkd.

T24S R24E
 $\frac{1}{4} \frac{S12}{S13}$
 1972

Survey of a Portion of the Subdivision,
T. 24 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS

	Continue along N. slope.
53.90	Bulldozed road, bears N. and S.
66.50	Bulldozed road, bears N. and S.
76.00	Top of small spur, slopes NW.; desc. over NW. slope.
80.48	The cor. of secs. 11, 12, 13, and 14.
	Land, broken. Soil, rocky loam. Timber, thick to sparsely scattered juniper and pinion. Undergrowth, scattered shadscale, sagebrush and grass.
	N. 0° 01' W., bet. secs. 11 and 12.
	Over broken land, with scattered juniper and pinion timber, scattered shadscale, sagebrush and grass undergrowth; desc. 80 ft. over NW. slope.
5.00	Slope changes; desc. 40 ft. over N. slope.
14.80	Spur, slopes E.; desc. 80 ft. along E. slope.
37.00	Bottom of draw, drains NW.; asc. 20 ft. over SW. slope.
38.70	Point of exposed sandstone spur and ledge, bears N. and S. 80° E.; thence along sandstone ledge sloping W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 12.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 5 ft. base to top, with brass cap mkd.
	T24S R24E $\frac{1}{4}$ S11 S12 1972
	Cor. is set at base of ledge, 6 ft. high and bears N. 5° W. and S. 5° W.
	Asc. 6 ft. along W. slope of ledge.
40.60	Top of ledge, bears N. 5° W. and curves S.; desc. 80 ft. over gradual N. slope.
56.00	Spur, slopes E.; desc. 240 ft. over NE. slope.
78.00	Bottom of draw, drains NW.; asc. 40 ft. over gentle W. slope and ledge.
79.80	Top of ledge, bears NW. and SE.; thence along gentle W. slope.
80.00	Point for the cor. of secs. 1, 2, 11 and 12.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 5 ft. base to top, with brass cap mkd.

Survey of a Portion of the Subdivision,
T. 24 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS

T24S R24E

S2	S1
S11	S12

1972

Land, broken.
Soil, exposed sandstone and rocky loam.
Timber, sparsely scattered juniper and pinion.
Undergrowth, scattered shadscale, sagebrush and grass.

From the cor. of secs. 1, 6, 7 and 12, on the E. bdy.
of the Tp., monumented with an iron post, 2 ins. diam.,
firmly set, extending 6 ins. above the ground, with brass
cap mkd.

T24S

R24E R25E

S1	S6
S12	S7

1933

from which

A pinion, 6 ins. diam., bears N. 35° E., 68 lks.
dist., mkd. T24S R25E S6 BT.

A pinion, 7 ins. diam., bears S. 85° E., 45 lks.
dist., mkd. T24S R25E S7 BT.

A juniper, 4 ins. diam., bears S. 73° W., 61 lks.
dist., mkd. BT.

A pinion, 6 ins. diam., bears N. 8° W., 49 lks.
dist., mkd. T24S R24E S1 BT.

S. 89° 53' W., bet. secs. 1 and 12.

Over broken land, with scattered juniper and pinion
timber, scattered shadscale, sagebrush and grass; asc.
80 ft. over E. slope of draw.

- 3.00 Top of spur, slopes N.; thence along gentle N. slope.
10.50 Dirt road, bears N. and S.
16.50 Slope changes; desc. 200 ft. over NW. slope.
27.00 Bottom of draw, drains NW.; asc. 80 ft. over NE. slope.
40.25 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12.
Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 5 ins. in
the ground to bedrock, in a mound of stone, 5 ft. base
to top, with brass cap mkd.

T24S R24E

$\frac{1}{4}$ S1
S12

1972

Asc. 40 ft. over NE. slope.

Survey of a Portion of the Subdivision,
T. 24 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS

- 46.00 Top of spur, slopes N.; desc. 80 ft. over NW. slope.
- 57.00 Bottom of descent, slopes NW.; asc. 160 ft. over NE. slope.
- 77.60 Top of spur, slopes N.; desc. 30 ft. over W. slope.
- 80.50 The cor. of secs. 1, 2, 11 and 12.
- Land, broken.
Soil, rocky loam.
Timber, scattered juniper and pinion.
Undergrowth, scattered shadscale, sagebrush and grass.
-
- N. 0° 01' W., bet. secs. 1 and 2.
- Over broken land, with scattered scrub juniper and pinon timber, shadscale, sagebrush and grass undergrowth; along W. slope.
- 2.00 Rim of canyon, bears NE. and SW.; desc. 120 ft. over rocky NW. slope.
- 8.00 Bottom of canyon, drains NE.; asc. 80 ft. over rocky SE. slope.
- 12.60 N. rim of canyon, bears NE. and SW.; desc. 80 ft. over gradual N. slope.
- 22.00 Rim of canyon, bears NE. and SW.; desc. 320 ft. over ledges and NW. slope.
- 35.90 Bottom of canyon, drains NE.; asc. 80 ft. over SE. slope.
- 38.90 Point for the witness $\frac{1}{4}$ sec. cor. of sec. 1 and 2
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, $4\frac{1}{2}$ ft. base to top, with brass cap mkd.
- T24S R24E
 $\frac{1}{4}$
W C
S2 \uparrow S1
1972
- 40.00 True point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2, falls on steep SE. slope and is unsafe to monument.
- Ascend 50 ft. over steep SE. slope.
- 41.50 Top of spur, slopes NE.; desc. 240 ft. over N. slope.
- 46.50 Bottom of side canyon, drains NW.; asc. 200 ft. over SW. slope.
- 52.00 Top of sandstone spur, slopes W.; desc. 440 ft. over NW. slope.
- 57.50 Bottom of descent, slopes W.; thence along steep W. slope.
- 67.00 Top of spur, slopes W.; desc. 400 ft. over steep N. slope into Cottonwood Canyon.

Survey of a Portion of the Subdivision,
T. 24 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
70.50	Bottom of Cottonwood Canyon, drains NE.; asc. 480 ft. over steep SE. slope.
80.50	N. rim of canyon, bears NE. and SW.; thence along E. slope.
82.77	Intersect the S. bdy. of sec. 35, T. 23 S., R. 24 E.
	Point for the closing cor. of secs. 1 and 2, T. 24 S., R. 24 E.
	Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to top, with brass cap mkd.
	<div style="text-align: center;"> T23S S35 <hr style="width: 50%; margin: 0 auto;"/> S2 S1 C C T24S R24E 1972 </div>
	From this closing cor., the ¼ sec. cor. of secs. 2 and 35, bears East, 5.52 chs. dist.
	Destroy markings on the cor. pertaining to T. 24 S., R. 24 E. This cor. now functions as the ¼ sec. cor. of sec. 35, T. 23 S., R. 24 E. only.
	Land, rough and broken. Soil, exposed sandstone and rocky loam. Timber, sparsely scattered scrub juniper and pinon. Undergrowth, scattered sagebrush, shadscale and grass.
	Point for the ¼ sec. cor. of sec. 1, on the S. bdy. of Sec. 35, T. 23 S., R. 24 E., at midpoint bet. the closing cor. of secs. 1 and 6, Tps. 24 S., Rs. 24 and 25 E., and the closing cor. of secs. 1 and 2, T. 24 S., R. 24 E.
	Set an iron post, 30 ins. long, 2½ ins. diam., on solid sandstone, over a cross (X) and in a mound of stone, 5 ft. base to top, with brass cap mkd.
	<div style="text-align: center;"> ¼ S1 T24S R24E 1972 </div>
	From this cor., the original cor. of secs. 1, 2, 35 and 3. Tps. 23 and 24 S., R. 24 E., bears East, 5.305 chs. dist.
	Destroy markings on the cor. pertaining to T. 24 S., R. 24 E. This cor. now functions as the cor. of secs. 35 and 36, T. 23 S., R. 24 E. only.
	From the cor. of secs. 1, 2, 11 and 12.
	West, bet. secs. 2 and 11.

Survey of a Portion of the Subdivision,
T. 24 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS

Over rough and broken land, with scattered scrub juniper and pinon, scattered sagebrush, shadscale and grass; desc. 40 ft. over W. slope.

- 2.50 Bottom of draw, drains N.; asc. 80 ft. over E. slope.
7.00 Top of spur, slopes N.; desc. 200 ft. over W. slope.
13.50 Bottom of small canyon, drains N.; asc. 280 ft. over E. slope.
24.00 Top of spur, slopes N.; desc. 240 ft. over steep W. slope.
34.00 Bottom of small canyon, drains N.; asc. 200 ft. over E. slope.
38.00 Top of spur, slopes N.; desc. 140 ft. over W. slope.
40.00 True point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11, falls on steep W. slope and is unsafe to monument an iron post. Desc. 20 ft. over W. slope.
42.50 Bottom of Cottonwood Canyon, drains N. 40° E.; asc. 200 ft. over steep E. slope and ledges.
48.57 Point for the witness $\frac{1}{4}$ sec. cor. of secs. 2 and 11.

Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 5 ft. base to top, with brass cap mkd.

T24S R24E
 $\frac{1}{4}$ $\frac{S2}{S11}$ → W
C
1972

Asc. 160 ft. over E. slope.

- 52.50 W. rim of Cottonwood Canyon, bears N. and S.; thence along N. slope.
80.00 Point for the cor. of secs. 2, 3, 10 and 11.

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to top, with brass cap mkd.

T24S R24E
 $\frac{S3}{S10} \mid \frac{S2}{S11}$
1972

There are no suitable bearing trees within limits.

Land, rough and broken.
Soil, sandstone outcroppings and rocky loam.
Timber, scattered scrub juniper and pinion.
Undergrowth, scattered sagebrush, shadscale and grass.

N. 0° 01' W., bet. secs. 2 and 3.

Survey of a Portion of the Subdivision,
T. 24 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS

Over broken land, with scattered scrub juniper and pinon, scattered sagebrush, shadscale and grass; desc. 40 ft. over N. slope.

- 6.50 Bottom of draw, drains N. 80° E.; asc. 40 ft. over SE. slope.
- 13.50 Top of ascent, bears N. 80° E.; and S. 80° W.; desc. 160 ft. over gradual N. slope.
- 32.00 Dirt road, bears N. 30° E. and S. 30° W.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 5 ft. base to top, with brass cap mkd.

T24S R24E

$\frac{1}{4}$
S3 | S2
1972

There are no suitable bearing trees within limits.

Descend 20 ft. over gradual N. slope.

- 43.00 Base of knoll, bears NW. and SE.; asc. 50 ft. over SW. slope.
- 46.80 Top of W. slope of knoll; desc. 40 ft. over NW. slope.
- 70.00 Bottom of gulch, drains NW.; asc. 80 ft. over SW. slope.
- 82.55 Intersect the S. bdy. of sec. 34, T. 23 S., R. 24 E.

Point for the closing cor. of secs. 2 and 3, T. 24 S., R. 24 E.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, and in a collar of stone, with brass cap mkd.

T23S

S34

S3 | S2

C|C

T24S R24E

1972

From this cor., the $\frac{1}{4}$ sec. cor. of secs. 3 and 34, bears East, 5.82 chs. dist.

Destroy markings on the S. side of the $\frac{1}{4}$ sec. cor. of secs. 3 and 34. This cor. now functions as the $\frac{1}{4}$ sec. cor. of sec. 34, T. 23 S., R. 24 E. only.

Land, rolling and broken.

Soil, rocky loam.

Timber, scattered scrub juniper and pinon.

Undergrowth, scattered sagebrush, shadscale and grass.

Point for the $\frac{1}{4}$ sec. cor. of of sec. 2, on the S. bdy. of sec. 34, T. 23 S., R. 24 E., at midpoint bet. the

Survey of a Portion of the Subdivision,
T. 24 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS

closing cor. of secs. 1 and 2, and the closing cor. of secs. 2 and 3, T. 24 S., R. 24 E.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, $4\frac{1}{2}$ ft. base to top, with brass cap mkd.

$\frac{1}{4}$ S2
T24S R24E
1972

From this cor., the original cor. of secs. 2, 3, 34 and 35, Tps. 23 and 24 S., R. 24 E., bears East, 5.67 chs. dist.

Destroy markings on the cor. pertaining to T. 24 S., R. 24 E. This cor. now functions as the cor. of secs. 34 and 35, T. 23 S., R. 24 E. only.

From the cor. of secs. 33 and 34, on the S. bdy. of the Tp., hereinbefore described.

N. $0^{\circ} 02'$ W., bet. secs. 33 and 34.

Over rough and broken land, with thick scrub juniper and pinon timber, scattered sagebrush, shadscale and grass; desc. 560 ft. over NE. slope of Fisher Mesa.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 5 ft. base to top, with brass cap mkd.

T24S R24E
 $\frac{1}{4}$
S33 | S34
1972

Desc. 50 ft. over NE. slope.

48.00 Base of main descent, bears NW. and SE.; desc. 180 ft. over gradual NE. slope.

79.15 Point for the witness cor. of secs. 27, 28, 33 and 34.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, $4\frac{1}{2}$ ft. base to top, with brass cap mkd.

T24S R24E
W C
S28↑S27
S33|S34
1972

80.00 True point for the cor. of secs. 27, 28, 33 and 34, falls in bottom of wash, 4 ft. deep, 20 lks. wide, draining NE. and is not safe to monument.

There are no suitable bearing trees within limits.

Survey of a Portion of the Subdivision,
T. 24 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS

Land, broken.
Soil, rocky loam.
Timber, scattered scrub juniper and pinon.
Undergrowth, scattered sagebrush, shadscale and grass.

N. 0° 02' W., bet. secs. 27 and 28.

Over rolling land, with scattered scrub juniper and pinon timber, scattered sagebrush, shadscale and grass; along gentle E.slope.

33.60 Spur, slopes E.; desc. 120 ft. over N. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, $4\frac{1}{2}$ ft base to top, with brass cap mkd.

T24S R24E
 $\frac{1}{4}$
S28|S27
1972

There are no suitable bearing trees within limits.

Desc. 560 ft. over steep N. slope.

56.00 Bottom of deep canyon, drains N. 80° W.; asc. 360 ft. over steep S. slope of gypsum ridge, leave timber.

70.00 Top of ridge, bears E. and W.; along ridge top.

73.40 N. rim of ridge, bears E. and W.; desc. 80 ft. over N. slope.

77.00 Bottom of deep draw, drains NE.; asc. 40 ft. over S. slope.

79.90 Top of small red knoll; desc. 5 ft. over gentle N. slope to cor.

80.00 Point for the cor. of secs. 21, 22, 27 and 28.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

T24S R24E
S21|S22
S28|S27
1972

Land, rolling S. portion; broken N. portion.
Soil, rocky loam S. portion; gypsum and red clay on N. portion.
Timber, scattered juniper and pinon on S. portion.
Undergrowth, scattered sagebrush, shadscale and grass.

N. 0° 02' W., bet. secs. 21 and 22.

Over rough and broken land, with scattered sagebrush, shadscale and grass; desc. 440 ft. over steep N. slope.

Survey of a Portion of the Subdivision,
T. 24 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
10.00	Onion Creek, 3 lks. wide, 1 in. deep, flows N. 80° W.
10.20	Dirt road in bottom of canyon, bears E. and N. 80° W.; asc. 400 ft. over steep S. slope of clay ridge.
26.00	Top of narrow clay ridge, bears E. and W.; desc. 320 ft. over steep N. slope.
33.00	Bottom of draw, drains NW. 4.00 chs., thence SW.; asc. 160 ft. over S. slope.
38.00	Top of spur, slopes W.; desc. 20 ft. over gentle N. slope.
39.80	Bottom of small draw, drains E.; asc. 5 ft. over gentle S. slope of small spur.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T24S R24E $\frac{1}{4}$ S21 S22 1972
	Asc. 5 ft. over gentle S. slope.
40.20	Top of small spur, slopes E.; desc. 40 ft. over NW. slope.
47.00	Bottom of draw, drains SW.; asc. 680 ft. over broken S. slope; enter scattered scrub juniper and pinon timber.
79.50	Top of high spur, slopes SE.; desc. 10 ft. over gradual N. slope to the cor.
80.00	Point for the cor. of secs. 15, 16, 21 and 22.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 5 ft. base to top with brass cap mkd.
	T24S R24E S16 S15 S21 S22 1972
	There are no suitable bearing trees within limits.
	Land, rough and broken. Soil, clay and rocky loam. Timber, scattered scrub juniper and pinon on N. portion. Undergrowth, scattered sagebrush, shadscale and grass.
	N. 0° 02' W., bet. secs. 15 and 16.
	Over rough and broken land, with scattered juniper and pinon timber; desc. 70 ft. over N. slope.
8.00	Slope changes; desc. 240 ft. over NE. slope.
14.00	Bottom of canyon, drains SE.; asc. 280 ft. over SW. slope.

Survey of a Portion of the Subdivision,
T 24 S, R. 24 E, S. 16 N. Sec. 9, 10, 15 and 16.

CHAINS	
33.70	Slope changes; asc. 80 ft. over S. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., over a cross (X) on solid sandstone, in a mound of stone, 5 ft. base to top, with brass cap mkd. T24S R24E $\frac{1}{4}$ S16 S15 1972 Asc. 1120 ft. over steep S. slope and sandstone ledge; by triangulation.
61.00	S. rim of mesa, bears E. and N. 55° W.; thence along bottom of draw draining S.; end of triangulation.
70.00	Leave draw; asc. 80 ft. over S. slope.
75.00	Top of ridge, bears NW. and SE.; desc. 40 ft. along E. slope to the cor.
80.00	Point for the cor. of secs. 9, 10, 15 and 16. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, $4\frac{1}{2}$ ft. base to top, with brass cap mkd. T24S R24E S9 S10 S16 S15 1972 Land, rough and broken. Soil, sandy and rocky loam. Timber. scattered juniper and pinon. Undergrowth, sparsely scattered shadscale, sagebrush and grass.
	N. $0^{\circ} 02'$ W., bet. secs. 9 and 10. Over broken land, with scattered juniper and pinon timber; desc. 81 ft. over NE. slope.
16.50	Slope changes; desc. 160 ft. over N. slope.
26.00	Small draw, drains E.; thence along E. slope.
36.00	Slope changes; desc. 120 ft. over NE. slope.
40.00	True point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10, falls in the bottom of a narrow canyon and is unsafe to monument; canyon drains NW.; asc. 40 ft. over SW. slope.
42.20	Rim of canyon, bears NW. and SE.
42.38	Point for the witness $\frac{1}{4}$ sec. cor. of secs. 9 and 10. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 5 ft. base to top, with brass cap mkd.

Survey of a Portion of the Subdivision,
T. 24 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T24S R24E $\frac{1}{4}$ S9 S10 W↓C 1972</p> <p>Thence along a W. slope.</p> <p>45.00 Top of spur, slopes W.; desc. 250 ft. over NW. slope.</p> <p>80.00 Point for the cor. of secs. 3, 4, 9, and 10.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., over a cross (X) on solid sandstone, in a mound of stone, 5 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T24S R24E S4 S3 — — S9 S10 1972</p> <p>from which</p> <p style="padding-left: 40px;">A pinon, 14 ins. diam., bears N. 9° W., 97 lks. dist., mkd. T24S R24E S4 BT.</p> <p style="padding-left: 40px;">There are no other suitable bearing trees within limits.</p> <p>Land, broken. Soil, rocky loam. Timber, scattered juniper and pinon. Undergrowth, scattered shadscale, sagebrush and grass.</p> <hr/> <p>N. 0° 02' W., bet. secs. 3 and 4.</p> <p>Over rolling and broken land, with scattered juniper and pinon timber; desc. 80 ft. over NW. slope.</p> <p>11.00 Top of spur, slopes NW.; desc. 400 ft. over NE. slope.</p> <p>36.00 Bottom of draw, drains NW.; asc. 30 ft. over SW. slope.</p> <p>40.00 Point for the ¼ sec. cor. of secs. 3 and 4.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T24S R24E $\frac{1}{4}$ S4 S3 1972</p> <p>Cor. is 10 ft. S. of base of sandstone ledge, 8 ft. high and bears E. and W.</p> <p>Asc. 80 ft. over ledge and SW. slope.</p> <p>47.00 Top of spur, slopes NW.; desc. 480 ft. over gradual N. slope.</p> <p>82.84 Intersect the S. bdy. of Sec. 33, T. 23 S., R. 24 E.</p>

Survey of a Portion of the Subdivision,
T. 24 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS

Point for the closing cor. of secs. 3 and 4, T. 24 S.,
R. 24 E.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins.
in the ground to bedrock, in a mound of stone, $4\frac{1}{2}$ ft.
base to top, with brass cap mkd.

T23S
S33
—
S4 | S3
|
C | C
T24S R24E
1972

From this cor., the original $\frac{1}{4}$ sec. cor. of secs. 4 and
33, bears East, 6.07 chs. dist.

Destroy markings on the cor. pertaining to T. 24 S.,
R. 24 E. This cor. now functions as the $\frac{1}{4}$ sec. cor. of
sec. 33, T. 23 S., R. 24 E. only.

Land, rolling and broken.
Soil, rocky loam.
Timber, scattered juniper and pinon.
Undergrowth, scattered shadscale, sagebrush and grass.

From the cor. of secs. 15, 16, 21 and 22, previously
described.

West, bet. secs. 16 and 21.

Over rough and broken land, with scattered juniper and
pinon; asc. 30 ft. along N. slope.

12.00 Top of ascent, bears N. and S.; desc. 120 ft. over NW.
slope.

26.00 Slope changes; desc. 40 ft. along N. slope.

38.00 Head of canyon, drains S.; thence along S. slope.

39.00 Point for the witness $\frac{1}{4}$ sec. cor. of secs. 16
and 21.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in
the ground to bedrock, in a mound of stone, $4\frac{1}{2}$ ft. base
to top, with brass cap mkd.

T24S R24E
W S16
C $\frac{1}{4}$ ← S21
1972

Cor. is set on top of small spur, slopes S.

Desc. 10 ft. over W. slope.

40.00 True point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 21, falls
in the bottom of a small draw, draining S. Point is
unsuitable for monumentation.

Asc. 80 ft. along S. slope.

50.00 Saddle on ridge, bears N. and S.; desc. 80 ft. over W.

Survey of a Portion of the Subdivision,
T. 24 S., R. 24 E. Salt Lake Meridian Utah

CHAINS

slope.

60.00 Bottom of draw, drains S.; asc. 120 ft. over SE. slope.

70.00 Top of high spur, slopes S.; desc. 320 ft. over steep W. slope into canyon.

80.00 True point for the cor. of secs. 16, 17, 20 and 21, falls on inaccessible slope of sandstone ledge and cannot be monumented.

81.52 Point for the witness cor. of secs. 16, 17, 20 and 21.

Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to top, with brass cap mkd.

T24S R24E
S17|S16 W
S20|S21 C
1972

Cor. is set on N. slope, 50 ft. west of base of ledge.

Land, rough and broken.

Soil, rocky loam.

Timber, scattered juniper and pinon.

Undergrowth, scattered shadscale, sagebrush and grass.

From the true point for the cor. of secs. 16, 17, 20 and 21.

Over rough and broken land, with scattered juniper and pinon timber; desc. 320 ft. over steep NW. slope; by triangulation.

8.00 Bottom of descent, slopes W.; asc. 80 ft. over SW. slope.

11.00 Top of small spur, slopes N. 80° W.; desc. 360 ft. over N. slope.

16.00 Bottom of canyon, drains SW.; asc. 360 ft. over steep S. slope.

24.00 Slope changes; asc. 200 ft. over vertical ledges and S. slope.

30.00 Top of spur, slopes S. 20° E.; desc. 360 ft. over NE. slope.

36.00 Bottom of draw, drains E.; asc. 240 ft. over S. slope.

40.00 Point for the ¼ sec. cor. of secs. 16 and 17, falls on a steep S. slope. Due to the inaccessibility of this area, this cor. was not monumented.

Asc. 40 ft. over steep S. slope.

41.00 Top of spur, slopes SE.; desc. 80 ft. over NE. slope.

45.00 Bottom of draw, drains E.; thence along broken E. slope.

56.00 Base of main ascent, bears NE. and SW.; asc. 720 ft. over steep and rocky SE. slope.

Survey of a Portion of the Subdivision,
T. 24 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
80.00	<p>True point for the cor. of secs. 8, 9, 16 and 17, falls on inaccessible steep slope and cannot be monumented; end triangulation. A witness cor. established West 8.82 chs. dist. is hereinafter described.</p> <p>Land, rough and broken. Soil, clay and rocky loam. Timber, sparsely scattered juniper and pinon. Undergrowth, scattered shadscale, sagebrush and grass.</p>
	<p>From the cor. of secs. 9, 10, 15 and 16, previously described.</p> <p>West, bet. secs. 9 and 16.</p> <p>Over rough and broken mountainous land, with scattered juniper and pinon timber; asc. 42 ft. over NE. slope.</p>
7.70	Top of spur, slopes N.; desc. 160 ft. over NW. slope.
12.00	Bottom of draw, drains NW.; asc. 80 ft. along N. slope.
21.00	Top of spur, slopes N.; desc. 40 ft. over NW. slope.
26.00	Bottom of draw, drains NE.; asc. 40 ft. over E. slope.
29.00	Top of ascent, bears NW. and SE.; desc. 10 ft. over gradual W. slope.
33.18	<p>Point for the witness $\frac{1}{4}$ sec. cor. of secs. 9 and 16.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 5 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R24E</p> <p>W₁ ← S9</p> <p>C_{1/4} ← S16</p> <p>1972</p> </div>
33.50	Rim of mesa, bears NW. and SE.; desc. 360 ft. over ledges and steep SW. slope; by triangulation.
39.97	<p>True point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16, falls on inaccessible SW. slope and cannot be monumented.</p> <p>Desc. 120 ft. over SW. slope.</p>
47.00	Top of spur, slopes SW.; desc. 440 ft. over steep W. slope.
53.00	Bottom of draw, drains SW.; thence along steep S. slope.
63.00	Spur, slopes SW.; desc. 320 ft. over SW. slope.
68.00	Bottom of canyon, drains S.; asc. 560 ft. over steep SE. slope.
79.94	<p>True point for the cor. of secs. 8, 9, 16 and 17.</p> <p>Asc. 400 ft. over SE. slope.</p>
88.76	Point for the witness cor. of secs. 8, 9, 16 and 17; end triangulation.

Survey of a Portion of the Subdivision,
T. 24 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, $4\frac{1}{2}$ ft. base to top, with brass cap mkd.

T24S R24E
S8 | S9 W
S17 | S16 C
1972

Land, rough and broken.

Soil, clay and rocky loam.

Timber, sparsely scattered juniper and pinon.

Undergrowth, scattered shadscale, sagebrush and grass.

From the cor. of secs. 32 and 33, on the S. bdy. of the Tp.

N. $0^{\circ} 03'$ W., bet. secs. 32 and 33.

Over rolling and broken land, with scattered juniper and pinon timber; asc. 10 ft. over gradual S. slope.

7.60 Rim of shallow canyon, bears NE. and SW.; desc. 160 ft. over NW.slope.

12.50 Bottom of canyon, drains SW.; asc. 120 ft. over S. slope.

18.90 Rim of canyon, bears NE. and SW.; asc. 120 ft. over SW. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 5 ft. base to top, with brass cap mkd.

T24S R24E
 $\frac{1}{4}$
S32 | S33
1972

Thence along gradual W. slope.

40.80 Trail road, bears E. and SW.; desc. 50 ft. over NW. slope.

60.10 Sandstone ledge, 10 ft. high, bears NW. and SE.; desc. 80 ft. along W. slope.

71.37 Point for the witness cor. of secs. 28, 29, 32 and 33.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 5 ft. base to top, with brass cap mkd.

W C
T24S R24E
S29 | S28
S32 | S33
1972

71.55 N. rim of Fisher Mesa, bears NW. and SE.; desc. 280 ft. over steep NE. slope.

80.00 True point for the cor. of secs. 28, 29, 32 and 33, falls on a steep NE. slope and is unsafe to monument.

Survey of a Portion of the Subdivision,
T. 24 S. R. 24 E., Salt Lake Meridian. Utah

CHAINS	
	<p>Land, rolling and broken. Soil, rocky loam. Timber, scattered juniper and pinon. Undergrowth, scattered shadscale, sagebrush and grass.</p>
	<p>From the cor. of secs. 31 and 32 on the S. bdy. of the Tp.</p> <p>N. 0° 03' W., bet. secs. 31 and 32.</p> <p>Over rough and broken land, with scattered juniper and pinon timber; asc. 720 ft. over a steep SW. slope.</p>
30.00	Top of high spur, slopes W.; desc. 240 ft. over NW. slope.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, $4\frac{1}{2}$ ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R24E</p> <p>$\frac{1}{4}$</p> <p> </p> <p>S31 S32</p> <p>1972</p> </div> <p>Desc. 20 ft. over NW. slope.</p>
43.00	Bottom of draw, drains S. 80° W.; asc. 440 ft. over steep SW. slope and ledge; by triangulation.
54.00	S. rim of Fisher Mesa, bears NW. and SE.; desc. 80 ft. over N. slope; end of triangulation.
57.00	Bottom of draw, drains W.; asc. 80 ft. over S. slope
60.00	Thence over nearly level land of mesa top; asc. 80 ft. over gradual S. slope with sagebrush and grass; leave scattered timber.
80.00	<p>Point for the cor. of secs. 29, 30, 31 and 32.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R24E</p> <p><u>S30 S29</u></p> <p>S31 S32</p> <p>1972</p> </div> <p>Set a cedar post, 6 ft. long, 2 ft. in the ground, alongside the iron post.</p> <p>Land, S. portion, broken; N. portion, most level. Soil, clay S. portion; rocky loam on N. portion. Timber, scattered juniper and pinon. Undergrowth, shadscale, sagebrush and grass.</p>
	<p>From true point for the cor. of secs. 28, 29, 32 and 33.</p>

Survey of a Portion of the Subdivision,
T. 24 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS

S. 89° 59' W., bet. secs. 29 and 32.

Over broken land, with thick juniper and pinon timber;
asc. 280 ft. over NE. slope; by triangulation.

18.00 Top of spur, slopes NW.; desc. 40 ft. over E. slope.

22.00 Bottom of draw, drains NW.; asc. 120 ft. over NE. slope.

26.00 Thence over nearly level mesa top; end of triangulation.

39.93 Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T24S R24E
S29
 $\frac{1}{4}$ — S32
1972

Set a cedar post, 6 ft. long, 2 ft. in the ground,
alongside the iron post.

Asc. 20 ft. over SE. slope.

45.00 Top of ascent, slopes SW.; desc. 80 ft. over gradual W.
slope.

52.60 Trail road, bears NW. and SE.

79.86 The cor. of secs. 29, 30, 31 and 32.

Land, broken E. portion; rolling, W. portion.

Soil, rocky and sandy loam.

Timber, juniper and pinon mostly on E. portion.

Undergrowth, scattered shadscale, sagebrush and grass.

General Description

The area surveyed within T. 24 S., R. 24 E., is mostly rough and broken with some rolling terrain on the mesa tops. The elevation ranges from about 5,100 ft. above sea level to about 7,200 ft. above sea level. The soil varies from sandy clay loam to rocky loam along the ledges and canyon slopes. The vegetation consists of shadscale, sagebrush and meadow grass and other sparse native grasses. There are scattered juniper and pinon over most of the township.

There is one improved dirt road along Onion Creek, in the south half of the township and numerous trail roads in the northeast portion.

The drainage in the south half of the township is the west, and in the north portion, the drainage is to the north.

Blank

Page

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

[illegible]

CERTIFICATE OF SURVEY

(I ~~was~~), Jerry L. Thomas, , HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 22nd day of September, 19 50, (I ~~was~~) have independently resurveyed a portion of the south boundary and surveyed a portion of the south boundary and subdivisional lines of Township 24 South, Range 24 East

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), (~~me~~) and under (my) (~~own~~) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 19, 1973
(Date)

Jerry L. Thomas
(Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

FORWARDED FOR APPROVAL
Date JAN 18 1974

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the independent resurvey of a portion of the south boundary and the survey of a portion of the south boundary and surveyed a portion of the south boundary and subdivisional lines of Township 24 South, Range 24 East, Salt Lake Meridian, Utah

executed by Jerry L. Thomas, Supervisory Cadastral Surveyor
having been critically examined and found correct, are hereby approved.

JUL 8 1974
(Date)

Bernard W. Hartigan
(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in~~
~~, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief, Division of Cadastral Survey)~~

Blank

Page

Blank

Page

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
ORIGINAL

ORIGINAL 31

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF THE

EXTERIOR AND SUBDIVISIONAL LINES OF

TOWNSHIP 35 SOUTH, RANGE 5 WEST

Of the SALT LAKE Meridian,

In the State of UTAH

EXECUTED BY

Craig P. Sylvester Supervisory Cadastral Surveyor

Under special instructions dated May 5, 19 72, which provided for the surveys
included under Group Number 535, approved May 11, 1972,
and assignment instructions dated June 14, 19 72.

Survey commenced July 5, 19 72

Survey completed November 3, 19 72

INDEX DIAGRAM

Township 35 S., Range 5 W.

27	26	25	23	22	21
20 6	88 5	73 4	62 3	50 2	38 1 14
87	86	72	61	49	37
19 7	84 8	71 9	60 10	48 11	36 12 13
84	83	70	59	47	35
18 18	82 17	69 16	57 15	45 14	34 13 12
81	80	68	57	44	33
17 19	79 20	67 21	55 22	43 23	32 24 11
78	78	66	54	42	31
16 30	77 29	65 28	53 27	41 26	30 25 9
76	75	64	52	40	29
15 31	74 32	63 33	51 34	39 35	28 36 8
7	6	5	4	3	2

CHAINS

History of Surveys

SOUTH BOUNDARY (Seventh Standard Parallel South)

NORTH BOUNDARY

WEST BOUNDARY

EAST BOUNDARY (Panguitch Guide Meridian)

SUBDIVISION

All	Bailey and Burrill
	1874

The following field notes are those of a dependent resurvey of the north, south, east and west boundaries and subdivisional lines in Township 35 South, Range 5 West, of the Salt Lake Meridian, Utah

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions 1947, and the Special Instructions dated May 5, 1972

The direction of the lines of this survey were determined from observations on the sun and carried forward by sustained angulation, being supplemented by numerous other observations throughout the survey.

Before restoring lost corners, the lines of the original survey were retraced and a diligent search made for any evidence of the original corners. The rules of proportionate measurement were applied to ascertain the position of the lost corner after every reasonable possibility of finding direct evidence of the corner had been exhausted.

All private land owners with land adjacent to public land in this township were notified by the Bureau of Land Management District Office, at Kanab, Utah, of this survey, and a date set to meet with the cadastral surveyor if they had any question concerning this survey.

The geographic position for the southeast corner of township is at Latitude $37^{\circ} 42' 57.58''$ N. and Longitude $112^{\circ} 21' 35.53''$ W. This position is also a U.S.G.S. triangulation station.

The magnetic declination was read at a number of stations throughout the township and the average of the several readings was found to be 15° 30' East.

Dependent Resurvey, South Boundary,
(Seventh Standard Parallel South), T. 35 S., R. 5 W.,
S

CHAINS

Dependent Resurvey, South Boundary,
(Seventh Standard Parallel South), T. 35 S., R. 5 W.,
Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
T. C. Bailey, Deputy Surveyor, in 1874

Beginning at the standard cor. of Tps. 35 S., Rs. $4\frac{1}{2}$ and
5 W., reestablished by Elliot Bird in 1925 and is monu-
mented with an iron post, 3 ins. diam., 12 ins. above
ground, in a small collar of stone, with brass cap mkd.

S C
T35S
R5W R $4\frac{1}{2}$ W
S36|S31

1925

N. $89^{\circ} 42'$ W., along the S. bdy. of sec. 36, T. 35 S.,
R. 5 W.

Over bench land, draining W., covered with shadscale.

27.80 Low terrace, bears N. 75° W. and S. 75° E.; desc. 60 ft.
over general W. slope.

40.28 The standard $\frac{1}{4}$ sec. cor. of sec. 36, monumented with a
trachyte stone, 6x12x12 ins., plainly mkd. $\frac{1}{4}$.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

S C
T35S R5W
 $\frac{1}{4}$ S36
1972

Bury the original cor. stone alongside the iron post.

N. $89^{\circ} 45'$ W., beginning new measurement.

Desc. gentle NW. slope.

2.02 Wash, 6 ft. deep, 20 lks. wide, drains N. 75° W.

16.30 Wash, 6 ft. deep, 30 lks. wide, drains N. 75° W.

28.20 Wash, 3 ft. deep, 10 lks. wide, in small ravine, drains
N. 50° W.

36.70 Rise, bears SE. and NW. about 5.00 chs. to end.

38.20 Small wash, drains N. about 2.00 chs., thence W.

40.41 The standard cor. of secs. 35 and 36, monumented with a
trachyte stone, 10x10x12 ins., mkd. 1 notch on E., 5
notches on W. and 6 notches on N. edges. SC on S. face.

Dependent Resurvey, South Boundary
(Seventh Standard Parallel South), T. 35 S., R. 5 W.,
Salt Lake Meridian, Utah

CHAINS

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, in a collar of stone, with brass cap mkd.

S C
T35S R5W
S35/S36
1972

Place the original cor. stone alongside the iron post,
in a collar of stone.

Land, rolling, bench.

Soil, clay with gravelly rises.

Timber, none.

Undergrowth, shadscale and sagebrush.

N. $89^{\circ} 44'$ W., along the S. bdy. of sec. 35, T. 35 S.,
R. 5 W.

Over benchland, covered with shadscale.

1.50 Graded dirt road, bears N. 10° W. and S. 10° E.

9.00 Graded dirt road, bears N. and S.; enter river bottom
land.

26.50 Sevier River, 1.00 ch. wide, flows N.

34.00 Fence, bears N. $19^{\circ} 30'$ E. and S. $19^{\circ} 30'$ W.

35.40 Hard surface, U.S. Highway No. 89, bears N. $19^{\circ} 30'$ E.
and S. $19^{\circ} 30'$ W.

36.70 Fence, bears N. $19^{\circ} 30'$ E. and S. $19^{\circ} 30'$ W.; enter
hills.

40.21 The standard $\frac{1}{4}$ sec. cor. of sec. 35, monumented with a
trachyte stone, 8x8x14 ins., plainly mkd. $\frac{1}{4}$.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

S C
T35S R5W
 $\frac{1}{4}$ S35
1972

Bury the original cor. stone alongside the iron post.

Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.

N. $89^{\circ} 47'$ W., beginning new measurement.

Over mountainous land; asc. 100 ft. over general E.
slope.

17.80 Small spur, slopes S. 40° E.; desc. along S. slope of
draw.

Dependent Resurvey, South Boundary
(Seventh Standard Parallel South, T. 35 S., R. 5 W.,
Salt Lake Meridian Utah)

CHAINS

- 20.03 Point for the standard W. 1/16 sec. cor. of sec. 35, on the S. bdy. of the Tp., and midpoint bet. the standard $\frac{1}{2}$ sec. cor. of sec. 35 and the standard cor. of secs. 34 and 35.
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.
- S C
T35S R5W
W1/16 S35
1972
- Set a steel fence post alongside cor.
- Desc. 20 ft. along S. slope of draw.
- 37.50 Wash in draw, drains S. 85° E. irregularly.
- 40.06 The standard cor. of secs. 34 and 35, monumented with a trachyte stone, 8x12x18 ins., mkd. 2 notches on E., 4 notches on W. and 6 notches on N. edges.
- from which
- A cedar, 20 ins. diam., bears S. $37\frac{1}{2}^\circ$ E., 150 lks. dist., only BT legible. (Record S. 55° E., 146 lks.)
- At the cor. point
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.
- S C
T35S R5W
S34|S35
1972
- from which
- A cedar, 8 ins. diam., bears N. $55\frac{1}{2}^\circ$ E., 84 lks. dist., mkd. S35 BT.
- Bury the original cor. stone alongside the iron post.
- Land, river bottom E. portion; mountainous W. portion.
Soil, clay E. portion; gravelly W. portion.
Timber, scattered cedar W. portion.
Undergrowth, grass on bottom land, shadscale on hills.
- N. $89^\circ 35'$ W., along the S. bdy. of sec. 34, T. 35 S., R. 5 W.
- Over mountainous land; asc. 100 ft. along N. slope of draw.
- 36.50 Small draw, drains N. 80° E.; asc. 40 ft. along S. slope. of draw.
- 40.17 The standard $\frac{1}{4}$ sec. cor. of sec. 34, monumented with a volcanic stone, 12x12x14 ins., plainly mkd. $\frac{1}{4}$.

Dependent Resurvey, South Boundary
(Seventh Standard Parallel South), T. 35 S., R. 5 W.,
Salt Lake Meridian, Utah

CHAINS

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

S C
T35S R5W
¼ S34
1972

from which

A pine, 6 ins. diam., bears N. 5° E., 37 lks. dist.,
mkd. ¼ S34 BT.

Bury the original cor. stone alongside the iron post.

Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.

N. 89° 35' W., beginning new measurement.

Asc. 30 ft. along S. slope of draw.

9.00 Wash in draw, drains S. 85° E.; asc. 80 ft. over NE.
slope.

26.00 Low rim, bears NW. and SE., irregularly; asc. 40 ft. over
gentle E. slope.

40.17 The standard cor. of secs. 33 and 34, monumented with a
volcanic stone, 12x12x12 ins., mkd. 3 notches on E. and
W. edges and 6 notches on N. edge.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

S C
T35S R5W
S33|S34
1972

from which

A red cedar, 15 ins. diam., bears S. 45° W., 16 lks.
dist., mkd. BT.

A red cedar, 5 ins. diam., bears N. 28° W., 90 lks.
dist., mkd. T35S R5W S33 BT.

Bury the original cor. stone alongside the iron post.

Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.

Land, mountainous.

Soil, rocky gravel.

Timber, juniper and pine.

Undergrowth, shadscale and sagebrush.

N. 89° 24' W., along the S. bdy. of sec. 33, T. 35 S.,
R. 5 W.

Over rolling brush covered mountain land.

Dependent Resurvey, South Boundary
(Seventh Standard Parallel South), T. 35 S., R. 5 W.,
Salt Lake Meridian Utah

CHAIN#

- 40.33 The standard $\frac{1}{4}$ sec. cor. of sec. 33, monumented with a
volcanic stone, 6x10x14 ins., plainly mkd. $\frac{1}{4}$.

t the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

S C
T35S R5W
 $\frac{1}{4}$ S33

1972

A cedar, 12 ins. diam., bears N. 10° E., 130 lks.
dist., mkd. $\frac{1}{4}$ S33.

ury the original cor. stone alongside the iron post.

aise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.

. 89° 48 W., beginning new measurement.

- 1.46 Power line, bears N. 1° 59' W., and S. 1° 59' E.
9.00 ash, 4 ft. deep, 40 lks. wide, drains S.
39.00 Graded dirt road, bears N. 47° W. and S. 47° E.
40.39 The standard cor. of secs. 32 and 33, monumented with a
volcanic stone, 12x12x18 ins., mkd. 2 notches on W.,
4 notches on E. and 6 notches on N. edges.

t the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

S C
T35S R5W
S32 | S33

1972

ury the original cor. stone alongside the iron post.

aise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

and, rolling mountain.
Soil, rocky gravel.
imber, very scattered juniper.
ndergrowth, shadscale and sagebrush

. 89° 29' W., along the S. bdy. of sec. 32, T. 35 S.,
. 5 W.

ver brush covered mountain land.

- 2.80 mall wash, drains S. 35° E.
21.00 ash, 3 ft. deep, 20 lks. wide, drains S. 10° E.

Dependent Resurvey, South Boundary
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
35.50	Same wash, drains N. 75° E.
40.29	The standard $\frac{1}{4}$ sec. cor. of sec. 32, monumented with a volcanic stone, 14x14x14 ins., plainly mkd. $\frac{1}{4}$.
	At the cor point
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	$\begin{array}{r} \text{S C} \\ \text{T35S R5W} \\ \hline \frac{1}{4} \text{ S32} \\ \hline 1972 \end{array}$
	Bury the original cor. stone alongside the iron post.
	N. 89° 46' W., beginning new measurement.
	Asc. 100 ft. over E. slope.
25.00	Spur, slopes N. 20° E.; desc. 20 ft. along N. slope.
35.90	Wash in small ravine, drains N. 50° E.
40.08	The standard cor. of secs. 31 and 32, monumented with a volcanic stone, 12x16x20 ins., mkd. 1 notch on W., 5 notches on E. and 6 notches on N. edges.
	At the cor. point
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins., diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} \text{S C} \\ \text{T35S R5W} \\ \hline \text{S31 S32} \\ \hline 1972 \end{array}$
	Bury the original cor. stone alongside the iron post.
	Set steel fence post alongside the cor.
	Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.
	Land, broken.
	Soil, rocky gravel.
	Timber, very scattered juniper.
	Undergrowth, shadscale and sagebrush.
	N. 89° 43' W., along the S. bdy. of sec. 31, T. 35 S., R. 5 W.
	Over rolling brush covered mountain top.
21.90	Small draw, drains N. 65° E.; also trail road, bears N. 65° E. and SW.; asc. 90 ft. over E. slope.
40.38	The standard $\frac{1}{4}$ sec. cor. of sec. 31, monumented with a volcanic stone, 12x14x18 ins., plainly mkd. $\frac{1}{4}$.
	At the cor. point

Dependent Resurvey, South Boundary
(Seventh Standard Parallel South) T. 35 S., R. 5 W.,
Salt Lake Meridian Utah

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S C
T35S R5W
 $\frac{1}{2}$ S31
1972

Place the original cor. stone alongside the iron post.

Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.

N. $89^{\circ} 36'$ W., beginning new measurement.

Asc. 140 ft. over E. slope.

19.60 N. side of old volcano cone; desc. 80 ft. over W. slope.

40.14 The standard cor. of Tps. 35 S., Rs. 5 and 6 W.,
monumented with a volcanic stone, $14 \times 14 \times 18$ ins., mkd.
6 notches on N., E. and W. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S C
T35S
R6W R5W
S36/S31
1972

Place the original cor. stone alongside the iron post.

Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.

Land, rolling mountain.

Soil, gravelly.

Timber, scattered juniper.

Undergrowth, shadscale and sagebrush.

Dependent Resurvey, East Boundary
(Panguitch Guide Meridian) T. 35 S., R. 5 W.,
Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
Bailey and Burrill, Deputy Surveyors, in 1874

From the standard cor. of Tps. 35 S., Rs. $4\frac{1}{2}$ and 5 W.,
previously described.

N. $0^{\circ} 31'$ E., bet. secs. 31 and 36.

Over high bench land, along gentle W. slope.

2.80 Wash, 10 ft. deep, 20 lks. wide, drains N. 60° W.

Dependent Resurvey, East Boundary
(Panguitch Guide Meridian) T. 35 S., R. 5 W.,
Salt Lake Meridian, Utah

CHAINS	
26.60	Wash, 8 ft. deep, 20 lks. wide, drains W.
40.23	The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, monumented with a trachyte stone, 8x12x12 ins., plainly mkd. $\frac{1}{4}$.
	At the cor. point
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T35S R5W R4$\frac{1}{2}$W $\frac{1}{4}$ S36 S31 1972</p>
	Bury the original cor. stone alongside the iron post.
	Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.
	N. 0° 45' E., beginning new measurement.
3.20	Trail road, bears N. 80° W. and S. 80° E.
11.10	Wash, 6 ft. deep, 20 lks. wide, drains N. 80° W.
15.80	Wash, 10 ft. deep, 30 lks. wide, drains W.
40.31	The cor. of secs. 25, 30, 31 and 36, monumented with a sandstone, 6x10x12 ins., plainly mkd. 1 notch on S., 5 notches on N. and 6 notches on E. and W. edges.
	At the cor. point
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T35S R5W R4$\frac{1}{2}$W S25 S30 S36 S31 1972</p>
	from which
	A cedar, 14 ins. diam., bears S. 28° W., 153 lks. dist., mkd. T35S R5W S36 BT.
	Bury the original cor. stone alongside the iron post.
	Land, rolling bench.
	Soil, clay.
	Timber, scattered juniper.
	Undergrowth, shadscale and sagebrush.
	N. 0° 29' E., bet. secs. 25 and 30.
	Over high bench land; along gentle W. slope.
5.10	Wash, 5 ft. deep, 20 lks. wide, drains N. 80° W.
12.50	Wash, 6 ft. deep, 15 lks. wide, drains N. 85° W.

Dependent Resurvey, East Boundary
(Panguitch Guide Meridian) T. 35 S., R. 5 W.,

CHAINS

- 24.50 Wash, 5 ft. deep, 20 lks. wide, drains W.
26.40 Dirt road, bears W. and NE.
40.45 The $\frac{1}{4}$ sec. cor. of secs. 25 and 30, monumented with a sandstone, 8x10x14 ins., plainly mkd. $\frac{1}{4}$.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S
R5W R4 $\frac{1}{2}$ W
 $\frac{1}{4}$
S25|S30
1972

Bury the original cor. stone alongside the iron post and place 2 large boulders alongside iron post.

N. 0° 21' E., beginning new measurement.

- 9.70 Old dirt road, bears NW. and SE.
12.11 Power line, bears S. 89° 20' W. and N. 89° 20' E.
20.07 Point for the N. 1/16 sec. cor. of secs. 25 and 30, at proportionate distance.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S
R5W R4 $\frac{1}{2}$ W
N1/16
S25|S30
1972

Set cedar post, 5 ins. diam., 5 ft. high alongside the iron post.

- 38.00 Bulldozed road, bears N. 40° E. and S. 10° W.
40.14 Point for the cor. of secs. 19, 24, 25 and 30, at proportionate distance. There is no evidence of original cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S
R5W R4 $\frac{1}{2}$ W
S24|S19
S25|S30
1972

from which

A pipe in ground, bears E., 3 lks. dist.

A pipe in ground, bears N. 11° 30' E., 20 lks. dist.

A pipe in ground, bears N. 1° 55' E., 163 lks. dist.

Set cedar post, 4 ins. diam., 5 ft. high alongside the iron post.

Dependent Resurvey, East Boundary
(Panguitch Guide Meridian) T. 35 S., R. 5 W.,
Salt Lake Meridian, Utah

CHAINS

Land, rolling bench.
Soil, clay.
Timber, none.
Undergrowth, shadscale and sagebrush.

N. 0° 21' E., bet. secs. 19 and 24.

Over bench land; along gentle W. slope.

6.00 Wash, 12 ft. deep, 50 lks. wide, drains N. 48° W.

17.18 Fence, parallels highway.

18.15 Hard surface State Highway No. 12, bears N. 86° 30' W.
and curves to S. 77° 30' E.

19.20 Fence, parallels highway.

20.07 Point for the S. 1/16 sec. cor. of secs. 19 and 24, at
proportionate distance.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T35S
R5W R4½W
S1/16
S24|S19
1972

Set cedar post, 5 ins. diam., 5 ft. high, alongside cor.

29.00 Wash, 3 ft. deep, 80 lks. wide drains W.

35.00 Base of hills, bears NW. and E.; asc. 150 ft. over S.
slope, enter timber.

40.14 The ¼ sec. cor. of secs. 19 and 24, monumented with a
lava stone, 6x10x14 ins., plainly mkd. ¼.

from which

A pine, 12 ins. diam., bears N. 58½° E., 33 lks.
dist., mks. not legible.

A pine, 14 ins. diam., bears S. 78¼° W., 43 lks.
dist., mks. not legible.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in
the ground, in a mound of stone, 4 ft. base to top, with
brass cap mkd.

T35S
R5W R4½W
¼
S24|S19
1972

Place original cor. stone alongside the iron post,
in mound.

N. 1° 35' E., beginning new measurement.

Dependent Resurvey, East Boundary
(Panguitch Guide Meridian) T. 35 S., R. 5 W.,
Salt Lake Meridian, Utah

CHAINS

Asc. 150 ft. over S. slope.

17.00 Crest of ascent on top of ridge, bears E. and W.; desc. gentle N. slope on ridge.

40.34 The cor. of secs. 13, 18, 19 and 24, monumented with a volcanic stone, 12x12x14 ins., mkd. 3 notches on N. and S. edges, 6 notches on E. and W. edges.

from which

A pine, 18 ins. diam., bears S. $86^{\circ} 20'$ E., 44 lks. dist., mks. not legible.

A pine, 14 ins. diam., bears S. $88^{\circ} 45'$ W., 55 lks. dist., blaze grown over.

A cedar, 18 ins. diam., bears N. $33\frac{1}{2}^{\circ}$ W., 76 lks. dist., mkd. T35S R5W S13 BT.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.

T35S
R5W R4 $\frac{1}{2}$ W
S13|S18
S24|S19
1972

Place the original cor. stone in mound alongside the iron post.

Land, bench S. portion; mountainous N. portion.
Soil, clay, S. portion, rocky and gravelly N. portion.
Timber, pinon and juniper on mountainous portion.
Undergrowth, shadscale and sagebrush.

N. $0^{\circ} 38'$ E., bet. secs. 13 and 18.

Over mountainous land, through timber; desc. 100 ft. over N. slope.

21.20 Trail road, bears E. and W. along base of hills; leave hills, enter wide bench.

23.40 Wash, 3 ft. deep, 20 lks. wide, drains W.

40.03 The $\frac{1}{4}$ sec. cor. of secs. 13 and 18, determined by a sandstone, 4x8x12 ins., with old cedar post and lath lying beside stone. Marks have weathered off sandstone, which is the only stone in this area. This position also fits the general pattern of this resurvey.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey, East Boundary,
(Panguitch Guide Meridian) T. 35 S., R. 5 W.,
Salt Lake Meridian, Utah

CHAINS	
	<p>T35S R5W R4$\frac{1}{2}$W $\frac{1}{4}$ S13 S18 1972</p> <p>Place the stone alongside the iron post.</p> <p>Set cedar post, 6 ins. diam., 6 ft. high, by cor.</p> <hr/> <p>N. 0° 27' E., beginning new measurement.</p> <p>Over wide valley, draining W.</p> <p>11.20 Wash, 3 ft. deep, 40 lks. wide, drains N. 50° W.</p> <p>25.30 Wash, 3 ft. deep, 10 lks. wide, drains N. 40° W.</p> <p>40.14 The cor. of secs. 7, 12, 13 and 18, monumented with a sandstone, 8x8x12 ins., mkd. 2 notches on N., 4 notches on S. and 6 notches on E. and W. edges. Also old fence cor., old posts for fence bear S., W. and E.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p>T35S R5W R4$\frac{1}{2}$W S12 S7 S13 S18 1972</p> <p>Bury original cor. stone alongside the iron post.</p> <p>Cedar corner post of old fence, 8 ins. diam., 6 ft. high, alongside iron post.</p> <p>Land, hills S. portion, mountain valley N. portion. Soil, rocky S. portion, clay N. portion. Timber, pinon and juniper on hills. Undergrowth, shadscale and sagebrush.</p> <hr/> <p>N. 0° 31' E., bet. secs. 7 and 12.</p> <p>Over mountain valley, draining W.</p> <p>19.40 Wash, 6 ft. deep, 40 lks. wide, drains W.</p> <p>40.44 The $\frac{1}{4}$ sec. cor. of secs. 7 and 12, monumented with a sandstone, 8x10x12 ins., plainly mkd. $\frac{1}{4}$.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p>T35S R5W R4$\frac{1}{2}$W $\frac{1}{4}$ S12 S7 1972</p> <p>Bury the original cor. stone alongside the iron post.</p> <p>No other accessories.</p> <hr/> <p>N. 0° 44' E., beginning new measurement.</p> <p>10.30 Wash, 6 ft. deep, 1.00 ch. wide, drains generally W.</p> <p>12.10 Trail road, bears E. and W.</p>

Dependent Resurvey, East Boundary
(Panguitch Guide Meridian) T. 35 S., R. 5 W.,
Salt Lake Meridian, Utah

CHAINS	
18.00	Base of low hills, bear E. and W. irregularly; thence over low hills, enter trees.
20.09	Point for the N. 1/16 sec. cor. of secs. 7 and 12, at proportionate distance.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T35S R5W R4½W N1/16 S12 S7 1972
	Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.
25.60	Graded gravel road, bears N. 84° E. and S. 84° W.
40.16	The cor. of secs. 1, 6, 7 and 12, monumented with a trachyte stone, 8x8x12 ins., mkd. 1 notch on N., 5 notches on S., and 6 notches on E. and W. edges.
	from which
	A cedar stump, 12 ins. diam., bears N. 54½° W., 148 lks. dist., mks. not legible.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T35S R5W R4½W S1 S6 S12 S7 1972
	Bury the original cor. stone alongside the iron post.
	Raise a small mound of stone, W. of cor.
	Land, valley S. portion, hills, N. portion. Soil, clay in valley, gravelly in hills. Timber, scattered juniper and pinon in hills. Undergrowth, shadscale and sagebrush.
	N. 0° 25' E., bet. secs. 1 and 6.
	Over rolling hills, draining W.
9.00	Low ridge, bears E. and W.
35.50	Wash, 6 ft. deep, 30 lks. wide, drains N. 80° W.
40.39	The ¼ sec. cor. of secs. 1 and 6, monumented with a trachyte stone, 8x10x12 ins., plainly mkd. ¼.
	from which
	A cedar, 15 ins. diam., bears N. 5° W., 61 lks. dist., mks. grown over.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T35S R5W R4½W ¼ S1 S6 1972
	Bury the original cor. stone alongside the iron post.

Dependent Resurvey, East Boundary
(Panguitch Guide Meridian) T. 35 S., R. 5 W.,
Salt Lake Meridian, Utah

CHAINS	Raise a small mound of stone, W. of cor.
	N. 0° 25' E., beginning new measurement.
14. 90	Low spur, projects W.; desc. 80 ft. over N. slope.
25.00	Wash, 6 ft. deep, 30 lks. wide, drains W.; also base of spur, thence over valley draining W.
39.86	True point for the cor. of Tps. 34 and 35 S., Rs. 4½ and 5 W., determined from record course and distance of original bearing tree.
	from which
	A red cedar, 12 ins. diam., bears S. 20° W., 175 lks. dist., mkd. T35S R5W S1 BT.
	True point for corner falls in wash draining S. 30° W., and cannot be perpetuated.
	Therefore, at a point North, 0.30 chs. of true point for the cor. of Tps. 34 and 35 S., Rs. 4½ and 5 W.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	W C T34S R5W R4½W S36 S31 S 1½ S 6 T35S 1972
	Raise a mound of stone, 2 ft. base, 2 ft. high, N. of witness corner.
	Land, rolling hills and small valleys. Soil, gravelly on hills, clay in valleys. Timber, pinon and juniper on hills. Undergrowth, shadscale and sagebrush.
Dependent Resurvey, West Boundary, T. 35 S., R. 5 W., Salt Lake Meridian, Utah.	
Reestablishment of the Survey Executed by T. C. Bailey, Deputy Surveyor, in 1874	
	From the standard corner of Tps. 35 S., Rs. 5 and 6 W., previously described.
	N. 0° 22' E., bet. secs. 31 and 36.
	Over brush covered mountain land, draining generally E.
28.90	Small ravine, drains N. 80° E.
40.38	The ¼ sec. cor. of secs. 31 and 36, monumented with a volcanic stone, 10x12x12 ins., plainly mkd. ¼.
	At the cor. point

Dependent Resurvey, West Boundary, T. 35 S., R. 5 W.,
Salt Lake Meridian, Utah

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, in a collar of stone, with brass cap mkd.

T35S
R6W R5W
 $\frac{1}{4}$
S36|S31
1972

Bury original cor. stone alongside the iron post.

N. $0^{\circ} 23'$ E., beginning new measurement.

Continue along gentle E. slope.

- 8.10 Wash, 4 ft. deep, 30 lks. wide, drains E.
- 26.00 Curve of trail road, bears S. 1° W. and NW.
- 35.20 Small ravine, drains N. 75° E.; also trail road in bottom.
- 40.25 The cor. of secs. 25, 30, 31 and 36, monumented with a volcanic stone, $12 \times 12 \times 14$ ins., mkd. 1 notch on S. and 5 notches on N. edge.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T35S
R6W R5W
S25|S30
S36|S31
1972

Bury the original cor. stone alongside the iron post.

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Land, rolling mountain top.
Soil, gravelly and rocky.
Timber, none.
Undergrowth, shadscale and sagebrush.

N. $0^{\circ} 25'$ E., bet. secs. 25 and 30.

Over rolling mountain land, draining E.

- 20.00 Swale, drains N. 80° E.
- 34.90 Small swale, drains E.
- 40.09 The $\frac{1}{4}$ sec. cor. of secs. 25 and 30, monumented with a volcanic stone, $6 \times 12 \times 12$ in., plainly mkd. $\frac{1}{4}$.

At the cor. point

Dependent Resurvey, West Boundary, T. 35 S., R. 5 W.,
Salt Lake Meridian, Utah

CHAINS	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35S R6W R5W ¼ S25 S30 1972</p> <p>Bury original cor. stone alongside the iron post.</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p> <hr/> <p>N. 0° 22' E., beginning new measurement.</p>
13.10	Bulldozed road, bears NW. and SE.
26.00	Graded dirt road, bears NE. and SW.
29.00	Wash, 4 ft. deep, 40 lks. wide, drains N. 75° E.
40.20	<p>The cor. of secs. 19, 24, 25 and 30, monumented with a volcanic stone, 10x12x18 ins., plainly mkd. 2 notches on S., and 4 notches on N. edge.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35S R6W R5W S24 S19 S25 S30 1972</p> <p>Bury original cor. stone alongside the iron post.</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p> <p>Land, rolling mountain top. Soil, gravelly. Timber, none. Undergrowth, shadscale and sagebrush.</p> <hr/> <p>N. 0° 38' E., bet. secs. 19 and 24.</p> <p>Over rolling mountain land, draining E.</p>
12.00	Swale, drains S. 50° E.; asc. 80 ft. over S. slope.
23.40	Top of wide spur, slopes S. 50° E.; desc. 110 ft. over NE. slope.
40.14	<p>The ¼ sec. cor. of secs. 19 and 24, monumented with a volcanic stone, 8x12x12 ins., plainly mkd. ¼.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T35S R6W R5W ¼ S24 S19 1972</p> <p>Bury original cor. stone alongside the iron post.</p> <p>Set steel fence post alongside the cor.</p>

Dependent Resurvey, West Boundary, T. 35 S., R. 5 W.,
Salt Lake Meridian Utah

CHAINS

- N. $0^{\circ} 36'$ E., beginning new measurement.
Along general E. slope.
- 4.50 Wash in small draw, drains E.
- 5.90 Trail road, bears E. and curves SW.
- 11.00 Rise, bears E. and W.
- 19.40 Enter trees.
- 25.30 Small wash, drains E.
- 40.05 The cor. of secs. 13, 18, 19 and 24, monumented with a volcanic stone, 12x18x24 ins., mkd. 3 notches on N. and S. edges.
- At the cor. point
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T35S
R6W R5W
S13|S18
S24|S19
1972

Bury original cor. stone alongside the iron post.

Land, rolling mountain.

Soil, gravelly.

Timber, small juniper and pinon on N. portion.

Undergrowth, shadscale and sagebrush.

- N. $0^{\circ} 43'$ E., bet. secs. 13 and 18.
- Over mountains land, along general E. slope.
- 13.00 Wash in bottom of draw, about 100 ft. deep, drains N. 65° E.
- 38.00 S. rim of canyon, bears W. and SE.; desc. 70 ft. over N. slope.
- 39.98 Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 18, determined by original bearing tree.
- from which

A red cedar, 8 ins. diam., bears S. 50° E., 35 lks. dist., mkd. $\frac{1}{4}$ SBT.

Note: the original survey calls for this bearing tree to be a pine, but in many other calls of the original survey red cedar trees are referred to as pine. There is no trace of any other bearing trees.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.

T35S
R6W R5W
 $\frac{1}{4}$
S13|S18
1972

Cor. located on steep N. slope, in lava rock.

N. $0^{\circ} 28'$ E., beginning new measurement.

Dependent Resurvey, West Boundary, T. 35 S., R. 5 W.,
Salt Lake Meridian, Utah

CHAINS	
	Desc. 70 ft. over N. slope.
1.90	Wash in canyon bottom, drains E.
2.60	Hard surface highway, bears N. 84° 30' W. to Panguitch Lake, and S. 84° 30' E. to Panguitch; asc. 100 ft. over S. slope.
6.50	N. rim of canyon, bears N. 80° W. and S. 80° E.; thence over rolling mountain top, through patches of timber.
39.99	The cor. of secs. 7, 12, 13 and 18, monumented with a volcanic stone, 12x14x18 ins., mkd. 2 notches on N. and 4 notches on S. edges.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T35S R6W R5W S12 S 7 S13 S18 1972 </div>
	Bury original cor. stone alongside the iron post.
	Set steel fence post alongside the cor.
	Land, broken.
	Soil, rocky gravel.
	Timber, pinon and juniper.
	Undergrowth, shadscale and sagebrush.
	N. 2° 05' E., bet. secs. 7 and 12.
	Over rolling mountain top, through scattered patches of timber.
11.30	Small wash, drains N. 30° W.
39.37	The ¼ sec. cor. of secs. 7 and 12, monumented with a volcanic stone, 6x12x18 ins., plainly mkd. ¼.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T35S R6W R5W ¼ S12 S7 1972 </div>
	Bury original cor. stone alongside the iron post.
	Set steel fence post alongside the cor.
	Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.
	N. 1° 52' E., beginning new measurement.
	Continue over rolling mountain top.
21.30	Small wash, drains N. 30° E.
40.58	The cor. of secs. 1, 6, 7 and 12, monumented with a volcanic stone, 10x10x14 ins., mkd. 1 notch on N. and 5 notches on S. edges.

Dependent Resurvey, West Boundary, T. 35 S., R. 5 W.,
Salt Lake Meridian, Utah

CHAINS

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins.
in the ground, in a collar of stone, with brass cap mkd.

T35S
R6W R5W
S1 | S6
S12 | S7
1972

Bury the original cor. stone alongside the iron post.

Set steel fence post, alongside the cor.

Land, rolling mountain top.

Soil, rocky gravel.

Timber, scattered patches of pinon and juniper.

Undergrowth, shadscale and sagebrush.

N. $2^{\circ} 06'$ E., bet. secs. 1 and 6.

Over rolling mountain top, through scattered timber.

15.80 Small wash, drains N. 40° W.

40.32 The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, monumented with a
volcanic stone, 6x8x12 ins., plainly mkd. $\frac{1}{4}$.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T35S
R6W R5W
 $\frac{1}{4}$
S 1 | S 6
1972

from which

A pine, 5 ins. diam., bears S. $0^{\circ} 30'$ W., 13 lks.
dist., mkd. BT.

Bury the original cor. stone alongside the iron post.

Set steel fence post alongside the cor.

N. $1^{\circ} 48'$ E., beginning new measurement.

Desc. 180 ft. over gentle N. slope.

39.14 The cor. of Tps. 34 and 35 S., Rs. 5 and 6 W., monumented
with a volcanic stone, 8x12x14 ins., mkd. 6 notches on
N., S., E. and W. edges. Large mound of stone S. of cor.

from which

A pinon, 8 ins. diam., bears N. $11^{\circ} 45'$ E., 114 lks.
dist., mkd. T34S R5W S31 BT.

Dependent Resurvey, West Boundary, T. 35 S., R. 5 W.,
Salt Lake Meridian, Utah

CHAINS

A pinon, 8 ins. diam., bears S. $84\frac{1}{2}^{\circ}$ E., 264 lks.
dist., mkd. T35S R5W S6 BT.

A pinon, 6 ins. diam., bears S. $79\frac{1}{2}^{\circ}$ W., 230 lks.
dist., mkd. T35S R6W S1 BT.

A cedar, 10 ins. diam., bears N. $58\frac{1}{2}^{\circ}$ W., 58 lks.
dist., mkd. T34S R6W S36 BT.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T34S
R6W R5W
S36/S31
S 1/S 6
R6W R5W
T35S
1972

Bury the original cor. stone alongside the iron post.

Land, rolling mountain top.

Soil, rocky and gravelly.

Timber, juniper and pinon.

Undergrowth, shadscale and sagebrush.

Dependent Resurvey, North Boundary,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
T. C. Bailey, Deputy Surveyor, in 1874

From the true point for the cor of Tps. 34 and 35 S.,
Rs. $4\frac{1}{2}$ and 5 W., from which its witness cor. bears N.
0.30 chs. dist., previously described.

N. $89^{\circ} 39'$ W., bet. secs. 1 and 36.

Over rolling hills, draining generally W., through
scattered timber. Across wash.

.40 Center of wash, drains S. 30° W.

40.08 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 36, at propor-
tionate distance. There is no evidence of the original
cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T34S R5W
S36
 $\frac{1}{4}$ S1
T35S
1972

from which

A pine, 12 ins. diam., bears N. $22\frac{1}{2}^{\circ}$ W., 22 lks.

Dependent Resurvey, North Boundary,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

dist., mkd. $\frac{1}{4}$ S36 BT.

Raise a mound of stone, 3 ft. base, 3 ft. high, N. of co .

- 57.00 Small draw, drains S., about 7.00 chs. thence SW.
80.13 Fence, bears S. and N., 64 lks., thence E. and W.
80.16 The cor. of secs. 1, 2, 35 and 36, monumented with a trachyte stone, 5x12x14 ins., mkd. 1 notch on E., 5 notches on W. and 6 notches on N. and S. edges.

from which

A pine, 8 ins. diam., bears S. $10\frac{1}{4}^{\circ}$ E., 115 lks.
dist., mks. illegible. (Record S. 65° E., 116 lks.)

A pine, 14 ins. diam., bears S. 22° W., 127 lks.
dist., blaze grown over.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T34S	R5W
S35	S36
S 2	S 1
T35S	
1972	

Bury the original cor. stone alongside the iron post.

Land, broken.

Soil, gravelly.

Timber, juniper and pinon.

Undergrowth, shadscale and sagebrush.

S. $88^{\circ} 33'$ W., bet. secs. 2 and 35.

Over brush covered bench.

- 15.00 Head of draw, drains N. 80° W.; thence along N. slope.
of draw.
35.00 Small ravine, drains N. 20° W., asc. 120 ft. over NE.
slope.
39.92 The $\frac{1}{4}$ sec. cor. of secs. 2 and 35, monumented with a
trachyte stone, 4x8x12 ins., plainly mkd. $\frac{1}{4}$.

from which

A pine, 10 ins. diam., bears N. 2° W., 22 lks.
dist.; only BT legible. (Record N. 12° W., 24 lks.)

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

Dependent Resurvey, North Boundary,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T34S R5W $\frac{1}{4}$ <u>S35</u> S 2 T35S 1972</p> <p>Bury the original cor. stone alongside the iron post.</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 54' W., beginning new measurement.</p> <p>3.60 N. end of spur, slopes N. about 3.00 chs. to end; desc. 250 ft. over W. slope</p> <p>13.90 Base of hills, bears N. and S., also trail road along base of hills; desc. gentle W. slope in valley.</p> <p>24.50 Canal, drains northward.</p> <p>25.50 Gravel road, bears N. and S.</p> <p>25.75 Power line to local farms, bears along road; enter farms.</p> <p>39.86 Point for the cor. of secs. 2, 3, 34 and 35, at proportionate distance. There is no evidence of original cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T34S R5W <u>S34</u> <u>S35</u> S 3 S 2 T35S 1972</p> <p>Set cedar post, 5 ft. high, alongside cor.</p> <p>Land, hills on E. portion, farm land W. portion. Soil, gravelly on hills, clay on farm land. Timber, pinon and juniper on hills. Undergrowth, shadscale and sagebrush on hills.</p> <hr/> <p>S. 89° 54' W., bet. secs. 3 and 34.</p> <p>Over farm land, and pasture land.</p> <p>17.30 Sevier River, 2 ft. deep, 30 lks. wide, flows N., leave farms.</p> <p>19.93 Point for the E. 1/16 sec. cor. of secs. 3 and 34, at proportionate distance, falls in highway right-of-way, which is now under repair and cannot be monumented.</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 69° E., 71.2 lks. dist., with brass cap mkd. T34S R5W E1/16 S34 47 ft RM 1972 and an arrow pointing to the cor. point.</p>

Dependent Resurvey, North Boundary,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. $73\frac{1}{2}^{\circ}$ E., 80.3 lks. dist., with brass cap mkd. T35S R5W E1/16 S3 53 ft RM 1972 and an arrow pointing to the cor. point.

- 21.20 Center of U.S. Highway No.89, bears N. 8° W. and S. 8° E.
24.00 Base of mountains, bears N. and S.; asc. 400 ft. over general E. slope to cor.
34.50 Ravine, drains N. 75° E.
39.86 The $\frac{1}{4}$ sec. cor. of secs. 3 and 34, monumented with a trachyte stone, 8x10x16 ins., plainly mkd. $\frac{1}{4}$.

from which

A cedar, 9 ins. diam., bears N. 5° W., 48 lks. dist., mkd. $\frac{1}{4}$ S BT.

A pine, 8 ins. diam., bears S. 20° E., 10 lks. dist., mkd. $\frac{1}{4}$ S BT.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.

T34S R5W
 $\frac{1}{4}$ $\frac{S34}{S 3}$
T35S
1972

Place original cor. stone in mound, alongside the iron post.

N. $89^{\circ} 17'$ W., beginning new measurement.

Asc. 150 ft. over E. slope.

- 8.50 E. crest of ridge, bears N. and S.; thence over wide ridge.
16.80 W. crest same ridge, bears N. and S.; desc. 50 ft. over W. slope.
21.70 Old road, bears N. and S., also had a ravine draining W.; desc. 150 ft along N. slope, in ravine.
35.00 Slope changes, desc. 40 ft. over W. slope.
39.75 The cor. of secs. 3, 4, 33 and 34, monumented with a volcanic stone, 6x10x12 ins., mkd. 3 notches on E. and W. edges.

from which

A pine, 10 ins. diam., bears N. 40° E., 31 lks. dist., mkd. S34 BT. (Record 168 lks.)

Dependent Resurvey, North Boundary,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS		
	<p>A pine, 8 ins. diam., bears S. 45° E., 71 lks. dist., mkd. S3 BT. (record 144 lks.)</p> <p>A pine, 14 ins. diam., bears S. 30° W., 71 lks. dist., mkd. T35S R5W S4 BT. (Record 168 lks.)</p> <p>A pine, 7 ins. diam., bears N. 85° W., 120 lks. dist., mkd. T34S S33 BT. (record W., 125 lks.)</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T34S R5W S33 S34 S 4 S 3 T35S 1972</p> </div> <p>Bury the original cor. stone alongside the iron post.</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.</p> <p>Land, pasture, E. portion, mountain W. portion. Soil, clay in river bottom, gravelly on mountains. Timber, juniper and pinon on mountains. Undergrowth, shadscale and sagebrush on mountains.</p>	
	<p>N. 89° 57' W., bet. secs. 4 and 33.</p> <p>Over mountainous land;; desc. 50 ft. over W. slope.</p>	
2.00	Trail road, bears N. and S.	
3.70	Wash in draw, drains N.; asc. 170 ft. over E. slope.	
12.00	Trail road on top of ridge, bears N. and S.; desc. 130 ft. over general W. slope.	
39.80	<p>The ¼ sec. cor. of secs. 4 and 33, monumented with a volcanic stone, 16x16x20 ins., plainly mkd. ¼.</p> <p>from which</p> <p>A pine, 15 ins. diam., bears S. 35° E., 40 lks. dist., mkd. ¼ S BT.</p> <p>A pine, 6 ins. diam., bears N. 60° W., 11 lks. dist., blaze grown over.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T34S R5W S 33 ¼ S 4 T35S 1972</p> </div> <p>Bury the original cor. stone alongside the iron post.</p>	

Dependent Resurvey, North Boundary,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

	N. 89° 30' W., beginning new measurement.
	Desc. 40 ft. over NW. slope, leave hills.
13.20	Wash, drains N. 10° W.
17.50	Graded gravel road, bears S. 41° E. and W.
27.00	Same road, bears S. 85° W. and E.
30.00	Wash, drains N. 30° E.
40.04	The cor. of secs. 4, 5, 32 and 33, monumented with a volcanic stone, 10x10x12 ins., mkd. 2 notches on W. and 4 notches on E. edges.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T34S R5W S32 S33 S 5 S 4 T35S 1972 </div>
	Bury the original cor. stone alongside the iron post.
	Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.
	Land, mountainous E. portion, brushy valley W. portion.
	Soil, gravelly.
	Timber, juniper and pinon on E. portion.
	Undergrowth, shadscale and sagebrush.
	N. 89° 24' W., bet. secs. 5 and 32.
	Over brush covered valley land.
5.00	Dirt road, bears S. 80° E. and NW.
12.60	Hard surface highway bears N. 0° 49' W. to Panguitch and S. 0° 49' E. to Panguitch Lake.
26.00	Small wash, drains NE.; asc. 50 ft. over NE. slope, enter trees.
38.70	Old trail road, bears N. and S.
38.82	The ¼ sec. cor. of secs. 5 and 32, monumented with a volcanic stone, 8x10x14 ins., plainly mkd. ¼.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T34S R5W S34 ¼ ¼ S 5 T35S 1972 </div>
	Bury original cor. stone alongside the iron post.

Dependent Resurvey, North Boundary,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

Cor. is located in old N. and S. fence line

S. 89° 36' W., beginning new measurement.

Asc. 60 ft. over general E. slope.

26.50 Trail road, bears N. and S. also base of hills; asc. 160 ft. over steep E. slope and ledges facing E.

36.00 Crest of lava rim, bears N. and S.; asc. 30 ft. over gentle E. slope, on mountain.

41.17 The cor. of secs. 5, 6, 31 and 32, monumented with a volcanic stone, 8x10x12 ins., mkd. 1 notch on W. and 5 notches on E. edges.

from which

A pine, 10 ins. diam., bears N. 39° E., 108 lks. dist., mkd. T34S R5W S32 BT.

A cedar, 8 ins. diam., bears S. 54½° E., 147 lks. dist., mkd. T35S R5W S5 BT.

A pine, 10 ins. diam., bears S. 51¼° W., 109 lks. dist., mkd. T35S R5W S6 BT.

A pine, 12 ins. diam., bears N. 63½° W., 25 lks. dist., mkd. S31 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T34S R5W
S31|S32
S6 | S 5
T35S
1972

Bury original cor. stone alongside the iron post.

Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.

Land, valley E. portion, mountain W. portion.

Soil, gravelly.

Timber, juniper and pinon on W. portion.

Undergrowth, shadscale and sagebrush.

Reestablishment of the Survey Executed by
T. C. Bailey, Deputy Surveyor, in 1874 and
Retraced by Andrew Nelson, in 1924

N. 89° 43' W., bet. secs. 6 and 31.

Over mountainous land, through timber; asc. 100 ft. over gentle NE. slope.

3.22 Power line, bears N. 2° 03' E., and S. 2° 03' W.

29.50 Small ravine, drains N. 50° E.; asc. 40 ft. along gentle

Dependent Resurvey, North Boundary,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	N. slope.
40.01	The $\frac{1}{4}$ sec. cor. of secs. 6 and 31, monumented with a volcanic stone, 6x12x18 ins., plainly mkd. $\frac{1}{4}$.
	from which
	A cedar, 14 ins. diam., bears S. $62\frac{1}{2}^{\circ}$ W., 88 lks. dist., mkd. $\frac{1}{4}$ S BT.
	At the cor. point
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.
	<div style="text-align: center;"> T34S R5W $\frac{1}{4}$ <u>S31</u> S6 T35S 1972 </div>
	Bury original cor. stone alongside the iron post. from which
	A pine, 8 ins. diam., bears N. 60° E., 57 lks. dist., mkd. $\frac{1}{4}$ S31 BT.
	N. $89^{\circ} 53'$ W., beginning new measurement.
	Along gentle N. slope, through timber.
40.12	The cor. of Tps. 34 and 35 S., Rs. 5 and 6 W., previously described.
	Land, rolling mountain. Soil, rocky and gravelly. Timber, juniper and pinon. Undergrowth, shadscale and sagebrush.
<div style="text-align: center;"> Dependent Resurvey, Subdivision of T. 35 S., R. 5 W., Salt Lake Meridian, Utah </div> <div style="text-align: center;"> Reestablishment of the Survey Executed by Bailey and Burrill, Deputy Surveyors, in 1874 </div>	
	From the standard cor. of secs. 35 and 36, on the S. bdy. of the Tp., previously described.
	N. $0^{\circ} 37'$ E., bet. secs. 35 and 36.
	Over bench, drains W.
1.70	Small wash, drains W.
12.60	Wash area, 2 ft. deep, 1.00 ch. wide, drains N. 80° W.
25.10	Dirt road, bears N. $31^{\circ} 15'$ E. and S. $31^{\circ} 15'$ W.
26.10	Old fence, parallel to road, enter pasture land.
40.32	Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, at proportionate distance. There is no evidence of original cor.

Dependent Resurvey, Subdivision,
T. 3 S. R. 5 W. S. 35 & 36 T. 1 N. R. 1 E.

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W

¼

S35|S36

1972

Set a cedar post, 10 ins. diam., 4 ft. high, alongside cor.

56.00 Wash, 4 ft. deep, 50 lks. wide, drains W.

60.48 Point for the N. 1/16 sec. cor. of secs. 35 and 36, at portionate distance.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W

N1/16

S35|S36

1972

Cor. located alongside old N. and S. fence line.

70.60 Sevier River, 1 ft. deep, 80 lks. wide, flows N. 20° E.

80.64 Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance. There is no evidence of original cor. This point falls at beginning of road way construction for small lot subdivision and cannot be monumented.

from which

An iron post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 51° 19' E., 50 lks. dist., with brass cap mkd. T35S R5W S25 33ft RM 1972 and an arrow pointing to the true point.

An iron post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 74° 18' E., 42.4 lks. dist., with brass cap mkd. T35S R5W S36 28ft RM 1972 and an arrow pointing to the true point.

From the cor. point a survey stake, bears N. 77° 17' W., 3.25 chs. dist., mkd. Sec. 25, 26, 35 and 36.

Land, valley.

Soil, sandy clay.

Timber, none.

Undergrowth, shadscale, sagebrush and willows on river bottom.

From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., previously described.

N. 89° 52' W., bet. secs. 25 and 36.

Over brush covered bench land, draining W.

Dependent Resurvey, Subdivision,
T. 35 S. R. 5 W. S. 1 E. 1/4 Sec. 25

CHAINS

- 23.80 Wash, 4 ft. deep, 30 lks. wide, drains N. 25° W.
- 40.62 The $\frac{1}{4}$ sec. cor. of secs. 25 and 36, monumented with a volcanic stone, 8x10x14 ins., firmly set and plainly mkd. $\frac{1}{4}$.
- At the cor. point
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- T35S R5W

$\frac{1}{4}$ $\frac{S25}{S36}$

1972
- Bury original cor. stone alongside the iron post.
- Raise a mound of stone, 3 ft. base, 2 ft. high, alongside cor.
-
- N. 89° 28' W., beginning new measurement.
- 4.00 Crest of terrace, bears N. and S.; desc. W. slope of terrace.
- 16.50 Trail road, bears N. 10° E. and S. 10° W.
- 20.03 Point for the W. 1/16 sec. cor. of secs. 25 and 36, at proportionate distance.
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- T35S R5W

W1/16 $\frac{S25}{S36}$

1972
- Raise a small mound of stone, N. of cor.
- Set cedar post, 4 ft. high alongside iron post.
- From this cor., a wooden surveyors stake mkd. 1/16 bears N. 72° 45' W., 3.35 chs. dist., located on N. and S. fence line.
- 21.30 Base of terrace, bears NE. and S.; thence over bottom land.
- 23.23 Fence, bears N. and S.
- 31.10 Sevier River, 1 ft. deep, 70 lks. wide, flows N.
- 40.06 The true point for the cor. of secs. 25, 26, 35 and 36.
- Land, rolling.
- Soil, sandy clay.
- Timber, none.
- Undergrowth, shadscale on bench, willows along river.
-
- N. 0° 14' E., bet. secs. 25 and 26.
- Over pasture and river bottom land, and small tract subdivision.

Dependent Resurvey, Subdivision,
T. 35 S. R. 5 W. Salt Lake Meridian, Utah

CHAINS

- 20.50 Fence, bears E. and W.; enter grass pasture.
- 40.32 Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26, at proportionate distance. There is no evidence of original cor.
Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
T35S R5W
 $\frac{1}{4}$
S26|S25
1972
Cor. is located in grass pasture.
- 56.39 Power line, bears N. $85^{\circ} 43'$ W. and S. $85^{\circ} 43'$ E.; also fence and dirt road parallel power line.
- 80.40 Fence along E. side of U.S. Highway No. 89, bears N. 27° E. and curves to S.
- 80.64 Point for the cor. of secs. 23, 24, 25 and 26, at proportionate distance; there is no evidence of original cor.
Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
T35S R5W
S23|S24
S26|S25
1972
Cor. is located 5 lks. W. of highway right-of-way fence.
Land, river bottom and pasture.
Timber, none.
Undergrowth, grass.
Soil, sandy clay.
-
- From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., previously described.
N. $89^{\circ} 38'$ W., bet. secs. 24 and 25.
Over bench land, draining W.; desc. 60 ft. over W. slope.
- 12.50 Wash, 5 ft. deep, 50 lks. wide, drains N. 85° W. irregularly.
- 22.00 Same wash, drains S. 85° W.
- 31.00 E. edge of pond; thence over pond.
- 33.00 W. edge same pond; thence through corrals.
- 36.00 Leave corrals.
- 40.46 Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25, at proportionate distance; there is no evidence of original cor.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 E., Salt Lake

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T35S R5W ½ S24 S25 1972
	Raise a small mound of stone, N. of cor.
	Set pine post, 5 ft. high alongside cor.
	Over pasture land.
64.80	Sevier River, 1 ft. deep, 70 lks. wide, flows N.
80.87	Fence along highway, bears N. 27° E. and curves to S.
80.92	The cor. of secs. 23, 24, 25 and 26.
	Land, brush bench E. portion, pasture land W. portion. Soil, sandy clay. Timber, none. Undergrowth, shadscale, sagebrush and grass.
	N. 1° 27' E., bet. secs. 23 and 24.
	Over valley land.
3.10	Hard surface U.S. Highway No. 89, bears N. 27° E. and curves to S.
7.80	Fence, parallels highway.
16.50	Base of spur, bears NE. and SW.; asc. 80 ft. over S. slope.
22.10	Spur, slopes E.; desc. 100 ft. over NE. slope.
39.00	Base of spur, bears N. 30° W. and S. 30° E.; thence over valley
40.33	Point for the ½ sec. cor. of secs. 23 and 24, at proportionate distance; there is no evidence of original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T35S R5W ½ S23 S24 1972
	Set cedar post, 5 ins. diam., 5 ft. high alongside cor.
46.10	Fence, parallels highway.
46.80	Hard surface U.S. Highway No. 89, bears N. 31° 36' W. and S. 31° 36' E.
49.50	Fence, parallels highway.
62.90	Sevier River, 1 ft. deep, 75 lks. wide, flows N. 20° W. irregularly; enter pasture land.
78.00	Enter tall sagebrush.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

30.66

Point for the cor. of secs. 13, 14, 23 and 24, at proportionate distance; there is no evidence of original cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W
S14|S13
S23|S24
1972

Set cottonwood post, 5 ft. high alongside cor.

Land, mostly valley.

Soil, sandy clay.

Timber, none.

Undergrowth, sagebrush, willows along river and grass.

From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., previously described.

N. $38^{\circ} 41'$ W., bet. secs. 13 and 24.

Over mountainous land, covered with timber, on top of wide ridge.

24.00

Crest of ridge, bears N. 60° W. and S. 60° E.; desc. 160 ft. over SW. slope.

40.17

The $\frac{1}{4}$ sec. cor. of secs. 13 and 24, monumented with a volcanic stone, $8 \times 12 \times 20$ ins., plainly mkd. $\frac{1}{4}$.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T35S R5W
S13
 $\frac{1}{4}$ — S24
1972

Bury original cor. stone alongside the iron post.

Raise a mound of stone, 4 ft. base, 4 ft. high, N. of cor.

S. $89^{\circ} 46'$ W., beginning new measurement.

Desc. SW. slope, leave timber.

1.50

Trail road at base of slope, bears S. and NW.; thence over small bench.

20.025

Point for the W. $1/16$ sec. cor. of secs. 13 and 24, at proportionate distance.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	<div>T35S R5W</div> <div>W1/16 $\frac{S13}{S24}$</div> <div>1972</div> <div>Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.</div> <div>21.00Crest of terrace, bears NW. and SE.; desc. 160 ft. over SW. slope of terrace.</div> <div>32.00Base of terrace, bears NW. and SE.; thence over valley land.</div> <div>33.50Dirt road, bears N. 40° W. and S. 40° E.</div> <div>40.05The cor. of secs. 13, 14, 23 and 24.</div> <div>Land, mountain E. portion, valley W. portion. Soil, gravelly. Timber, juniper and pinon on mountains. Undergrowth, shadscale and sagebrush</div>
	<div>N. 0° 47' W., bet. secs. 13 and 14.</div> <div>6.00Dirt road, bears N. 40° W. and S. 40° E.</div> <div>9.00Base of terrace, bears N. 40° W. and S. 40° E.; asc. 140 ft. over SW. slope.</div> <div>19.80Crest of same terrace, bears N. 40° W. and S. 40° E.; thence over bench.</div> <div>20.16Point for the S. 1/16 sec. cor. of secs. 13 and 14, at proportionate distance.</div> <div>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</div> <div><div>T35S R5W</div><div>S1/16</div><div>S14 S13</div><div>1972</div><div>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</div><div>35.00Desc. gentle W. slope of bench.</div><div>40.32The ¼ sec. cor. of secs. 13 and 14, monumented with a lava stone, 8x8x14 ins., plainly mkd. ¼.</div><div>At the cor. point</div><div>Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</div><div><div>T35S R5W</div><div>¼</div><div>S14 S13</div><div>1972</div></div></div>

Dependent Resurvey, Subdivision,
T. 55 N. R. 5 W. S. 14 Sec. 13 and 14, Twp. 1

CHAINS

Place original cor. stone in mound alongside the iron post.

N. $0^{\circ} 06'$ W., beginning new measurement.

Desc. gentle N. slope on bench.

5.50 Wash, 3 ft. deep, 20 lks. wide, drains S. 80° W.

18.80 Small wash, drains W.

20.53 Point for the N. 1/16 sec. cor. of secs. 13 and 14, at proportionate distance.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W
N1/16
S14|S13
1972

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

41.06 The cor. of secs. 11, 12, 13 and 14, monumented with a granite stone, 12x12x14 ins., mkd. 4 notches on S. and 1 notch on E. edge.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W
S11|S12
S14|S13
1972

Bury original cor. stone alongside the iron post.

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

Land, mostly bench.

Soil, gravelly.

Timber, none.

Undergrowth, shadscale and sagebrush.

From the cor. of secs. 7, 12, 13 and 18, on the E. bdy of the Tp., previously described.

N. $86^{\circ} 15'$ W., bet. secs. 12 and 13.

Over brush covered bench land, draining W.

16.30 Wash, 8 ft. deep, 1.00 ch. wide, drains N. 60° W.

20.57 Point for the E. 1/16 sec. cor. of secs. 12 and 13, at proportionate distance.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;">T35S R5W E1/16 $\frac{S12}{S13}$ 1972</div>
	Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.
41.14	The ¼ sec. cor. of secs. 12 and 13, monumented with a trachyte stone, 6x8x14 ins plainly mkd. ¼.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;">T35S R5W ¼ $\frac{S12}{S13}$ 1972</div>
	Bury original cor. stone alongside the iron post.
	Raise a mound of stone, N. of cor.
	<hr style="width: 20%; margin: 10px auto;"/> S. 89° 05' W., beginning new measurement.
	Over brush covered bench.
23.70	Trail road, bears N. and S.
31.40	Trail road, bears N. and S.
40.56	The cor. of secs. 11, 12, 13 and 14.
	Land, rolling. Soil, clay. Timber, none. Undergrowth, shadscale and sagebrush.
	<hr/> N. 0° 16' W., bet. secs. 11 and 12.
	Over rolling brush covered bench.
16.90	Fence, bears E. and W.
20.70	N. crest of bench, bears E. and W.; desc. 120 ft. over steep N. slope.
26.60	Base of steep descent, bears E. and W., also wash, drains W.; thence over valley.
39.45	Fence, bears E. and W.
40.00	Point for the ¼ sec. cor. of secs. 11 and 12, at proportionate distance.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35S R5W ¼ S11 S12 1972</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p>
59.92	Fence, bears E. and W.
60.00	<p>Point for the N. 1/16 sec. cor. of secs. 11 and 12, at proportionate distance.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T35S R5W N1/16 S11 S12 1972</p>
67.40	Graded dirt road, bears N. 78° W. and S. 78° E.
80.00	<p>The cor. of secs. 1, 2, 11 and 12, monumented with a trachyte stone, 8x10x16 ins., mkd. 5 notches on S. and 1 notch on E. edge.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35S R5W S2 S1 S11 S12 1972</p> <p>Bury original cor. stone alongside the iron post.</p> <p>Cor. located at fence cor., fences bears N., W. and SE.</p> <p>Land, mostly rolling. Soil, sandy clay. Timber, none. Undergrowth, shadscale and sagebrush.</p>
36.60	<p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., previously described.</p> <p>N. 87° 37' W., bet. secs. 1 and 12.</p> <p>Over gently rolling hills, draining W., through juniper and pinon.</p> <p>Leave trees, continue over rolling bench land.</p>

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian Utah

CHAINS	
42.33	<p>The $\frac{1}{4}$ sec. cor. of secs. 1 and 12, monumented with a sandstone, 8x8x14 ins., plainly mkd. $\frac{1}{4}$, with cedar post set alongside.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35S R5W $\frac{1}{4}$ $\frac{S}{S12}$ 1972</p> <p>Bury original cor. stone alongside the iron post.</p> <p>Bury glass at base of iron post.</p> <p>Set cedar post, 8 ins. diam., 6 ft. high alongside the cor.</p>
	<p>S. $89^{\circ} 31'$ W., beginning new measurement.</p> <p>Over brush covered bench, draining W.</p>
26.30	Wash, 6 ft. deep, 50 lks. wide, drains S. 10° W., about 2.00 chs., thence W.; small streamwater in wash.
35.60	Same wash, drains N. 15° W., from SE., small stream of water.
40.54	<p>The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, rolling.</p> <p>Soil, clay.</p> <p>Timber, juniper and pinon on E. portion.</p> <p>Undergrowth, shadscale and sagebrush.</p>
	<p>N. $1^{\circ} 54'$ E., bet. secs. 1 and 2.</p> <p>Over brush covered bench, draining W.</p>
4.00	Wash, 4 ft. deep, 40 lks. wide, drains W., small stream water.
10.50	Small wash, drains SW.
21.00	Base steep ascent, bears W. and SE.; asc. 150 ft. over SE. slope.
35.00	S. crest of low ridge, bears N. 80° E. and S. 80° W.; thence over ridge.
38.50	N. crest same ridge, bears N. 80° E. and S. 80° W.; desc. 20 ft. over N. slope.
40.03	<p>The $\frac{1}{4}$ sec. cor. of secs. 1 and 2, monumented with a trachyte stone, 8x10x14 ins., plainly mkd. $\frac{1}{4}$.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

T35S R5W

 $\frac{1}{4}$

S 2 | S 1

1972

Bury original cor. stone alongside the iron post.

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.
Cor. located in N. and S. fence line.

N. 2° 48' E., beginning new measurement.

Desc. 100 ft. over N. slope.

- 5.50 Base of steep descent, bears E. and W.; thence over small valley.
- 13.40 Wash, 4 ft. deep, 30 lks. wide, drains W.
- 20.70 Base of steep ascent, bears W. and SE.; asc. 150 ft. over S. slope.
- 29.20 Crest of ascent, bears E. and W. irregularly; thence over sandy bench.
- 39.35 The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp.

Land, broken.

Soil, gravelly.

Timber, scattered juniper on hill tops.

Undergrowth, shadscale and sagebrush.

From the standard cor. of secs. 34 and 35, on the S. bdy. of the Tp., previously described.

N. 0° 15' E., bet. secs. 34 and 35.

Over mountainous land, draining E., through scattered juniper and pinon.

- 1.40 Wash, drains S. 78° E.; asc. 100 ft. over S. slope.
- 8.00 Spur, slopes E.; desc. 50 ft. over N. slope.
- 12.80 Wash in ravine, drains E.; asc. 90 ft. over S. slope.
- 16.00 Enter brush covered bench; thence along gentle E. slope.
- 31.00 Wash, 3 ft. deep, 20 lks. wide, drains N. 65° E.; asc. 60 ft. over SE. slope.
- 39.80 The $\frac{1}{4}$ sec. cor. of secs. 34 and 35, monumented with a trachyte stone, 10x12x16 ins., plainly mkd. $\frac{1}{4}$.

At the cor. point

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W

$\frac{1}{4}$
S34|S35
1972

from which

A pine, 8 ins. diam., bears S. $78\frac{1}{2}^{\circ}$ W., 77 lks. dist., mkd. $\frac{1}{4}$ S34 BT.

Bury original cor. stone alongside the iron post.

N. $0^{\circ} 23'$ E., beginning new measurement.

Along gentle E. slope.

- 9.50 Graded dirt road, bears N. 85° W. and S. 79° E.
19.30 Small ravine, drains E.
34.80 Swale, drains E.
39.96 The cor. of secs. 26, 27, 34 and 35, monumented with a trachyte stone, 10x12x14 ins., plainly mkd. 1 notch on S. and 2 notches on E. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W

S27|S26

S34|S35

1972

Bury original cor. stone alongside the iron post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, mountainous.

Soil, gravelly.

Timber, scattered juniper and pinon.

Undergrowth shadscale and sagebrush.

From the true point for the cor. of secs. 25, 26, 35 and 36, previously described.

N. $89^{\circ} 34'$ W., bet. secs. 26 and 35.

Over river bottom land.

- 5.50 Fence, parallels highway.
7.00 Hard surface U.S. Highway No. 89, bears N. $17^{\circ} 09'$ E. and S. $17^{\circ} 09'$ W.
8.30 Fence, parallels highway, also base of hills, bears N. and S. irregularly; asc. 150 ft. over general E. slope.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian. Utah

CHAINS

40.08

The $\frac{1}{4}$ sec. cor. of secs. 26 and 35, monumented with a trachyte stone, 10x10x14 ins., plainly mkd. $\frac{1}{4}$.

from which

A pine, 8 ins. diam., bears S. 45° E., 75 lks.
dist., mks. illegible.

A pine, 15 ins. diam., bears N. 80° W., 25 lks.
dist., mkd. $\frac{1}{4}$ S.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T35S R5W
S26
 $\frac{1}{4}$ $\frac{S26}{S35}$
1972

Bury original cor. stone alongside the iron post.

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

S. 88° 48' W., beginning new measurement.

Asc. 120 ft. over general E. slope.

35.00 Low spur, slopes SE.

39.00 Swale, drains SE.

40.64 The cor. of secs. 26, 27, 34 and 35.

Land, river bottom E. portion, mountain W. portion.

Soil, gravelly.

Timber, scattered juniper and pinon on hills.

Undergrowth, shadscale and sagebrush.

N. 0° 30' E., bet. secs. 26 and 27.

Over mountainous land, through timber; asc. 50 ft. over
S. slope.

9.10 Spur, slopes SE.

15.60 Small draw, drains S. 80° E.; asc. 110 ft. over S. slope.

21.10 Slope changes; thence along gentle E. slope.

30.40 Power line, bears N. 67° 44' E. and S. 67° 44' W.

33.20 Swale, drains N. 80° E.; asc. 80 ft. over S. slope.

39.84 The $\frac{1}{4}$ sec. cor. of secs. 26 and 27, marked by a pine, 10
ins. diam., mkd. 3 notches on N. and S. sides, also S $\frac{1}{4}$ on
N. side.

At the corner point, below the S $\frac{1}{4}$ on tree.

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins.
in the ground, with brass cap mkd.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian. Utah

CHAINS

T35S R5W

 $\frac{1}{4}$
S27|S26
1972

Place mound of rocks around tree and iron post.
from which

A pine, 8 ins. diam., bears S. 81° E., 22 lks.
dist., mkd. $\frac{1}{4}$ S26 BT.

A pine, 10 ins. diam., bears N. 78° W., 28 lks.
dist., mkd. $\frac{1}{4}$ S27 BT.

N. 0° 39' E., beginning new measurement.

Asc. 30 ft. over S. slope.

- 4.00 Spur, slopes E.; thence along general E. slope.
8.50 Small ravine, drains E.
20.50 Draw, about 80 ft. deep, drains E.
29.80 Trail road, bears E. and W.
34.50 Crest of steep descent, bears E. and W.; desc. 120 ft.
over N. slope.
39.90 The cor. of secs. 22, 23, 26 and 27, determined by
original bearing tree.

from which

A yellow pine, 24 ins. diam., bears S. 83° W., 130
lks. dist., blaze grown over, enough of the overgrowth
of this blaze was removed to make certain this was the
original bearing tree.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins.
in the ground, with brass cap mkd.

T35S R5W
S22|S23
S27|S26
1972

from which

A yellow pine, 30 ins. diam., bears S. 72° E., 31
lks. dist., mkd. T35S R5W S26 BT.

Raise a mound of boulders W. of cor. for water break.

Cor. located on N. edge of small wash in ravine, which
drains NE.

Land, mountainous.

Soil, rocky gravel.

Timber, pine and juniper.

Undergrowth, shadscale and sagebrush.

From the cor. of secs. 23, 24, 25 and 26.

S. 89° 04' W., bet. secs. 23 and 26.

Over highway right-of-way.

- 1.25 Hard surface U.S. Highway No. 89, bears N. 27° E. and

Dependent Resurvey, Subdivision,
T. 3 S. R. 5 W. S. 1 + 16 Sec. 23 and 26, U. 1

CHAINS

- 2.75 Fence, parallels highway, also base of hills; asc. 150 ft. over brush covered E. slope.
- 20.20 Point for the E. 1/16 sec. cor. of secs. 23 and 26, at proportionate distance.
Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
T35S R5W
E1/16 $\frac{S23}{S26}$
1972
Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.
Set a steel fence post alongside corner.
Asc. 100 ft. over E. slope.
- 29.50 Spur, slopes N. 50° E.; desc. 30 ft. over NW. slope.
- 32.30 Small ravine, drains N. 50° E.; asc. 110 ft. over NE. slope, enter timber.
- 40.40 The $\frac{1}{4}$ sec. cor. of secs. 23 and 26, monumented with a trachyte stone, 8x12x16 ins., plainly mkd. $\frac{1}{4}$. No original bearing trees located.
At the cor. point
Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
T35S R5W
 $\frac{1}{4}$ $\frac{S23}{S26}$
1972
Bury original cor. stone alongside the iron post.
from which
A pine, 12 ins. diam., bears N. $52\frac{1}{2}^\circ$ E., 35 lks. dist., mkd. $\frac{1}{4}$ S23 BT.
A pine, 14 ins. diam., bears S. 37° E., 25 lks. dist., mkd. $\frac{1}{4}$ S26 BT.
Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

S. $88^\circ 52'$ W., beginning new measurement.
Asc. 100 ft. over general E. slope.
- 33.50 Crest steep descent, bears NE. and SW.; desc. 100 ft. over NW. slope.
- 38.90 Wash, in draw, drains NE.
- 39.81 The cor. of secs. 22, 23, 26 and 27.
Land, mountainous.
Soil, gravelly.
Timber, juniper and pinon.
Undergrowth, shadscale and sagebrush.

N. $0^\circ 34'$ W., bet. secs. 22 and 23.
Over mountainous land; asc. 120 ft. along E. slope.
- 22.50 Slope changes; desc. 80 ft. over NE. slope.
- 27.30 Small draw, drains S. 65° E.; asc. 80 ft. over S. slope.
- 33.00 Spur, slopes S. 75° E.; desc. 40 ft. over N. slope.

Dependent Resurvey, Subdivision,
T. 35 S. R. 5 W. Salt Lake Meridian U a

CHAINS

- 35.70 Ravine, drains E.; asc. 70 ft. over S. slope.
39.40 The $\frac{1}{4}$ sec. cor. of secs. 22 and 23, monumented with a lava stone, 10x14x14 ins., plainly mkd. $\frac{1}{4}$.
from which

A pine, 8 ins. diam., bears S. 60° E., 15 lks.
dist., mkd. $\frac{1}{4}$ S.

A pine, 12 ins. diam., bears S. 30° W., 17 lks.
dist., mkd. $\frac{1}{4}$ S. (Record S. 45° W., 15 lks. dist.
mkd. $\frac{1}{4}$ S.).

t the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T35S R5W

$\frac{1}{4}$
S22|S23
1972

Bury original cor. stone alongside the iron post.

aise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

. 3° 44' E., beginning new measurement.

sc. gentle S. slope.

- 3.00 Spur, slopes E.; desc. 90 ft. over N. slope.
9.40 raw, drains E.; asc. 110 ft. over S. slope.
18.00 Spur, slopes E.; desc. 70 ft. over NE. slope.
24.50 raw, drains S. 40° E.; asc. 90 ft. over SW. slope.
29.00 Crest of ascent; thence along E. slope.
40.24 The cor. of secs. 14, 15, 22 and 23, monumented with a granite stone, 8x10x14 ins., mkd. 2 notches on E. and 3 notches on S. edges. Original bearing trees not found.

t the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T35S R5W

S15|S14
S22|S23
1972

from which

A pine, 9 ins. diam., bears S. 1° E., 47 lks.
dist., mkd. S23 BT.

Bury original cor. stone alongside the iron post.

aise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

and, mountainous.

Soil, rocky and gravelly.

Timber, pinon and juniper.

Undergrowth, shadscale and sagebrush.

From the cor. of secs. 13, 14, 23 and 24.

S. 88° 10' W., bet. secs. 14 and 23.

Over pasture land in valley bottom.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian. Utah

CHAINS

- 14.30 Sevier River, 1 ft. deep, 40 lks. wide, drains N. 10° W.
- 21.10 U.S. Highway No. 89, bears about N. 20° W. and S. 20° E.
- 23.60 Base of hills, bears N. 20° W. and S. 20° E.; asc. 240 ft. over E. slope.
- 39.97 Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23, at proportionate distance; there is no evidence of original cor.
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ in. diam., 24 ins. in the ground, with brass cap mkd.
- T35S R5W

$\frac{1}{4}$ $\frac{S14}{S23}$

1972
- Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
- Asc. gentle E. slope.
- 40.50 Spur, slopes N. 10° E.; desc. 100 ft. over NW. slope.
- 46.20 Draw, drains N. 55° E.; asc. 70 ft. over SE. slope.
- 49.10 Small spur, slopes S.; desc. 40 ft. over W. slope.
- 51.00 Same draw, drains S. 70° E.; asc. 320 ft. over E. slope.
- 70.00 Crest of steep ascent, bears N. and S. irregularly; asc. gentle E. slope.
- 79.94 The cor. of secs. 14, 15, 22 and 23.
- Land, valley E. portion, mountainous W. portion.
Soil, sandy in valley, gravelly on mountain.
Timber, juniper and pinon on mountains.
Undergrowth, grass in valley, shadscale and sagebrush.
-
- N. 0° 27' E., bet. secs. 14 and 15.
- Over mountainous land, draining E.
- 6.50 Ravine, about 60 ft. deep, drains E.
- 20.30 Ravine, about 50 ft. deep, drains E.
- 27.00 Crest steep descent, bears E. and W.; desc. 300 ft. over steep N. slope.
- 39.61 The $\frac{1}{4}$ sec. cor. of secs. 14 and 15, monumented with a volcanic stone, 8x12x16 ins., plainly mkd. $\frac{1}{4}$.
- from which
- A pine, 12 ins. diam., bears S. 30° E., 31 lks. dist., mkd. $\frac{1}{4}$ S BT. (Record, S. 45° E., 35 lks.)
- A dead mahogany, bears W., 20 lks. dist., mkd. $\frac{1}{4}$ S BT.
- At the cor. point
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins.

Dependent Resurvey, Subdivision,
T. 35 S. R. 5 W. Salt Lake Meridian Utah

CHAINS

in the ground, in a mound of stone, 4 ft. base to top,
with brass cap mkd.

T35S R5W

 $\frac{1}{4}$

S15|S14

1972

from which

A red cedar, 5 ins. diam., bears N. 10° E., 32 lks.
dist., mkd. $\frac{1}{4}$ BT.

Bury original cor. stone in mound, alongside the iron
post.

N. 0° 31' W., beginning new measurement.

Desc. 30 ft. over N. slope.

- 1.90 Wash in bottom of draw, drains E.; asc. 280 ft. over
steep S. slope.
- 15.00 High spur, slopes N. 60° E.; desc. 230 ft. over N. slope.
- 21.00 Draw, drains E.; asc. 120 ft. along general E. slope.
- 33.40 Spur, slopes N. 70° E.; desc. 200 ft. over steep N.
slope.
- 39.00 The cor. of secs. 10, 11, 14 and 15, monumented with a
granite stone, 10x14x18 ins. mkd. 4 notches on S. and
2 notches on E. edges.

from which

A pine, 18 ins. diam., bears N. 80° E., 15 lks.
dist., blaze grown over. (Record, N. 40° E., 25
lks. dist.)

A pine, 14 ins. diam., bears S. 70° E., 35 lks.
dist., mks. illegible.

A pine, 14 ins. diam., bears N. 80° W., 44 lks.
dist., blaze grown over. (Record, N. 75° W., 40
lks. dist.)

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins.
in the ground, in a collar of stone, with brass cap mkd.

T35S R5W

S10|S11

S15|S14

1972

from which

A pine, 12 ins. diam., bears N. 5° W., 8 lks.
dist., mkd. S 10 BT.

Place original cor. stone alongside the iron post.

Dependent Resurvey, Subdivision, T. 35 S., R. 5 W.,
Salt Lake Meridian, Utah

CHAINS

Land, mountainous.
Soil, rocky and gravelly.
Timber, pinon and juniper.
Undergrowth, shadscale and sagebrush.

From the cor. of secs. 11, 12, 13 and 14.

S. 88° 31' W., bet. secs. 11 and 14.

Over brush covered bench, draining W.

19.58 Fence, bears N. and S.

20.18 Point for the E. 1/16 sec. cor. of secs. 11 and 14, at proportionate distance.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W
 S11
E1/16 — S14
 1972

Raise a small mound of stone N. of cor.

32.40 Crest of terrace, bears N. and S.; desc. 80 ft. over W. slope of terrace.

38.00 Base of same terrace; thence over bench.

40.00 Trail road, bears NW. and SE.

40.36 The ¼ sec. cor. of secs. 11 and 14, monumented with a sandstone, 8x10x14 ins., dimly mkd. ¼, also cedar post alongside stone.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W
 S11
¼ — S14
 1972

Bury original cor. stone alongside the iron post.

Set cedar post, 8 ins. diam., 6 ft. high, alongside cor.

S. 83° 44' W., beginning new measurement.

Desc. 80 ft. over bench, draining W.

3.00 Trail road, bears N. and S.

17.60 Sevier River, 1 ft. deep, 60 lks. wide, flows N.

20.50 U.S. Highway No. 89, bears about N. and S.; asc. 60 ft. over E. slope.

Dependent Resurvey, Subdivision, T. 35 S., R. 5 W.,
Salt Lake Meridian, Utah

CHAINS	
29.00	Base of mountains, bears N. and S.; asc. 200 ft. over E. slope.
35.00	Slope changes; thence along steep N. slope.
39.23	The cor. of secs. 10, 11, 14 and 15.
	Land, bench on E. portion, mountains on W. portion. Soil, sandy clay E. portion, gravelly on mountains. Timber, juniper and pinon on mountains. Undergrowth, shadscale and sagebrush.
	N. 0° 41' W., bet. secs. 10 and 11.
	Over mountainous land, through timber; desc. 80 ft. over steep N. slope.
2.50	Wash in draw, drains N. 80° E.; asc. 140 ft. over SE. slope.
7.00	Spur, slopes E.; thence along steep E. slope.
11.00	Ravine, drains E.
20.00	Ravine, Drains E.
23.00	Spur, slopes E.; desc. 120 ft. over N. slope.
26.00	Draw, drains E.; asc. 120 ft. along general E. slope.
36.00	Spur, slopes N. 50° E.; desc. 120 ft. over N. slope.
39.50	Ravine, drains N. 70° E.; asc. 50 ft. over S. slope.
41.43	Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 10 and 11.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T35S R5W $\frac{1}{4}$ W C S10 \uparrow S11 1972</p>
	from which
	A pine, 6 ins. diam., bears E. 20 lks. dist., mkd. BT.
	A pine, 12 ins. diam., bears S. 38° W., 48 lks. dist., mkd. $\frac{1}{4}$ S10 BT.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Witness cor. located on small spur, which slopes E.
42.31	True point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11, at midpoint, falls on steep bank of wash in small ravine, drains S. 80° E., and cannot be perpetuated. No evidence of original cor.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS		
	Asc. 180 ft. over S. slope.	
49.00	Spur, slopes E.; desc. 200 ft. along steep E. slope	
65.00	Draw, drains N. 60° E.; desc. 80 ft. along E. slope.	
82.00	Ravine, drains N. 80° E.; asc. 60 ft. over S. slope.	
84.62	Point for the cor. of secs. 2, 3, 10 and 11, determined by remains of original bearing trees.	
	from which	
	A pine, 12 ins. diam., bears S. 15° E., 37 lks. dist., mkd. S11 BT.	
	A pine, stump, 10 ins. diam., bears S. 56° W., 60 lks. dist., part of blaze still remaining.	
	Other bearing trees have been removed by wood haulers.	
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, in a collar of stone, to top, with brass cap mkd.	
	<div style="text-align: center;"> T35S R5W S 3 S 2 ——— S10 S11 1972 </div>	
	from which	
	A pine, 12 ins. diam., bears N. 30° E., 113 lks. dist., mkd. S2 BT.	
	A cedar, 4 ins. diam., bears east, 5 lks. dist., mkd. BT.	
	A pine, 5 ins. diam., bears N. 80° W., 31 lks. dist., mkd. BT.	
	Land, mountainous.	
	Soil, gravelly.	
	Timber, juniper and pinon.	
	Undergrowth, shadscale and sagebrush.	
	From the cor. of secs. 1, 2, 11 and 12.	
	N. 89° 51' W., bet. secs. 2 and 11.	
	Over brush covered bench, draining W., along E. and W. fence line.	
36.50	Trail road, bears NW. and SE.	
40.16	Fence cor., fence bears E., W. and S.	
40.59	The ¼ sec. cor. of secs. 2 and 11, monumented with a trachyte stone, 8x12x14 ins., plainly mkd. ¼, also fence cor.; fence bears E. and N.	
	At the cor. point	

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35S R5W $\frac{1}{4}$ $\frac{S\ 2}{S11}$ 1972</p> <p>Bury original cor. stone alongside the iron post.</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p> <hr/> <p>S. 88° 48' W., beginning new measurement.</p> <p>Continue over bench.</p>
2.30	Crest of terrace, about 50 ft. high, bears N. and S.
4.30	Base of same terrace, also trail road, bears N. and S.
9.40	Small canal, 4 ft. deep, 15 lks. wide, flows N.
15.00	Sevier River, 2 ft. deep, 60 lks. wide, drains N.
28.00	Hard surface U.S. Highway No. 89, bears about N. 26° 20' W. and S. 26° 20' E.
30.00	Base of mountains, bears N. 26° W. and S. 26° E.; asc. 160 ft. over E. slope.
39.40	<p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, bench on E. portion, mountain W. portion. Soil, clay on bench, gravelly on mountains. Timber, juniper and pinon on mountains. Undergrowth, shadscale and sagebrush.</p>
	<p>N. 2° 34' E., bet. secs. 2 and 3.</p> <p>Over mountainous land; asc. 20 ft. over S. slope.</p>
1.40	Spur, slopes E.; desc. 180 ft. over NE. slope.
18.00	Base of mountains, bears N. 25° W. and S. 25° E.; thence over valley.
23.00	Hard surface U.S. Highway No. 89, bears about N. 26° 20' W. and S. 26° 20' E.
38.20	Sevier River, 1 ft. deep, 60 lks. wide, flows N. 25° W., enter farm land.
39.57	<p>Point for the ¼ sec. cor. of secs. 2 and 3, at proportionate distance; there is no evidence of original cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

T35S R5W

 $\frac{1}{4}$
S 3|S 2
1972

Set cottonwood post, 8 ins. diam., 4 ft. high, alongside cor.

from which

A cottonwood tree, -22 ins. diam., bears S. 50° W.,
51 lks. dist., mkd. $\frac{1}{4}$ S3 BT.

Continue over farm and pasture land.

79.14 The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp.

Land, mountain S. portion, valley N. portion.
Soil, gravelly S. portion, clay N. portion.
Timber, juniper and pinon S. portion, cottonwood along river.
Undergrowth, shadscale, sagebrush and grass.

From the standard cor. of secs. 33 and 34, on the S. bdy. of the Tp., previously described.

N. 0° 23' E., bet. secs. 33 and 34.

Over mountain top, draining E.

21.80 Wash, 2 ft. deep, 10 lks. wide, drains S. 80° E.

32.50 Low spur, slopes E.

40.03 The $\frac{1}{4}$ sec. cor. of secs. 33 and 34, monumented with a volcanic stone, 12x12x16 ins., plainly mkd. $\frac{1}{4}$.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W

 $\frac{1}{4}$
S33|S34
1972

Bury original cor. stone alongside the iron post.

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

from which

A pine, 10 ins. diam., bears S. 43° E., 36 lks. dist., mkd. $\frac{1}{4}$ S34 BT.

A pine, 6 ins. diam., bears S. 75° W., 48 lks. dist., mkd. BT.

N. 0° 20' E., beginning new measurement.

Dependent Resurvey, Subdivision, T. 35 S., R. 5 W
Salt Lake Meridian, Utah

CHAINS

Along gentle E. slope.

2.00 Small ravine, drains E.

18.90 Ravine, drains E.

33.90 Trail road, bears N. 80° W. and E.

37.10 Power line, bears N. 67° 44' E. and S. 67° 44' W.

39.85 The cor. of secs. 27, 28, 33 and 34, monumented with a lava stone, 10x12x14 ins., mkd. 1 notch on S. and 3 notches on E. edges, set in a small mound of stone.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, in a collar of stone, with brass cap mkd.

T35S R5W

S28|S27

S33|S34

1972

from which

A pine, 8 ins. diam., bears N. 3° E., 31 lks. dist., mkd. S27 BT.

A pine, 6 ins. diam., bears S. 76° E., 30 lks. dist., mkd. S34 BT.

A pine, 5 ins. diam., bears N. 35° W., 32 lks. dist., mkd. S28 BT.

Bury original cor. stone alongside the iron post.

Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.

Land, mountain top.

Soil, gravelly.

Timber, patches of juniper and pinon.

Undergrowth, shadscale and sagebrush.

From the cor. of secs. 26, 27, 34 and 35.

N. 89° 48' W., bet. secs. 27 and 34.

Over mountain top, through timber; asc. 150 ft. over gradual E. slope.

35.50 Low spur, slopes SE.; desc. 50 ft. over SW. slope.

40.19 The ¼ sec. cor. of secs. 27 and 34, monumented with a volcanic stone, 6x8x14 ins., plainly mkd. ¼.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

Dependent Resurvey, Subdivision
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

T35S R5W
S27
 $\frac{1}{4}$ S34

1972

From which

A pine, 8 ins. diam., bears N. 50° W., 65 lks.
dist., mkd. $\frac{1}{4}$ S27 BT.

Bury original cor. stone alongside the iron post.

N. 89° 13' W., beginning new measurement.

Desc. 50 ft. over SW. slope.

- 2.90 Small draw, drains SE.; asc. 70 ft. over NE. slope.
9.00 Spur, slopes SE.; asc. 100 ft. over gradual E. slope.
33.70 Power line, bears N. 67° 44' E. and S. 67° 44' W.
40.22 The cor. of secs. 27, 28, 33 and 34.

Land, broken mountain top.
Soil, gravelly.
Timber, pinon and juniper.
Undergrowth, sagebrush.

N. 0° 20' E., bet. secs. 27 and 28.

Over mountain land, through scattered timber; along
general E. slope.

- 1.60 Small ravine, drains E.
12.50 Small draw, drains S. 70° E.
40.12 The $\frac{1}{4}$ sec. cor. of secs. 27 and 28, monumented with a
volcanic stone, 10x10x12 ins., plainly mkd. $\frac{1}{4}$. Original
bearing tree not found.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T35S R5W
 $\frac{1}{4}$
S28|S27
1972

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

Bury original cor. stone alongside the iron post.

Set steel fence post alongside the cor.

N. 0° 27' E., beginning new measurement.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

- Asc. 60 ft. over SW. slope of small hill.
- 9.00 Crest of ascent on W. slope of hill; desc. 150 ft. over NW. slope.
- 18.00 Base of descent, bears NE. and SW.; thence over brush covered canyon bottom.
- 21.80 Wash, 4 ft. deep, 20 lks. wide, drains N. 80° E.
- 26.00 Base of ascent, bears N. 80° E. and SW.; asc. 160 ft. over S. slope.
- 35.50 Slope changes; thence along E. slope.
- 39.97 The cor. of secs. 21, 22, 27 and 28, monumented with a sandstone, 6x12x16 ins., mkd. 2 notches on S. and 3 notches on E. edges.

from which

A pine, 18 ins. diam., bears N. 21° E., 181 lks.
dist., mkd. S22 BT. (Record N. 15° E., 1.70 lks. dis)

A pine, 16 ins. diam., bears S. 15° E., 65 lks.
dist., mkd. T35S R5W S27 BT.

A pine, 14 ins. diam., bears S. 45° W., 88 lks.
dist., mkd. S28 BT.

A pine, 12 ins. diam., bears S. 1° W., 2.35 lks.
dist., mkd. S28 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, in a collar of stone, with brass cap mkd.

T35S R5W
S21|S22
S28|S27
1972

from which

A pine, 12 ins. diam., bears N. 72½° E., 47 lks.
dist., mkd. S22 BT.

A pine, 6 ins. diam., bears S. 62½° W., 17 lks.
dist., mkd. BT.

Bury original cor. stone alongside the iron post.

Land, mountainous.

Soil, gravelly.

Timber, juniper and pinon.

Undergrowth, mostly sagebrush.

From the cor. of secs. 22, 23, 26 and 27.

N. 88° 22' W., bet. secs. 22 and 27.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	Over mountainous land, up wash in bottom of canyon.
3.50	Leave wash, continue up canyon bottom.
27.00	Wash, 3 ft. deep, 30 lks. wide, drains E. irregularly from S. 75° W. Also base of hills; asc. 130 ft. over SE. slope, leave canyon bottom.
38.00	Spur, slopes S.; desc. 20 ft. over SW. slope.
40.62	The $\frac{1}{4}$ sec. cor. of secs. 22 and 27, monumented with a volcanic stone, 12x12x16 ins., plainly mkd. $\frac{1}{4}$. from which A pine, 20 ins. diam., bears S. 45° W., 30 lks. dist., blaze grown over. A pine, 14 ins. diam., bears N. 70° E., 105 lks. dist., blaze grown over. At the cor. point Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;">T35S R5W $\frac{1}{4}$ $\frac{S22}{S27}$ 1972</div> Bury original cor. stone alongside the iron post. Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor. <hr style="width: 20%; margin: 20px auto;"/> S. 89° 49' W., beginning new measurement. Desc. 50 ft. over SW. slope.
4.00	Small draw, drains S.; asc. 200 ft. along an irregular S. slope.
27.00	Spur, slopes S.; desc. 100 ft. over W. slope.
33.50	Draw, drains S. 5° E.; asc. 110 ft. over E. slope.
40.10	The cor. of secs. 21, 22, 27 and 28. Land, mountainous. Soil, gravelly. Timber, pinon and juniper. Undergrowth, shadscale and sagebrush.
	 N. 1° 02' E., bet. secs. 21 and 22. Over mountainous land, through timber; asc. 30 ft. along E. slope.

Dependent Resurvey, Subdivision
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
14.50	Trail road on top of ridge, bears NE. and SW.; desc. 50 ft. along gentle W. slope on ridge top.
40.08	<p>The $\frac{1}{4}$ sec. cor. of secs. 21 and 22, monumented with a volcanic stone, 10x14x14 ins., plainly mkd. $\frac{1}{4}$.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35S R5W $\frac{1}{4}$ S21 S22 1972</p> <p>from which</p> <p style="padding-left: 40px;">A red cedar, 18 ins. diam., bears S. 30° E., 38 lks. dist., mkd. $\frac{1}{4}$ S22 BT.</p> <p>Bury the original cor. stone alongside the iron post.</p> <p>Set steel fence post alongside cor.</p> <hr/>
32.00	<p>N. $0^{\circ} 44'$ E., beginning new measurement.</p> <p>Along gentle W. slope, on top of ridge.</p> <p>Head of small ravine, drains W.</p>
40.17	<p>The cor. of secs. 15, 16, 21 and 22, monumented with a volcanic stone, 8x10x14 ins., plainly mkd. 3 notches on S. and E. edges.</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears S. 20° E., 140 lks. dist., mkd. T35S R5W S22 BT. (Record S. 20° E., 180 lks. dist.).</p> <p style="padding-left: 40px;">A pine, 14 ins. diam., bears S. 35° W., 137 lks. dist., mkd. S21 BT. (Record S. 35° W., 150 lks. dist.).</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35S R5W <u>S16 S15</u> <u>S21 S22</u> 1972</p> <p>Bury original cor. stone alongside the iron post.</p> <p>Raise a small mound of stone, N. of cor.</p> <p>Land, mountainous. Soil, gravelly. Timber, pinon and juniper. Undergrowth, sagebrush.</p>

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

From the cor. of secs. 14, 15, 22 and 23.

N. 88° 17' W., bet. secs. 15 and 22.

Over mountainous land, through timber; asc. 40 ft. over gentle E. slope.

7.00 Low spur, slopes SE.; desc. 30 ft. over SW. slope.

16.20 Small draw, drains S. 40° E.; asc. 130 ft. over E. slope

33.00 Top of ascent, bears N. and S.; thence over top of wide ridge.

41.53 The $\frac{1}{4}$ sec. cor. of secs. 15 and 22, monumented with a volcanic stone, 14x14x18 ins., plainly mkd. $\frac{1}{4}$.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W

$\frac{1}{4}$ $\frac{S15}{S22}$

1972

from which

A pine, 10 ins. diam., bears N. 3° W., 64 lks. dist., mkd. $\frac{1}{4}$ S15 BT.

Bury original cor. stone alongside the iron post.

Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.

N. 89° 26' W., beginning new measurement.

Asc. gentle E. slope on ridge.

10.00 Crest of ascent on wide ridge, bears N. and S.; desc. gentle W. slope on ridge.

27.00 Trail road in small flat, bears N. 25° W. and S. 25° E.

34.00 Top of small rise, bears N. and S.; desc. 40 ft. over W. slope.

40.17 The cor. of secs. 15, 16, 21 and 22.

Land, mountainous.

Soil, gravelly.

Timber, juniper and pinon.

Undergrowth, shadscale and sagebrush.

N. 0° 57' E., bet. secs. 15 and 16.

Over mountainous land, through timber; desc. 60 ft. along W. slope of ridge.

7.50 Dirt road, bears N. 80° W. and E.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

16.00 Small draw, drains N. 80° W.

40.11 The $\frac{1}{4}$ sec. cor. of secs. 15 and 16, monumented with a lava stone, 12x12x18 ins., plainly mkd. $\frac{1}{4}$.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

T35S R5W
 $\frac{1}{4}$
S16|S15
1972

from which

A pine, 5 ins. diam., bears N. 68° E., 17 lks. dist., mkd. BT.

Bury original cor. stone alongside the iron post.

Raise a small mound of stone, W. of cor.

N. 1° 27' E., beginning new measurement.

Desc. 150 ft. along steep W. slope of ridge.

40.07 The cor. of secs. 9, 10, 15 and 16, monumented with a lava stone, 8x12x18 ins., plainly mkd. 4 notches on S. and 3 notches on E. edges.

from which

A pine, 14 ins. diam., bears N. 10° E., 13 lks. dist., mkd. S10 BT. No other bearing trees found. (Record N. 2° E., 10 lks. dist.).

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W
S 9|S10
S16|S15
1972

from which

A pine, 10 ins. diam., bears S. 45° W., 59 lks. dist., mkd. S16 BT.

Cedar, 6 ins. diam., bears N. 59° W., 34 lks. dist., mkd. BT.

Place original cor. stone alongside the iron post.

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

Set steel fence post alongside the corner.

Land, mountainous.

Soil, gravelly.

Undergrowth, shadscale and sagebrush.

Timber, pinon and juniper.

From the cor. of secs. 10, 11, 14 and 15.

N. 86° 09' W., bet. secs. 10 and 15.

Over mountainous land, through timber; desc. 40 ft.
along steep N. slope.

3.00 Bottom of deep draw, drains NE. from S. 85° W. irregularly;
asc. 200 ft. along steep S. slope in bottom of draw.

35.00 Same draw, drains S. 85° E. irregularly; asc. 40 ft. along
steep N. slope.

40.89 The $\frac{1}{4}$ sec. cor. of secs. 10 and 15, monumented with a
granite boulder, 2x2x3 ft., plainly mkd. $\frac{1}{4}$ on N. side.

from which

A pine, 10 ins. diam., bears S. 20° E., 25 lks.
dist., mkd. $\frac{1}{4}$ S BT.

A pine, 14 ins. diam., bears N. 45° E., 30 lks.
dist., mkd. $\frac{1}{4}$ S BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam. 20 ins.
in the ground, in a collar of stone, with brass cap mkd.

T35S R5W

$\frac{1}{4}$ $\frac{S10}{S15}$

1972

from which

A pine, 14 ins. diam., bears N. 60° E., 32 lks.
dist., mkd. $\frac{1}{4}$ S10 BT.

Place original boulder alongside the iron post.

N. 89° 20' W., beginning new measurement.

Asc. 40 ft. over E. slope.

7.00 Top of flat ridge, bears N. and S.

11.20 Crest of rim, bears N. 30° E. and S. 30° W.; desc. 100
ft. over W. slope.

17.00 Base same rim; thence over small flat.

26.50 Ridge, bears N. and S.; desc. 200 ft. over steep W. slope.

Dependent Resurvey, Subdivision,
T. 35 S. R. 5 W. Salt Lake Meridian Utah

CHAINS	
39.18	<p>The cor. of secs. 9, 10, 15 and 16.</p> <p>Land, mountainous. Soil, gravelly. Timber, juniper and pinon. Undergrowth, shadscale and sagebrush</p>
	<p>N. 0° 41' E., bet. secs. 9 and 10.</p> <p>Over mountainous land, through timber; desc. 140 ft. along steep W. slope.</p>
39.96	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10, at proportionate distance. There is no evidence of original cor.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p>T35S R5W $\frac{1}{4}$ S 9 S10 1972</p>
	<p>from which</p>
	<p>A pine, 14 ins. diam., bears S. 88° E., 34 lks. dist., mkd. $\frac{1}{4}$ S10 BT.</p>
	<p>A pine, 10 ins. diam., bears N. 85° W., 41 lks. dist., mkd. $\frac{1}{4}$ S9 BT.</p>
	<p>Desc. 80 ft. along W. slope.</p>
45.00	<p>Mouth of draw, drains W.; asc. 70 ft. over SW. slope.</p>
50.20	<p>Spur, slopes W.; desc. 110 ft. over N. slope.</p>
56.00	<p>Draw, drains E. about 2.00 chs., thence N. irregularly; asc. 70 ft. along E. slope of ridge.</p>
64.00	<p>Bulldozed road, bears E. and W.</p>
79.92	<p>The cor. of secs. 3, 4, 9 and 10, monumented with a volcanic stone, 8x14x18 ins., mkd. 5 notches on S. and 3 notches on E. edges.</p>
	<p>from which</p>
	<p>A pine, 12 ins. diam., bears N. 16° E., 50 lks. dist., faint scribe mks. No other bearing tree located. (Record N. 15° E., 75 lks. dist.).</p>
	<p>A pine, 14 ins. diam., bears S. 31° E., 49 lks. dist., faint scribe mks. on blaze. (Record S. 30° E., 20 lks. dist.).</p>
	<p>At the cor. point</p>
	<p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

T35S R5W

$\frac{S\ 4}{S\ 9} \frac{S\ 3}{S10}$

1972

from which

A pine, 14 ins. diam., bears S. 34° W., 16 lks.
dist., mkd. S9 BT.

A pine, 12 ins. diam., bears N. 58° W., 36 lks.
dist., mkd S 4 BT.

Bury original cor. stone alongside the iron post.

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

Set steel fence post alongside corner.

Land, mountainous.

Soil, gravelly.

Timber, juniper and pinon.

Undergrowth, shadscale and sagebrush.

From the cor. of secs. 2, 3, 10 and 11.

S. $87^{\circ} 52'$ W., bet. secs. 3 and 10.

Over mountainous land, through timber; asc. 260 ft.
over steep E. slope.

12.50 High spur, slopes N.; desc. 250 ft. over W. slope.

24.40 Draw, drains N.; asc. 240 ft. over NE. slope.

39.06 The $\frac{1}{4}$ sec. cor. of secs. 3 and 10, monumented with a
volcanic stone, 8x10x14 ins., plainly mkd. $\frac{1}{4}$.

from which

A dead pine lying on ground, 10 in. diam., bears
N. 40° E., 30 lks. dist., mkd. $\frac{1}{4}$ S BT. No other
bearing trees found.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T35S R5W

$\frac{S\ 3}{\frac{1}{4}\ S10}$

1972

A pine, 10 ins. diam., bears N. 78° W., 39 lks.
dist., mkd. $\frac{1}{4}$ S3 BT.

A pine, 8 ins. diam., bears S. 50° W., 29 lks.
dist., mkd. $\frac{1}{4}$ S10 BT.

Bury original cor. stone alongside the iron post.

Dependent Resurvey, Subdivision.
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	Cor. located on top of spur, which slopes N.
	<hr/>
	S. 89° 56' W., beginning new measurement.
	Desc. 130 ft. over W. slope.
9.80	Draw, drains N. 20° E.; asc. 180 ft. over E. slope.
19.00	Trail road, bears N. and S.
21.00	Ridge, bears N. and S.; desc. 300 ft. over W. slope.
33.50	Trail road, bears N. and S.
35.70	Draw, drains N.; asc. 100 ft. over E. slope.
38.88	The cor. of secs. 3, 4, 9 and 10.
	Land, mountainous. Soil, gravelly. Timber, juniper and pinon. Undergrowth, shadscale and sagebrush.
	<hr/>
	N. 1° 14' E., bet. secs. 3 and 4. Over mountainous land, through timber; asc. 80 ft. along E. slope.
20.50	Top of ascent on E. side of ridge; desc. 220 ft. over NE. slope.
37.00	Base of steep descent, bears N. 30° W. and S. 30° E.
38.00	Wash in bottom of canyon, drains N. irregularly.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at proportionate distance. There is no evidence of original cor.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T35S R5W $\frac{1}{4}$ S 4 $\frac{1}{2}$ S 3 1972
	from which
	A lone ponderosa pine, 32 ins. diam., bears S. 12° 45' W., 115 lks. mkd. $\frac{1}{4}$ S4 BT.
	Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.
	Set steel fence post alongside the corner.
	Desc. 30 ft. down canyon, along E. side of wash.
42.00	Trail road, bears N. 10° W. and S. 10° E. in canyon bottom.
80.95	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the

Dependent Resurvey, Subdivision,
T. 35 S. R. 5 W. S. 1 E. M. 1 N. 100'

CHAINS

Tp., previously described.

Land, mountainous.

Soil, gravelly.

Timber, pinon and juniper.

Undergrowth, shadscale and sagebrush.

From the standard cor. of secs. 32 and 33, on the S. bdy. of the Tp., previously described.

N. 0° 36' E., bet. secs. 32 and 33.

Over broken mountain land, draining SE.; asc. 70 ft. over gentle SE. slope.

1.30 Graded dirt road, bears N. 47° W. and S. 47° E.

34.60 Wash, 2 ft. deep, 40 lks. wide, drains S. 34° E.

39.99 The $\frac{1}{4}$ sec. cor. of secs. 32 and 33, monumented with a volcanic stone, 12x14x18 ins., plainly mkd. $\frac{1}{4}$.

from which

A pine, 16 ins. diam., bears S. 8 $\frac{1}{2}$ ° E., 157 lks. dist., dimly mkd. $\frac{1}{4}$ S BT. Other bearing tree not found. (Record S. 8° E., 195 lks. dist.).

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W

$\frac{1}{4}$
S32|S33

1972

from which

A red cedar, 8 ins. diam., bears S. 47 $\frac{1}{2}$ ° E., 73 lks. dist., mkd. $\frac{1}{4}$ S33 BT.

Bury original cor. stone alongside the iron post.

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

N. 1° 04' E., beginning new measurement.

Asc. 60 ft. over gentle SE. slope.

22.50 Dirt road, bears N. 80° E. and S. 80° W., also small saddle, which bears E. and W.; desc. 40 ft. over gentle NE. slope.

40.17 The cor. of secs. 28, 29, 32 and 33, monumented with a volcanic stone, 10x12x16 ins., mkd. 1 notch on S. and 4 notches on E. edges.

At the cor. point

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W
S29|S28
S32|S33
1972

Bury original cor. stone alongside the iron post.

Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.

Land, rolling to broken mountain top.

Soil, gravelly.

Timber, scattered juniper and pinon.

Undergrowth, shadscale and sagebrush.

From the cor. of secs. 27, 28, 33 and 34.

N. $89^{\circ} 27'$ W., bet. secs. 28 and 33.

Over mountainous land, through scattered timber; asc. 70 ft. over gentle E. slope.

15.00 Dirt road, bears N. 40° W. and S. 40° E.

20.00 Small ravine, drains S.

26.50 Same road, bears N. 30° E. and S. 30° W.; desc. 60 ft. over gentle W. slope.

39.98 The $\frac{1}{4}$ sec. cor. of secs. 28 and 33, monumented with a lava stone, 8x10x14 ins., plainly mkd. $\frac{1}{4}$.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W
 $\frac{1}{4}$ S28
S33
1972

from which

A lone cedar, 12 ins. diam., bears N. 80° E., 21 lks. dist., mkd. $\frac{1}{4}$ S28 BT.

Bury original cor. stone alongside the iron post.

Raise a small mound of stone, N. of cor.

N. $89^{\circ} 27'$ W., beginning new measurement.

Over small brushy flat.

2.90 Small wash, drains N. 20° E.

5.09 Power line, bears N. $1^{\circ} 59'$ W. and S. $1^{\circ} 59'$ E.; asc. 140 ft. over gentle E. slope.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

32.20 Dirt road, on top of low ridge, bears N. 15° E. and S. 15° W.; desc. 50 ft. over W. slope.

37.50 Small wash, drains N.

38.00 Trail road, bears N. and S.

40.11 The cor. of secs. 28, 29, 32 and 33.

Land, mountainous.

Soil, gravelly.

Timber, scattered juniper and pinon.

Undergrowth, shadscale and sagebrush.

N. 1° 18' E., bet. secs. 28 and 29.

Over rolling mountain land, draining N., through scattered timber.

31.80 Wash, 3 ft. deep, 30 lks. wide, drains N. 25° E.

32.30 Graded dirt road, bears N. 25° E. and S. 25° W.

40.36 The $\frac{1}{4}$ sec. cor. of secs. 28 and 29, monumented with a volcanic stone, 6x10x18 ins., plainly mkd. $\frac{1}{4}$. Original bearing trees have been cut on by post haulers and campers and could not be identified.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W

$\frac{1}{4}$
S29 | S28
1972

from which

A red cedar, 18 ins., diam., bears S. 51½° W., 123 lks. dist., mkd. $\frac{1}{4}$ S29 BT.

Bury original cor. stone alongside the iron post.

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

N. 1° 15' E., beginning new measurement.

Asc. 70 ft. along gentle E. slope.

13.75 Power line, bears N. 41° 44' W. and S. 41° 44' E.

14.00 Top of small hill, about 3.00 chs. diam.; desc. 70 ft. along gentle E. slope.

40.24 The cor. of secs. 20, 21, 28 and 29, monumented with a lava stone, 8x12x18 ins., plainly mkd. 2 notches on S. and 4 notches on E. edges. Original bearing trees have probably been removed by wood haulers.

Dependent Resurvey, Subdivision,
T. 35 S. R. 5 W. Salt Lake Meridian, Utah

CHAINS

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W
S20|S21
S29|S28
1972

Bury original cor. stone alongside the iron post.

Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.

Land, rolling mountain.

Soil, gravelly.

Timber, scattered juniper and pinon.

Undergrowth, shadscale and sagebrush.

From the cor. of secs. 21, 22, 27 and 28.

N. $89^{\circ} 30'$ W., bet. secs. 21 and 28.

Over mountainous land, through juniper and pinon; asc. 50 ft. over E. slope.

- 3.50 Spur, slopes S.; desc. 90 ft. over SW. slope.
- 11.00 Small draw, drains S.; asc. 100 ft. over E. slope.
- 19.60 Trail road on top of ridge, bears N. 20° E. and S. 20° W. desc. 80 ft. over W. slope.
- 39.13 The $\frac{1}{4}$ sec. cor. of secs. 21 and 28, monumented with a lava stone, 10x12x18 ins., plainly mkd. $\frac{1}{4}$.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W
 $\frac{1}{4}$ S21
S28
1972

Bury original cor. stone alongside the iron post.

Set cedar post, 6 ins. diam., 5 ft. high alongside cor.

N. $88^{\circ} 37'$ W., beginning new measurement.

Desc. gentle SW. slope.

- 15.00 Rocky ravine, about 50 ft. deep, 1.00 chs. wide, drains N.; asc. gentle E. slope.
- 24.60 Graded dirt road, bears N. and S.
- 39.77 The cor. of secs. 20, 21, 28 and 29.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

Land, mountainous.
Soil, gravelly.
Timber, scattered juniper and pinon.
Undergrowth, shadscale and sagebrush.

N. 0° 21' E., bet. secs. 20 and 21.

Over rolling mountain land, through scattered timber;
along gentle E. slope.

- 7.00 Low spur, slopes E.
- 13.40 Wash, 2 ft. deep, 20 lks. wide, drains E.
- 30.00 Top of wide spur, slopes E.; desc. 60 ft. over N. slope.
- 37.90 Small ravine, drains N. 80° E.; asc. 50 ft. over S. slope.
- 39.89 The $\frac{1}{4}$ sec. cor. of secs. 20 and 21, monumented with a volcanic stone, 12x12x16 ins., plainly mkd. $\frac{1}{4}$.

from which

A pine, 14 ins. diam., bears N. 68° E., 56 lks. dist., mkd. $\frac{1}{4}$ S BT. Other bearing tree missing. (Record, N. 83° E., 54 lks. dist.).

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T35S R5W

$\frac{1}{4}$
S20|S21
1972

from which

A red cedar, 12 ins. diam., bears S. 45° W., 33 lks. dist., mkd. $\frac{1}{4}$ S20 BT.

Bury original cor. stone alongside the iron post.

Raise a small mound of stone, W. of cor.

N. 0° 46' E., beginning new measurement.

Asc. 20 ft. over S. slope.

- 2.50 Spur, slopes E.; desc. 70 ft. over N. slope.
- 8.50 Small ravine, drains N. 80° E.; thence over flat, through scattered timber.
- 38.00 Wash, 3 ft. deep, 40 lks. wide, drains N. 55° E.
- 40.13 The cor. of secs. 16, 17, 20 and 21, monumented with a volcanic stone, 8x12x14 ins., plainly mkd. 3 notches on S. and 4 notches on E. edges.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

from which

A pine, 30 ins. diam., bears S. 5° E., 166 lks. dist., blaze grown over. Other bearing tree not identified. (Record, S. 12° E., 170 lks. dist.)

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T35S R5W
S17|S16
S20|S21
1972

from which

A red cedar, 12 ins. diam., bears S. 59½° E., 109 lks. dist., mkd. S21 BT.

Bury original cor. stone alongside the iron post.

Land, mountain.

Soil, gravelly.

Timber, scattered juniper and pinon.

Undergrowth, shadscale and sagebrush.

From the cor. of secs. 15, 16, 21 and 22.

N. 88° 35' W., bet. secs. 16 and 21.

Over mountainous land, through timber; desc. 150 ft. over W. slope.

14.00 Small ravine, drains N. 63° W.

31.70 Small wash in valley bottom, drains N. 10° E.

37.00 Graded dirt road, bears N. 10° E. and S. 10° W.

40.11 The ¼ sec. cor. of secs. 16 and 21, monumented with a lava stone, 6x6x12 ins., plainly mkd. ¼.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W
¼ S16
S21
1972

from which

A red cedar, 14 ins. diam., bears N. 47° E., 83 lks. dist., mkd. ¼ S16 BT.

A pine, 14 ins. diam., bears S. 47° W., 71 lks. dist., mkd. ¼ S21 BT.

Bury original cor. stone alongside the iron post.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Saline Co., Mo.

CHAINS

Raise a small mound of stone N. of cor.

N. 89° 51' W., beginning new measurement.

Along gentle S. slope of small hill.

- 1.60 Low ridge, bears N. and S.; desc. 100 ft. Over W. slope.
- 8.30 Wash, 6 ft. deep, 40 lks. wide, drains N. 30° E.; asc. 140 ft. over E. slope.
- 19.00 Top of ascent, bears N. and S.; thence over rolling land.
- 36.20 Wash, 5 ft. deep, 60 lks. wide, drains N. 50° E.
- 39.23 The cor. of secs. 16, 17, 20 and 21.

Land, mountainous.

Soil, gravelly.

Timber, pinon and juniper.

Undergrowth, shadscale and sagebrush.

N. 1° 38' E., bet. secs. 16 and 17.

Over rolling mountainous land, draining E.

- 21.50 Wash in small ravine, drains N. 60° E.
- 40.61 The $\frac{1}{4}$ sec. cor. of secs. 16 and 17, monumented with a volcanic stone, 6x12x20 ins., plainly mkd. $\frac{1}{4}$.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W

$\frac{1}{4}$

S17|S16

1972

Place original cor. stone alongside the iron post.

Set cedar post, 6 ins. diam., 4 ft. high, alongside cor.

N. 0° 59' W., beginning new measurement.

Continue over rolling mountain land.

- 15.50 Wash, 3 ft. deep, 20 lks. wide, drains N. 40° E.
- 37.30 S. crest of rocky canyon, bears N. 75° E. and S. 20° W.; desc. 50 ft. over steep N. slope.
- 40.15 The cor. of secs. 8, 9, 16 and 17, monumented with a volcanic stone, 12x14x20 ins., plainly mkd. 4 notches on S. and E. edges. No original bearing trees identified.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian Utah

CHAINS

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W
S 8 | S 9
— S17 | S16
1972

from which

A pine, 8 ins. diam., bears N. 62° E., 44 lks. dist., mkd. S9 BT.

A pine, 14 ins. diam., bears N. 45° W., 30 lks. dist., mkd. T35S R5W S8 BT.

Bury original cor. stone alongside the iron post.

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

Land, mountainous.

Soil, gravelly.

Timber, pinon and juniper.

Undergrowth, shadscale and sagebrush.

From the cor. of secs. 9, 10, 15, and 16.

N. $89^{\circ} 51'$ W., bet. secs. 9 and 16.

Over mountainous land, through timber; desc. 100 ft. over W. slope.

8.50 Rocky wash, in canyon bottom, drains N. 10° W., asc. 70 ft. over NE. slope.

15.00 Wash, drains N.

16.50 Graded dirt road, bears N. and S.; asc. 100 ft. over E. slope.

25.00 Spur, slopes S. 20° E.; asc. 40 ft. along gentle S. slope

39.93 The $\frac{1}{4}$ sec. cor. of secs. 9 and 16, monumented with a volcanic stone, 8x12x16 ins., plainly mkd. $\frac{1}{4}$. Original bearing trees have been removed by wood haulers.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W
 $\frac{1}{4}$ S 9
— S16

1972

Bury original cor. stone alongside the iron post.

Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.

Dependent Resurvey, Subdivision,
T. 35 S. R. 5 W. Salt Lake Meridian. Utah

CHAINS

Set steel fence post alongside the corner.

N. 87° 45' W., beginning new measurement.

Asc. 40 ft. over E. slope.

- 6.00 Wide, range, bears N. 25° E. and S. 25° W.; thence along N. slope on top of ridge.
- 9.50 Small ravine, drains N. 25° E.
- 23.50 Spur, slopes N.; desc. 60 ft. over W. slope.
- 27.40 Small draw, drains N. 5° E.; asc. 40 ft. over E. slope.
- 30.50 Low spur, slopes N.; desc. 40 ft. over W. slope.
- 33.60 Small ravine, drains N.; asc. 40 ft. along N. slope.
- 40.67 The cor. of secs. 8, 9, 16 and 17.

Land, mountainous.

Soil, gravelly.

Timber, juniper and pinon.

Undergrowth, shadscale and sagebrush.

N. 0° 27' E., bet. secs. 8 and 9.

Over mountainous land, through timber; desc. 80 ft. over steep N. slope.

- 3.20 Deep ledgy draw, drains N. 70° E.; asc. 70 ft. over ledgy S. slope.
- 5.10 N. crest of draw, bears N. 70° W. and S. 70° E.; asc. 20 ft. along gentle E. slope.
- 20.00 Dirt road, bears N. 5° W. and S. 25° E.
- 39.91 The $\frac{1}{4}$ sec. cor. of secs. 8 and 9, monumented with a lava stone, 8x12x16 ins., plainly mkd. $\frac{1}{4}$. Original bearing trees have been destroyed.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W

$\frac{1}{4}$
S 8 | S 9
1972

from which

A cedar, 6 ins. diam., bears N. 85° W., 32 lks. dist., mkd. $\frac{1}{4}$ S8 BT.

A pine, 8 ins. diam., bears east, 16 lks. dist. mkd. $\frac{1}{4}$ S9 BT.

Bury original cor. stone alongside the iron post.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt La

CHAINS	
	N. 2° 05' W., beginning new measurement.
	Desc. 40 ft. along gentle E. slope
11.00	Top of low ridge, bears N. 5° E. and S. 5° W.; desc. 120 ft. along W. slope of ridge.
29.00	Small draw, drains N. 20° E.; desc. 60 ft. over NE. slope.
39.67	The cor. of secs. 4, 5, 8 and 9, monumented by a lava stone, 8x12x16 ins., plainly mkd. 5 notches on S. and 4 notches on E. edges. No original bearing trees could be identified.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T35S R5W S 5 S 4 S 8 S 9 1972 </div>
	from which
	A pine, 14 ins. diam., bears N. 40° E., 75 lks. dist., mkd. T35S R5W S4 BT.
	A cedar, 6 ins. diam., bears S. 78° E., 55 lks. dist., mkd. S9 BT.
	A pine, 10 ins. diam., bears S. 60° W., 33 lks. dist., mkd. T35S R5W S8 BT.
	A pine, 12 ins. diam., bears N. 75° W., 14 lks. dist., mkd. S5 BT.
	Bury original cor. stone alongside the iron post.
	Raise a small mound of stone, N. of cor.
	Land, mountainous.
	Soil, gravelly.
	Timber, pinon.
	Undergrowth, shadscale and sagebrush.
	From the cor. of secs. 3, 4, 9 and 10.
	N. 87° 16' W., bet. secs. 4 and 9.
	Over mountainous land, through timber; asc. 70 ft. over E. slope.
3.00	Trail road, on top of ridge, bears N. and S.; desc. 90 ft. over W. slope.
19.50	Wash in draw, drains N. 20° W.; asc. 80 ft. over gentle NE. slope.
22.40	Graded dirt road, bears N. 10° W. and S. 10° E.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

43.65

The $\frac{1}{4}$ sec. cor. of secs. 4 and 9, monumented with a sandstone 6x8x16 ins., plainly mkd. $\frac{1}{4}$.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T35S R5W} \\ \frac{\text{S } 4}{\text{S } 9} \\ \hline 1972 \end{array}$$

from which

A pine, 24 ins. diam., bears S. 40° W., 114 lks. dist., mkd. $\frac{1}{4}$ S9 BT.

Bury original cor. stone alongside iron post.

Raise a small mound of stone N. of cor.

Set steel fence post alongside the cor.

S. $88^\circ 53'$ W., beginning new measurement.

Over small flat, through trees

12.00 E. crest of rocky ravine, bears N. 10° E. and S. 10° W.; desc. 120 ft. over W. slope.

17.00 Bottom of ravine, drains N. 10° E., from forks which drain from S., SE. and W.; asc. 30 ft. along N. slope of small ravine, which drains from W.

30.60 Leave ravine, which curves to S.; asc. 80 ft. over NE. slope.

39.06 The cor. of secs. 4, 5, 8 and 9.

Land, mountainous.

Soil, gravelly.

Timber, juniper and pinon.

Undergrowth, shadscale and sagebrush.

N. $3^\circ 12'$ E., bet. secs. 4 and 5.

Over mountainous land, through timber; desc. 140 ft. over gentle N. slope.

37.60 Wash, 4 ft. deep, 30 lks. wide, drains N. 20° E.

40.04 Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5, at proportionate distance. There is no evidence of original corner.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	<div>T35S R5W</div> <div>$\frac{1}{4}$</div> <div>S 5 S 4</div> <div>1972</div>
	from which
	A pine, 10 ins. diam., bears S. 25° E., 152 lks. dist., mkd. $\frac{1}{4}$ S4 BT.
	A pine, 8 ins. diam., bears S. 75° W., 40 lks. dist., mkd. $\frac{1}{4}$ S5 BT.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Desc. 140 ft. over gentle N. slope.
60.00	Leave timber.
78.20	Graded dirt road, bears N. 85° W. and E., enter valley.
80.08	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., previously described.
	Land, mountainous. Soil, gravelly. Timber, pinon and juniper. Undergrowth, sagebrush and shadscale.
	<hr/>
	From the standard cor. of secs. 31 and 32, on the S. bdy. of the Tp., previously described.
	N. 0° 28' E., bet. secs. 31 and 32.
	Over barren mountain top; desc. 90 ft. over N. slope.
13.50	Dirt road in ravine, bears N. 60° E. and S. 60° W., ravine, drains N. 60° E.; asc. 90 ft. over S. slope.
26.00	Rise, bears N. 40° E. and W.; desc. 70 ft. over gentle N. slope.
39.70	Wash, 2 ft. deep, 10 lks. wide, drains N. 42° E.
39.92	The $\frac{1}{4}$ sec. cor. of secs. 31 and 32, monumented with a volcanic stone, 12x12x16 ins., plainly mkd. $\frac{1}{4}$.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div>T35S R5W</div> <div>$\frac{1}{4}$</div> <div>S31 S32</div> <div>1972</div>
	Bury original cor. stone alongside the iron post.
	Raise a small mound of stone, W. of cor.
	Set steel fence post alongside the corner.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

Corner located in swale, which drains NE.

N. $0^{\circ} 19'$ E., beginning new measurement.

Asc. 50 ft. over gentle SE. slope.

10.00 Rise, bears N. 80° E. and S. 80° W.; desc. 60 ft. over gentle NE. slope.

25.40 Small wash, drains E.; thence along gentle E. slope.

39.97 The cor. of secs. 29, 30, 31 and 32, monumented with a sandstone, $8 \times 10 \times 12$ ins., plainly mkd. 1 notch on S. and 5 notches on E. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W
S30|S29
S31|S32
1972

Bury original cor. stone alongside the iron post.

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

Land, rolling top of mountain.

Soil, gravelly.

Timber, none.

Undergrowth, shadscale and sagebrush.

From the cor. of secs. 28, 29, 32 and 33.

N. $88^{\circ} 39'$ W., bet. secs. 29 and 32.

Over rolling mountain land.

15.00 Rise, bears N. 20° E. and S.

21.30 Graded dirt road, bears N. 50° E. and S. 50° W., also small ravine, which drains NE.

40.82 The $\frac{1}{4}$ sec. cor. of secs. 29 and 32, monumented with a lava stone, $6 \times 12 \times 14$ ins., plainly mkd. $\frac{1}{4}$.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W
S29
 $\frac{1}{4}$ S32

1972

Bury original cor. stone alongside the iron post.

Raise a small mound of stone, N. of cor.

Dependent Resurvey, Subdivision,
T. 35 S. R. 5 W. Salt Lake Meridian Utah

CHAINS

S. 88° 55' W., beginning new measurement.

Over rolling mountain top.

- 23.00 Graded dirt road, bears N. 30° W. and S. 30° E.
31.20 Wash, 2 ft. deep, 20 lks. wide, drains S. 35° E.
40.21 The cor. of secs. 29, 30, 31 and 32.

Land, rolling mountains.
Soil, gravelly.
Timber, none.
Undergrowth, shadscale and sagebrush.

N. 88° 49' W., bet. secs. 30 and 31.

Over rolling mountain land; asc. 100 ft. over gentle NE. slope.

- 40.31 The $\frac{1}{4}$ sec. cor. of secs. 30 and 31, monumented with a lava stone, 8x8x16 ins., plainly mkd. $\frac{1}{4}$.

At the cor. point

Set an iron post 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W

$\frac{1}{4}$ $\frac{S30}{S31}$

1972

Bury original cor. stone alongside the iron post.

Raise a small mound of stone, N. of cor.

N. 89° 28' W., beginning new measurement.

Asc. gentle NE. slope.

- 32.20 Small ravine, drains N. 50° E.
35.00 Dirt road, bears S. 75° W. and N.
40.24 The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., previously described.

Land, rolling mountain.
Soil, gravelly.
Timber, none.
Undergrowth, shadscale and sagebrush.

From the cor. of secs. 29, 30, 31 and 32.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

N. 0° 29' E., bet. secs. 29 and 30.

Over rolling mountain land, draining E.

3.50 Wash, drains E. from SW.

8.00 Dirt road, bears N. 85° W. and S. 85° E.

35.90 Wash, 3 ft. deep, 20 lks. wide, drains N. 80° E.

39.91 The $\frac{1}{4}$ sec. cor. of secs. 29 and 30, monumented with a volcanic stone, 10x12x16 ins., plainly mkd. $\frac{1}{4}$.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W

$\frac{1}{4}$
S30|S29
1972

Bury original cor. stone alongside the iron post.

Set steel fence post alongside the corner.

N. 0° 17' E., beginning new measurement.

Continue over rolling mountain land.

6.10 Wash, 2 ft. deep, 30 lks. wide, drains S. 80° E.; asc. 50 ft. over S. slope.

13.00 S. crest of small terrace, bears N. 80° W. and S. 50° E.; thence over top of small bench.

29.00 N. crest of bench, bears N. 80° W. and S. 80° E.; desc. 40 ft. over gentle NE. slope.

40.06 The cor. of secs. 19, 20, 29 and 30, monumented by a volcanic stone, 12x16x20 ins., plainly mkd. 2 notches on S. and 5 notches on E. edges.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W

S19|S20
S30|S29
1972

Bury original cor. stone alongside iron post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Set steel fence post alongside the corner.

Land, rolling mountain.

Soil, gravelly.

Timber, none.

Undergrowth, shadscale and sagebrush.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	<p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 89° 29' W., bet. secs. 20 and 29.</p> <p>Over rolling mountain land, draining NE.</p>
15.00	Wash, 3 ft. deep, 20 lks. wide, drains N. 15° E.
24.01	Power line, bears N. 41° 44' W. and S. 41° 44' E.
40.49	<p>The $\frac{1}{4}$ sec. cor. of secs. 20 and 29, monumented with a lava stone, 8x10x14 ins., plainly mkd. $\frac{1}{4}$.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T35S R5W</p> <p>$\frac{1}{4}$ $\frac{S20}{S29}$</p> <p>1972</p> </div> <p>Bury original cor. stone alongside the iron post.</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.</p>
	<hr/> <p>S. 89° 56' W., beginning new measurement.</p> <p>Asc. gentle NE. slope.</p>
41.77	<p>The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, rolling mountain.</p> <p>Soil, gravelly.</p> <p>Timber, none.</p> <p>Undergrowth, shadscale and sagebrush.</p>
	<hr/> <p>N. 88° 41' W., bet. secs. 19 and 30.</p> <p>Over rolling mountain land; asc. gentle NE. slope.</p>
30.00	Top of rise, bears NW. and SE.; desc. gentle SW. slope.
40.19	<p>The $\frac{1}{4}$ sec. cor. of secs. 19 and 30, monumented with a volcanic stone, 8x8x12 ins., plainly mkd. $\frac{1}{4}$.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T35S R5W</p> <p>$\frac{1}{4}$ $\frac{S19}{S30}$</p> <p>1972</p> </div> <p>Bury original cor. stone alongside the iron post.</p>

Dependent Resurvey, Subdivision,
T. 35 S. R. 5 W. Salt Lake Meridian Utah

CHAINS

Raise a small mound of stone, N. of corner.

Set steel fence post alongside the corner.

N. 89° 07' W., beginning new measurement.

Asc. gentle NE. slope.

- 0.70 Wash, 2 ft. deep, 10 lks. wide, drains S. 60° E.
25.00 Same wash, drains N. 65° E.
32.30 Graded dirt road, bears N. 20° E. and S. 20° W.
38.00 Small wash, drains N. 50° E.
40.29 The cor. of secs. 19, 24, 25 and 30, on the W. bdy.
of the Tp., previously described.

Land, rolling mountain.

Soil, gravelly.

Timber, none.

Undergrowth, shadscale and sagebrush.

From the cor. of secs. 19, 20, 29 and 30.

N. 0° 25' E., bet. secs. 19 and 20.

Over broken mountain land, draining E.

- 6.00 Wash, 5 ft. deep, 60 lks. wide, drains N. 80° E.; asc.
120 ft. over SE. slope, enter timber.
24.00 Spur, slopes E.; desc. 60 ft. over NE. slope.
35.50 Small draw, drains E.; thence along gentle E. slope.
39.96 The $\frac{1}{4}$ sec. cor. of secs. 19 and 20, monumented with a
volcanic stone, 4x6x14 ins., plainly mkd. $\frac{1}{4}$.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T35S R5W
 $\frac{1}{4}$
S19|S20
1972

Bury original cor. stone alongside the iron post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of
cor.

Set cedar post, 6 ins. diam., 4 ft. high, alongside cor.

N. 0° 30' E., beginning new measurement.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5W., Salt Lake Meridian, Utah

CHAINS

Desc. 100 ft. along gentle E. slope.

16.70 Graded dirt road, bears N. 70° E. and S. 70° W.

27.80 Small wash, drains E.

40.12 The cor. of secs. 17, 18, 19 and 20, monumented with a volcanic stone, 14x14x18 ins., plainly mkd. 3 notches on S. and 5 notches on E. edges.

from which

A pine, 9 ins. diam., bears N. 32° E., 69 lks.
dist., mkd. S17 BT. (Record N. 21° E., 66 lks. dist.)

A pine, 8 ins. diam., bears S. 45½° E., 75 lks.
dist., mkd. S20 BT.

A pine, 12 ins. diam., bears S. 70° W., 18 lks.
dist., mkd. S19 BT. (Record, S. 61° W., 16 lks.
dist.).

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins.
in the ground, in a mound of stone, 4 ft. base to top,
with brass cap mkd.

T35S	R5W
S18	S17
S19	S20
1972	

from which

A pine, 8 ins. diam., bears N. 29° W., 48 lks.
dist., mkd. S18 BT.

Place original cor. stone in mound alongside the iron
post.

Land, mountain.

Soil, gravelly.

Timber, juniper and pinon on N. portion.

Undergrowth, shadscale and sagebrush.

From the cor. of secs. 16, 17, 20 and 21.

S. 89° 28' W., bet. secs. 17 and 20.

Over mountainous land, through scattered timber; asc.
80 feet over general NE. slope.

16.00 Wash, 4 ft. deep, 30 lks. wide, drains N. 15° E.

40.59 The ¼ sec. cor. of secs. 17 and 20, monumented with a
volcanic stone 8x10x14 ins., plainly mkd. ¼.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

T35S R5W

$$\frac{1}{4} \frac{S17}{S20}$$

1972

Bury original cor. stone alongside iron post.

Set cedar post, 6 ins. diam., 4 ft. high, alongside corner.

N. 89° 56' W., beginning new measurement.

Asc. 80 ft. over gentle E. slope.

6.22 Power line, bears N. 8° 03' W. and S. 8° 03' E.

27.10 Graded dirt road, bears N. 8° E. and S. 8° W.

41.92 The cor. of secs. 17, 18, 19 and 20.

Land, mountain.

Soil, gravelly.

Timber, pinon and juniper.

Undergrowth, shadscale and sagebrush.

N. 87° 46' W., bet. secs. 18 and 19.

Over mountainous land, through timber; asc. 70 ft. over gentle NE. slope.

22.50 Rise, bears N. and S.; thence along gentle N. slope.

38.60 Wash, 3 ft. deep, 20 lks. wide, drains N. 65° E.

40.23 The $\frac{1}{4}$ sec. cor. of secs. 18 and 19, monumented with a volcanic stone, 10x12x18 ins., plainly mkd. $\frac{1}{4}$.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, in a collar of stone, with brass cap mkd.

T35S R5W

$$\frac{1}{4} \frac{S18}{S19}$$

1972

from which

A red cedar, 5 ins. diam., bears S. 32° E., 43 lks. dist., mkd. $\frac{1}{4}$ S19 BT.

Place original cor stone alongside the iron post.

N. 89° 50' W., beginning new measurement.

Asc. 100 ft. over gentle E. slope.

40.01 The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., previously described.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

Land, mountainous.
Soil, gravelly.
Timber, juniper and pinon.
Undergrowth, shadscale and sagebrush.

From the cor. of secs. 17, 18, 19 and 20.

N. 0° 33' E., bet. secs. 17 and 18.

Over mountainous land, through timber; along gentle E. slope.

10.00 Wash, 2 ft. deep, 20 lks. wide, drains N. 25° E.

40.46 The $\frac{1}{4}$ sec. cor. of secs. 17 and 18, monumented with a volcanic stone, 10x12x16 ins., plainly mkd. $\frac{1}{4}$.

from which

A pine, 12 ins. diam., bears S. 80° E., 25 lks. dist., mkd. $\frac{1}{4}$ S BT.

A pine, 14 ins. diam., bears S. 60° W., 62 lks. dist., mkd. $\frac{1}{4}$ S BT. (Record, S. 60° W., 30 lks. dist.)

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W

$\frac{1}{4}$

S18|S17

1972

Bury original cor. stone alongside the iron post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

N. 1° 02' E., beginning new measurement.

Desc. 60 ft. over NE. slope.

5.50 S. crest of ledgy canyon, bears N. 80° E. and S. 50° W.; desc. 90 ft. over ledgy N. slope.

7.50 Wash in canyon bottom, drains N. 73° E.

8.40 Hard surface highway, bears N. 73° E. to Panguitch and S. 73° W. to Panguitch Lake; asc. 90 ft. over ledgy S. slope.

12.60 N. crest same canyon, bears N. 80° E. and S. 80° W.; thence along gentle E. slope.

39.73 The cor. of secs. 7, 8, 17 and 18, monumented with a volcanic stone, 8x12x14 ins., plainly mkd. 4 notches on S. and 5 notches on E. edges.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

from which

A pine, 12 ins. diam., bears S. 82° E., 67 lks.
dist., mkd. S 17 BT. (Record, S. 81° E., 70 lks.
dist.) No other bearing trees identified, having
probably been destroyed by wood haulers.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T35S R5W
 $\frac{S\ 7\ | S\ 8}{S18\ | S17}$
1972

from which

A pine, 10 ins. diam., bears N. $37\frac{1}{4}^{\circ}$ E., 31 lks.
dist., mkd. T35S R5W S8 BT.

Bury original cor. stone alongside the iron post.

Set steel fence post alongside corner.

Land, mountainous.

Soil, gravelly.

Timber, juniper and pinon.

Undergrowth, shadscale and sagebrush.

From the cor. of secs. 8, 9, 16 and 17.

S. $89^{\circ} 21'$ W., bet. secs. 8 and 17.

Over mountainous land, through timber; desc. 80 ft. over
ledgy W. slope.

3.20 Wash in bottom of rocky ravine, drains N. about 3.00
chs. thence NE.; asc. 100 ft. over ledgy E. slope.

5.50 W. crest of same ravine, bears N. and S.; thence over
rolling land.

16.00 Dirt road, bears N. 4° E. and S. 4° W.

40.96 Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17, at propor-
tionate distance. There is no evidence of original cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, in a collar of stone, with brass cap mkd.

T35S R5W
 $\frac{S\ 8}{S17}$
1972

Set steel fence post alongside the corner.

Corner located at N. end old gravel pit.

Asc. 120 ft. over gentle E. slope.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

- 46.60 Hard surface highway, bears N. 20° 30' E. to Panguitch,
and S. 20° 30' W. to Panguitch Lake.
- 58.52 Power line, bears N. 8° 03' W. and S. 8° 03' E.
- 64.80 Dirt road, bears N. 5° W. and S. 5° E.
- 81.92 The cor. of secs. 7, 8, 17 and 18.
- Land, mountainous.
Soil, gravelly.
Timber, pinon and juniper.
Undergrowth, shadscale and sagebrush.

N. 89° 10' W., bet. secs. 7 and 18.

Over mountainous land, through timber; asc. 140 ft.
over gentle E. slope.

- 30.70 Low ridge, bears N. and S.; desc. 40 ft. over W. slope.
- 34.20 Enter small dry natural lake.
- 40.46 The $\frac{1}{4}$ sec. cor. of secs. 7 and 18, monumented with a
volcanic stone, 6x8x14 ins., plainly mkd. $\frac{1}{4}$.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T35S R5W

$\frac{1}{4}$ $\frac{S\ 7}{S18}$
1972

Bury original cor. stone alongside the iron post.

Set steel fence post alongside the corner.

N. 88° 45' W., beginning new measurement.

Over small dry lake bed.

- 1.00 Leave lake bed; asc. 100 ft. over gentle E. slope.
- 19.00 Top of ascent, bears N. and S.; thence over rolling
mountain top.
- 40.02 The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of
the Tp., previously described.

Land, mountain.
Soil, gravelly.
Timber, juniper and pinon.
Undergrowth, shadscale and sagebrush.

From the cor. of secs. 7, 8, 17 and 18.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

N. 0° 30' E., bet. secs. 7 and 8.

Over mountainous land, through timber; desc. 70 ft. along E. slope.

17.50 Small ravine, drains NE.; asc. 30 ft. along E. slope.

34.00 Unimproved road, bears E. and W.

40.06 The $\frac{1}{4}$ sec. cor. of secs. 7 and 8, monumented with a volcanic stone, 8x10x14 ins., plainly mkd. $\frac{1}{4}$. No original bearing trees identified.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W

$\frac{1}{4}$
S 7 | S 8
1972

from which

A pine, 12 ins. diam., bears N. 29° E., 19 lks. dist., mkd. $\frac{1}{4}$ S8 BT.

A pine, 5 ins. diam., bears N. 83° W., 28 lks. dist., mkd. $\frac{1}{4}$ S7 BT.

Bury original cor. stone alongside the iron post.

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

Cor. located on point, which projects E.

N. 1° 37' W., beginning new measurement.

Desc. 90 ft. over NE. slope.

7.50 Draw, drains N. 40° E.; asc. 80 ft. along ledgy E. slope.

20.00 Crest of rim, bears N. 10° E. and S. 20° W.; desc. 80 ft. over gentle NE. slope.

39.90 The cor. of secs. 5, 6, 7 and 8, monumented with a volcanic stone, 8x12x16 ins., mkd. 5 notches on S. and E. edges.

from which

A pine, 12 ins. diam., bears N. $58\frac{1}{2}$ ° E., 13 lks. dist., mks. not legible.

A pine, 12 ins. diam., bears S. $39\frac{1}{2}$ ° E., 13 lks. dist., mkd. T35S R5W S8 BT.

A pine, 14 ins. diam., bears N. $7\frac{1}{2}$ ° W., 10 lks. dist., mks. not legible. No other bearing trees found.

Dependent Resurvey, Subdivision,
T. 35 S. R. 5 W. Salt Lake Meridian Utah

CHAINS

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, in a collar of stone, with brass cap mkd.

T35S R5W
 $\frac{S\ 6}{S\ 7} \frac{S\ 5}{S\ 8}$
 1972

from which

A pine, 12 ins. diam., bears S. $35\frac{1}{2}^\circ$ W., 51 lks. dist., mkd. S7 BT.

Bury original cor. stone alongside the corner.

Land, mountainous.

Soil, gravelly.

Timber, pinon and juniper.

Undergrowth, shadscale and sagebrush.

From the cor. of secs. 4, 5, 8 and 9.

S. $89^\circ 52'$ W., bet. secs. 5 and 8.

Over mountainous land, through timber; asc. 60 ft. over NE. slope.

7.50 Low spur, slopes N.; desc. 30 ft. over W. slope.

11.60 Wash, 2 ft. deep, 20 lks. wide, drains N.; thence along gentle N. slope, through scattered timber.

24.00 Wash, drains N.

25.60 Hard surface highway, bears N. $1^\circ 00'$ E. to Panguitch, and S. $1^\circ 00'$ W. to Panguitch Lake.

32.00 Panguitch City rifle range, in old gravel pit.

41.14 The $\frac{1}{4}$ sec. cor. of secs. 5 and 8, monumented with a lava stone, 6x8x14 ins., firmly set and dimly mkd. with a 4, the upper part of the $\frac{1}{4}$ has been broken off.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T35S R5W
 $\frac{1}{4} \frac{S\ 5}{S\ 8}$

1972

Bury original cor. stone alongside the iron post.

Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.

Set steel fence post alongside the corner.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah'

CHAINS	
	S. 89° 30' W., beginning new measurement.
	Asc. 80 ft. over gentle NE. slope.
9.60	Trail road, bears N. 80° E. and S.
17.20	Wash, 2 ft. deep, 20 lks. wide, drains N. 42 E.
27.72	Power line, bears N. 8° 03' W. and S. 8° 03' E.
29.00	Base of steep and ledgy ascent, bears N. and S.; asc. 130 ft. over steep and ledgy E. slope.
35.00	Point, projects N.; thence along N. slope.
40.37	The cor. of secs. 5, 6, 7 and 8.
	Land, mountainous. Soil, gravelly. Timber, juniper and pinon. Undergrowth, shadscale and sagebrush.
	N. 88° 56' W., bet. secs. 6 and 7.
	Over mountainous land, through timber; asc. 140 ft. over gentle NE. slope to corner.
26.50	Small ravine, drains N. 63° E.
38.41	Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7, at proportionate distance. There is no evidence of original corner.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T35S R5W $\frac{1}{4} \frac{S 6}{S 7}$ 1972
	from which
	A pine, 8 ins. diam., bears S. 80° W., 34 lks. dist., mkd. $\frac{1}{4}$ S7 BT.
	A pine, 10 ins. diam., bears N. 40° W., 23 lks. dist., mkd. $\frac{1}{4}$ S6 BT.
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	Asc. 80 ft. over gentle E. slope
52.10	Saddle on low ridge, bears N. and S.; desc. 40 ft. over gentle W. slope.
71.00	Small wash, drains N. irregularly.
77.02	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., previously described.
	Land, mountainous. Soil, gravelly. Timber, pinon and juniper. Undergrowth, shadscale and sagebrush.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

From the cor. of secs. 5, 6, 7 and 8.

N. 5° 10' E., bet. secs. 5 and 6.

Over mountainous land, through timber; along broken
and ledgy E. slope.

- 6.00 Point projects E.
11.40 Draw, drains E.
29.00 Draw, drains E.
39.91 The $\frac{1}{4}$ sec. cor. of secs. 5 and 6, monumented with a lava
stone, 6x12x16 ins., dimly mkd. $\frac{1}{4}$.

from which

A cedar, 14 ins. diam., bears W., 8 lks. dist.,
mkd. $\frac{1}{4}$ BT. No other bearing tree found.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 12 ins.
in the ground, in a mound of stone, 4 ft. base to top,
with brass cap mkd.

T35S R5W

$\frac{1}{4}$

S 6 $\frac{1}{2}$ S 5

1972

from which

A cedar, 20 ins. diam., bears N. 32° E., 53 lks.
dist., mkd. $\frac{1}{4}$ S5 BT.

Place original cor stone in mound alongside the iron post

Cor. located on crest of Volcanic ledge, facing E.

N. 3° 15' E., beginning new measurement.

Along E. slope, above volcanic rim.

- 9.50 Small draw, drains E.
18.15 Power line, bears N. 8° 03' W. and S. 8° 03' E.
28.00 Head of draw, drains E.; desc. 50 ft. over gentle NE.
slope.
40.90 The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of
the Tp., previously described.

Land, broken mountain.

Soil, gravelly.

Timber, juniper and pinon.

Undergrowth, shadscale and sagebrush.

Dependent Resurvey, Subdivision,
T. 35 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

General Description

Township 35 South, Range 5 West located about 1 mile south of Panguitch, Utah. The township consists mainly of mountain land, with the exception of a few small farms and pastures along the Sevier River, which enters the township on the south boundary of sec. 35, flows northward, leaving the township on the north boundary of sec. 3, U.S. Highway No. 89 generally parallels the Sevier River through the township. There are numerous other roads throughout the township used for recreation, post hauling and management of livestock. The timber on the township consists of pinon and juniper. The elevation of the township varies from about 6680 to 7800 feet above sea level.

The magnetic declination was read at a number of stations throughout the township and the average of the several readings was found to be 15° 30' E.

Blank Page

NAMES

CAPACITY

Surveying Technician

Surveying Aid

Surveying Aid

Surveying Aid

CERTIFICATE OF SURVEY

(I) ~~(XX)~~, Craig P. Sylvester

, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 5th d
of May , 19 72 . (I) ~~(XX)~~ have dependently resurveyed the exterior
and subdivisional lines of Township 35 South, Range 5 West,

of the Salt Lake Meridian, in the State of Utah , which
are represented in the foregoing field notes as having been executed by (me), ~~(XX)~~ and under (my
~~XXXX~~ direction; and that said survey has been made in strict conformity with said special instruc
tions, the Manual of Instructions for the Survey of the Public Lands of the United States, and i
specific manner described in the foregoing field notes.

March 9, 1973

(Date)

(Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL

Date

11th Feb 1974

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the dependent resurvey of the exterior and sub-
divisional lines of Township 35 South, Range 5 West, Salt Lake, Meridian
Utah

executed by Craig P. Sylvester, Supervisory Cadastral Surveyor
having been critically examined and found correct, are hereby approved.

FEB 11 1975

(Date)


(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

, is a true copy of the original field notes.

Blank

Page

Blank

Page

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL
FIELD NOTES
of the

DEPENDENT RESURVEY OF

A PORTION OF THE WEST BOUNDARY,

A PORTION OF THE SOUTH BOUNDARY AND

A PORTION OF THE SUBDIVISIONAL LINES

OF

TOWNSHIP 36 SOUTH, RANGE 5 WEST

Of the Salt Lake Meridian,

In the State of Utah

EXECUTED BY

H. Dennis Badger Supervisory Cadastral Surveyor

Under special instructions dated May 5, 1972, approved May 11, 1972

, which provided for the surveys included under U.S. Survey Group
number 535, and assignment instructions dated June 14, 1972

Survey commenced September 18, 1972

Survey completed November 3, 1972

INDEX DIAGRAM

Township 36 South , Range 5 West ,

	59		58		45		34		24		17	
10	6		57	5	44	4	33	3	23	2	16	1
	56			56		43		32		22		15
9	7		55	8	42	9	31	10	22	11	14	12
	54			53		41		30		21		14
8	18		52	17	40	16	29	15	20	14	13	13
	52			51		39		28		19		
7	19		50	20	38	21	27	22		23	12	24
	49			48		37						
6	30		47	29	36	28		27		26		25
	46			45		35		26				
	31			32	34	33	25	34	18	35		36
						4		3		2		

Township 36 South, Range 5 West, Salt Lake Meridian, Utah

CHAINS

T. 36 S., R. 5 W.

History of Surveys

Surveyed by Retr. or Resurveyed by

NORTH BOUNDARY (Seventh Standard Parallel South)

All	T. C. Bailey	1874	
E. 10.08 chs.			E. Bird 1925

SOUTH BOUNDARY

W. 5 miles	T. C. Bailey	1874	
			A. J. Stewart 1883
E. 1 mile	A. J. Stewart	1883	
			E. Bird 1925
S. bdy., Sec. 33			A. B. Lewis 1897

EAST BOUNDARY

N. 3 miles	T. C. Bailey	1874	
			E. Bird 1925
S. 3 miles	E. Bird	1925	

WEST BOUNDARY (Panguitch Guide Meridian)

All	T. C. Bailey	1874	
All			A. J. Stewart 1883
All			A. B. Lewis 1897

SUBDIVISIONS

All except portions of secs. 24, 25 and 36	T. C. Bailey	1874
Portions Secs. 24, 25 and all 36	E. Bird	1925

The following field notes are those of the dependent re-survey of a portion of the west boundary, a portion of the south boundary and a portion of the subdivisional lines of Township 36 South, Range 5 West. The dependent resurvey was executed in accordance with the specifications as set the Special Instructions dated May 5, 1972, Group No. 535, Utah.

The lines of this dependent resurvey were determined by altitude observations of the sun and hour angle observations of Polaris and carried forward with sustained angulation. The distances were determined by chaining and triangulation.

Before restoring the corners, the lines of the original survey were retraced and a diligent search made for any evidence of the original corners, or other calls of the original field note record. The rules of proportionate measurement were applied to ascertain the position of the lost corners, but not until exhausting every reasonable possibility of finding direct evidence for the control of each particular corner.

The geographic position for the southeast corner of the Section 35 is at Latitude 37° 37' 45" N. and Longi-

Townshi 36 South Range 5 West, Salt Lake Meridian a a

CHAINS

tude $112^{\circ} 22' 37''$ W. as determined by scaling from U.S.G.S topographic map Hatch, Utah, 7 1/2' series.

The magnetic declination was found to be $15^{\circ} 15'$ East.

Dependent Resurvey of a Portion of the South Boundary, Township 36 South, Range 5 West, Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by T. C. Bailey, Deputy Surveyor, in 1874, and the Resurvey Executed by A. J. Stewart, Deputy Surveyor, in 1883

Beginning at the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., a sandstone, $16 \times 8 \times 5$ ins., firmly set 6 ins. in the ground and plainly mkd. 1 notch on E. and 5 notches on W. edges.

from which the original bearing trees:

A pinon, 6 ins. diam., bears S. 50° E., 13 lks. dist., mkd. S1 BT. (Record, S. 80° E., 10 lks.)

A pinon, 10 ins. diam., bears S. 45° W., 41 lks. dist., mkd. S2 BT. (Record, S. 37° W., 45 lks.)

A juniper, 15 ins. diam., bears N. 45° W., 61 lks. dist., mkd. S35 BT. (Record NW., 3 lks.)

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T36S R5W

S35|S36

S2|S1

T37S R5W

1972

Bury original cor. stone alongside iron post.

N. $89^{\circ} 38'$ W., bet. secs. 2 and 35.

Over rolling land through pinon and juniper, along fence line. Desc. 250 ft. over W. slope.

21.50 Trail road, bears N. 10° E. and S. 10° W.

34.50 Wash, drains irregularly N. 42° W.

39.95 The $\frac{1}{4}$ sec. cor. of secs. 2 and 35, which is marked by the cor. of N., E., and W. fences. This position is harmoniously related to existing original corners, and is accepted as the best existing evidence of the position of the original cor.

Dependent Resurvey of a Portion of the South Boundary,
Township 36 South, Range 5 West, Salt Lake Meridian, Utah

CHAINS

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, in a collar of stone, with brass cap mkd.

T36S R5W
 $\frac{1}{4}$ $\frac{S35}{S2}$
T37S R5W
1972

N. $89^{\circ} 38'$ W., beginning new measurement.

Continue over rolling land through pinon and juniper, ' along fence line.

- 1.40 Trail road, bears N. 40° E. and S. 35° E.
- 29.30 Wash, drains irregularly N. 40° W.
- 40.24 The cor. of secs. 2, 3, 34 and 35, monumented with a sandstone, 18x8x4 ins., firmly set 6 ins. in the ground, at the cor. of N., S. and E. fences, plainly mkd. 2 notches on E. and 4 notches on W. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins.
in the ground to solid rock, in a mound of stone, 3 ft.
base to top, with brass cap mkd.

T36S R5W
 $\frac{S34}{S3} \frac{S35}{S2}$
T37S R5W
1972

Place original cor. stone in mound of stone alongside the iron post.

N. $89^{\circ} 24'$ W., bet. secs. 3 and 34.

Over rolling land through dense pinon and juniper.

- 12.60 Trail road, bears N. 20° W. and S. 10° E.
- 29.20 Wash, drains N.
- 38.60 Trail road, bears N. 10° W. and S. 10° E.
- 39.80 W. edge of wash, 15 lks. wide, 5 ft. deep, drains N.
- 39.92 The $\frac{1}{4}$ sec. cor. of secs. 3 and 34, monumented with a sandstone, 14x10x3 ins., firmly set 6 ins. in the ground and plainly mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the South Boundary,
Township 36 South, Range 5 West, Section 34, T36S R5W S34

CHAINS

T36S R5W

$$\frac{1}{4} \frac{S34}{S3}$$
T37S R5W
1972

Bury original cor. stone alongside iron post and set a steel fence post, 6 ft. long, alongside.

Raise a mound of stone, 2 ft. base, 1 ft. high to N. of cor.

N. 89° 28' W., beginning new measurement.

Over hilly land through dense pinon, juniper and ponderosa.

19.96 Point for the W. 1/16 sec. cor. of secs. 3 and 34.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36S R5W

$$W1/16 \frac{S34}{S3}$$
T37S R5W
1972

Raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of cor.

32.80 Fence, bears N. and S.

32.94 Trail road, bears N. 15° W. and S. 40° W.

39.92 The cor. of secs. 3, 4, 33 and 34, monumented with a sandstone, 16x13x6 ins., firmly set 8 ins. in the ground at cor. of fences bearing N. and W., plainly mkd. 3 notches on E. and 3 notches on W. edges.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T36S R5W

$$\frac{S33|S34}{S4|S3}$$
T37S R5W
1972

Bury original cor. stone alongside iron post.

Reestablishment of the Survey Executed by T. C. Bailey, Deputy Surveyor, in 1874, the Resurvey Executed by A. J. Stewart, Deputy Surveyor, in 1883, and the Retracement Executed by Alfred B. Lewis, Deputy Surveyor, in 1897.

S. 89° 53' W., bet. secs. 4 and 33.

Dependent Resurvey of a Portion of the South Boundary,
T₁ 36 South Range 5 West. Salt Lake Meridian Utah

CHAINS

Over rolling land through sagebrush and scattered pinon and juniper, along a fence line.

20.00 Wash, drains N. 35° W.

38.90 Enter dense pinon and juniper.

40.17 The $\frac{1}{4}$ sec. cor. of secs. 4 and 33, monumented with a sandstone, 18x10x8 ins., firmly set 6 ins. in the ground, at cor. of fences bearing N., S. and E., plainly mkd. $\frac{1}{4}$ on W. face.

From which the original bearing trees:

A pinon, 14 ins. diam., bears S. 65° W., 15 lks. dist., blaze and dim scribe marks visible. (Record, S. 60° W., 12 lks.)

A pinon, 10 ins. diam., bears N. 13° W., 28 lks. dist., blaze and dim scrib marks visible. (Record, North.)

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36S R5W
 $\frac{1}{4}$ $\frac{S33}{S4}$
T37S R5W
1972

Bury original cor. stone alongside iron post.

N. 89° 13' W., beginning new measurement.

Continue over rolling land through dense pinon and juniper.

26.00 Descend over SW. slope.

31.11 Wash, at base of slope, drains N. 60° W.; asc. NE. slope.

39.81 The cor. of secs. 4, 5, 32 and 33, monumented with a sandstone, 18x16x7 ins., firmly set 6 ins. in the ground, and plainly mkd. 4 notches on E. and 2 notches on W. edges.

From which the original bearing trees:

A pinon, 12 ins. diam., bears S. 60° W., 99 lks. dist., mkd. BT. (Record, S. 65° W., 98 lks.).

A juniper stump, 6 ins. diam., bears N. 30° W., 27 lks. dist., mkd. BT. (Record, N. 31° W., 25 lks.)

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the South Boundary,
Township 36 South Range 5 West, Salt Lake Meridian, Utah

CHAINS

T36S R5W
S32|S33
S5|S4
T37S R5W
1972

Bury original cor. stone alongside iron post and set a steel fence post, 6 ft. long, alongside.

Dependent Resurvey of a Portion of the West Boundary,
(Panguitch Guide Meridian) Township 36 South, Range 5
West, Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by T. C. Bailey
and J. G. Burrill, Deputy Surveyor, in 1883, and the
Retracement Executed by Alfred B. Lewis, Deputy
Surveyor, in 1897.

The cor. of secs. 30 and 31, on W. bdy. of the Tp., a
sandstone, 10x8x6 ins., firmly set 8 ins. in the ground,
in old E. W. fence line, plainly mkd. 5 notches on N. and
1 notch on S. edges.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, in a collar of stone, with brass cap mkd.

T36S
R6W R5W
S36 |S30
|S31
1972

Bury original cor. stone alongside the iron post.

N. 0° 04' E., along W. bdy. of Sec. 30.

Over hilly land through sagebrush and scattered pinon
and juniper.

3.90 Ascend SW. slope.

14.65 Spur, slopes SE.; trail road, bears N. 25° W. and S. 40°
E.; desc. NE. slope.

34.40 Bottom of descent continue over sagebrush flat.

39.90 The W. ¼ sec. cor. of sec. 30 monumented with a mound of
stone, foreign to immediate area, 2 ft. base, 1½ ft.
high, no mkd. stone visible. This position is harmoniously
related to existing original corners and is accepted as
the best existing evidence of the position of the original
cor.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, in a collar of stone, with brass cap mkd.

Dependent Resurvey of a Portion of the West Boundary,
(Panguitch Guide Meridian) Township 36 South, Range 5
West Salt Lake Meridian Utah

CHAINS

T36S
R6W R5W
|
S30
1972

Set a 6 ft. steel fence post alongside iron post.

N. 0° 46' E., beginning new measurement.

Over nearly level land through sagebrush. By triangulation, topography scaled.

- 4.80 Wash, drains S. 70° E.
- 8.80 Limestone Creek, drains S. 50° E.; asc. about 300 ft. over SW. slope.
- 11.30 Trail road, bears N. 55° W. and S. 55° E.
- 36.85 Trail road on ridge, bears N. 75° W. and S. 60° E.; end triangulation.
- 39.84 The cor. of secs. 19 and 30, a granite stone, 12x10x10 ins., with top broken off, base firmly set 6 ins. in the ground plainly mkd. 4 notches on N. edge and only 1 notch remaining on S. edge.

From which the only remaining original bearing tree:

A juniper, 8 ins. diam., bears S. 75° W., 79 lks.
dist., mkd. T36S R6W S25 (Record, S. 70° W., 80 lks.)

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock and in a collar of stone, with brass cap mkd.

T36S
R6W R5W
| S19
S25 | S30
1972

From which

A juniper, 10 ins. diam., bears N. 81° E., 71 lks.
dist., mkd. T36S R5W S19 BT.

A juniper, 12 ins. diam., bears S. 51° E., 64 lks.
dist., mkd. T36S R5W S30 BT.

Bury original cor. stone alongside iron post and set a 6 ft. steel fence post alongside.

N. 1° 01' E., along W. bdy. of sec. 19.

Desc. NE. slope through scattered pinon and juniper.

- 10.60 Draw, drains S. 50° E. from N. 20° W.; asc. S. slope.
- 29.00 Top of low hill; desc. NW. slope.

Dependent Resurvey of a Portion of the West Boundary,
(Panguitch Guide Meridian) Township 36 South, Range 5
West, Salt Lake Meridian, Utah

CHAINS	
39.25	Wash, drains N. 70° E.
39.78	Point for the W. $\frac{1}{4}$ sec. cor. of sec. 19 at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam. 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T36S R6W R5W $\frac{1}{4}$ S19 1972 </div>
	Raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. and set a 6 ft. steel fence post alongside iron post.
	Continue over hilly land through scattered pinon and juniper.
44.55	Draw, drains S. 15° E. from N. 55° W.; asc. SW. slope.
50.00	Top of ascent; continue over small bench projecting E.
54.90	Graded dirt road, bears N. 55° W. and S. 55° E.
76.60	Draw, drains N. 55° E.
79.56	The cor. of secs. 18 and 19, monumented with a sandstone, 16x10x8 ins. firmly set 6 ins. in the ground, plainly mkd. 3 notches on N. and 3 notches on S. edges.
	At the cor. point
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	<div style="text-align: center;"> T36S R6W R5W S24 S18 S19 1972 </div>
	Bury original cor. stone alongside iron post and set a 6 ft. steel fence post alongside.
	N. 0° 56' W., along the W. bdy. of sec. 18.
	Over hilly land through dense juniper and pinon, by triangulation. Topography scaled.
8.60	Wash, drains irregularly E.; asc. 200 ft. over S. slope.
19.60	Ridge, bears E. and W.; desc. general N. slope.
27.60	Draw, drains E.
39.59	The W. $\frac{1}{4}$ sec. cor. of sec. 18, monumented with a granite stone, 14x10x8 ins., firmly set 6 ins. in the ground, plainly mkd. $\frac{1}{4}$ on W. face. End triangulation.

Dependent Resurvey of a Portion of the West Boundary,
(Panguitch Guide Meridian) Township 36 South, Range 5
West, Salt Lake Meridian, Utah

CHAINS

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T36S
R6W R5W
 $\frac{1}{4}$
|S18
1972

Bury original cor. stone alongside iron post and set a 6 ft. fence post alongside.

N. $0^{\circ} 08'$ E., beginning new measurement.

- 0.15 Wash, drains S. 75° E.; asc. S. slope.
- 8.30 Trail road, bears S. 60° E. and S. 80° W.
- 12.50 Trail road on spur, bears N. 40° E. and S. 60° W.; desc. NW. slope.
- 25.00 Draw, drains N.
- 35.00 Leave draw, drains N. 15° W.
- 39.80 The cor. of secs. 7 and 18, monumented with a granite stone, 16x12x6 ins., firmly set 8 ins. in the ground, plainly mkd. 2 notches on N. and 4 notches on S. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T35S
R6W R5W
S13 |S7
 |S18
 1972

Bury original cor. stone alongside the iron post.

N. $0^{\circ} 46'$ E., along the W. bdy. of sec. 7.

Over hilly land through dense pinon and juniper.

- 11.20 Wash, drains N. 60° E.; continue over bottom land through sagebrush.
- 24.70 Wash, drains S. 85° E.; asc. S. slope through dense pinon and juniper.
- 39.59 The W $\frac{1}{4}$ sec. cor. of sec. 7, a dead, fallen ponderosa, 16 ins. diam., blaze marks visible on partly rotted W. side, a point near the base where an old root system was visible was determined as the original cor. point.

from which an original bearing tree:

A pinon, dead and standing, 12 ins. diam., bears S. 72° W., 30 lks. dist., mkd. $\frac{1}{4}$ S BT (Record, S. 40° W., 35 lks.)

Dependent Resurvey of a Portion of the West Boundary,
(Panguitch Guide Meridian) Township 36 South, Range 5
West, Salt Lake Meridian, Utah

CHAINS

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock, and in a mound of stone, 5 ft. base to top, with brass cap mkd.

T36S R5W

$\frac{1}{4}$

|S7

1972

N. $0^{\circ} 21'$ E., beginning new measurement.

Continue ascent of S. slope through pinon and juniper.

1.00 Top of ascent, continue over rolling land through sagebrush.

36.60 Wash, drains N. 75° E.

40.62 The cor. of secs. 6 and 7, monumented with a mound of stone, $2\frac{1}{2}$ ft. base, 1 ft. high, no mkd. stone visible. This position is harmoniously related to existing original corners and is accepted as the best existing evidence of the position of the original cor.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, $3\frac{1}{2}$ ft. base to top, with brass cap mkd.

T36S

R6W R5W

|S6

|S 7

1972

N. $0^{\circ} 08'$ E., along the W. bdy. of sec. 6.

Over rolling land through sagebrush.

11.25 Trail road, bears N. 80° E. and S. 80° W.

21.50 Wash, drains N. 75° E.

40.23 The W. $\frac{1}{4}$ sec. cor. of sec. 6 monumented with a volcanic stone, 16x12x8 ins., firmly set 8 ins. in the ground, plainly mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.

Dependent Resurvey of a Portion of the West Boundary,
(Panguitch Guide Meridian) Township 36 South, Range 5
West, Salt Lake Meridian, Utah

CHAINS

T36S
R6W R5W
|
1/4
|S6
1972

Bury original cor. stone alongside iron post and set 6
ft. steel fence post alongside.

N. 0° 21' E., beginning new measurement.

- 1.10 Descend NE. slope.
- 8.70 Bottom of draw, drains S. 70° E.; asc. SW. slope through
pinon and juniper.
- 18.90 Top of ascent; continue over rolling land through sage-
brush.
- 21.00 Junction of trail road from E. with trail road bearing
S. 50° E. and N. 50° W.
- 40.09 Intersect the Seventh Standard Parallel South on the S.
bdy. of sec. 31, T. 35 S., R. 5 W., at the closing cor.
of Tp. 36 S., Rs. 5 and 6 W., monumented with a volcanic
stone 14x10x5 ins., firmly set 10 ins. in the ground,
plainly mkd. 6 notches on the S. and 6 notches on the E.
edges.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins.
in the ground, with brass cap mkd.

T35S R5W
S31
S1 | S6
C|C
R6W R5W
T36S
1972

Bury original cor. stone alongside iron post, raise
a mound of stone, 3 ft. base, 1½ ft. high, S. of cor.

From this cor., the standard cor. of Tp. 35 S., Rs. 5
and 6 W., a 2½ in. iron post, set, mkd. and witnessed
as described in the field notes of the concurrent re-
survey of T. 35 S., R. 5 W., bears N. 89° 36' W., 14.11 chs.
dist.

Dependent Resurvey of a Portion of the Subdivisional
Lines, of Township 36 South, Range 5 West, Salt Lake
Meridian, Utah

Reestablishment of the Survey Executed by T. C. Bailey
and J. G. Burrill, Deputy Surveyors, in 1874, and the
Resurvey Executed by Elliot Bird, U. S. Cadastral
Engineers, in 1925

Dependent Resurvey of a Portion of the Subdivisional

CHAINS

From the $\frac{1}{4}$ sec. cor. of secs. 23 and 24, an iron post, 1 in. diam., extending 5 ins. above ground, with brass cap mkd.

$\frac{1}{4}$
S23|S24
1925

N. $1^{\circ} 00'$ E., bet. secs. 23 and 24.

Over nearly level land through sagebrush, scattered pinon and juniper.

3.30 Wash, drains N. 40° W.

7.80 Wash, drains N. 45° W.

14.30 Ascend S. slope, through pinon and juniper.

20.03 Point for the N $1/16$ sec. cor. of secs. 23 and 24.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36S R5W
N $1/16$
S23|S24
1972

from which

A pinon, 10 ins. diam., bears N. $67^{\circ} 30'$ E., 16 lks. dist., mkd. N $1/16$ S24 BT.

A pinon, 12 ins. diam., bears S. $19^{\circ} 30'$ W., 67 lks. dist., mkd. N $1/16$ S23 BT.

25.00 Top of ascent, continue over rolling land through pinon and juniper.

31.00 Descend N. slope.

36.60 Bottom of descent.

38.40 Trail road, bears N. 55° W. and N. 80° E.

40.06 The cor. of secs. 13, 14, 23 and 24, monumented with a sandstone, $18 \times 6 \times 5$ ins., firmly set 10 ins. in the ground, in old fence line which bears N. $88^{\circ} 45'$ W. and S. $88^{\circ} 45'$ E., plainly mkd. 1 notch on E. and 3 notches on S. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36S R5W
S14|S13
S23|S24
1972

Bury original cor. stone alongside iron post.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

Reestablishment of the Survey Executed by T. C. Bailey
and J. G. Burrill, Deputy Surveyors, in 1874

N. 2° 19' W., bet. secs. 13 and 14.

Over rolling land through scattered pinon and juniper.

7.60 Top of low rise, covered with dense pinon and juniper.

25.45 Power line, bears N. 80° 33' W. and S. 80° 33' E.

29.65 Graded dirt road, on curve, bears S. 70° W. and S. 60° E.

39.64 The $\frac{1}{4}$ sec. cor. of secs. 13 and 14, monumented with a sandstone, 14x12x8 ins., firmly set 6 ins. in the ground, plainly mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36S R5W

$\frac{1}{4}$

S14|S13

1972

Bury original cor. stone alongside iron post and set a 6 ft. steel fence post alongside.

N. 2° 13' E., beginning new measurment.

Continue over rolling land through sagebrush and scattered juniper and pinon.

3.10 Wash, drains irregularly W.

23.90 Graded dirt road, bears S. 80° W. and N. 80° E.

39.06 The cor. of secs. 11, 12, 13 and 14, monumented with a badly weathered sandstone, 12x6x4 ins., firmly set in a collar of stone, no marks visible, foreign to the immediate area and is accepted as the best existing evidence of the original cor.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36S R5W

S11|S12

S14|S13

1972

Bury original cor. stone alongside iron post and set a 6 ft. steel fence post alongside.

From the cor. of secs. 12 and 13, on the E. bdy. of the

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Tp., a 2 in. iron post, extending 10 ins. above ground with brass cap mkd.</p> <div>T36S T36S R5W R4½W S12 S13 1925</div> <p>N. 89° 33' W., bet. secs. 12 and 13.</p> <p>Over rolling land through dense pinon, juniper and ponderosa.</p> <p>8.10 Trail road on curve, bears N. 50° W. and S. 65° E.</p> <p>30.40 Enter scattered pinon, juniper and ponderosa.</p> <p>40.00 Graded dirt road, curves N. 63° E. and S. 40° W.</p> <p>40.11 Point for the ¼ sec. cor. of secs. 12 and 13, as determined by an original bearing tree:</p> <p>A pinon, 26 ins. diam., bears N. 12° W., 166 lks. dist., mkd. ¼ S BT.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div>T36S R5W ¼ S12 S13 1972</div> <hr/> <p>S. 89° 25' W., beginning new measurement.</p> <p>Continue over rolling land through scattered juniper and pinon.</p> <p>18.55 Trail road, bears N. 70° W. and S. 70° E.</p> <p>27.85 Main wash, drains N. 75° W.</p> <p>32.10 Wash, drains N. 75° W.</p> <p>37.30 Wash, drains N. 75° W.</p> <p>38.90 Wash, drains N. 40° W.</p> <p>41.29 The cor. of secs. 11, 12, 13 and 14.</p>
	<p>N. 1° 05' W., bet. secs. 11 and 12.</p> <p>Over rolling land through sagebrush.</p> <p>2.18 Wash, drains N. 85° W.</p> <p>23.20 Trail road, bears N. 30° W. and S. 30° E.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
35.90	Wash, drains N. 40° W.
41.18	<p>The $\frac{1}{4}$ sec. cor. of secs. 11 and 12, monumented with a volcanic stone, 14x12x6 ins., firmly set 6 ins. in the ground, plainly mkd. $\frac{1}{4}$ on W. face.</p> <p>from which an original bearing tree:</p> <p>A pinon, 12 ins. diam., bears N. 30° W., 17 lks. dist., with overgrown blaze. (Record, NW. 15 lks.).</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T36S R5W</p> <p>$\frac{1}{4}$</p> <p>S11 S12</p> <p>1972</p> </div> <p>Bury original cor. stone alongside iron post.</p> <hr/> <p>N. 1° 11' E., beginning new measurement.</p> <p>Continue over rolling land through scattered pinon and juniper.</p>
27.60	Wash, drains irregularly W.
40.12	<p>The cor. of secs. 1, 2, 11 and 12, monumented with a volcanic stone, 24x15x10 ins., firmly set 10 ins. in the ground, plainly mkd. with 1 notch on E. and 5 notches on S. edges.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T36S R5W</p> <p><u>S2 S1</u></p> <p>S11 S12</p> <p>1972</p> </div> <p>Bury original cor. stone alongside iron post and set 6 ft. steel fence post alongside.</p> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.</p>
	<p>From the cor. of secs. 1 and 12, on the E. bdy. of the Tp., a 2 in. iron post, extending 10 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T36S T36S</p> <p>R5W R4½W</p> <p><u>S1</u> S5</p> <p>S12</p> <p>1925</p> </div> <p>N. 88° 39' W., bet. secs. 1 and 12.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

Over rolling land through dense juniper and pinon.

- 4.50 Trail road, bears N. 40° E. and S. 40° W.
7.30 Trail road, bears S. 55° E. and N. 55° W.
22.00 Wash, drains N. 50° W.
40.11 The $\frac{1}{4}$ sec. cor. of secs. 1 and 12, monumented with a sandstone, 12x9x5 ins., firmly set 5 ins. in the ground, plainly mkd. $\frac{1}{4}$ on N. face.

from which the original bearing trees:

A pinon, 8 ins. diam., bears S. 44° E., 14 lks. dist., mkd. $\frac{1}{4}$ S BT.

A pinon, 12 ins. diam., bears N. 43° 45' W., 14 lks. dist., dimly scribed $\frac{1}{4}$ S BT.

There is no record of these bearing trees.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36S R5W
 $\frac{1}{4}$ $\frac{S1}{S12}$
1972

Bury original cor. stone alongside iron post and set a 6 ft. steel fence post alongside.

Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.

N. 89° 37' W., beginning new measurement.

Continue over rolling land through sagebrush, scattered pinon and juniper.

- 5.00 Wash, drains N. 80° W.
6.00 Trail road, bears N. 35° W. and S. 35° E.
20.75 Wash, drains N. 35° W.
41.47 The cor. of secs. 1, 2, 11 and 12.

N. 1° 23' E., bet. secs. 1 and 2.

Over rolling land through sagebrush, scattered pinon and juniper.

- 22.55 Wash, drains N. 80° W.
27.30 Leave scattered timber.
40.09 The $\frac{1}{4}$ sec. cor. of secs. 1 and 2, monumented with a volcanic stone, 12x10x8 ins., firmly set 5 ins. in the ground plainly mkd. $\frac{1}{4}$ on W. face.

Dependent Resurvey of a Portion of the Subdivisional
Lines of Township 36 South, Range 5 West

CHAINS

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T36S R5W

$\frac{1}{4}$
S2|S1
1972

Bury original cor. stone alongside iron post and set
a 6 ft. fence post alongside.

N. $0^{\circ} 52'$ E., beginning new measurement.

Continue over rolling land through sagebrush.

2.00 Graded dirt road, curves S. 30° E. and N. 15° W

38.56 Intersect the Seventh Standard Parallel South on the
S. bdy. of Sec. 36, T. 35 S., R. 5 W., at the closing
cor. of secs. 1 and 2, monumented with a volcanic
stone, 14x12x4 ins., firmly set 6 ins. in the ground,
plainly mkd. CC on S. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T35S R5W

S36
S2|S1

C C

T36S R5W
1972

Bury original cor. stone alongside iron post.

From this cor., the standard cor. of secs. 35 and 36,
T. 35 S., R. 5 W., set, mkd. and witnessed as described
in the field notes of the concurrent resurvey of T. 35 S.
R. 5 W., bears N. $89^{\circ} 45'$ W., 10.29 chs. dist.

Point for the N. $\frac{1}{4}$ sec. cor. of sec. 1 on the N. bdy. of
the Tp., at midpoint longitudinally between the closing
cor. of secs. 1 and 2, and the NE. cor. of the Tp.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T35S R5W

$\frac{1}{4}$ S1
T36S R5W
1972

from which

A juniper, 12 ins. diam., bears S. 11° E., 44 lks.
dist., mkd. $\frac{1}{4}$ S 1 BT.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian Utah

CHAINS	
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor. and set a 6 ft. steel fence post alongside iron post.</p> <p>From this cor., the standard $\frac{1}{4}$ sec. cor. of secs. 36, T. 35 S., R. 5 W., a $2\frac{1}{2}$ in. iron post, set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 35 S., R. 5 W., bears N. $89^{\circ} 42'$ W., 10.12 chs.</p>
	<p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp.</p> <p>N. $0^{\circ} 55'$ E., bet. secs. 34 and 35.</p> <p>Over nearly level land through sagebrush, along fence line.</p>
14.00	Wash, drains N. 35° W.
19.75	Fence turns W., enter cultivated land.
20.00	<p>Point for the S. $\frac{1}{16}$ sec. cor. of secs. 34 and 35.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36S R5W S $\frac{1}{16}$ S34 S35 1972</p> <p>Set 6 ft. steel fence post alongside iron post.</p>
24.70	Trail road, bears S. 80° E. and N. 80° W.
31.50	Wash, drains N. 30° W.
40.00	<p>The $\frac{1}{4}$ sec. cor. of secs. 34 and 35, monumented with a sandstone, 10x8x5 ins., firmly set 5 ins. in the ground, in old E-W fence line, plainly mkd. $\frac{1}{4}$ on W. face.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36S R5W $\frac{1}{4}$ S34 S35 1972</p> <p>Bury original cor. stone alongside iron post.</p>
	<p>N. $0^{\circ} 10'$ E., beginning new measurement.</p> <p>Continue over cultivated land.</p>
3.10	Wash, drains N. 80° W.
40.12	Graded dirt road, bears E. and W.
40.32	The cor. of secs. 26, 27, 34 and 35, determined by the cor. of old fences bearing N. and W., this position is harmoniously related to existing original corners and is

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

accepted as the best existing evidence of the position
of the original cor.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, in a collar of stone, with brass cap mkd.

T36S R5W
S27|S26
S34|S35
1972

From the cor. of secs. 13, 14, 23 and 24, previously
described.

S. $89^{\circ} 38'$ W., bet. secs. 14 and 23.

Over rolling land through scattered pinon and juniper,
along fence line.

- 2.50 Trail road, curves N. 75° W. and S. 60° E.
- 19.50 Junction of trail road bearing N. 30° W. and S. 10° E.,
with trail road bearing N. 85° E. and N. 85° W.
- 20.29 Point for E. 1/16 sec. cor. of secs. 14 and 23.
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T36S R5W
S14
E 1/16 S23
1972

Continue along fence line.

- 40.20 Trail road, bears N. and S.
- 40.58 The $\frac{1}{4}$ sec. cor. of secs. 14 and 23, monumented with a
sandstone, 10x8x4 ins., firmly set 5 ins. in the ground,
at cor. of fences, extending E., N. and W.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T36S R5W
S14
 $\frac{1}{4}$ S23
1972

Bury original cor. stone alongside iron post.

S. $89^{\circ} 56'$ W., beginning new measurement.

Continue along fence line.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S. R. 5 W. Salt Lake Meridia U a

CHAINS

9.10 Small stream of water, 1 lk. wide, 2 ins. deep, flows
N. 60° W.

13.90 Wash, drains N.

40.10 The cor. of secs. 14, 15, 22 and 23, determined by the
intersection of E-W fence line, and an old abandoned
fence line to S. This position is harmoniously related
to existing original cors. and is accepted as the best
available evidence of the original cor.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T36S R5W

S15|S14

S22|S23

1972

N. 0° 40' E., bet. secs. 14 and 15.

Over bottom land through low brush and grass.

15.90 Spring branch, flows irregularly W.

19.00 Fence, bears E. and W.

20.40 Spring branch, flows S. 70° W.

23.50 Spring branch, flows W.

40.06 The ¼ sec. cor. of secs. 14 and 15, monumented with a
sandstone, 19x14x4 ins. firmly set 8 ins. in the ground,
plainly mkd. ¼ on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, in a collar of stone, with brass cap mkd.

T36S R5W

¼

S15|S14

1972

Bury original cor. stone alongside iron post and set a
6 ft. steel fence post alongside.

N. 0° 15' E., beginning new measurement.

Continue over gently rolling land through sagebrush.

2.00 Improved dirt road, bears N. 70° E. and S. 70° W.

20.03 Point for the N. 1/16 sec. cor. of secs. 14 and 15.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, and in a collar of stone, with brass cap
mkd.

Dependent Resurvey of a Portion of the Subdivisional
 Mining Tract Surveyed by the Salt Lake Meridian, Utah

CHAINS	
	<div>T36S R5W</div> <div>N 1/16</div> <div>S15 S14</div> <div>1972</div>
21.50	Fence line, bears E. and W.
25.10	Wash, drains S. 60° W.
28.20	Trail road, bears E. and W.
35.70	Wash, drains N. 70° W.
40.06	<p>The cor. of secs. 10, 11, 14 and 15, monumented with a sandstone, 10x6x4 ins., firmly set 5 ins. in the ground, at cor. of old fences that bear N. and W., no mks. visible, however, this cor. is harmoniously related to found original cors. and is accepted as the best existing evidence of the original cor.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div>T36S R5W</div> <div>S10 S11</div> <div>S15 S14</div> <div>1972</div> <p>Bury original cor. stone alongside iron post.</p>
	<hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 88° 32' W., bet. secs. 11 and 14.</p> <p>Over gently rolling land, through sagebrush.</p>
39.33	<p>The ¼ sec. cor. of secs. 11 and 14, monumented with a sandstone, 14x10x8 ins., firmly set 6 ins. in the ground, plainly mkd. ¼ on W. face.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div>T36S R5W</div> <div>S11</div> <div>¼ S14</div> <div>1972</div> <p>Bury original cor. stone alongside iron post and set a 6 ft. steel fence post alongside.</p>
	<hr/> <p>N. 89° 51' W., beginning new measurement.</p> <p>Continue over gently rolling land through sagebrush.</p>
31.70	Graded dirt road, bears N. 10° E. and S. 10° W.
32.20	Wash, drains S. 30 lks., thence SW.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
40.60	The cor. of secs. 10, 11, 14 and 15.
	N. 0° 19' E., bet. secs. 10 and 11.
	Over nearly level land through low brush, along fence line.
40.00	Dirt road, bears E. and W.
40.26	The $\frac{1}{4}$ sec. cor. of secs. 10 and 11, determined by the cor. of old fences, bearing E., W., and S.; this position is related to existing original cors. and is accepted as the best existing evidence of the original cor. position.
	At the cor. point
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T36S R5W $\frac{1}{4}$ S10 S11 1972</p>
	N. 0° 05' E., beginning new measurement.
	Over bottom land, and across the Sevier River
	By triangulation and traverse, topography scaled.
8.00	Wash, drains N. 60° E.
18.00	Sevier River, 70 lks. wide, 3 ft. deep, flows N. from irregularly W.
24.00	Sevier River, flows N. 30° E.
30.00	Sevier River, flows N. 60° W.
34.00	Sevier River, flows S. 40° E. from SW.
36.00	Sevier River, flows irregularly N.
39.62	True point for the cor. of secs. 2, 3, 10 and 11, at proportionate distance, falls in the Sevier River; no remaining evidence of the original cor. End triangulation and traverse.
	From this point, the witness cor. of secs. 2, 3, 10 and 11 bears N. 89° 48' E., 98 lks. dist., hereinafter described.
	From the cor. of secs. 1, 2, 11 and 12.
	S. 89° 48' W., bet. secs. 2 and 11.
	Over rolling land through sagebrush.
24.55	Wash, drains irregularly N. 35° W.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

39.84 Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11, at proportionate distance, there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36S R5W

$\frac{1}{4}$ $\frac{S2}{S11}$
1972

Set a 6 ft. steel fence post, alongside iron post.

Continue over gently rolling land through sagebrush.

44.00 Wash, drains N. 70° W.

47.95 Improved dirt road, bears N. 7° E. and S. 7° W.

60.04 Fence, bears S. and N. 65 lks. to cor., thence W.

78.70 Point for the witness cor. of secs. 2, 3, 10 and 11.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36S R5W
W $\frac{S3}{S10}$ | $\frac{S2}{S11}$
C $\frac{S10}{S11}$
1972

Set 6 ft. steel fence post alongside iron post.

79.06 E. bank of the Sevier River, bears N. 40° W. and S. 40° E.

79.68 Point for cor. of secs. 2, 3, 10 and 11.

N. $0^\circ 35'$ E., bet. secs. 2 and 3.

Over level river bottom, down river, by triangulation.

0.74 End of fence from E., bears East 13 lks. dist.

3.25 Leave Sevier River, flows N. 75° E.

13.80 U.S. Highway No. 89, bears N. $32^\circ 15'$ E. and S. $32^\circ 15'$ W.

Asc SE. slope.

19.70 End triangulation.

20.19 Right-of-Way fence, parallels U.S. Highway No. 89.

22.70 Top of low hill; desc. N. slope.

32.00 Trail road, bears E. and W.

37.00 Wash, drains S. 70° E.

39.63 Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, at propor-

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

tionate distance; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T36S R5W

$\frac{1}{4}$
S3|S2
1972

Set a 6 ft. steel fence post alongside the iron post.

Asc. S. slope, through sagebrush.

43.10 Top of ascent, desc. N. slope.

46.30 Draw, drains S. 35° E.

76.90 Wash, drains S. 30° E.; asc. S. slope.

79.26 Intersect the Seventh Standard Parallel South, on the S. boundary of sec. 35, T. 35 S., R. 5 W. Point for the closing cor. of secs. 2 and 3, at proportionate distance longitudinally between the standard cor. of secs. 34 and 35, and the standard $\frac{1}{4}$ sec. cor. sec. 35; there is no remaining evidence of the original closing corner.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins in the ground, in a collar of stone, with brass cap mkd.

T35S R5W
S35
—
S3|S2
C|C
T36S R5W
1973

Set a 6 ft. steel fence post alongside the iron post.

From this cor., the standard cor. of secs. 34 and 35, T. 35 S., R. 5 W., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 35 S., R. 5 W., bears N. $89^\circ 47'$ W., 10.17 chs. dist.

Point for the N. $\frac{1}{4}$ sec. cor. of sec. 2, on the N. bdy. of the township at midpoint longitudinally between the closing cor. of secs. 2 and 3, and the closing cor. of secs. 1 and 2.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W
 $\frac{1}{4}$ S2
—
T36S R5W
1972

Set a 6 ft. steel fence post alongside the iron post.

From this cor., the standard $\frac{1}{4}$ sec. cor. of sec. 35, T. 35 S., R. 5 W., a $2\frac{1}{2}$ in. iron post, set, mkd., and witnessed as described in the field notes of the

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

concurrent resurvey of T. 35 S., R. 5 W., bears N. 89° 44' W., 10.305 chs. dist.

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp.

N. 1° 26' E., bet. secs. 33 and 34.

Over rolling land through dense pinon and juniper, along E. side of fence line.

23.55 Fence, bears N. 80° E. and S. 80° W. 43 lks. to cor., thence N. 2° 30' E. and S. 0° 20' W.

27.40 Leave pinon and juniper, continue over rolling land through sagebrush.

40.54 The $\frac{1}{4}$ sec. cor. of secs. 33 and 34, monumented with a sandstone, 15x10x6 ins., firmly set 8 ins. in the ground, at the cor. of fences that bear S. 2° 30' W. and N. 89° 45' W., plainly mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36S R5W

$\frac{1}{4}$

S33|S34

1972

Bury original cor. stone alongside iron post.

N. 0° 34' W., beginning new measurement.

Continue over rolling land through sagebrush.

0.15 Trail road, bears S. 30° E. and W.

19.65 Wash, drains N. 50° W.

39.30 Wash, drains N. 50° W.

39.78 Fence, bears E. and W.

39.86 The cor. of secs. 27, 28, 33 and 34, marked by iron post, 1 in. diam., extending 2 ins. above ground. This point is locally used and recognized as the cor. point and is accepted as the best available evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36S R5W

S28|S27

S33|S34

1972

Set a 6 ft. steel fence post alongside the iron post.

Raise a mound of stone, 3 ft. base. 2½ ft. high, W. of cor.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

From this cor., the $\frac{1}{4}$ sec. cor. of secs. 27 and 28,
monumented with a limestone, 18x12x8 ins., firmly set
10 ins. in the ground, plainly mkd. $\frac{1}{4}$ on W. face,
bears N. $1^{\circ} 10'$ E., 40.81 chs. dist.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T36S R5W

$\frac{1}{4}$

S28|S27

1972

Bury original cor. stone alongside iron post and set
a 6 ft. steel fence post alongside.

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

From the cor. of secs. 26, 27, 34 and 35.

N. $89^{\circ} 23'$ W., bet. secs. 27 and 34.

Over gently rolling land through sagebrush, along N.
side of fence line, on N. side improved dirt road.

19.90 Trail road, bears N. 5° E. and S. 5° W.; fence turns S.
to S. side of road, thence W., continue along N. side
of improved dirt road.

30.00 Wash, drains N. 50° W.

32.50 Trail road, bears N.

38.50 Trail road, bears S.

40.00 The $\frac{1}{4}$ sec. cor. of secs. 27 and 34, marked by an iron
post, 1 in. diam., extending 6 ins. above ground. This
point is locally used and recognized as the cor. point and
and is accepted as the best existing evidence of
the original cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T36S R5W

$\frac{1}{4}$ S27

S34

1972

Set a 6 ft. fence post alongside the iron post.

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of
cor.

S. $89^{\circ} 57'$ W., beginning new measurement.

Continue along N. side of road.

25.15 Trail road, bears N. 60° W.

32.10 Trail road bears N. 20° W.

Dependent Resurvey of a Portion of the Subdivisional
 T. W. S. W. 1/4 Sec. 21, 22, 27 and 28, T. 12 N., R. 10 E., S. 12 E., Utah

CHAINS

39.96 The cor. of secs. 27, 28, 33 and 34.

From the cor. of secs. 21, 22, 27 and 28, determined by the cor. of old fences bearing N., E. and W. This position is harmoniously related to existing original corners and is accepted as the best existing evidence of the position of the original cor.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36S R5W
 $\frac{S21}{S28} | \frac{S22}{S27}$
 1972

N. $0^{\circ} 17'$ W., bet. secs. 21 and 22.

Over gently rolling cultivated land, along fence line.

7.00 Wash, drains N. 85° W.

12.75 Wash, drains N. 80° W.

25.68 Cor. of fences bearing N., S. and W.; continue along fence line.

39.99 The $\frac{1}{4}$ sec. cor. of secs. 21 and 22, monumented with a sandstone, $14 \times 8 \times 6$ ins., firmly set 3 ins. in the ground, at the cor. of fences bearing N., S., E. and W., plainly mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36S R5W
 $\frac{1}{4}$
 $\frac{S21}{S28} | \frac{S22}{S27}$
 1972

Bury original cor. stone alongside the iron post.

N. $0^{\circ} 09'$ W., beginning new measurement.

Over gently rolling cultivated land; along fence line.

3.05 Sevier River, flows irregularly E.

22.33 Right-of-way fence, parallels U.S. Highway No. 89, leave cultivated land, and fence line.

23.77 Centerline of U.S. Highway No. 89, bears N. $62^{\circ} 38'$ E. and S. $62^{\circ} 38'$ W.

25.58 Right-of-way fence, parallels highway; asc. S. slope.

37.50 Top of ascent, continue over rolling land through sagebrush, pinon and juniper.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

- 40.03 The cor. of secs. 15, 16, 21 and 22, monumented with a volcanic stone, 16x12x6 ins., firmly set 8 ins. in the ground, erroneously mkd. with 6 notches on E. and 6 notches on S. edges.
- From which an original bearing tree
- A juniper, 12 ins. diam., bears S. 65° E., 165 lks. dist., dimly scribed S. 22° BT.
- At the cor. point
- Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
- $$\begin{array}{r} \text{T36S R5W} \\ \text{S16|S15} \\ \hline \text{S21|S22} \\ 1972 \end{array}$$
- Bury original cor. stone alongside iron post and set a 6 ft. steel fence post alongside.
-
- From the cor. of secs. 14, 15, 22 and 23.
- N. 88° 35' W., bet. secs. 15 and 22.
- Over nearly level land through sagebrush, along N. side of fence line, bears W.
- 19.98 Point for the E. 1/16 sec. cor. of secs. 15 and 22.
- Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
- $$\begin{array}{r} \text{T36S R5W} \\ \text{E 1/16} \quad \frac{\text{S15}}{\text{S22}} \\ 1972 \end{array}$$
- Set a 6 ft. steel fence post alongside the iron post.
- from which an E-W fence line bears S. 54 lks. dist.,
- 20.50 Fence line bears N. and S. 54 lks. to E-W fence; continue along N. side of fence line.
- 39.96 The ¼ sec. cor. of secs. 15 and 22, monumented with a sandstone, 14x10x6 ins., firmly set 6 ins. in the ground, at the cor. of fences bearing E. and S., plainly mkd. ¼ on N. face.
- At the cor. point
- Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
- $$\begin{array}{r} \text{T36S R5W} \\ \frac{1}{4} \quad \frac{\text{S15}}{\text{S22}} \\ 1972 \end{array}$$
- Bury original cor. stone alongside iron post, and raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of cor.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

N. 89° 21' W. beginning new measurement.

Over nearly level bottom land through low brush, by
triangulation, topography scaled.

- 7.00 Sevier River, flows N. 63° E.
9.50 U.S. Highway No. 89, bears N. 62° 40' E.
and S. 62° 40' W.
12.70 Asc. SE. slope.
21.00 Spur, slopes SE.; desc. SW. slope.
26.00 Draw, drains S.
31.00 Draw, drains S. 25° E.; asc. SE. slope.
39.40 End ascent and triangulation.
39.94 The cor. of secs. 15, 16, 21 and 22.

N. 0° 34' E., bet. secs. 15 and 16.

Over rolling land through sagebrush, scattered pinon
and juniper.

- 5.16 Power line, bears N. 26° 16' E. and S. 26° 16' W.
13.00 Trail road, bears N. 65° E. and S. 65° W.
16.10 Wash, drains S. 70° E.
40.30 The $\frac{1}{4}$ sec. cor. of secs. 15 and 16, monumented with a
volcanic stone 14x12x4 ins., firmly set 6 ins. in the
ground, plainly mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 12 ins.
in the ground to solid rock and in a mound of stone,
3 ft. base to top, with brass cap mkd.

T36S R5W

$\frac{1}{4}$

S16|S15

1972

Bury original cor. stone alongside iron post and set a
6 ft. steel fence post alongside.

N. 0° 32' E., beginning new measurement.

Continue over rolling land through sagebrush, scattered
pinon and juniper.

- 21.80 Wash, drains S. 55° E.
35.90 Wash, drains S. 55° E.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

40.43 The cor. of secs. 9, 10, 15 and 16, monumented with a volcanic stone, 16x10x10 ins., firmly set 8 ins. in the ground, plainly mkd. 3 notches on E. and 4 notches on S. edges.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36S R5W
S9|S10
S16|S15
1972

Bury original cor. stone alongside iron post and set a 6 ft. steel fence post alongside.

Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

From the cor. of secs. 10, 11, 14 and 15.

N. 88° 27' W., bet. secs. 10 and 15.

Over nearly level bottom land, along fence line, through low brush; by triangulation, topography scaled.

13.50 Wash, drains N.

23.50 Sevier River, flows N. 20° W.; end of fence line.

25.50 U.S. Highway No. 89, bears N. 22° 40' W. ad S. 22° 40' E.

28.70 Ascend NE. slope.

39.93 The ¼ sec. cor. of secs. 10 and 15, monumented with a volcanic stone, 30x30x18 ins., above ground, plainly mkd. ¼ on N. face, with a mound of stone, 2 ft. base, 1 ft. high, S. of cor.

from which an original bearing tree:

A juniper, 8 ins. diam., bears S. 24° 15' E., 50 lks. dist., mkd. S BT in partially healed blaze (No record of this tree).

On N. side of cor. stone

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock, in a mound of stone, 4 ft. base to top, with brass cap mkd.

T36S R5W
¼ S10
S15
1972

N. 88° 36' W., beginning new measurement.

Continue gradual ascent of E. slope.

39.81 The cor. of secs. 9, 10, 15 and 16.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

N. 0° 14' W., bet. secs. 9 and 10;

Over rolling land through sagebrush.

13.80 Draw, drains irregularly E.

28.80 Wash, drains S. 75° E.

40.56 The $\frac{1}{4}$ sec. cor. of secs. 9 and 10, monumented with a granite stone, 14x11x9 ins., firmly set, 6 ins. in the ground, plainly mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36S R5W

$\frac{1}{4}$

S9|S10

1972

Bury original cor. stone alongside iron post and set a 6 ft. steel fence post alongside.

N. 0° 05' E., beginning new measurement.

Desc. N. slope through sagebrush, scattered pinon and juniper.

12.00 Bottom of small canyon, drains N. 70° E.; asc. SE. slope.

32.00 Top of ascent.

34.70 Desc. NW. slope through dense pinon, fir and juniper.

39.52 The cor. of secs. 3, 4, 9 and 10, monumented with a volcanic stone, 3x2x2 ft. above ground, plainly mkd. 3 grooves on E. and 5 grooves on S. faces.

from which the remaining original bearing trees:

A dead fir, still standing, 14 ins. diam., bears N. 79° E., 11 lks. with healed blaze (Record, N. 60° E., 12 lks.)

A dead ponderosa, still standing, 20 ins. diam., bears S. 61° 30' E., 15 lks. with healed blaze. (Record S. 80° E., 15 lks.).

A dead ponderosa, still standing, 14 ins. diam., bears N. 2° 30' W., 15 lks., with healed blaze. (Record N. 5° W. No distance given).

The cor. point cannot be improved upon.

from which

A fir, 7 ins. diam., bears N. 50° E., 50 lks. dist., mkd S3 BT.

A fir, 10 ins. diam., bears S. 66° 10' W., 42 lks. dist., mkd. T36S R5W S9 BT.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

- From the true point for the cor. of secs. 2, 3, 10 and 11.
- N. 88° 25' W., bet. secs. 3 and 10.
- Over broken land, through sagebrush,; asc. SE. slope.
- 0.20 Left bank of the Sevier River, bears N. and S.
- 7.95 Center line of U.S. Highway No. 89, bears N. 32° 35' E., and S. 32° 35' W., asc; broken SE. slope, enter scattered timber.
- 20.11 Point for the E. 1/16 sec. cor. of secs. 3 and 10.
- Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
- T36S R5W
E 1/16 $\frac{S3}{S10}$
1972
- Set a 6 ft. steel fence post alongside the iron post.
- Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
- 38.40 Top of low spur, projects N.; desc. W. slope.
- 40.10 Bottom of draw, drains N. 20° W.
- 40.22 The ¼ sec. cor. of secs. 3 and 10, monumented with a sandstone, 12x8x8 ins., firmly set 6 ins. in the ground, mkd. ¼ on N. face.
- At the cor. point
- Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
- T36S R5W
¼ $\frac{S3}{S10}$
1972
- Bury original cor. stone alongside iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
-
- N. 88° 24' W., beginning new measurement.
- Continue over hilly S. side of Rock Canyon, through scattered pinon and juniper.
- 2.50 Top of low spur, projects N.; desc. W. slope.
- 16.35 Bottom of gully, drains N. 50° E.; asc. E. slope.
- 20.60 Enter dense pinon, ponderosa and juniper.
- 34.90 Top of ascent, slopes N.; desc. NW. slope.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

39.90 The cor. of secs. 3, 4, 9 and 10.

N. 1° 22' E., bet. secs. 3 and 4.

Over broken land, through dense pinon, juniper and fir.
By triangulation; desc. steep NW. slope.

3.50 Bottom of Rock Canyon, drains N. 60° E.; asc. SE.
slope.

10.50 Top of spur, projects E.; desc. NE. slope.

15.60 Bottom of draw, drains S. 40° E.

20.50 Same draw, drains S. 50° W.; asc. broken SE. slope.

25.70 N. rim of Rock Canyon; continue over rolling land.
End triangulation.

28.20 Leave dense pinon and juniper; continue through
scattered pinon and juniper.

39.49 Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at propor-
tionate distance; there is no remaining evidence of the
original cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T36S R5W

$\frac{1}{4}$

S4|S3

1972

Set a 6 ft. steel fence post alongside the iron post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of
cor.

Continue over rolling land through scattered juniper and
pinon.

51.00 Wash, drains S. 20° E.

77.50 Intersect the Seventh Standard Parallel South on the
S. bdy. of sec. 34, T. 35 S., R. 5 W., at the closing cor.
of secs. 3 and 4, monumented with a volcanic stone,
16x12x10 ins., firmly set 10 ins. in the ground, plainly
mkd. 3 notches on the E. and 3 notches on the W. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T35S R5W

S34

S4|S3

C|C

T36S R5W

1972

Bury original cor. stone and set a 6 ft. steel fence
post alongside the iron post.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, S. of cor.

From this cor., the standard cor. of secs. 33 and 34, T. 35 S., R. 5 W., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 35 S., R. 5 W., bears N. $89^{\circ} 35'$ W., 11.64 chs. dist.

Point for the N. $\frac{1}{4}$ sec. cor. of sec. 3, on the N. bdy. of the Tp, at midpoint longitudinally between the closing cor. of secs. 3 and 4, and the closing cor. of secs. 2 and 3.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W

$\frac{1}{4}$ S3
T36S R5W
1972

Set a 6 ft. steel fence post alongside the iron post.

From this cor., the standard $\frac{1}{4}$ sec. cor. of sec. 34, T. 35 S., R. 5 W., a $2\frac{1}{2}$ ins. iron post, set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 35 S., R. 5 W. bears N. $89^{\circ} 35'$ W., 10.905 chs. dist.

From the cor. of secs. 4, 5, 32 and 33, on the S.bdy. of the Tp.

N. $0^{\circ} 21'$ E., bet. secs. 32 and 33.

By triangulation, desc. over N. slope through scattered pinon and juniper, topography scaled.

- | | |
|-------|--|
| 10.50 | Bottom of draw, drains N. 35° W.; asc. over SW. slope. |
| 15.00 | Desc. NW. slope. |
| 20.00 | Leave timber. |
| 35.00 | Ditch, 15 lks. wide, 3 ft. deep, drains N. 60° E. |
| 38.00 | Sevier River flows N. 33° E.; continue over bottom land through dense willows and scattered cottonwood. |
| 40.45 | Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33, at proportionate distance falls on low sand bar of the Sevier River deemed unsafe to perpetuate; there is no remaining evidence of the original cor. |
| 41.60 | Right bank of the Sevier River, bears N. 65° W. and S. 65° E.; end triangulation. |
| 41.98 | Point for the witness $\frac{1}{4}$ sec. cor. of secs. 32 and 33. |
| | Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. |

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

T36S R5W

 $\frac{1}{4}$
 S32|S33

 ↓
 W C
 1972

Continue over bottom land through willows and cottonwood
by triangulation.

- 43.50 Sevier River, flows N. 30° E.
 57.50 Sevier River, flows S. 43° W.
 62.00 Sevier River, flows N. 48° E.
 68.00 Sevier River, flows S. 60° W.
 75.00 Sevier River, flows N. 30° E. curving N.
 80.90 The cor. of secs. 28, 29, 32 and 33, determined by the
cor. of old fence lines bearing N. and E. This position
is harmoniously related to existing original corners
and is accepted as the best existing evidence of the
position of the original cor. End triangulation.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T36S R5W
 S29|S28
 S32|S33
 1972

No accessories available.

From the cor. of secs. 27, 28, 33 and 34.

N. 89° 10' W., bet. secs. 28 and 33.

Over rolling land through sagebrush, along S. side of
improved dirt road, with fence line along S. side.

- 1.85 Road turns N. 40° W.; wash, drains N. 50° W.
 15.35 Trail road, bears N. 30° E. and S. 30° W.
 24.85 Wash, drains N. 30° W.
 39.80 The ¼ sec. cor. of secs. 28 and 33, determined by the
cor. of old fences bearing N., S., E. and W. This
position is harmoniously related to existing original
corners and is accepted as the best existing evidence
of the position of the original cor.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

T36S R5W
 $\frac{1}{4}$ $\frac{S28}{S33}$
 1972

No accessories available

N. 89° 27' W., beginning new measurement.

Continue over rolling land through sagebrush, by
triangulation, and along fence line.

- 1.20 Desc. NW. slope.
- 24.20 Wash, drains N. 40° E.; end descent, enter willows and
cottonwoods in river bottom.
- 38.90 Sevier River, flows N. 5° E.
- 40.24 The cor. of secs. 28, 29, 32 and 33. End triangulation.

N. 0° 20' E., bet. secs. 28 and 29.

Over nearly level cultivated land, along fence line.

- 13.50 Gravel road, bears N. and W. continue along fence line
on E. side of road, along E. side of Hatch, Utah.
- 23.00 Gravel road to W.
- 32.00 Gravel road to W.
- 40.26 Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29, at inter-
section of gravel road to E. and W. and fence line
bearing N-S. This point is harmoniously related to
existing original cors. and has been recognized by
local residents of Hatch, Utah, and is accepted as
the best existing evidence of the position of the
original cor.

Set brass tablet pigtail 6 ins. in the ground,
with brass cap mkd.

T36S R5W
 $\frac{1}{4}$
 S29|S28
 1972

from which

An iron post, 30 ins. long, 2½ ins. diam., set 24
ins. in the ground, in E-W fence line, bears N. 45°
E., 30½ lks. dist., with brass cap mkd. T36S R5W
 $\frac{1}{4}$ S29 RM 1972 and an arrow pointing to the true cor.

An iron post, 30 ins. long, 2½ ins. diam., set 24
ins. in the ground, in an E-W fence line, bears S.
45° E., 30½ lks. dist., with brass cap mkd. T36S
R5W $\frac{1}{4}$ S29 RM 1972, and an arrow pointing to the true
cor.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

N. $0^{\circ} 20'$ E., beginning new measurement.

Continue along fence line on E. side of roadway through Hatch.

- 10.25 Gravel road to W.
- 19.25 Gravel road to W.
- 20.20 Fence, bears W., leave roadway, continue along fence.
- 38.75 Power line substation, bears W. 1.50 chs. dist.
- 40.20 Road, bears E. and W.
- 40.26 Point for the cor. of secs. 20, 21, 28 and 29, at projected intersection of fence from E. with fence from S. This position is referred to as the sec. cor. point by the Utah State Highway Department records, is harmoniously related to existing original corners and is accepted as the best available evidence of the position of the original cor. point

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T36S R5W
S20/S21
S29/S28
1972

From the cor. of secs. 21, 22, 27 and 28.

N. $88^{\circ} 56'$ W., bet. secs. 21 and 28.

Over rolling land through grass and sagebrush, along fence line.

- 20.30 Fence line, bears N. and S., continue along S. side of fence line.
- 25.70 Wash, drains N. 50° W.
- 36.00 Wash, drains N. 45° W.
- 40.36 The $\frac{1}{4}$ sec. cor. of secs. 21 and 28, monumented with a sandstone, $18 \times 12 \times 10$ ins., firmly set 12 ins. in the ground, plainly mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36S R5W
S21
 $\frac{1}{4}$ S28
1972

Bury original cor. stone alongside the iron post.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	From this cor., the cor. of fences which bear N. and E., bears N. 52° W., 10 lks. dist.
	S. 89° 31' W., beginning new measurement.
	Continue over nearly level land through low brush and grass. By triangulation, topography scaled.
14.10	Sevier River, flows N. 50° W.
20.00	Fence, bears S. and W., thence along fence line.
40.85	The cor. of secs. 20, 21, 28 and 29. End triangulation.
	N. 0° 16' E., bet. secs. 20 and 21.
	Over gently rolling land through sagebrush.
1.45	Center line of U.S. Highway No. 89, bears N. 45° 25' E. and S. 45° 25' W.
1.65	Power line, bears N. 11° E. and S. 10° W.
2.90	Fence, parallel to U.S. Highway No. 89.
8.70	Wash. drains irregularly E.
20.17	Point for the S. 1/16 sec. cor. of secs. 20 and 21. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T36S R5W S 1/16 S20 S21 1972 Set a 6 ft. steel fence post alongside iron post. Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor.
27.50	Trail road, bears N. 50° W. and S. 50° E.
38.74	Point for the witness ¼ sec. cor. of secs. 20 and 21 Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. WC T36S R5W ¼ S20↑S21 1972 Set a 6 ft. steel fence post alongside iron post. Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor.
40.34	Point for the ¼ sec. cor. of secs. 20 and 21, at pro-

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

portionate distance, there is no remaining evidence of the original cor. The cor. point falls in a wash which drains S. 50° E., and is unsuitable for monumentation.

- 51.90 Improved gravel road, bears S. 50° E. and N. 50° W.
- 67.20 Wash, drains E.; asc. SE. slope, enter scattered timber.
- 80.68 The cor. of secs. 16, 17, 20 and 21, monumented with a sandstone, 16x13x9 ins., firmly set 6 ins. in the ground, plainly mkd. 4 notches on E. and 3 notches on S. edges.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36S R5W
 $\frac{S17|S16}{S20|S21}$
 1972

Bury original cor. stone alongside iron post.

Set a 6 ft. steel fence post alongside.

Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor.

From the cor. of secs. 15, 16, 21 and 22.

N. 89° 38' W., bet. secs. 16 and 21.

Over hilly land through scattered pinon and juniper.

- 2.42 Power line, bears N. 26° 16' E., and S. 26° 16' W.
- 3.80 Trail road, bears N. 10° E. and S. 10° W.
- 28.90 Wash, drains irregularly S.
- 39.64 The ¼ sec. cor. of secs. 16 and 21, monumented with a granite stone, 16x14x6 ins., firmly set 8 ins. in the ground, plainly mkd. ¼ on N. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T36S R5W
 $\frac{1}{4} \frac{S16}{S21}$
 1972

Bury original cor. stone alongside iron post and set a 6 ft. steel fence post alongside.

N. 88° 58' W., beginning new measurement.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	Continue over rolling land through sagebrush, scattered pinon and juniper.
4.10	Graded road, bears S. 30° E. and N. 30° W.
7.70	Wash, drains S. 30° E.
26.20	Power line, bears N. 10° E. and S. 10° W.
36.00	Wash, drains S. 10° E.
40.89	The cor. of secs. 16, 17, 20 and 21.
	N. 0° 43' E., bet. secs. 16 and 17.
	Over nearly level land through sagebrush, scattered pinon and juniper.
9.30	Asc. S. slope.
14.50	Top of narrow ridge, bears E. and W.; desc. N. slope.
22.40	Bottom of descent, wash, drains E.; continue over rolling land through sagebrush
27.40	Wash, drains E.
31.00	Wash, drain S. 50° E.
39.35	Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T36S R5W $\frac{1}{4}$ S17 S16 1972
	Set a 6 ft. steel fence post alongside the iron post.
	Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.
	Asc. S. slope through pinon and juniper.
41.70	Small draw, drains E.; asc. S. slope.
46.50	Top of low spur, projects S. 10° E. from W.; desc. N. slope.
50.10	Bottom of draw, drains E.; asc. S. slope.
55.70	Top of low ridge, bears E. and W.; desc. N. slope.
56.80	Trail road, bears E. and W.
66.50	Wash, drains S. 30° E.; asc. S. slope.
74.50	Top of spur, projects SE.; desc. N. slope.
76.70	Bottom of descent; continue over rolling land.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S. R. 5 W. Salt Lake Meridian, Utah

CHAINS

78.70 The cor. of secs. 8, 9, 16 and 17, monumented with a trachyte stone, 16x10x5 ins., firmly set 8 ins. in the ground, plainly mkd. with 4 notches on E. and S. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36S R5W
 $\frac{S8|S9}{S17|S16}$
 1972

Bury original cor. stone alongside the iron post and set a 6 ft. steel fence post alongside.

Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

From the cor. of secs. 9, 10, 15 and 16.

S. $89^{\circ} 58'$ W., bet. secs. 9 and 16.

Over rolling land through sagebrush

8.40 Wash, drains S. 60° E.; asc gentle E. slope.

24.70 Enter pinon and juniper.

32.60 Top of slope; desc. gentle W. slope through sagebrush.

40.10 The $\frac{1}{4}$ sec. cor. of secs. 9 and 16, monumented with a sandstone, 18x14x10 ins., firmly set 10 ins. in the ground, plainly mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36S R5W
 $\frac{S9}{\frac{1}{4} S16}$
 1972

from which

A juniper, 6 ins. diam., bears S. 30° W., $43\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S 16 BT.

Bury original cor. stone alongside iron post, and set a 6 ft. steel fence post alongside.

S. $88^{\circ} 50'$ W., beginning new measurement.

Continue over rolling land through scattered pinon and juniper.

1.10 Wash, drains S.

9.10 Dirt road, bears N. 30° E. and S. 30° W.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
13.30	Power line, bears N. 10° E. and S. 10° W.
39.20	Bottom of a draw, drains SE.
40.13	The cor. of secs. 8, 9, 16 and 17.
	N. 1° 02' E., bet. secs. 8 and 9.
	Over rolling land.
0.25	Bottom of draw, drains S. 80° E.; over rolling land; asc. S. slope through dense pinon and juniper,.
11.10	Top of spur, projects W.; desc. N. slope.
29.60	Bottom of descent, wash, drains N. 75° E.; continue over rolling land.
39.68	The $\frac{1}{4}$ sec. cor. of secs. 8 and 9, monumented with a granite stone, 12x10x5 ins., firmly set 6 ins. in the ground, plainly mkd. $\frac{1}{4}$ on W. face.
	At the cor. point
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T36S R5W
	$\frac{1}{4}$
	S8 S9
	1972
	Bury original cor. stone alongside the iron post and set a 6 ft. steel fence post alongside.
	Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.
	N. 0° 21' W., beginning new measurement.
	Continue over rolling land through sagebrush, scattered pinon and juniper.
12.55	Rock Canyon, drains E.
25.90	Trail road, bears N. 80° E. and N. 65° W.
33.00	Wash, drains N. 80° E.
39.95	The cor. of secs. 4, 5, 8 and 9, monumented with a granite stone, 14x12x10 ins., firmly set 6 ins. in the ground, plainly mkd. with 4 notches on E. and 5 notches on S. edges.
	At the cor. point
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

T36S R5W

S5/S4S8/S9

1972

Bury original cor. stone alongside iron post.

Raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

From the cor. of secs. 3, 4, 9 and 10.

S. $87^{\circ} 58'$ W., bet. secs. 4 and 9.

Over broken land by triangulation, topography scaled.

Desc. NW. slope through pinon, juniper and fir.

5.50 Bottom of Rock Canyon, drains N. 15° E.; asc. SE. slope through dense pinon, juniper and fir.

15.40 NW. rim of Rock Canyon, continue over rolling land through scattered pinon and juniper. End triangulation.

28.00 Desc. gentle SW. slope. Leave timber.

39.22 The $\frac{1}{4}$ sec. cor. of secs. 4 and 9, monumented with a granite stone, $14 \times 12 \times 6$ ins., firmly set 4 ins. in the ground, plainly mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36S R5W

 $\frac{1}{4}$ S4S9

1972

Bury original cor. stone alongside the iron post and set a 6 ft. steel fence post alongside.

Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

N. $89^{\circ} 57'$ W., beginning new measurement.

Continue over rolling land, through sagebrush, scattered pinon and juniper.

3.50 Wash, drains S. 40° E.

10.90 Power line, bears N. $0^{\circ} 53'$ W. and S. $0^{\circ} 53'$ E.

25.05 Trail road, bears N. 70° E. and S. 70° W.

30.20 Wash, drains S. 15° E.

31.60 Graded dirt road, bears N. 10° W. and S. 10° E.

36.10 Trail road, bears S. 50° E. and N. 50° W.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Sec. 4, 5, 8 and 9.

CHAINS

40.40 The cor. of secs. 4, 5, 8 and 9.

N. 0° 14' W., bet. secs. 4 and 5.

Over rolling land through sagebrush.

1.60 Trail road, bears N. 80° W. and S. 80° E.

7.00 Wash, drains S. 30° E.

20.20 Trail road, bears N. 40° W. and S. 40° E.

34.00 Wash, drains S. 70° E.

40.18 The $\frac{1}{4}$ sec. cor. of secs. 4 and 5, monumented with a volcanic stone, 14x8x6 ins., firmly set 6 ins. in the ground, plainly mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock and in a mound of stone, 2½ ft. base to top, with brass cap mkd.

T36S R5W

$\frac{1}{4}$

S5|S4

1972

Bury original cor. stone alongside iron post and set a 6 ft. steel fence post alongside.

N. 0° 34' E., beginning new measurement.

Continue over rolling land through sagebrush.

17.90 Graded dirt road, bears N. 30° W. and S. 45° E.

21.30 Wash, drains S. 60° E. from W.

39.32 Intersect the Seventh Standard Parallel South on the S. bdy. of sec. 33, T. 35 S., R. 5 W., at the closing cor. of secs. 4 and 5, T. 36 S., R. 5 W., monumented with a volcanic stone, 10x8x6 ins., firmly set 6 ins. in the ground, mkd. with 4 notches on the E. and 6 notches on the S. edges.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

T35S R5W

S33

S5|S4

C C

T36S R5W

1972

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

Bury original cor. stone alongside iron post and set a 6 ft. steel fence post alongside.

From this cor., the standard cor. of secs. 32 and 33, T. 35 S., R. 5 W., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 35 S., R. 5 W., bears N. 89° 48' W., 11.09 chs. dist.

Point for the N. $\frac{1}{4}$ sec. cor. of sec. 4 on the N. bdy. of the Tp., at midpoint longitudinally between the closing cor. of secs. 4 and 5, and the closing cor. of secs. 3 and 4.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W

$\frac{1}{4}$ S4
T36S R5W
1972

Set a 6 ft. steel fence post alongside the iron post.

From this cor., the standard $\frac{1}{4}$ sec. cor. of sec. 33, T. 35 S., R. 5 W., a 2½ ins. iron post, set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 35 S., R. 5 W., bears N. 89° 24' W., 11.335 chs. dist.

From the cor. of secs. 28, 29, 32 and 33.

N. 89° 40' W., bet. secs. 29 and 32.

Over cultivated land.

- 12.26 Fence, parallels U.S. Highway No. 89.
- 13.09 U.S. Highway No. 89, bears N. 24° 02' E. and S. 24° 02' W.; asc. E. slope. Enter sagebrush.
- 20.16 Power line, bears N. 0° 40' E. and S. 0° 40' W.
- 20.60 Graded dirt road, parallels power line.
- 21.05 Cor. of fences which bear N., S., and N. 89° 30' W., continue along fence line; asc. E. slope.
- 40.51 The $\frac{1}{4}$ sec. cor. of secs. 29 and 32, monumented with a granite stone, 15x6x6 ins., firmly set 6 ins. in the ground, in old fence line which bears S. 89° 40' E., and N. 89° 53' W., plainly mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock, in a collar of stone, with brass cap mkd.

T36S R5W
 $\frac{1}{4}$ S29
S32
1972

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Mer. 14. 0. Utah

CHAINS

Bury original cor. stone alongside the iron post.

N. 89° 53' W., beginning new measurement.

Continue asc. of E. slope along fence line, through
scattered pinon and juniper.

15.40 End ascent, continue over rolling land.

30.00 Gully, drains irregularly S., fence turns S.

31.10 Top of low hill; desc. W. slope.

36.00 Base of slope, continue over rolling land.

37.90 Trail road, bears N. and S.

39.38 The cor. of secs. 29, 30, 31 and 32, monumented with a
sandstone, 18x10x8 ins., firmly set 10 ins. in the
ground, in old fence line which bears N. 0° 10' E. and
S. 0° 10' W., plainly mkd. 5 notches on E. and 1 notch
on S. edges.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, in a collar of stone, with brass cap mkd.

T36S R5W
S30|S29
S31|S32
1972

Bury original cor. stone alongside the iron post.

N. 89° 24' W., bet. secs. 30 and 31.

Over rolling land through sagebrush, scattered pinon and
juniper.

6.40 Wash, drains S. 40° E.

13.40 Limestone Creek, flows S. 60° E.

30.00 Fence, bears N. 89° 24' W. and N. 40° E., thence along
fence line.

40.96 The ¼ sec. cor. of secs. 30 and 31, monumented with a
sandstone, 14x8x6 ins.; firmly set 6 ins. in the ground,
at the cor. of fences which bear S., E. and W., plainly
mkd. ¼ on N. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, in a collar of stone, with brass cap mkd.

T36S R5W
¼ S30
S31
1972

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

Bury original cor. stone alongside the iron post.

N. 89° 52' W., beginning new measurement.

Continue over rolling land through sagebrush, scattered
pinon and juniper, along fence line.

- 0.10 Trail road, bears N. and S.
13.90 Ditch, drains S.
20.00 Trail road, bears S. and N. 10° W.
37.11 The cor. of secs. 30 and 31, on the W. bdy. of the Tp.
hereinbefore described.

From the cor. of secs. 29, 30, 31 and 32.

N. 0° 10' E., bet. secs. 29 and 30.

Over gently rolling land.

Asc. SE. slope through sagebrush, along fence line.

- 20.11 The cor. of fences which bear EW. and S. 10° E. Leave
fence line.
20.80 Trail road, bears N. 80° E. and W.
33.30 Top of spur, projects E.; desc. N. slope through pinon
and juniper.
40.18 The $\frac{1}{4}$ sec. cor. of secs. 29 and 30, monumented with a
sandstone, 16x12x8 ins., firmly set 8 ins. in the
ground, and plainly mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins.
in the ground to solid rock, and in a collar of stone,
with brass cap mkd.

T36S R5W

$\frac{1}{4}$
S30|S29
1972

Bury original cor. stone alongside the iron post and set
a 6 ft. steel fence post alongside.

N. 0° 50' W., beginning new measurement.

Continue descent of N. slope through pinon and juniper.

- 0.25 Bottom of wash, drains S. 55° E.; asc. S. slope.
17.30 Top of ridge, bears E. and W.; desc. NE. slope.
23.70 Bottom of draw, drains S. 70° E.; asc. S. slope.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian Utah

CHAINS

39.94 The cor. of secs. 19, 20, 29 and 30, monumented with a sandstone, 14x10x8 ins., firmly set 6 ins. in the ground, plainly mkd. with 5 notches on E. and 2 notches on S. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground to solid rock, in a mound of stone, $3\frac{1}{2}$ ft. base to top, with brass cap mkd.

T36S R5W
S19|S20
S30|S29
1972

Bury original cor. stone alongside the iron post and set a 6 ft. steel fence post alongside.

From the cor. of secs. 20, 21, 28 and 29.

S. $89^{\circ} 19'$ W., bet. secs. 20 and 29.

Over rolling land through sagebrush.

1.40 U.S. Highway No. 89, bears N. $45^{\circ} 25'$ E. and curves S.

2.35 Fence, parallels U.S. Highway No. 89.

14.70 Wash, drains N.

14.76 Fence, bears N. and S.

20.20 Point for the E. $\frac{1}{16}$ sec. cor. of secs. 20 and 29.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36S R5W
E $\frac{1}{16}$ $\frac{S20}{S29}$
1972

Set a 6 ft. steel fence post alongside.

20.39 Fence, bears N. and S.

37.20 Low spur, slopes S. 50° E.

40.40 The $\frac{1}{4}$ sec. cor. of secs. 20 and 29, monumented with a sandstone, 16x10x6 ins., firmly set, 6 ins. in the ground, plainly mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36S R5W
 $\frac{1}{4}$ $\frac{S20}{S29}$
1972

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

Bury original cor. stone alongside the iron post and set a 6 ft. steel fence post alongside.

N. 89° 31' W., beginning new measurement.

Continue over gently rolling land through sagebrush, scattered pinon and juniper.

6.00 Wash, drains S. 40° E.; asc. NE. slope.

36.60 Top of low spur, with trail road, bears N. 55° W. and S. 80° E.; spur, projects S. 55° E.; desc. SW. slope.

40.29 The cor. of secs. 19, 20, 29 and 30.

N. 89° 38' W., bet. secs. 19 and 30.

Over mountainous land.

Asc. SE. slope through dense pinon and juniper.

39.81 The $\frac{1}{4}$ sec. cor. of secs. 19 and 30, monumented with a granite stone, 14x12x6 ins., firmly set 6 ins. in the ground, plainly mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36S R5W
 $\frac{1}{4}$ $\frac{S19}{S30}$
1972

from which

A juniper, 10 ins. diam., bears N. 80° E.; 39 lks. dist., mkd. $\frac{1}{4}$ S 19 BT.

A juniper, 6 ins. diam., bears S. 60° W., 63 lks. dist., mkd. $\frac{1}{4}$ S30 BT.

Bury original cor. stone alongside iron post.

S. 89° 52' W., beginning new measurement.

Continue ascent of gentle E. slope through dense pinon and juniper.

6.00 Top of ascent; desc. over SW. slope.

24.50 Bottom of draw, drains S. 40° E.; asc. NE. slope.

37.32 The cor. of secs. 19 and 30, on the W. bdy. of the Tp., hereinbefore described.

From the cor. of secs. 19, 20, 29 and 30.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

N. 0° 14' W., bet. secs. 19 and 20.

Over rolling land.

Asc. S. slope through scattered pinon and juniper.

2.65 End ascent, trail road, bears S. 55° E. and N. 55° W.;
continue along gentle E. slope.

6.40 Top of low spur, projects E.; desc. N. slope.

13.70 Bottom of draw, drains S. 75° E.; asc. S. slope.

20.95 Top of ascent, trail road, bears N. 85° E. and S. 85°
W.; along the top of a low ridge; desc. N. slope.

29.60 Bottom of ravine, drains E.; asc. S. slope.

40.00 Top of spur, projects E.

40.15 The $\frac{1}{4}$ sec. cor. of secs. 19 and 20, monumented with a
sandstone, 14x10x8 ins., firmly set 6 ins. in the
ground, plainly mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T36S R5W

$\frac{1}{4}$

S19|S20

1972

from which

A pinon, 10 ins. diam., bears S. 43° E., 62 lks.
dist., mkd. T36S R5W $\frac{1}{4}$ S20 BT.

A pinon, 16 ins. diam., bears N. 22° W., 38
lks. dist., mkd. T36S R5W $\frac{1}{4}$ S19 BT.

Bury original cor. stone alongside the iron post and set
a 6 ft. steel fence post alongside.

Raise a mound of stone 3 ft. base, 2 ft. high,, W. of
cor.

N. 2° 22' E., beginning new measurement.

Desc. NE. slope through scattered pinon and juniper.

2.80 Bottom of draw, drains S. 70° E.; asc. S. slope.

4.75 Top of ascent, improved gravel road, bears S. 88° E
and N. 88° W.; desc. N. slope.

12.40 Bottom of draw, drains N. 80° E.; asc. S. slope.

26.30 Top of spur, projects E.; desc. N. slope.

29.80 Bottom of draw, drains irregularly E.; asc. S. slope.

37.85 Top of spur, projects NE.; desc. N. slope.

Dependent Resurvey of a Portion of the Subdivisional
 14. 1. 2. S. 1. 2. 3. 4. 5. 6. 7. 8. 9. 10. 11. 12.

CHAINS

- 39.10 Bottom of small draw, drains E.; asc. SE. slope.
- 39.36 The cor. of secs. 17, 18, 19 and 20, monumented with a sandstone, 16x14x10 ins., firmly set 6 ins. in the ground, plainly mkd. with 5 notches on E. and 3 notches on S edges.

from which the original bearing trees:

A pinon, half dead, 12 ins. diam., bears S. 25° E., 125 lks. dist., mkd. T36S R5W S20 BT.

A juniper, 30 ins. diam., bears S. 5° 30' W., 128 lks. dist., mkd. T36S R5W S19 BT. (No record of these bearing trees).

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36S R5W
 S18|S17
 S19|S20
 1972

Bury original cor. stone alongside the iron post and set a 6 ft. steel fence post alongside.

Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor.

From the cor. of secs. 16, 17, 20 and 21.

S. 89° 06' W., bet. secs. 17 and 20.

Over rolling land.

Asc. along S. slope through dense pinon and juniper.

22.60 Draw, drains S. 70° E.

37.60 Draw, drains S. 65° E.; asc. NE. slope.

39.80 Point for the ¼ sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T36S R5W
 ¼ S17
 S20
 1972

Set a 6 ft. steel fence post alongside the iron post.

42.40 Spur, slopes SE.; thence along S. slope through dense pinon and juniper.

49.60 Draw, drains S. 60° E.

72.60 Top of spur, projects N. 50° E.; desc. NW. slope.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S. R. 5 W. Salt Lake Meridian Utah

CHAINS

76.50 Bottom of draw, drains N. 40° E.; asc. E. slope.

79.60 The cor. of secs. 17, 18, 19 and 20.

N. 89° 38' W., bet. secs. 18 and 19.

Over mountainous land.

Asc. gentle E. slope through scattered pinon and juniper.

34.60 Desc. NW. slope.

40.32 The $\frac{1}{4}$ sec. cor. of secs. 18 and 19, monumented with a
granite stone, 14x12x6 ins., firmly set, 6 ins. in the
ground, plainly mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins.
in the ground, in a collar of stone, with brass cap mkd.

T36S R5W

$\frac{1}{4}$ $\frac{S18}{S19}$

1972

Bury original cor. stone alongside the iron post and set
a 6. ft. steel fence post alongside.

N. 89° 51' W., beginning new measurement.

Continue descent over NW. slope.

9.10 Bottom of draw, drains N. 45° E.; thence along N. slope.

22.00 Bottom of draw, drains N. 35° E.; asc. E. slope.

25.60 Top of spur, projects NE.; desc. NW. slope.

32.50 Bottom of draw, drains N. 55° E.; asc. SE. slope

37.09 The cor. of secs. 18 and 19, on the W. bdy. of the Tp.
hereinbefore described.

From the cor. of secs. 17, 18, 19 and 20.

N. 0° 08' E., bet. sec. 17 and 18.

Over rolling land.

Asc. SE. slope through scattered pinon and juniper.

3.60 Top of spur, projects E.; desc. NE. slope.

19.60 Draw, drains N. 60° E.

29.70 Bottom of draw, drains S. 65° E.; asc. S. slope.

34.60 Top of spur, projects S. 60° E.; desc. NE. slope.

35.50 Bottom of draw, drains S. 55° E.; asc. S. slope.

Dependent Resurvey of a Portion of the Subdivisional

CHAINS

39.56

The $\frac{1}{4}$ sec. cor. of secs. 17 and 18, monumented with a volcanic stone, 16x10x10 ins., firmly set 8 ins. in the ground, plainly mkd. $\frac{1}{4}$ on W. face.

from which an original bearing tree:

A pinon, 12 ins. diam., bears N. 5° W., 187 lks.
dist., mkd. $\frac{1}{4}$ S BT. (No record of this bearing tree)

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

T36S R5W

$\frac{1}{4}$
S18 | S17
1972

Bury original cor. stone alongside iron post.

N. 0° 14' E., beginning new measurement.

Continue ascent of SE. slope through dense pinon and juniper.

13.80

Top of ascent, continue over rolling land through sagebrush, scattered pinon and juniper.

39.98

The cor. of secs. 7, 8, 17 and 18, monumented with a volcanic stone, 18x8x6 ins., firmly set 6 ins. in the ground, plainly mkd. 5 notches on E. and 4 notches on S. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to solid rock, in a mound of stone, 2 ft. base to top, with brass cap mkd.

T36S R5W

S7 | S8
S18 | S17
1972

Bury original cor. stone alongside iron post and set a 6 ft. steel fence post alongside.

From the cor. of secs. 8, 9, 16 and 17.

N. 89° 57' W., bet. secs. 8 and 17.

Over rolling land.

Asc. SE. slope through dense pinon and juniper.

1.50

Spur, slopes S. 25° E.; thence along general S. slope.

14.00

Draw, drains S.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

32.00 Draw, drains S. 50° E.; asc. SE. slope.

40.06 The $\frac{1}{4}$ sec. cor. of secs. 8 and 17, monumented with a sandstone, 16x12x16 ins., firmly set 6 ins. in the ground, plainly mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, to solid rock in a mound of stone, $2\frac{1}{2}$ ft. base to top, with brass cap mkd.

T36S R5W
 $\frac{1}{4}$ $\frac{S8}{S17}$
1972

From which

A juniper, 6 ins. diam., bears N. 7° E.; 50 lks. dist., mkd. $\frac{1}{4}$ S8 BT.

A pinon, 8 ins. diam., bears S. 87° W., 37 lks. dist., mkd. $\frac{1}{4}$ S17 BT.

Bury original cor. stone alongside iron post.

S. 89° 12' W., beginning new measurement.

Continue ascent over SE. slope through dense pinon and juniper.

29.20 Top of ascent, continue over rolling land through sagebrush, scattered pinon and juniper.

40.27 The cor. of secs. 7, 8, 17 and 18.

S. 89° 57' W., bet. secs. 7 and 18.

Over rolling land through sagebrush.

1.00 Trail road, bears N. 65° E. and S. 65° W.

21.40 Draw, drains N. 30° E.

40.22 The $\frac{1}{4}$ sec. cor. of secs. 7 and 18, monumented with a sandstone, 18x9x6 ins., firmly set 6 ins. in the ground, plainly mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36S R5W
 $\frac{1}{4}$ $\frac{S7}{S18}$
1972

Bury original cor. stone alongside iron post and set a 6 ft. steel fence post alongside.

N. 89° 57' W., beginning new measurement.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

Continue over rolling land through sagebrush.

15.00 Ridge, bears N. and S.; desc. gentle NW. slope.

31.00 E. rim of Rock Canyon curves S. and E.

37.84 The cor. of secs. 7 and 18, on W. bdy. of the Tp., herein
before described.

From the cor. of secs. 7, 8, 17 and 18.

N. 0° 11' E., bet. secs. 7 and 8.

Over rolling land through sagebrush.

0.50 Trail road, bears N. 65° E. and S. 65° W.

11.20 S. rim of Rock Canyon, bears E. and W.; desc. N. slope.

24.80 Bottom of Rock Canyon, drains S. 80° E.; asc. S. slope.

33.70 Top of ascent, N. rim of Rock Canyon, bears E. and W.;
continue over rolling land through sagebrush

39.72 The $\frac{1}{4}$ sec. cor. of secs. 7 and 8, monumented with a
granite stone, 16x10x8 ins., firmly set 6 ins. in the
ground, plainly mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 16 ins.
in the ground to solid rock, in a mound of stone, 2 ft.
base to top, with brass cap mkd.

T36S R5W

$\frac{1}{4}$

S7|S8

1972

Bury original cor. stone alongside iron post and set
a 6 ft. steel fence post alongside.

N. 0° 11' W., beginning new measurement

Continue over rolling land through sagebrush, scattered
pinon and juniper.

5.90 Wash, drains S. 85° E.

40.18 The cor. of secs. 5, 6, 7 and 8, monumented with a
granite stone, 16x8x5 ins., firmly set 6 ins. in the
ground, plainly mkd. with 5 notches on E. and S.
edges.

from which the original bearing trees:

A juniper, 10 ins. diam., bears N. 78° 45' E.,
60 lks. dist., with a healed blaze. (Record,
N. 81° E., 59 lks.).

A juniper, 10 ins. diam., bears S. 22° 45' E.,
160 lks. dist., dimly scribed S8 BT. (Record,

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S. R. 5 W. Salt Lake Meridian. Utah

CHAINS

S. 22° E., 162 lks.).

A juniper, 10 ins. dia., bears S. 67° W., 135 lks. dist., with a healed blaze. (Record, S. 72° W., 135 lks.).

A juniper, 18 ins., diam., bears N. 79° 45' W., 98 lks. dist., dimly scribed S6 BT. (Record, N. 75° W., 98 lks.).

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock, in a collar of stone, with brass cap mkd.

T36S R5W
S6 S5
S7 S8
1972

Bury original cor. stone alongside the iron post and set a 6 ft. steel fence post alongside.

From the cor. of secs. 4, 5, 8 and 9.

N. 89° 27' W., bet. secs. 5 and 8.

Over rolling land through sagebrush, scattered pinon and juniper.

30.00 Trail road, bears N. 60° W. and S. 60° E.

39.96 The ¼ sec. cor. of secs. 5 and 8, monumented with a granite stone, 15x10x8 ins., firmly set 6 ins. in the ground, plainly mkd. ¼ on N. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36S R5W
S5
¼ S8
1972

Bury original cor. stone alongside iron post and set a 6 ft. steel fence post alongside.

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

S. 89° 11' W., beginning new measurement.

Continue over rolling land through dense pinon and juniper.

40.88 The cor. of secs. 5, 6, 7 and 8.

S. 89° 55' W., bet. secs. 6 and 7.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

Over rolling land through sagebrush.

8.65 Wash, drains N. 50° E.

40.20 Wash, drains N. 70° E.

40.40 The $\frac{1}{4}$ sec. cor. of secs. 6 and 7, monumented with a volcanic stone, 18x12x6 ins., firmly set, 10 ins. in the ground, plainly mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock, in a mound of stone, 4 ft. base to top, with brass cap mkd.

T36S R5W

$\frac{1}{4}$ $\frac{S6}{S7}$
1972

Place original cor. stone in mound of stone, alongside iron post and set a 6 ft. steel fence post alongside.

N. 89° 29' W., beginning new measurement.

Continue over rolling land through sagebrush.

36.83 The cor. of secs. 6 and 7, on W. bdy. of the Tp., hereinbefore described.

From the cor. of secs. 5, 6, 7 and 8.

N. 0° 21' E., bet. secs 5 and 6.

Over rolling land through sagebrush, scattered pinon and juniper.

4.50 Wash, drains N. 85° E.

17.30 Wash, drains N. 70° E.

24.70 Wash, drains S. 55° E.

40.21 The $\frac{1}{4}$ sec. cor. of secs. 5 and 6, monumented with a granite stone, 10x6x6 ins., firmly set 6 ins. in the ground, plainly mkd. $\frac{1}{4}$ on W. face.

from which an original bearing tree:

A pinon, 16 ins. diam., bears N. 73° 30' W., 247 lks. dist., dimly scribed $\frac{1}{4}$ S BT. (Record, N. 85° W., 234 lks.).

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36S R5W

$\frac{1}{4}$
S6|S5
1972

CHAINS

Point for the N. $\frac{1}{4}$ sec. cor. of sec. 6 on the N. bdy. of the Tp., at proportionate distance longitudinally between the NW. cor. of the Tp., and the closing cor. of secs. 5 and 6.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T35S R5W

$\frac{1}{4}$ S6
T36S R5W
1972

Set a 6 ft. steel fence post alongside.

From this cor., the standard $\frac{1}{4}$ sec. cor. of sec. 31, T. 35 S., R. 5 W., a $2\frac{1}{2}$ in. iron post, set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 35 S., R. 5 W., bears N. $89^{\circ} 43'$ W., 11.30 chs. dist.

General Description

The general elevation of the township varies from about 6900 ft. to 7500 ft. above sea level.

The Sevier River flows northeasterly through the township entering in section 32 and leaving in section 2. The land drains generally toward the river channel, and is hilly and broken except for nearly flat agricultural land along the river banks. The soil varies from sandy clay along the river to rocky and sandy elsewhere.

The vegetation is mostly sagebrush, pinon and juniper except for willows and cottonwood along the river.

The township is accessible by U.S. Highway No. 89, which follows the Sevier River and by numerous trail roads located throughout the township.

The town of Hatch is located in section 29 and is bisected by U.S. Highway No. 89.

The magnetic declination was found to be $15^{\circ} 15'$ East.

Blank Page

[illegible]

CERTIFICATE OF SURVEY

I, ~~XXX~~ H. Dennis Badger

, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 5th day

of May, 1972, (I) ~~XXX~~ have dependently resurveyed a portion of the west boundary, a portion of the south boundary and a portion of the subdivisional lines of T. 36 S., R. 5 W., Salt Lake Meridian, Utah

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), (~~XX~~) and under (my) ~~XXX~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 8, 1973

(Date)

H. Dennis Badger
(Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
1974

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the dependent resurvey of a portion of the west bound a portion of the south boundary, and a portion of the subdivisional lines of Township 36 South, Range 5 West, Salt Lake Meridian, Utah

executed by H. Dennis Badger, Supervisory Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

1973

(Date)

Bernard W. Holby
(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

. is a true copy of the original field notes.

Blank

Page

Blank

Page

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF THE NORTH AND SOUTH MILES

OF THE EAST BOUNDARY AND

A PORTION OF THE SUBDIVISIONAL LINES OF

TOWNSHIP 23 SOUTH, RANGE 7 WEST

Of the SALT LAKE Meridian,

In the State of UTAH

EXECUTED BY

Milton R. Workman Supervisory Cadastral Surveyor

Under special instructions dated August 10, 19 72, which provided for the surveys
included under Group Number 541, approved August 11, 1972,
and assignment instructions dated October 16, 19 72.

Survey commenced November 7, 19 72

Survey completed May 9, 19 73

INDEX DIAGRAM

Township 23 South, Range 7 West,

6 27	28 5 27	17 4	8	2	7 1 5	3
7 25	26 8 25	16 9	10	11	12	
18 24	24 17 23	16 16	15	14	13	
19 21	22 20 21	15 21 14	22	23	24	
30 19	20 29 19	13 28 13	11 27 10	26 9	25 5	
31	18 32	12 33	9 34	35	4 36	2

The following field notes are those of a dependent resurvey of the north and south miles of the east boundary and a portion of the subdivisional lines of Township 23 South, Range 7 West, Salt Lake Meridian, Utah.

The north, south and east boundaries and the subdivisional lines, were surveyed by Andrew J. Stewart in 1876. The west boundary was surveyed by Julian Bausman in 1869, and resurveyed by Scott P. Stewart and Edward N. Thompson in 1915. The north boundary was resurveyed by Fred R. Chappell in 1968. The southeast corner of the township was remonumented by John W. Dougall in 1911. The south boundary was resurveyed by Howard Miller in 1917.

The dependent resurvey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated August 10, 1972.

The directions of all lines were determined by the solar transit. The lines were carried forward by sustained angulation being supplemented by observations on Polaris taken throughout the progress of the survey. The distances were determined by chaining.

Prior to restoration of any corners, all necessary lines of the original survey were retraced and a diligent search was made for any evidence of the original monuments and other calls of the official record. Identified corners were remonumented in their original positions. Lost corners were reestablished at proportionate positions, but not until exhausting every reasonable possibility of finding direct evidence of the control of each corner.

The geographic position of the southeast corner of the township is at Latitude $38^{\circ} 45' 35''$ N. and Longitude $112^{\circ} 34' 46''$ W. as determined through section line ties from U.S.C. & G.S. triangulation station, "Range", which is a $3/4$ " re-bar protruding 3" above ground, located S. $19^{\circ} 21' 40''$ W., 127.76 chains from the corner of sections 26, 27, 34 and 35, T. 23 S., R. 7 W., at Latitude $38^{\circ} 45' 10.468''$ N. and Longitude $112^{\circ} 37' 35.979''$ W.

The magnetic declination was read at a number of stations throughout the progress of the survey, and the average of these readings was found to be $15^{\circ} 30'$ E.

Dependent Resurvey of a Portion of the East Boundary,
T. 23 S., R. 7 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by Andrew J.
Stewart, Deputy Surveyor, on 1876

Beginning at the cor. of Tps. 23 and 24 S., Rs. 6 and 7 W., which was remonumented by John W. Dougall in 1911 in connection with the survey in T. 24 S., R. 6 W., and is an iron post, 3 ins. diam., protruding 18 ins. above ground, with brass cap mkd.

Dependent Resurvey of a Portion of the East Boundary,
T. 23 S., R. 7 W., Salt Lake Meridian, Utah

CHAINS

T23S
S36|S31
S1|S6
R7W R6W
T24S
1911

Cor. is located at the cor. of fences, bearing
North and East.

N. 0° 26' E., bet. secs. 31 and 36, on the E. bdy. of
the Tp.

Over gently rolling land, through sagebrush, along fence.

37.70 Wash, 100 lks. wide, 10 ft. deep, drains N. 30° E.

40.74 Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, at propor-
tionate distance; there is no remaining evidence of the
original corner.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T23S
R7W R6W
 $\frac{1}{4}$
S36|S31
1972

Set a steel fence post, 6 ft. long, 2 ft. in the
ground, alongside the iron post.

Cor. is located 3 lks. W. of north-south fence.

81.48 The cor. of secs. 25, 30, 31 and 36, monumented with a
sandstone, 12x8x3 ins., firmly set 6 ins. in the ground,
and plainly mkd. 1 notch on the S. edge and 5 notches on
the N. edge.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T23S
R7W R6W
S25|S30
S36|S31
1972

Bury the original cor. stone alongside the
iron post.

Cor. is located 5 lks. W. of cor. of fences
bearing East, West and South.

From the cor. of secs. 1, 6, 7 and 12, on the E. bdy.
of the Tp., determined latitudinally by proportionate
measurement, and longitudinally in line with a fence
to the S.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the East Boundary,
T. 23 S., R. 7 W., Salt Lake Meridian, Utah

CHAINS

T23S
R7W R6W
S1|S6
S12|S7
1972

Set a steel fence post 6 ft. long, 2 ft. in the ground alongside the iron post.

Cor. is located 3.34 chs. N. $0^{\circ} 04' 30''$ W., of cor. of fences bearing E. W. and S.

From this point the cor. of secs. 19, 24, 25 and 30, bears S. $0^{\circ} 04' 30''$ E., 246.03 chs. dist., monumented with a white flintstone, 20x12x10 ins., firmly set 10 ins. in the ground, and plainly mkd. 4 notches on the N. edge and 2 notches on the S. edge.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23S
R7W R6W
S24|S19
S25|S30
1972

Bury the original cor. stone alongside the iron post.

This control line is over private land, was fully re-traced and a careful search was made for evidence of intervening corners, none of which were recovered, or remonumented.

N. $0^{\circ} 30'$ E., bet. secs. 1 and 6, on the E. bdy. of the Tp.

Over gently rolling land, through sagebrush.

41.00 The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, monumented with a black lava stone, 14x12x6 ins., firmly set 8 ins. in the ground and plainly mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23S
R7W R6W
 $\frac{1}{4}$
S1|S6
1972

Bury the original corner stone and set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.

N. $0^{\circ} 18'$ E., beginning new measurement.

Over gently rolling land.

39.82 The cor. of Tps. 22 and 23, S., Rs. 6 and 7 W., monu-

Dependent Resurvey of a Portion of the East Boundary,
T. 23 S., R. 7 W., Salt Lake Meridian, Utah

CHAINS

mented with an iron post, 2½ ins. diam., protruding
6 ins. above ground, with brass cap mkd.

T22S
R7W R6W
S36|S31
S1|S6
R7W R6W
T23S
1968

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 23 S., R. 7 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by Andrew J.
Stewart, Deputy Surveyor, in 1876

From the cor. of secs. 35 and 36, on the S. bdy. of the
Tp., monumented with an iron post, 2 ins. diam., pro-
truding 8 ins. above ground, with brass cap mkd.

T23S R7W
S35|S36
1917

N. 0° 12' E., bet. secs. 35 and 36.

Over nearly level grass land.

39.98 Fence, bears E. and W.; enter sagebrush.

40.54 Point for the ¼ sec. cor. of secs. 35 and 36, at pro-
portionate distance; there is no remaining evidence of
the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T23S R7W
¼
S35|S36
1973

Set a steel fence post, 6 ft. long, 2 ft. in the
ground alongside the iron post.

Raise a mound of stone, 2 ft. base, 1½ ft. high,
W. of cor.

81.08 The cor. of secs. 25, 26, 35 and 36, monumented with a
conglomerate stone, 14x8x6 ins., firmly set 6 ins.
in the ground and plainly mkd. 1 notch on the S. edge
and 1 notch on the E. edge.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 23 S., R. 7 W., Salt Lake Meridian, Utah

CHAINS

T23S R7W
S26|S25
S35|S36
1972

Bury the original corner stone and set a steel
fence post, 6 ft. long, 2 ft. in the ground,
alongside the iron post.

Cor. is located on a low spur, sloping N.

From the cor. of secs. 25, 30, 31 and 36, on the E. bdy.
of the Tp., hereinbefore described.

S. 88° 59' W., bet. secs. 25 and 36.

Over gently rolling land, through sagebrush and along
fence line.

34.00 Enter scattered timber.

40.70 Fence, bears S. and N. 92 lks., thence E.

40.97 The $\frac{1}{4}$ sec. cor. of secs. 25 and 36, monumented with a
quartzite stone, 18x16x12 ins., firmly set 10 ins. in the
ground, and plainly mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T23S R7W
 $\frac{1}{4}$ $\frac{S25}{S36}$
1972

Bury original cor. stone and set a steel fence
post, 6 ft. long, 2 ft. in the ground alongside
the iron post.

From this point, a $\frac{1}{2}$ in. re-bar, protruding 3 ins. above
ground, bears N. 21° 31' E., 63.2 lks.

N. 89° 07' W., beginning new measurement.

Over gently rolling land, through scattered timber.

9.00 Draw, drains N.; leave timber.

38.15 Top of low ridge.

39.50 Draw, drains N.

40.64 The cor. of secs. 25, 26, 35 and 36.

From the cor. of secs. 1, 6, 7 and 12, on the E. bdy.
of the Tp., hereinbefore described.

S. 88° 02' W., bet. secs. 1 and 12.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 23 S., R. 7 W., Salt Lake Meridian, Utah

CHAINS	
	Over gently rolling land, through sagebrush and along the N. side of a fence.
14.70	Trail road, bears N. 10° W. and S. 10° E. 2.00 chs. to junction.
22.20	Trail road, bears N. 44° W. and S. 44° E.
40.98	The $\frac{1}{4}$ sec. cor. of secs. 1 and 12, monumented with a black lava stone, 14x14x4 ins., firmly set 10 ins. in the ground, and plainly mkd. $\frac{1}{4}$ on N. face.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} \text{T23S R7W} \\ \frac{1}{4} \frac{\text{S1}}{\text{S12}} \\ 1972 \end{array}$
	Bury the original corner stone and set a steel fence post, 6 ft. long, 2 ft. in the ground alongside the iron post.
	Cor. is located 1.00 ch. N. of fence bearing east and west.
	<hr/>
	S. 89° 55' W., beginning new measurement.
	Over gently rolling land and along the N. side of fence.
40.26	The cor. of secs. 1, 2, 11 and 12, determined by cor. of fences bearing N. and E., with old decayed cedar post and lath lying loose alongside. This position is harmoniously related to existing original corners, and is accepted as the best existing evidence of the position of the original corner.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} \text{T23S R7W} \\ \frac{\text{S2} \text{S1}}{\text{S11} \text{S12}} \\ 1972 \end{array}$
	To verify that this is the original corner position, I retraced bet. secs. 11 and 12, and found the cor. of secs. 11, 12, 13 and 14 to be S. 0° 01' E., 82.68 chs. dist., monumented with a limestone, 18x12x10 ins., firmly set 10 ins. in the ground, and plainly mkd. 4 notches on the S. edge and 1 notch on the E. edge.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 23 S., R. 7 W., Salt Lake Meridian, Utah

CHAINS

T23S R7W
 $\frac{S11|S12}{S14|S13}$
 1972

Bury the original corner stone alongside the
iron post.

I also retraced bet. secs. 2 and 11, and found the cor.
of secs. 2, 3, 10 and 11 to be S. $89^{\circ} 44'$ W., 80.18 chs.
dist., monumented with a white limestone, 16x8x6 ins.,
firmly set, 10 ins. in the ground, and plainly mkd. 5
notches on the S. edge and 2 notches on the E. edge.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T23S R7W
 $\frac{S3|S2}{S10|S11}$
 1972

Bury the original corner stone alongside the
iron post.

These control lines are over private land, were fully
retraced and careful search was made for evidence of
intervening corners, none of which was recovered or
remonumented.

N. $1^{\circ} 29'$ E., bet. secs. 1 and 2.

Over gently rolling land, through sagebrush and along
fence.

37.80 Trail road, bears N. 70° W. and S. 70° E.

41.59 The $\frac{1}{4}$ sec. cor. of secs. 1 and 2, monumented with a
black lava stone, 12x12x8 ins., firmly set 6 ins. in
the ground, and plainly mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T23S R7W
 $\frac{1}{4}$
 $\frac{S2|S1}{1972}$

Bury original corner stone and set a steel
fence post, 6 ft. long, 2 ft. in the ground
alongside the iron post.

Cor. is located 60 lks. E. of fence bearing
north and south.

N. $0^{\circ} 07'$ E., beginning new measurement.

Over gently rolling land, along E. side of fence.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 23 S. R. 7 W. Salt Lake Meridian Utah

CHAINS

- 27.50 Trail road, bears N. 45° E. and S. 45° W.
- 39.30 Fence cor. bears W. 1.21 chs. Fences bear S. and W.
- 40.02 The cor. of secs. 1, 2, 35 and 36 on the N. bdy. of the
Tp., monumented with an iron post, 2½ ins. diam., pro-
truding 6 ins. above ground, with brass cap mkd.

T22S R7W
S35|S36
S2|S1
T23S R7W
1968

From the cor. of secs. 34 and 35, on the S. bdy. of the
Tp., monumented with an iron post, 2 ins. diam., pro-
truding 8 ins. above ground, with brass cap mkd.

T23S R7W
S34|S35
1917

Cor. is located in cor. of fences, bearing N. 0°
17' W. and E. for 1.99 chs. thence S.

N. 0° 33' E., bet. secs. 34 and 35.

Over nearly level land, through sagebrush and along
E. side of fence.

- 40.05 Fence cor., bears W. 57 lks. Fences bear E., W. and
S. 0° 17' E.
- 40.40 Point for the ¼ sec. cor. of secs. 34 and 35, at pro-
portionate distance; there is no remaining evidence of
the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T23S R7W
¼
S34|S35
1973

Set a steel fence post, 6 ft. long, 2 ft. in the
ground, alongside the iron post.

Deposit the broken glass at base of iron post.

- 80.80 The cor. of secs. 26, 27, 34 and 35, monumented with a
blue limestone, 12x8x6 ins., firmly set 6 ins. in the
ground and plainly mkd. 1 notch on the S. edge and 2
notches on the E. edge.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T23S R7W
S27|S26
S34|S35
1972

Dependent Resurvey of a Portion of the Subdivisional
 T23S R7W S26 S33 S34

CHAINS

Bury the original corner stone and set a steel fence post, 6 ft. long, 2 ft. in the ground alongside the iron post.

From this cor., U.S.C. & G.S. triangulation station "Range" bears S. $19^{\circ} 21' 40''$ W., 127.76 chs. dist.

From the cor. of secs. 25, 26, 35 and 36.

West, bet. secs. 26 and 35.

Over gently rolling land, through sagebrush.

1.35 Wash, 15 lks. wide, 3 ft. deep, drains N. 45° E.

8.05 Trail road, bears N. and S.

40.26 The $\frac{1}{4}$ sec. cor. of secs. 26 and 35, monumented with a blue limestone, 14x10x10 ins., firmly set 6 ins. in the ground, and plainly mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23S R7W

$\frac{1}{4}$ $\frac{S26}{S35}$
 1972

Bury the original corner stone and set a steel fence post, 6 ft. long, 2 ft. in the ground alongside the iron post.

N. $89^{\circ} 50'$ W., beginning new measurement.

Over gently rolling land.

27.40 Improved dirt road, bears N. 31° W. and S. 31° E.

40.30 The cor. of secs. 26, 27, 34 and 35.

From the cor. of secs. 33 and 34, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., protruding 12 ins. above ground, with brass cap mkd.

T23S R7W
 $\frac{S33}{S34}$
 1917

Cor. is located in a fence, bearing east and west.

N. $0^{\circ} 14'$ E., bet. secs. 33 and 34.

Over gently rolling land, through sagebrush.

31.00 Trail road, bears E. and W.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 23 S. R. 7 W. Salt Lake Meridian, Utah

CHAINS

40.28 The $\frac{1}{4}$ sec. cor. of secs. 33 and 34, monumented with a blue limestone, 14x10x5 ins., firmly set 6 ins. in the ground, and plainly mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23S R7W

$\frac{1}{4}$
S33|S34
1972

Bury the original corner stone and set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.

N. $0^{\circ} 14'$ E., beginning new measurement.

Over gently rolling land.

9.10 Fence, bears S. 45° E. and N. 45° W. 85 lks., thence N.

40.38 The cor. of secs. 27, 28, 33 and 34, monumented with a sandstone, 18x14x12 ins., firmly set 10 ins. in the ground, and plainly mkd. 1 notch on the S. edge and 3 notches on the E. edge.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23S R7W
S28|S27
S33|S34
1972

Bury the original corner stone and set a steel fence post, 6 ft. long, 2 ft. in the ground alongside the iron post.

From the cor. of secs. 26, 27, 34 and 35.

N. $89^{\circ} 51'$ W., bet. secs. 27 and 34.

Over gently rolling land, through sagebrush.

40.88 The $\frac{1}{4}$ sec. cor. of secs. 27 and 34, monumented with a gray limestone, 14x10x5 ins., firmly set 6 ins. in the ground and plainly mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional
 T23S R7W S27 S34

CHAINS

T23S R7W
 $\frac{1}{4}$ $\frac{S27}{S34}$
 1972

Bury the original corner stone and set a steel
 fence post, 6 ft. long, 2 ft. in the ground
 alongside the iron post.

N. 89° 53' W., beginning new measurement.

Over gently rolling land.

40.32 The cor. of secs. 27, 28, 33 and 34.

N. 0° 22' E., bet. secs. 27 and 28.

Over gently rolling land, through sagebrush along E.
 side of fence.

40.62 The $\frac{1}{4}$ sec. cor. of secs. 27 and 28, monumented with a
 blue limestone, 12x8x6 ins., firmly set 6 ins. in the
 ground and plainly mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
 in the ground, with brass cap mkd.

T23S R7W
 $\frac{1}{4}$
 S28|S27
 1972

Bury the original corner stone and set a
 steel fence post, 6 ft. long, 2 ft. in the ground,
 alongside the iron post.

Cor. is located 22 lks. E. of fence, bearing north
 and south.

N. 0° 26' E., beginning new measurement.

Over gently rolling land, along E. side of fence.

40.70 The cor. of secs. 21, 22, 27 and 28, monumented with a
 white limestone, 18x8x4 ins., firmly set 10 ins. in
 the ground, and plainly mkd. 2 notches on the S. edge
 and 3 notches on the E. edge.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
 in the ground, with brass cap mkd.

T23S R7W
 S21|S22
 S28|S27
 1972

Bury the original corner stone and set a steel
 fence post, 6 ft. long, 2 ft. in the ground

Dependent Resurvey of a Portion of the Subdivisional
 Line of T. 2 S. R. 7 W. Cal. 1891

CHAINS

alongside the iron post.

Cor. is located 14 lks. E. of fence, bearing north
 and south.

From the cor. of secs. 32 and 33, on the S. bdy. of
 the Tp., monumented with an iron post, 2 ins. diam.,
 6 ins. underground, with brass cap mkd.

T23S R7W
S32|S33
 1917

I set a steel fence post, 6 ft. long, 2 ft. in
 the ground alongside the iron post.

Cor. is located 60 lks. W. of cor. of fences
 bearing E., W. and N.

N. 0° 51' E., bet. secs. 32 and 33.

Over gently rolling land, through sagebrush, along
 W. side of fence line.

4.20 Trail road, on top of low ridge, bears E. and W.

39.36 The $\frac{1}{4}$ sec. cor. of secs. 32 and 33, monumented with a
 black lava stone, 14x8x4 ins., firmly set 6 ins. in the
 ground in old N-S fence and plainly mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins.
 in the ground, with brass cap mkd.

T23S R7W
 $\frac{1}{4}$
S32|S33
 1972

Bury the original corner stone and set a steel
 fence post, 6 ft. long, 2 ft. in the ground
 alongside the iron post.

N. 0° 15' E., beginning new measurement.

Over gently rolling land, continue along fence.

40.44 The cor. of secs. 28, 29, 32 and 33, monumented with a
 black lava stone, 14x7x3 ins., firmly set 6 ins. in the
 ground, at cor. of fences bearing S. and N. 88° 32' W.,
 and plainly mkd. 1 notch on the S. edge and 4 notches
 on the E. edge.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins.
 in the ground, with brass cap mkd.

T23S R7W
S29|S28
S32|S33
 1972

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 23 S., R. 7 W., Salt Lake Meridian, Utah

CHAINS

Bury the original corner stone alongside the
iron post.

From the cor. of secs. 27, 28, 33 and 34.

S. 89° 54' W., bet. secs. 28 and 33.

Over gently rolling land, through sagebrush.

0.36 Fence, bears N. and S.

40.32 Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33, at propor-
tionate distance; there is no remaining evidence of the
original corner.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T23S R7W
 $\frac{1}{4}$ S28
S33
1972

Set a steel fence post, 6 ft. long, 2 ft. in the
ground alongside the iron post.

54.65 Wash, 20 lks. wide, 3 ft. deep, drains N.

80.64 The cor. of secs. 28, 29, 32 and 33.

N. 0° 14' E., bet. secs. 28 and 29.

Over gently rolling land, through sagebrush.

40.14 The $\frac{1}{4}$ sec. cor. of secs. 28 and 29, monumented with a
decayed cedar post, no visible scribe marks, firmly
set in the ground, with old lath lying loose alongside.
This position is harmoniously related to existing
original corners and is accepted as the best existing
evidence of the position of the original corner.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T23S R7W
 $\frac{1}{4}$
S29|S28
1972

Set old cedar post, alongside the iron post.

N. 0° 03' E., beginning new measurement.

Over gently rolling land.

32.00 Enter scattered timber.

Dependent Resurvey of a Portion of the Subdivisional
T. 22 S., R. 7 E., S. 1 E., T. 22 S., R. 7 E., S. 1 E., T. 22 S., R. 7 E., S. 1 E.

CHAINS

40.84

The cor. of secs. 20, 21, 28 and 29, determined from the original bearing trees:

A juniper, 8 ins. diam., bears N. 64° E., 115 lks. dist., mkd. BT.

A juniper, 12 ins. diam., bears S. 43° E., 118 lks. dist., mkd. S28 BT. (Record bearing is S. 40° E.)

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23S R7W

S20|S21

S29|S28

1972

Set a steel fence post, 6 ft. long, 2 ft. in the ground alongside the iron post.

From the cor. of secs. 21, 22, 27 and 28.

S. 89° 30' W., bet. secs. 21 and 28.

Over gently rolling land, through sagebrush.

0.14

Fence, bears S. and N. 18 lks., thence W.

41.60

The ¼ sec. cor. of secs. 21 and 28, monumented with a granite stone, 10x8x6 ins., firmly set 5 ins. in the ground, and plainly mkd. ¼ on N. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23S R7W

S21

¼ S28

1972

Bury the original corner stone and set a steel fence post, 6 ft. long, 2 ft. in the ground alongside the iron post.

Cor. is located 107 lks. S. of fence, bearing east and west.

S. 89° 51' W., beginning new measurement.

Over gently rolling land, along S. side of fence.

32.00

Enter scattered timber.

39.42

The cor. of secs. 20, 21, 28 and 29.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 23 S., R. 7 W., Salt Lake Meridian, Utah

CHAINS

N. 0° 41' E., bet. secs. 20 and 21.

Over gently rolling land, through scattered timber and sagebrush.

2.10 Cor. of fences, bearing E. and N.; thence along fence.

8.00 Leave timber.

41.54 Point for the $\frac{1}{4}$ sec. cor. of secs 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23S R7W

$\frac{1}{4}$

S20|S21

1972

Set a steel fence post, 6 ft. long, 2 ft. in the ground alongside the iron post.

Cor. is located 4 lks. W. of fence, bearing north and south.

62.31 Point for the N. 1/16 sec. cor. of secs. 20 and 21.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23S R7W

N1/16

S20|S21

1972

Set a steel fence post, 6 ft. long, 2 ft. in the ground alongside the iron post.

Cor. is located 5 lks. W. of fence, bearing north and south.

83.08 The cor. of secs. 16, 17, 20 and 21, monumented with a black lava stone, 16x6x3 ins., firmly set 10 ins. in the ground, plainly mkd. 3 notches on the S. edge and 4 notches on the E. edge.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23S R7W

S17|S16

S20|S21

1972

Bury the original corner stone and set a steel fence post, 6 ft. long, 2 ft. in the ground alongside the iron post.

Cor. is located 7 lks. W. of fence, bearing north and south.

Dependent Resurvey of a Portion of the Subdivisional
 Lines of the 2nd 12th R. 7th S. 10th T. 12th N. 12th E.

CHAINS

N. 0° 09' W., bet. secs. 16 and 17.

Over gently rolling land, through sagebrush and along fence.

- 39.96 The $\frac{1}{2}$ sec. cor. of secs. 16 and 17, determined from a mound of stone, no marked stone was found. This position is harmoniously related to existing original corners and is accepted as the best existing evidence of the position of the original corner.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam. 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T23S R7W

$\frac{1}{2}$
 S17|S16
 1972

Set a steel fence post, 6 ft. long, 2 ft. in the ground alongside the iron post.

Cor. is located 6 lks. W. of fence, bearing north and south.

N. 0° 11' W., beginning new measurement.

Over gently rolling land.

- 19.40 Improved dirt road, bears E. and W. 2.00 chs. to junction.

- 40.20 The cor. of secs. 8, 9, 16 and 17, determined by cor. of fences, bearing N., S. and W. This position is harmoniously related to existing original corners, and is accepted as the best existing evidence of the position of the original corner.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23S R7W

S8|S9
 S17|S16
 1972

N. 0° 06' W., bet. secs. 8 and 9.

Over gently rolling land, through sagebrush, and along fence.

- 39.56 The $\frac{1}{2}$ sec. cor. of secs. 8 and 9, determined by cor. of fences, bearing N., S. and E. This position is harmoniously related to existing original corners and is accepted as the best existing evidence of the position of the original corner.

At the cor. point

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 23 S., R. 7 W., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T23S R7W

$\frac{1}{4}$
S8|S9
1972

N. $0^{\circ} 06'$ W., beginning new measurement.

Over gently rolling land, and along fence.

5.50 Drainage ditch, drains W.

42.70 The cor. of secs. 4, 5, 8 and 9, monumented with a
blue limestone, $18 \times 12 \times 5$ ins., firmly set 10 ins. in the
ground and plainly mkd. 5 notches on the S. edge and 4
notches on the E. edge and set in a north-south fence
line.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T23S R7W
S5|S4
S8|S9
1972

Bury the original corner stone alongside the
iron post.

N. $0^{\circ} 07'$ W., bet. secs. 4 and 5.

Over gently rolling land, through sagebrush and along
fence.

40.96 The $\frac{1}{4}$ sec. cor. of secs. 4 and 5, determined by decayed
cedar post lying loose at the cor. of fences, bearing
N., S. and E. This position is harmoniously related
to existing original corners, and is accepted as the
best existing evidence of the position of the original
corner.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground at fence cor., with brass cap mkd.

T23S R7W
 $\frac{1}{4}$
S5|S4
1972

N. $0^{\circ} 20'$ W., beginning new measurement.

Over gently rolling land, and along fence.

39.78 The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of
the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam.,
protruding 6 ins. above ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional

13. 0 1 T 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039

CHAINS

T22S R7W

S32 | S33

S5 | S4

T23S R7W

1968

Cor. is located at cor. of fences, bearing
N. 45° E., E. and S.

From the cor. of secs. 31 and 32, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., protruding 8 ins. above ground, with brass cap mkd.

T23S R7W

s31|s32

1917

Cor. is located at cor. of fences, bearing E. and N.

N. $0^{\circ} 31'$ E., bet. secs. 31 and 32.

Over gently rolling land, through sagebrush and along fence.

40.32 Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23S R7W

 $\frac{1}{4}$

S31 | S32

1972

Set a steel fence post, 6 ft. long, 2 ft. in the ground alongside the iron post.

Cor. is located 8 lks. E. of fence, bearing north and south.

Continue along fence line.

80.44 Fence cor. bears W. 22 lks. Fences bear S. and E.

80.64 The cor. of secs. 29, 30, 31 and 32, monumented with a black lava stone, 15x8x6 ins., firmly set 6 ins. in the ground, and plainly mkd. 1 notch on the S. edge and 5 notches on the E. edge.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23S R7W

s30 | s29

S31	S32
-----	-----

1972

Bury the original corner stone and set a steel fence post, 6 ft. long, 2 ft. in the ground alongside the iron post.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 23 S., R. 7 W., Salt Lake Meridian, Utah

CHAINS

From the cor. of secs. 28, 29, 32 and 33.

N. 88° 32' W., bet. secs. 29 and 32.

Over nearly level land, through sagebrush along old
fence line.

38.30 Unimproved dirt road, bears N. 30° E. and S. 30° W.

40.06 The $\frac{1}{4}$ sec. cor. of secs. 29 and 32, monumented with
a black lava stone, 12x12x4 ins., firmly set 6 ins. in
the ground in a fence line, and plainly mkd. $\frac{1}{4}$ on N.
face.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins.
in the ground with brass cap mkd.

T23S R7W
 $\frac{1}{4}$ $\frac{S29}{S32}$
1973

Bury the original corner stone and set a steel
fence post, 6 ft. long, 2 ft. in the ground
alongside the iron post.

Deposit broken glass at base of iron post.

N. 87° 51' W., beginning new measurement.

Over gently rolling land, and along fence.

32.00 Base of lava ridge, bears N. and S.; asc. 65 ft. over
E. slope and lava ledges.

33.15 Top of lava ledges, bears N. and S.; thence over nearly
level land.

40.55 The cor. of secs. 29, 30, 31 and 32.

N. 89° 29' W., bet. secs. 30 and 31.

Over rolling land, through sagebrush.

24.50 Enter scattered timber, bears N. and S.

31.40 Begin descent over W. slope.

40.40 The $\frac{1}{4}$ sec. cor. of secs. 30 and 31, monumented with a
broken sandstone, bottom portion firmly set 6 ins. in
the ground, top portion broken off plainly mkd. $\frac{1}{4}$.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T23S R6W
 $\frac{1}{4}$ $\frac{S30}{S31}$
1973

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 23 S., R. 7 W., Salt Lake Meridian, Utah

CHAINS	<p>Bury the original corner stone and set a steel fence post, 6 ft. long, 2 ft. in the ground alongside the iron post.</p> <hr/> <p>N. 89° 58' W., beginning new measurement.</p> <p>6.00 Leave timber, bears NE. and SW.</p> <p>39.88 The cor. of secs. 30 and 31, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., protruding 18 ins. above ground and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T23S R8W R7W S25 S36 S30 S31 1915</p> </div> <p>I destroyed markings pertaining to sec. 25 and added 1973 above 1915.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0° 23' E., bet. secs. 29 and 30.</p> <p>Over gently rolling land, through sagebrush.</p> <p>39.50 The $\frac{1}{4}$ sec. cor. of secs. 29 and 30, monumented with a black lava stone, 18x16x6 ins., firmly set 10 ins. in the ground, and plainly mkd. $\frac{1}{4}$ on W. face.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T23S R7W $\frac{1}{4}$ S30 S29 1972</p> </div> <p>Bury the original corner stone and set a steel fence post, 6 ft. long, 2 ft. in the ground alongside the iron post.</p> <hr/> <p>N. 0° 31' E., beginning new measurement.</p> <p>Over gently rolling land.</p> <p>40.97 The cor. of secs. 19, 20, 29 and 30, monumented with a black lava stone, 12x10x8 ins., firmly set 6 ins. in the ground, and plainly mkd. 2 notches on the S. edge and 5 notches on the E. edge.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
--------	---

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 23 S., R. 7 W., Salt Lake Meridian, Utah

CHAINS

T23S R7W
S19|S20
S30|S29
1972

Bury the original corner stone and set a steel
fence post, 6 ft. long, 2 ft. in the ground
alongside the iron post.

Raise a mound of stone, 2½ ft. base, 1½ ft. high,
W. of cor.

From the cor. of secs. 20, 21, 28 and 29.

N. 88° 31' W., bet. secs. 20 and 29.

Over gently rolling land, through scattered timber
and sagebrush.

36.75 Unimproved dirt road, bears N. 18° W. and S. 18° E.

40.01 The ¼ sec. cor. of secs. 20 and 29, monumented with a
juniper, 18 ins. diam. plainly mkd. ¼ S. on N. face

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground under markings on tree, with brass cap mkd.

T23S R7W
¼ S20
S29
1972

from which

A juniper, 8 ins. diam., bears South 81.5 lks.
dist., mkd. ¼ S BT.

N. 88° 34' W., beginning new measurement.

Over gently rolling land.

11.00 Leave timber at base of lava flow.

15.00 Top of lava flow.

40.19 The cor. of secs. 19, 20, 29 and 30.

N. 89° 20' W., bet. secs. 19 and 30.

Over gently rolling land, through sagebrush.

40.58 The ¼ sec. cor. of secs. 19 and 30, monumented with a
black lava stone, 18x10x6 ins., firmly set 10 ins. in
the ground, and plainly mkd. ¼ on N. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins.
in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional
 Lines of T. 2 S. R. 7 W., Salt Lake Meridian, Utah

CHAINS

T23S R7W
 $\frac{1}{4}$ $\frac{S19}{S30}$
 1972

Bury the original cor. stone alongside the iron post.

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

N. 89° 44' W., beginning new measurement.

Over gently rolling land.

6.00 Top of lava flow.

12.00 Base of lava flow.

32.00 Improved dirt road, bears N. 39° E. and S. 39° W.

39.98 The cor. of secs. 19 and 30, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., protruding 18 ins. above ground, with brass cap mkd.

T23S
 R8W R7W
 $\frac{S24}{S25}$ $\frac{S19}{S30}$
 1915

I destroyed markings pertaining to sec. 24 and added 1973 above 1915.

From the cor. of secs. 19, 20, 29 and 30.

N. 0° 28' E., bet. secs. 19 and 20.

Over gently rolling land, through sagebrush.

40.44 The $\frac{1}{4}$ sec. cor. of secs. 19 and 20, monumented with a black lava stone, 20x14x6 ins., firmly set 12 ins. in the ground, and plainly mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T23S R7W
 $\frac{1}{4}$ $\frac{S19}{S20}$
 1972

Bury the original corner stone and set a steel fence post, 6 ft. long, 1 ft. in the ground, alongside the iron post.

N. 0° 12' E., beginning new measurement.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 23 S., R. 7 W., Salt Lake Meridian Utah

CHAINS

Over gently rolling land.

2.40 Ridge, bears NE. and SW.

20.26 Point for the N. 1/16 sec. cor. of secs. 19 and 20.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23S R7W
N1/16
S19|S20
1972

Set a steel fence post, 6 ft. long, 2 ft. in the ground alongside the iron post.

22.25 Improved dirt road, bears N. 60° E. and S. 60° W.

40.52 Point for the cor. of secs. 17, 18, 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23S R7W
S18|S17
S19|S20
1972

Set a steel fence post, 6 ft. long, 2 ft. in the ground alongside the iron post.

From the cor. of secs. 16, 17, 20 and 21.

S. 89° 27' W., bet. secs. 17 and 20.

Over gently rolling land, through sagebrush.

40.04 The $\frac{1}{4}$ sec. cor. of secs. 17 and 20, monumented with a cobblestone, 12x12x6 ins., firmly set 6 ins. in the ground, and plainly mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23S R7W
 $\frac{1}{4}$ $\frac{S17}{S20}$
1972

Bury the original corner stone and set a steel fence post, 6 ft. long, 2 ft. in the ground alongside the iron post.

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

N. 89° 36' W., beginning new measurement.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 23 S. R. 7 W. Salt Lake Meridian Utah

CHAINS	
	Over rolling land.
5.70	Improved dirt road, bears N. 34° E. and S. 34° W.
40.66	The cor. of secs. 17, 18, 19 and 20.
	N. 89° 49' W., bet. secs. 18 and 19.
	Over gently rolling land, through sagebrush.
40.82	Point for the ¼ sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div>T23S R7W S18 ¼ ——— S19 1972</div>
	Set a steel fence post, 6 ft. long, 2 ft. in the ground alongside the iron post.
80.62	The cor. of secs. 18 and 19, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., protruding 18 ins. above ground, with brass cap mkd.
	<div>T23S R8W R7W S13 S24 S18 S19 1915</div>
	I destroyed markings pertaining to sec. 13 and added 1973 above 1915.
	From the cor. of secs. 17, 18, 19 and 20.
	N. 0° 25' E., bet. secs. 17 and 18.
	Over gently rolling land, through sagebrush.
40.52	Point for the ¼ sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div>T23S R7W ¼ S18 S17 1972</div>
	Set a steel fence post, 6 ft. long, 2 ft. in the ground alongside the iron post.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 23 S., R. 7 W., Salt Lake Meridian, Utah

CHAINS

81.04 The cor. of secs. 7, 8, 17 and 18, monumented with a
chard cedar post, 3 ft. long, 4 ins. diam., set 12 ins.
in the ground at cor. of fences, bearing N. and E.,
dimly mkd. 4 notches on S. edge and 5 notches on E. edge.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T23S R7W
S7|S8
S18|S17
1972

Set the original cedar post alongside the iron
post.

From the cor. of secs. 8, 9, 16 and 17.

N. $89^{\circ} 26'$ W., bet. secs. 8 and 17.

Over gently rolling land, through sagebrush and along
fence.

18.25 Improved dirt road, bears N. $34^{\circ} 30'$ W. and S. $34^{\circ} 30'$
E.

39.96 The $\frac{1}{4}$ sec. cor. of secs. 8 and 17, monumented with a
sandstone, $18 \times 14 \times 4$ ins., firmly set 6 ins. in the
ground in fence line and plainly mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T23S R7W
S8
 $\frac{1}{4}$ S17
1973

Bury the original corner stone alongside the
iron post.

N. $89^{\circ} 26'$ W., beginning new measurement.

Continue along fence line.

13.80 Spur, slopes N.

39.96 The cor. of secs. 7, 8, 17 and 18.

N. $89^{\circ} 36'$ W., bet. secs. 7 and 18.

Over gently rolling land, through sagebrush.

40.73 Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18, at propor-
tionate distance; there is no remaining evidence of the
original corner.

22

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 23 S., R. 7 W., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23S R7W
 $\frac{1}{4}$ $\frac{S7}{S18}$
1972

Set a steel fence post, 6 ft. long, 2 ft. in the ground alongside the iron post.

80.44 The cor. of secs. 7 and 18, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., protruding 12 ins. above ground, with brass cap mkd.

T23S
 $\frac{S12}{S13} | \frac{S7}{S18}$
R8W R7W
1915

I destroyed markings pertaining to sec. 12 and added 1973 above 1915.

From the cor. of secs. 7, 8, 17 and 18.

N. $0^{\circ} 27'$ W., bet. secs. 7 and 8.

Over gently rolling land, through sagebrush and along fence.

40.00 Fence, bears W. and E. 72 lks. thence S.

40.47 Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23S R7W
 $\frac{1}{4}$
S7 | S8
1972

Set a steel fence post, 6 ft. long, 2 ft. in the ground alongside the iron post.

48.00 Improved dirt road, bears E. and W.

80.94 The cor. of secs. 5, 6, 7 and 8, monumented with a decayed cedar post, 3 ft. long, 4 ins. diam., set 12 ins. in the ground, with 3 notches still visible on the S. edge.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23S R7W
 $\frac{S6}{S7} | \frac{S5}{S8}$
1972

21

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 23 S., R. 7 W., Salt Lake Meridian, Utah

CHAINS

Set the original cedar post, and a steel fence post, 6 ft. long, 2 ft. in the ground alongside the iron post.

From the cor. of secs. 4, 5, 8 and 9.

S. 89° 37' W., bet. secs. 5 and 8.

Over neary level land, through sagebrush.

29.10 Unimproved dirt road, bears N. and S.

40.20 Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23S R7W
 $\frac{1}{4} \frac{S5}{S8}$
1973

Set a steel fence post, 6 ft. long, 2 ft. in the ground alongside the iron post.

67.20 Unimproved dirt road, bears N. 50° W. and S. 50° E.

80.40 The cor. of secs. 5, 6, 7 and 8.

S. 89° 59' W., bet. secs. 6 and 7.

Over nearly level land, through sagebrush.

40.44 Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23S R7W
 $\frac{1}{4} \frac{S6}{S7}$
1973

Set a steel fence post, 6 ft. long, 2 ft. in the ground alongside the iron post.

Continue over nearly level land.

79.37 The cor. of secs. 6 and 7, on the W. bdy. of the Tp., monumented with an old rotten cedar post firmly set in the ground. There is no evidence of an iron post, as described by Stewart and Thompson in 1915. To prove that this the original corner point, I checked the bearing to the cor. of Tps. 22 and 23 S., R. 7 W., and found it to be N. 0° 12' E., the same as Stewart and Thompson found it to be in 1915. I also found the closing corner of secs. 1 and 12, T. 23 S., R. 8 W., to be on line at N. 0° 12' E., 4.03 chs. dist., the same as record.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 23 S., R. 7 W., Salt Lake Meridian, Utah

CHAINS

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam. 24 ins.
in the ground, with brass cap mkd.

T23S
R8W R7W
S12 | S6
 | S7

1973

Set a steel fence post, 6 ft. long, 2 ft. in the
ground alongside the iron post.

From the cor. of secs. 5, 6, 7 and 8.

N. 0° 28' W., bet. secs. 5 and 6.

Over gently rolling land, through sagebrush.

11.85 Unimproved dirt road, bears N. 50° W. and S. 50° E.

40.17 Point for the $\frac{1}{4}$ sec. cor. of secs 5 and 6, at propor-
tionate distance; there is no remaining evidence of the
original corner.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T23S R7W
 $\frac{1}{4}$
S6 | S5
1972

Set a steel fence post, 6 ft. long, 2 ft. in the
ground alongside the iron post.

81.05 The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of
the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam.,
protruding 6 ins. above ground, with brass cap mkd.

T22S R7W
S31 | S32
S6 | S5
T23S R7W
1968

General Description

Township 23 South, Range 7 West is situated about
8 miles west of Kanosh, Utah. The elevation varies
from about 4,800 to 5,200 feet above sea level. The
soil varies from volcanic on the higher elevation to
sandy clay on the lower elevations. The land is mostly
gently rolling. There is a scattered growth of
juniper in the southwest portion of the township. The
undergrowth is sagbrush. The township is accessible by an
improved gravel road from Kanosh, which enters the
township through sec. 13, and by numerous trail roads
located throughout the township. The general
drainage is in a northerly direction. There was no clear
water, and no permanent habitations noted.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 23 S., R. 7 W., Salt Lake Meridian, Utah

CHAINS

An average number of readings throughout the
the area surveyed gives a mean magnetic declination
of 15° 30' E., with no noticeable difference due to
local attraction.

Blank

Page

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Craig P. Sylvester	Cadastral Surveyor
H. Dennis Badger	Cadastral Surveyor
Fernal D. Reynolds	Survey Technician
Gail E. Reynolds	Survey Aid

CERTIFICATE OF SURVEY

(I) ~~(We)~~ Milton R. Workman

, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 10th day

of August, 1972, (I) ~~(We)~~ have dependently resurveyed the north and south miles of the east boundary and a portion of the subdivisional lines of Township 23 South, Range 7 West

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~(Us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

May 16, 1973
(Date)

Milton R. Workman
(Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL

Date JUN 14 1974

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the dependent resurvey of the north and south miles of the east boundary and a portion of the subdivisional lines of T. 23 S., R. 7 W., Salt Lake Meridian, Utah

executed by Milton R. Workman, Supervisory Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

AUG 5 1975
(Date)

Bernard W. Fisher
(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in~~
~~is a true copy of the original field notes.~~

(Date)

(Chief, Division of Cadastral Survey) ~~PRO TROSA~~

Blank

Page

Blank

Page

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
ORIGINAL

FIELD NOTES

OF THE

RETRACEMENT OF THE

UTAH-ARIZONA STATE BOUNDARY FROM

MILE POST 19.463 TO MILE POST 24 AND

A DEPENDENT RESURVEY OF THE WEST BOUNDARY AND

A PORTION OF THE SUBDIVISIONAL LINES

AND THE SURVEY

OF A PORTION OF THE SUBDIVISION OF SECTION 22

AND THE MEANDERS OF A PORTION OF THE VIRGIN RIVER

TOWNSHIP 43 SOUTH, RANGE 16 WEST

Of the Salt Lake Meridian,In the State of Utah

EXECUTED BY

Craig P. Sylvester Supervisory Cadastral Surveyor

Under special instructions dated October 15, 19 70, which provided for the surveys
included under Group Number 521, approved October 15, 1970,
and assignment instructions dated February 9, 19 71.

Survey commenced February 22, 19 71Survey completed April 4, 19 72

INDEX DIAGRAM

Township 43 South, Range 16 West,

13 6 64	65 8 63	48 4 47	34 8 34	22 2 21	1
12 7 61	62 8 60	46 9 45	33 10 32	20 11 20	14 12
10 18 58	59 17 57	44 16 43	31 15 30	19 14	13
9 19 55	56 20 54	42 21 39	28 22 27	18 23	24
8 30 51	52 29 50	38 28 37	25 27 24	17 26	25
6 31 2	49 32 3	35 33 4	23 34 5	15 35 5	36
19.463 M.P. 20 M.P.	UTAH 21 M.P.	ARIZONA 22 M.P.	STATE 23.087 M.P.	BOUNDARY 24 M.P.	

Partial subdivision of section 22, pages 66-67.

Present meanders of Virgin River, pages 67-74.

Adjusted original meanders of Virgin River, pages 74-75.

CHAINS

Towns 43 South, R. 16 West, Salt Lake Meridian, Utah

T. 43 S., R. 16 W.History of SurveysSurveyed by Retr. or Resurveyed byUTAH-ARIZONA STATE BOUNDARYM.P. 19 to 26 Howard B. Carpenter
1901M.P. 19.463 to M.P.
20 and M.P. 22 to M.P.
23.087Joseph P. Davis 1920-
1921SOUTH BOUNDARY (later Superseded by Utah-Arizona State
Bdy.)All Washington Jenkins and
Joseph A. West
1897EAST BOUNDARY (Pine Valley Guide Meridian)E. Bdy., Sec. 1 Joseph Gorlinksi
1870South 5 miles W. Jenkins &
J.A. West 1897E. Bdy., Sec. 36 A.J. Stewart Jr. &
L.A. Snow 1909WEST BOUNDARYAll W. Jenkins &
J.A. West 1897W. Bdy., Sec. 31 A.J. Stewart Jr. &
L.A. Snow 1909NORTH BOUNDARYE. 2 miles Joseph Gorlinski
1870W. 4 miles W. Jenkins &
J.A. West 1897All Mayhew H. Dalley 1900
W. 5½ miles Glen B. Hatch 1968SUBDIVISIONSPortions of Secs. 1 & 2
Joseph Gorlinski
1870All but the above
portions W. Jenkins &
J.A. West 1897South tier of sections A.J. Stewart Jr. &
L.A. Snow 1909MEANDERS OF VIRGIN RIVERAll W. Jenkins &
J.A. West 1897The following field notes are those of the retracement of
the Utah-Arizona State Boundary from mile post 19.463 to
mile post 24, and a dependent resurvey of the west bound-

Townshi 43 South, Range 16 West Salt Lake Meridian Utah

ary and a portion of the subdivisional lines and meanders of the Virgin River through sections 15, 20, 21, 22, 27 and 28, and the survey of a portion of the subdivision of section 22, Township 43 South, Range 16 West, Salt Lake Meridian, Utah.

The dependent resurvey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated October 15, 1970.

The direction of the lines of this survey were determined by hour angle observations on Polaris. The lines were carried forward by sustained angulation being supplented by numerous observations on Polaris taken throughout the progress of the survey.

The lengths of all lines were determined by chaining where possible; otherwise by triangulation. The details of such triangulations have been thoroughly verified and in order to simplify the record the diagrams and reductions are omitted from these field notes.

Prior to restoration of any corners, all necessary lines of the original survey were retraced and a diligent search was made for any evidence of the original monuments and other calls of the official record. Identified corners were remonumented in their original positions. Lost corners were reestablished at proportionate positions, but not until exhausting every reasonable possibility of finding direct evidence of the control of each corner.

The geographic position of the southeast corner of section 34 is at Latitude 37° 00' 00" N. and Longitude 113° 37' 18" W., as determined through section line ties from U.S.C. & G.S. triangulation station "St. George Airport" located in sec. 36, T. 42 S., R. 16 W.

The magnetic declination was read at a number of stations throughout the progress of the survey and the average of these readings was found to be 15° 00' E.

Retracement of the Utah-Arizona Boundary
from mile post 19.463 to mile post 24

Retracement of the Survey Executed by Howard B. Carperter, U.S. Surveyor and Astronomer, in 1901, and the Retracement Executed by Joseph P. Davis, U.S. Cadastral Engineer, in 1920-21

Beginning at the 19.463 Mile Post, monumented with a limestone, 32x30x8 ins., firmly set 10 ins. in the ground and plainly mkd. UTAH on N. face other marks have been obliterated.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Retracement of the Utah-Arizona Boundary

19.463M 19.463M 19.463M 19.463M

CHAINS

19.463M

UTAHARIZ

1971

Bury the original mile post stone alongside the iron post.

Raise a mound of stone, 3 ft. base, 2 ft. high, E. of corner.

S. 89° 58' E., on the 20th mile.

Over broken canyon land, through sagebrush.

Descend 160 ft. over SE. slope.

15.65 West edge of ledgy canyon, bears N. 20° E. and S. 40° W.

22.95 Wash, in bottom of canyon, 30 lks. wide, 2 ft. deep, drains irregularly N. 10° E. Ascend 35 ft. over W. slope.

23.15 East edge of ledgy canyon, bears N. 10° E. and S. 10° W. Descend 95 ft. over E. slope.

38.00 Low ridge, bears S. and N. 35° E.

43.47 The 20th mile post, monumented with a limestone, 32x12x8 ins., firmly set, 18 ins. in the ground, and plainly mkd. UTAH on N. face, ARIZ. on S. face, 20M on W. face and 37NL on E. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone, 5 ft. base to top, with brass cap mkd.

20M

UTAHARIZ

1971

Deposit the original mile post stone in mound of stone, alongside the iron post.

Land, broken canyons.

Soil, sandy.

Undergrowth, sagebrush.

Retracement of the Survey Executed by Howard B. Carpenter, U.S. Surveyor and Astronomer, in 1901

S. 89° 58' E., on the 21st mile.

Over broken canyon land, through sagebrush.

Descend 80 ft. over E. slope.

8.75 Small wash, drains SE. Ascend 20 ft. over W. slope.

19.15 Low ridge, bears N. 20° W. and S. 35° E.

36.85 Low ridge, slopes N. Descend 195 ft. over E. slope.

Retracement of the Utah-Arizona Boundary
from mile ost 19.463 to mile ost 24

CHAINS

- 49.35 Wash, 100 lks. wide, 2 ft. deep, drains N. 10° E. Ascend 175 ft. over W. slope.
- 54.15 Ridge, bears N. 50° E. and S. 15° W. Descend 240 ft. over E. slope.
- 64.75 Wash, 10 lks. wide, 2 ft. deep, drains N. 75° E.
- 78.25 Small wash, drains S. 70° E.
- 79.83 The 21st mile post, monumented with a limestone, 30x12x8 ins., firmly set, 12 ins. in the ground, and plainly mkd. UTAH on N. face, ARIZ. on S. face, 21M on W. face and 37NL on E. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, to solid rock, and in a mound of stone, 5 ft. base to top, with brass cap mkd.

21M
UTAH
ARIZ
1971

Deposit the original mile post stone in mound of stone, alongside the iron post.

Land, broken canyons.
Soil, sandy.
Undergrowth, sagebrush.

S. 89° 56' E., on the 22nd mile.

Over broken canyon land, through sagebrush.

Descend 15 ft. over E. slope.

- 0.60 Wash, 20 lks. wide, 2 ft. deep, drains irregularly N. 30° E. Ascend 60 ft. over W. slope.
- 3.60 Low spur, slopes S. 30° W. Descend 90 ft. over E. slope.
- 13.00 Wash, 20 lks. wide, 2 ft. deep, drains N. 75° E. from W. Ascend 50 ft. over W. slope.
- 23.80 Low ridge, bears NE. and SW. Descend 165 ft. over E. slope.
- 32.30 Low spur, slopes S.
- 46.40 Wash, 30 lks. wide, 2 ft. deep, drains N. 85° E. from S. 70° W. Ascend 40 ft. over W. slope.
- 65.80 Low spur, slopes N. 10° E. Descend 75 ft. over E. slope.
- 72.90 Wash, 40 lks. wide, 3 ft. deep, drains irregularly N. 45° W. Ascend 105 ft. over W. slope.
- 80.08 The 22nd mile post, monumented with a limestone, 48x18x10 ins., firmly set, 18 ins. in the ground and plainly mkd. UTAH on N. face, ARIZ on S. face, 22M on W. face and 37NL on E. face.

Retracement of the Utah-Arizona Boundary
from mile post 19.463 to mile post 24

CHAINS

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

22M

UTAHARIZ

1971

Bury the original mile post stone alongside the iron post.

Land, broken canyons.

Soil, sandy.

Undergrowth, sagebrush.

Retracement of the Survey Executed by Howard B. Carpenter, U.S. Surveyor and Astronomer, in 1901, and the Retracement Executed by Joseph P. Davis, U.S. Cadastral Engineer in 1920-21.

S. $89^{\circ} 57'$ E., on the 23rd mile.

Ascend 340 ft. over W. slope.

10.10 Drift fence, bears N. 60° W. and S. 68° E.

42.55 Spur, slopes NE. Descend 205 ft. over E. slope.

69.45 Draw, drains N. 15° W. Ascend 260 ft. over W. slope.

78.43 The 23.087 mile post, monumented with a limestone, $30 \times 14 \times 14$ ins., set on solid rock, and in a mound of stone, and plainly mkd. UTAH on N. face, 37NL on E. face, ARIZ on S. face and 23.087 on W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., over a cross (X) on solid rock, and in a mound of stone, 5 ft. base to top, with brass cap mkd.

23.087M

UTAHARIZ

1971

Deposit the original mile post stone in mound of stone alongside the iron post.

Land, broken canyons.

Soil, sandy.

Undergrowth, sagebrush.

Retracement of the Survey Executed by Howard B. Carpenter, U.S. Surveyor and Astronomer, in 1901

East, on the 24th mile.

Retracement of the Utah-Arizona Boundary
from mile ost 19.463 to mile ost 24

CHAINS

Over broken canyon land, through sagebrush.

Descend 150 ft. over E. slope.

20.65 Small wash, drains N. 65° E.

24.75 Trail road, bears N. 60° W. and S. 60° E.

27.00 Small wash, drains N. 20° E. Ascend 155 ft. over W. slope.

38.92 Centerline of North bound lane of I-15, bears N. 10° E.
and S. 10° W., under construction.

53.75 Small wash, drains N. 10° E.

73.03 The 24th mile post, monumented with a limestone, 48x18x14
ins., firmly set, 6 ins. in the ground and in a mound of
stone, and plainly mkd. UTAH on N. face, 37NL on E. face
ARIZ on S. face and 24 on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in
the ground, to solid rock, and in a mound of stone, 5
ft. base to top, with brass cap mkd.

24M
UTAH
ARIZ
1971

Deposit the original mile post stone in mound of stone
alongside the iron post.

Land, broken canyons.
Soil, sandy and sandstone.
Undergrowth, sagebrush.

Dependent Resurvey of the West Boundary,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by W. Jenkins and
J.A. West, Deputy Surveyors, in 1897, and the Resurvey
Executed by A. J. Stewart Jr. and L. A. Snow, Deputy
Surveyors in 1909

Beg. at the cor. of secs. 25, 30, 31 and 36, on the W.
bdy. of the Tp., monumented with a limestone, 18x12x4 ins.
firmly set 10 ins. in the ground, and plainly mkd. 5
notches on the N. edge and 1 notch on the S. edge.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins.
in the ground to solid rock, and in a mound of stone,
4 ft. base to top, with brass cap mkd.

T43S
R17W R16W
S25|S30
S36|S31
1971

Dependent Resurvey of the West Boundary,
T. 43 S. R. 16 W. Salt Lake Meridian Utah

CHAINS

Deposit the original corner stone in mound
alongside the iron post.

S. $0^{\circ} 03'$ E., bet. secs. 31 and 36.

Over broken canyon land, through sagebrush.

Ascend 305 ft. over N. slope.

Begin triangulation.

14.40 S. edge of the Virgin River Canyon, bears irregularly
E. and W. End triangulation.

31.60 Wash, 20 lks. wide, 2 ft. deep, drains E.

39.89 The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, monumented with a
limestone, $18 \times 10 \times 8$ ins., firmly set, 10 ins. in the
ground, with a mound of stone to the W., the stone is
deteriorated and the markings have been obliterated, this
stone is harmoniously related to existing original corners
and is accepted as the best available evidence of the
original corner.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T43S
R17W R16W
 $\frac{1}{4}$
S36|S31
1971

Bury the original corner stone alongside the
iron post.

Rebuild the mound of stone, 2 ft. base, $1\frac{1}{2}$ ft.
high, W. of corner.

S. $0^{\circ} 28'$ E., beginning new measurement.

Ascend 30 ft. over N. slope.

4.75 Top of rocky hill. Descend 55 ft. over S. slope.

7.46 Intersect the Utah-Arizona State Boundary.

Point for the closing corner of secs. 31 and 36, Tps. 43
S., Rs. 16 and 17 W.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T43S
R17W R16W
C/C
S36|S31
ARIZ
1971

Dependent Resurvey of the West Boundary,
T. 43 S. R. 16 W. Salt Lake Meridian Utah

CHAINS

Raise a mound of stone, 3 ft. base, 1½ ft. high,
N. of cor.

From this closing cor., the 19.463 Mile Post on the
Utah-Arizona State Boundary, bears N. 89° 58' W., 1.775
chs. dist., monumented with an iron post, hereinbefore
described.

From this same cor., the original closing cor. of Tps.
43 S., Rs. 16 and 17 W., bears S. 0° 28' E., 0.10 chs.
dist., monumented with an iron post, 3 ins. diam.,
protruding 12 ins. above ground, with brass cap mkd.

U
T43S
R17W R16W
S36|S31
C|C
—
A
1909

I add "AM" and 1971 to the brass cap markings.

Land, broken canyons.
Soil, rocky clay.
Undergrowth, sagebrush.

Reestablishment of the Survey Executed by W. Jenkins
and J. A. West, Deputy Surveyors, in 1897

From the corner of secs. 25, 30, 31 and 36, on the W.
bdy. of the Tp.

N. 0° 03' W., bet. secs. 25 and 30.

Over broken land through sagebrush undergrowth.
Begin triangulation; descend about 200 ft. over N. slope,
topography scaled.

- 6.00 Virgin River, flows W. Ascend about 760 ft. over S.
slope.
- 20.90 N. edge of the Virgin River Canyon, bears irregularly
E. and W.
- 30.30 Knoll; end triangulation; thence over rolling canyon
land.
- 37.60 Wash, 20 lks. wide, 2 ft. deep, drains N. 80° E.
- 39.92 The ¼ sec. cor. of secs. 25 and 30, monumented with a
limestone, 14x12x4 ins., firmly set, 6 ins. in the ground
and plainly mkd. ¼ on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins.
in the ground to solid rock, and in a mound of stone,
4½ ft. base to top, with brass cap mkd.

Dependent Resurvey of the West Boundary,
T. 4 S. R. 16 E. S. 18 E. Meridian, Utah

CHAINS

T43S
R17W R16W
 $\frac{1}{4}$
S25|S30
1971

Deposit the original corner stone in mound
alongside the iron post.

N. $0^{\circ} 02'$ W., beginning new measurement.

- 6.10 Spur, slopes S. 75° E.
- 14.00 S. edge of canyon, bears E. and W.
- 18.30 Wash in bottom of canyon, 40 lks. wide, 3 ft. deep,
drains E.
- 22.70 N. edge of canyon, bears E. and W.
- 36.60 Spur, slopes SW.
- 39.98 The corner of secs. 19, 24, 25 and 30, monumented with a
limestone, 16x12x12 ins., firmly set in a mound of stone,
and plainly mkd. 4 notches on the N. edge and 2 notches
on the S. edge.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins.
in the ground to solid rock, and in a mound of stone, 5
ft. base to top, with brass cap mkd.

T43S
R17W R16W
S24|S19
S25|S30
1971

Deposit the original corner stone in mound
alongside the iron post.

Land, broken canyons.
Soil, sandstone and sandy.
Undergrowth, sagebrush.

N. $0^{\circ} 02'$ W., bet. secs. 19 and 24.

Over broken desert land, through sagebrush.

- 1.00 Small wash, drains S. 20° W.
- 14.20 Trail road, bears N. 80° W. and S. 80° E.
- 18.30 Ridge, bears NE. and SW.; desc. 120 ft. over NW. slope.
- 40.00 The $\frac{1}{4}$ sec. cor. of secs. 19 and 24, monumented with a
limestone, 14x8x6 ins., firmly set, 6 ins. in the ground,
and plainly mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Dependent Resurvey of the West Boundary,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

T43S
R17W R16W
 $\frac{1}{4}$
S24|S19
1971

Bury the original corner stone alongside the iron post.

Raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

N. $0^{\circ} 05'$ W., beginning new measurement.

Desc. 50 ft. over NW. slope.

- 4.80 Wash, in bottom of canyon, 30 lks. wide, 3 ft. deep, drains N. 60° E., asc. 120 ft. over broken SE. slope.
- 19.50 Spur, slopes N. 85° E., desc. 100 ft. over NE. slope.
- 25.80 Draw, drains E.; asc. 80 ft. over SE. slope.
- 32.00 Spur, slopes E. from SW., desc. 100 ft. over N. slope.
- 35.80 Mountain Valley Wash, 40 lks. wide, 3 ft. deep, drains E. from the SW., asc. 50 ft. over SW. slope.
- 39.94 The cor. of secs. 13, 18, 19 and 24, monumented with a limestone, $18 \times 12 \times 4$ ins., firmly set 10 ins., in the ground and plainly mkd. 3 notches on the N. and S. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T43S
R17W R16W
S13|S18
S24|S19
1971

Bury the original corner stone alongside the iron post.

Raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.

Cor. is located on a steep SW. slope.

Land, broken desert.
Soil, sandy.
Undergrowth, sagebrush.

N. $0^{\circ} 03'$ W., bet. secs. 13 and 18.

Dependent Resurvey of the West Boundary,
T 43 S. R. 1. W., Salt Lake Meridian, Utah

CHAINS

Over broken desert land, through sagebrush. Asc. 40 ft. over SW. slope.

1.50 Spur, slopes SW.; desc. .75 ft. over steep NW. slope.

6.30 Draw, drains S. 30° W. Ascend 190 ft. over steep S. slope.

8.50 Point projects S.

19.03 Drift fence, bears N. 54° W. and S. 54° E.

20.00 Spur, slopes NW. Descend 165 ft. over NW. slope.

28.40 Base of hill, bears E. and SW.

35.20 Wash, 20 lks. wide, 6 ft. deep, drains N. 42° E.

39.97 The $\frac{1}{4}$ sec. cor. of secs. 13 and 18, monumented with a limestone, 16x8x6 ins., firmly set, 10 ins. in the ground, and plainly mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T43S
R17W R16W

$\frac{1}{4}$
S13|S18
1971

Bury the original corner stone alongside the iron post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.

Cor. is located on a low rise, sloping NE.

N. 0° 04' W., beginning new measurement.

Descend 50 ft. over NE.slope.

9.00 Unimproved dirt road, in bottom of draw, bears N. 45° E. and S. 45° W. Draw, drains N. 45° E. Ascend 195 ft. over SE. slope.

26.20 Spur, slopes NE.

29.90 Wash, 20 lks. wide, 2 ft. deep, drains E.; asc. 120 ft. over S. slope.

39.94 The cor. of secs. 7, 12, 13 and 18, monumented with a limestone, 18x8x6 ins., firmly set 10 ins. in the ground, and plainly mkd. 2 notches on the N. edge and 4 notches on the S. edge.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 12 ins. in the ground to solid rock, and in a mound of stone, 5 ft. base to top, with brass cap mkd.

Dependent Resurvey of the West Boundary,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS

T43S
R17W R16W
S12|S7
S13|S18
1971

Deposit the original corner stone in mound
alongside the iron post.

Land, broken desert.
Soil, sandy.
Undergrowth, sagebrush.

N. 0° 05' W., bet. secs. 7 and 12.

Over broken desert land, through sagebrush.

Ascend 45 ft. over S.slope.

1.10 S. rim of mesa, bears W. and NE.

3.00 N. rim of mesa, curves NW. and SE.; desc. 80 ft. over N.
slope.

6.00 Head of draw, drains E.; asc. 40 ft. over SE. slope.

12.50 Spur, slopes E.; desc. 40 ft. over gentle NW. slope.

27.70 Descend 160 ft. over steep NW.slope.

40.01 The $\frac{1}{4}$ sec. cor. of secs. 7 and 12, monumented with a
limestone, 18x10x6 ins., firmly set, 12 ins. in the
ground, and plainly mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T43S
R17W R16W
 $\frac{1}{4}$
S12|S7
1971

Bury the original cor. stone alongside the iron
post.

Raise a mound of stone, 3 ft. base, 2 ft. high,
W. of cor.

N. 0° 04' W., beginning new measurement.

Descend 25 ft. over NW. slope.

2.20 Unimproved dirt road in bottom of Curly Hollow Wash,
bears N. 20° E. and S. 20° W. Hollow drains N. 20° E.
Ascend 120 ft. over S. slope.

12.90 Top of ascent. Descend 150 ft. along E. slope.

34.40 Unimproved dirt road, bears N. 40° W. and S. 40° E.

Dependent Resurvey of the West Boundary,
T. 43 S. R. 16 W. Salt Lake Meridian Utah

CHAINS
39.30

Cottonwood Wash, 20 lks. wide, 2 ft. deep, drains
S. 45° E., with trail road in bottom.

40.01

The cor. of secs. 1, 6, 7 and 12, monumented with a
limestone, 16x8x6 ins., firmly set 10 ins. in the
ground, and plainly mkd. 1 notch on the N. edge and
5 notches on S. edge.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T43S
R17W R16W
S1 | S6
S12 | S7

1971

Bury the original cor. stone alongside the iron
post.

Raise a mound of stone, 3 ft. base, 2 ft. high,
W. of cor.

Land, broken desert.
Soil, sandy.
Undergrowth, sagebrush.

N. 0° 03' W., bet. secs. 1 and 6.

Over broken desert land, through sagebrush.

Begin triangulation. Ascend about 100 ft. over SW.
slope.

24.00

Base of steep and ledgy slope; asc. about 200 ft. over
steep SW. slope.

39.90

The ¼ sec. cor. of secs. 1 and 6, monumented with a
sandstone, 24x12x5 ins., firmly set, 12 ins. in the
ground, and plainly mkd. ¼ on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins.
in the ground to solid rock, and in a mound of stone,
4 ft. base to top, with brass cap mkd.

T43S
R17W R16W
¼
S1 | S6
1971

Deposit the original cor. stone in mound alongside
the iron post.

Cor. is located on a ledgy shelf facing W., 75
ft. below top of mountain.

N. 0° 04' W., beginning new measurement.

Dependent Resurvey of the West Boundary,
T. 43 S. R. 16 W. Salt Lake Meridian Utah

CHAINS

- Ascend 115 ft. over SW. slope.
- 5.00 Crest of rim, bears NW. and SE. End triangulation.
Thence over gently rolling land.
- 40.02 The cor. of Tps. 43 S., Rs. 16 and 17 W., on the S. bdy.
of Sec. 31, T. 42 S., R. 16 W., monumented with an iron
post, 2½ ins. diam., protruding 18 ins. above
ground, with brass cap mkd.

T42S
R16W
S31
—
S1|S6
R17W R16W
T43S
1968

Land, broken desert.
Soil, sandstone and sandy.
Undergrowth, sagebrush.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah.

Reestablishment of the Survey Executed by J. A.
West and W. Jenkins, Deputy Surveyors, in 1897.

Point for the cor. of secs. 11, 12, 13 and 14, is now
under an apartment house and cannot be monumented. The
original position for this cor. was verified by Bush
and Gudgeon Engineering Company, Salt Lake City, Utah,
and referenced this corner position.

From which

A concrete block, 6x6 ins., level with the ground,
with a brass tablet, 1½ ins. diam., mkd. with a
cross, bears N. 0° 03' W., 135 ft. dist.

A concrete block, 6x6 ins., level with the ground,
with a brass tablet, 1½ ins. diam., mkd. with a
cross, bears S. 89° 58' W., 120 ft. dist.

This point is harmoniously related to existing original
corners and is the only existing evidence of the orig-
inal corner.

N. 0° 03' W., bet. secs. 11 and 12.

Over nearly level golf course.

- 30.40 Leave golf course.
- 39.97 The ¼ sec. cor. of secs. 11 and 12, monumented with a
sandstone, 16x10x5 ins., firmly set, 8 ins. in the
ground, and plainly mkd. ¼ on W. face.

At the cor. point

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, and in a collar of stone, with brass cap
mkd.

T43S R16W

$\frac{1}{4}$

S11|S12

1972

Bury the original corner stone alongside the iron
post.

N. $0^{\circ} 06'$ W., beginning new measurement.

Over nearly level land, through sagebrush.

1.60 Enter rolling hills. Ascend 185 ft. over SW. slope.

33.90 Top of ascent. Descend 50 ft. over NW. slope.

39.57 The cor. of secs. 11 and 12, on the S. bdy. of Sec. 1,
monumented with a sandstone, 20x10x5 ins., firmly set
10 ins. in the ground, and plainly mkd. 5 notches on the
S. edge, and 1 notch on the E. edge.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, and in a collar of stone, with brass cap
mkd.

T43S R16W

S1

S11|S12

1972

Bury the original corner stone alongside the
iron post.

Land, nearly level to rolling hills.

Soil, sandy.

Undergrowth, sagebrush.

Reestablishment of the Survey Executed by W. Jenkins and
J. A. West, Deputy Surveyors, in 1897 and the Resurvey
Executed by A. J. Stewart Jr. and L. A. Snow, Deputy
Surveyors, in 1909.

The cor. of secs. 26, 27, 34 and 35, determined by a
mound of stone at cor. of fences, bearing W. and S. 45°
E. This point is harmoniously related to existing orig-
inal corners and is accepted as the best existing evidence
of the position of the original cor.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, and in a collar of stone, with brass cap
mkd.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS

T43S R16W
S27|S26
S34|S35
1971

South, bet. secs. 34 and 35.

Over rolling desert land, through sagebrush.

17.90 S. crest of small mesa, bears E. and W.

23.10 Right-of-way fence, bears NE. and SW. on a curve.

35.60 Small wash, drains N. 45° E.

39.92 The $\frac{1}{4}$ sec. cor. of secs. 34 and 35, monumented with a limestone, 14x8x5 ins., firmly set 6 ins. in the ground, and plainly mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T43S R16W
 $\frac{1}{4}$
S34|S35
1971

Bury the original corner stone alongside the iron post.

Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

Cor. is located at N. base of small spur.

South, beginning new measurement.

Ascend 80 ft. over N. slope.

7.73 Intersect the Utah-Arizona State Boundary.

Point for the closing corner of secs. 34 and 35, T. 43 S., R. 16 W., at proportionate distance bet. mile post, 23.087 and mile post 24, falls in north bound lane of I-15, bears N. 10° E. and S. 10° W., under construction; and is not monumented; there is no remaining evidence of the original cor.

Point for the witness closing cor. bears East, 1.48 chs. dist.

At witness cor. point, set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

UT
T43S R16W
C|C
W S34|S35
C ARIZ
1972

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W. Salt Lake Meridian Utah

CHAINS

From the true point for the closing cor. of secs. 34 and 35, the 24th mile post, on the Utah-Arizona State Bdy., monumented with an iron post, hereinbefore described, bears East, 34.13 chs.

Land, rolling desert.
Soil, sandy.
Undergrowth, sagebrush.

Reestablishment of the Survey Executed by W. Jenkins
and J. A. West, Deputy Surveyors, in 1897

From the cor. of secs. 26, 27, 34 and 35.

N. 0° 03' W., bet. secs. 26 and 27.

Over rolling desert land, through sagebrush.

Ascend 30 ft. over S. slope.

9.70 N. crest of mesa, bears NE. and SW. Descend 130 ft. over N. slope.

12.00 Base of mesa, bears NE. and SW.

26.10 Wash, 20 lks. wide, 2 ft. deep, drains N. 40° W.

39.98 Point for the ¼ sec. cor. of secs. 26 and 27, at proportionate distance, falls in wash, 30 lks. wide, 2 ft. deep, drains W. for 1.50 chs. to junction, thence NW.; point not suitable for monumentation; there is no remaining evidence of the original cor.

40.38 Point for the witness ¼ sec. cor. of secs. 26 and 27.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T43S R16W

¼

S27|S26

W|C

↓

1971

Raise a mound of stone, 3 ft. base, 3 ft. high,
W. of iron post.

Ascend 90 ft. over gentle SW. slope.

56.60 Low ridge, bears S. 70° E. and N. 70° W. Descend 130 ft. over gentle NE. slope.

79.96 The cor. of secs. 22, 23, 26 and 27, monumented with a black lava stone, 18x10x6 ins., firmly set 10 ins. in the ground, and plainly mkd. 2 notches on the S. and E. edges.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W. Salt Lake Meridian Utah

CHAINS

T43S R16W
 $\frac{S22}{S27} | \frac{S23}{S26}$
 1971

Bury the original cor. stone alongside the iron post.

Raise a mound of stone, 4 ft. base, 3 ft. high,
W. of corner.

Land, rolling desert.
 Soil, sandy.
 Undergrowth, sagebrush.

N. $0^{\circ} 02'$ W., bet. secs. 22 and 23.

Over nearly level desert land, through sagebrush.

25.60 Atkinsville Wash, 1.00 ch. wide, 4 ft. deep, drains N. 76° W.

32.80 Enter sand and gravel pit.

39.98 Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23, at proportionate distance, falls in sand and gravel pit; point not suitable for monumentation; there is no remaining evidence of the original corner.

42.98 Point for the witness $\frac{1}{4}$ sec. cor. of secs. 22 and 23.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T43S R16W
 $\frac{1}{4}$
 $\frac{S22}{W} | \frac{S23}{C}$
 \downarrow
 1971

Cor. is located at N. end of sand and gravel pit.

57.05 Crest of terrace, bears NE. and SW.

78.42 Point for the witness cor. of secs. 14, 15, 22 and 23.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T43S R16W
 $\frac{W}{S15} | \frac{C}{S14}$
 $\frac{S22}{S22} | \frac{S23}{S23}$
 1971

79.56 Present left bank of the Virgin River, bears irregularly E. and W.

79.96 Point for the cor. of secs. 14, 15, 22 and 23, determined latitudinally by proportionate measurement, and longitudinally by the projection of a fence line from the north, falls in the Virgin River where a cor. cannot be perpetuated, there is no remaining evidence of the orig. cor.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS

Land, nearly level desert.
Soil, sandy.
Undergrowth, sagebrush.

North, bet. secs. 14 and 15.

Over level desert land, through sagebrush. By triangulation. Topography approximate.

- 7.27 Point for the original meander cor. for the left bank of the Virgin River, at proportionate distance; there is no remaining evidence of the original meander cor. Point not monumented.
- 8.46 Present right bank of the Virgin River, bears irregularly E. and N. 64° W.
- 24.00 Fence, bears N., thence along fence.
- 25.06 Point for the meander cor. for the right bank of the Virgin River, at proportionate distance; there is no remaining evidence of the original meander cor. Point not monumented.
- 39.98 Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original cor. End triangulation.
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- T43S R16W
 $\frac{1}{4}$
S15|S14
1971
- Cor. is located in a N-S fence line by S. gate post.
- 40.60 Base of hill, bears N. 80° E. and S. 80° W. Ascend 115 ft. over SE. slope.
- 44.05 Low spur, slopes N. 80° E.
- 52.15 Cor. of fences, bearing S. and N. 40° E.
- 59.95 Cor. of fences, bearing N. and E., thence along fence.
- 62.55 Top of ascent, descend 55 ft. along E. slope.
- 79.96 The cor. of secs. 10, 11, 14 and 15, monumented with a sandstone, 14x12x8 ins., firmly set. 6 ins. in the ground, and plainly mkd. 2 notches on the E. edge and 4 notches on the S. edge.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T43S R16W
S10|S11
S15|S14
1971

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Bury the original corner stone alongside the iron post.</p> <p>Cor. is located in N-S fence line, 5.5 lks. S. of gate.</p> <p>Land, level to gently rolling. Soil, sandy. Undergrowth, sagebrush.</p>
	<p>From the true point for the cor. of secs. 11, 12, 13 and 14.</p> <p>S. 89° 58' W., bet. secs. 11 and 14.</p> <p>Over level golf course.</p>
33.00	Leave golf course, thence over level desert land, through sagebrush.
39.93	<p>The $\frac{1}{4}$ sec. cor. of secs. 11 and 14, monumented with a sandstone, 14x5x5 ins., firmly set 6 ins. in the ground, and plainly mkd. $\frac{1}{4}$ on N. face.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div><p>T43S R16W</p><p>$\frac{1}{4}$ $\frac{S11}{S14}$</p><p>1972</p></div> <p>Bury the original corner stone alongside the iron post.</p>
	<p>S. 89° 57' W., beginning new measurement.</p> <p>Continue over level desert land.</p>
39.92	<p>The cor. of secs. 10, 11, 14 and 15.</p> <p>Land, level. Soil, sandy. Undergrowth, grass and sagebrush.</p>
	<p>N. 0° 02' W., bet. secs. 10 and 11.</p> <p>Over nearly level land, through sagebrush, along fence Begin triangulation.</p>
.30	Unimproved dirt road, bears E. and W.
9.00	Fence ends at base of steep and ledgy bluff. Ascend about 300 ft. over steep SW. slope.
24.60	Top of bluff, bears NW. and SE. End triangulation.
39.72	The $\frac{1}{4}$ sec. cor. of secs. 10 and 11. monumented with a

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S. R. 16 W. Salt Lake Meridian Utah

CHAINS

limestone, 14x8x8 ins., firmly set, 6 ins. in the ground,
and plainly mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins.
in the ground to solid rock, and in a mound of stone,
4 ft. base to top, with brass cap mkd.

T43S R16W

$\frac{1}{4}$
S10|S11
1971

Bury the original corner stone alongside the iron
post.

Raise a mound of stone, 3 ft. base, 2 ft. high,
W. of corner.

N. $0^{\circ} 01'$ W., beginning new measurement.

Descend 50 ft. along broken E. slope.

3.00 Draw, drains E. Ascend 60 ft. along E. slope.

8.00 Spur, slopes E. Descend 205 ft. along broken E. slope.

17.70 Ledgy draw, drains E.

39.91 The cor. of secs. 2, 3, 10 and 11, monumented with a
sandstone, 10x15 ft., protruding 6 ins. above ground
plainly mkd. by a cross (X) with 2 grooves on the E. and
5 grooves S. of the cross. This point is in the bottom
of a draw that drains S. 45° E., and is not suitable for
monumentation. A witness cor. bears N. $0^{\circ} 09'$ W., 0.18
chs. dist., hereinafter described.

Land, level to broken desert.

Soil, sandy and sandstone.

Undergrowth, sagebrush.

From the cor. of secs. 11 and 12, on the S. bdy. of sec.
1.

N. $89^{\circ} 45'$ W., along the N. bdy. of sec. 11.

Over broken desert land, through sagebrush.

Descend 25 ft. over W. slope.

2.30 Paved road, bears N. 5° E. and S. 5° W. Ascend 110 ft.
over E. slope.

39.90 The $\frac{1}{4}$ sec. cor. of secs. 2 and 11, marked by a cross (X)
and $\frac{1}{4}$ in solid sandstone, and a mound of stone to the
N.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., over
the cross (X), and in a mound of stone, 4 ft. base
to top, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS	
	<p>T43S R16W $\frac{1}{4} \frac{S2}{S11}$ 1972</p> <hr/> <p>S. 89° 45' W., beginning new measurement.</p> <p>Ascend 35 ft. along gentle N. slope.</p>
13.50	Sandstone ridge, bears N. and S. Descend 150 ft. over gentle W. slope.
36.90	Wash, 40 lks. wide, 2 ft. deep, drains irregularly S.
39.83	<p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, broken desert. Soil, sandy. Undergrowth, sagebrush.</p> <p>N. 0° 09' W., bet. secs. 2 and 3.</p> <p>Over gently rolling desert land, through sagebrush.</p> <p>Ascend 80 ft. along gentle E. slope.</p>
.13	<p>Point for the witness cor. of secs. 2, 3, 10 and 11.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 5 ins. in the ground to solid rock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p>T43S R16W $\frac{S3 S2}{S10 S11}$ W↓C 1971</p>
5.30	Wash, 20 lks. wide, 2 ft. deep, drains irregularly S. 10° E.
39.96	<p>The ¼ sec. cor. of secs. 2 and 3, monumented with a lava stone, 18x12x8 ins., firmly set 6 ins. in the ground, and plainly mkd. ¼ on W. face.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p>T43S R16W $\frac{1}{4} \frac{S3 S2}{S10 S11}$ 1971</p> <p>Bury the original corner stone alongside the iron post.</p> <hr/> <p>N. 0° 10' W., beginning new measurement.</p>

Dependent Resurvey of a Portion of the Subdivision,

43 S. 16 E. 16 N. 16 W. 16 S. 16 E. 16 N. 16 W.

CHAINS

Descend 25 ft. over N. slope.

22.30 Wash, 20 lks. wide, 2 ft. deep, drains irregularly N. 45° E. Ascend 15 ft. over S. slope.

38.85 The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., protruding 8 ins. above ground, with brass cap mkd.

T42S R16W

S34|S35

S3|S2

T43S R16W

1968

Land, gently rolling desert.

Soil, sandy.

Undergrowth, sagebrush.

Reestablishment of the Survey Executed by W. Jenkins and J. A. West, Deputy Surveyors, in 1897, and the Resurvey Executed by A. J. Stewart Jr. and L. A. Snow, Deputy Surveyors, in 1909

The cor. of secs. 27, 28, 33 and 34, monumented with a limestone, 16x14x5 ins., firmly set 8 ins. in the ground, and plainly mkd. 1 notch on the S. edge and 3 notches on the E. edge.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone, 5 ft. base to top, with brass cap mkd.

T43S R16W

S28|S27

S33|S34

1971

Bury the original corner stone alongside the iron post.

S. 0° 07' E., bet. secs. 33 and 34.

Over rolling desert land, through sagebrush.

6.50 Top of knoll.

11.70 Wash, 5 lks. wide, 1 ft. deep, drains N. 75° E.

20.45 Spur, slopes N. 85° E.

34.50 Wash, 10 lks. wide, 2 ft. deep, drains N. 46° E.

39.97 The ¼ sec. cor. of secs. 33 and 34, monumented with a limestone, 14x8x4 ins., firmly set 6 ins. in the ground, and plainly mkd. ¼ on W. face.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W. Salt Lake Meridian Utah

CHAINS

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock, and in a mound of stone, 5 ft. base to top, with brass cap mkd.

T43S R16W

$\frac{1}{4}$

S33|S34

1971

Bury the original corner stone alongside the iron post.

S. $0^{\circ} 14'$ E., beginning new measurement.

Ascend 120 ft. over N. slope.

7.64 Intersect the Utah-Arizona State Boundary.

Point for the closing corner of secs. 33 and 34,
T. 43 S., R. 16 W.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T43S R16W

C|C

S33|S34

ARIZ

1971

From this cor., the 22nd mile post on the Utah-Arizona State Bdy., bears N. $89^{\circ} 57'$ W., 37.28 chs. dist., monumented with an iron post, hereinbefore described.

From the same cor., the closing cor. of secs. 33 and 34, bears S. $0^{\circ} 14'$ E., 0.05 chs. dist. and monumented with an iron post, 2 ins. diam., protruding 10 ins. above ground, with brass cap mkd.

T43S R16W

C|C

S33|S34

A

1909

I add "AM" and 1971 to the brass cap markings.

From the cor. of secs. 26, 27, 34 and 35.

est, bet. secs. 27 and 34.

Over nearly level desert land, through sagebrush, along an old fence line.

scend over E. slope.

1.00 op of ridge, bears N. 20° W. and S. 20° E. Descend 35 ft. over SW. slope.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S. R. 16 W. Salt Lake Meridian, Utah

CHAINS

- 6.00 Wash, 10 lks. wide, 4 ft. deep, drains N. 40° W., asc.
145 ft. over NE. slope.
- 25.60 Top of bluff. Descend 90 ft. over SW. slope.
- 31.80 Fence, bears N. 45° W. and S. 45° E.
- 38.60 Edge of bluff, descend 85 ft. over steep SW. slope.
- 40.06 The $\frac{1}{4}$ sec. cor. of secs. 27 and 34, monumented with a
limestone, 14x8x8 ins., firmly set 6 ins. in the
ground, and plainly mkd.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T43S R16W

$\frac{1}{4}$ $\frac{S27}{S34}$

1971

Bury the original corner stone alongside the iron
post.

Raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high,
N. of corner.

S. 89° 55' W., beginning new measurement.

Descend 55 ft. over SW. slope.

- 1.90 Wash, 10 lks. wide, 1 ft. deep, at base of steep descent,
drains S.
- 18.20 Road, in bottom of draw, bears N. 45° W. and S. 45° E.
Draw, drains irregularly NW. Ascend 20 ft. over E.
slope.
- 36.30 Top of ascent, descend 20 ft. along N. slope.
- 40.10 The cor. of secs. 27, 28, 33 and 34.
- Land, nearly level desert.
Soil, sandy.
Undergrowth, sagebrush.

Reestablishment of the Survey Executed by W. Jenkins
and J. A. West, Deputy Surveyors, in 1897

N. 0° 06' W., bet. secs. 27 and 28.

Over broken desert land, through sagebrush undergrowth.
Descend 80 ft. over general N. slope.

Dependent Resurvey of a Portion of the Subdivision,
T

CHAINS

- 21.30 Gulch, 60 lks. wide, 30 ft. deep, drains N. 65° W.
- 26.20 Trail road, bears N. 70° W. and S. 70° E.; asc. 120 ft. over SW. slope.
- 32.00 Top of small knoll.
- 38.00 Top of ledge, thence along W. slope.
- 40.02 The $\frac{1}{2}$ sec. cor. of secs. 27 and 28, monumented with a sandstone, 20x10x4 ins., firmly set 15 ins. in the ground, plainly mkd. $\frac{1}{2}$ on W. face, with mound of stone to the W.
- At the cor. point
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- T43S R16W
- $\frac{1}{2}$
S28|S27
- 1971
- Bury original corner stone alongside iron post, and rebuild mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
-
- N. 0° 03' W., beginning new measurement.
- Along W. slope.
- 1.90 Desc. 25 ft. over NW. slope.
- 6.30 Spur, slopes N. 35° W.; desc. 100 ft. over NW. slope.
- 21.00 Base of descent; asc. 40 ft. over SW. slope.
- 27.10 Trail road, bears E. and W., on spur, slopes W.; desc. 20 ft. over N. slope.
- 28.50 Small draw, drains W.; asc. 60 ft. over S. slope.
- 32.50 Spur, slopes W.; desc. gentle N. slope.
- 34.20 Rim, above Virgin River, bears E. and W.; desc. 50 ft. over N. slope.
- 36.23 Point for the original meander cor. of secs. 27 and 28, for left bank of Virgin River at proportionate distance; there is no remaining evidence of the original cor. Point not monumented.
- 36.34 Point for the witness meander cor. of secs. 27 and 28.
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with cedar post, 4 ins. diam., 5 ft. alongside, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W. Salt Lake Meridian, Utah

CHAINS

WMC

S28 AS27

T43S R16W
1972

- 36.64 Present left bank of Virgin River, bears N. 65° 25' E.,
and S. 81° 75' W.

Point for the meander cor. of secs. 27 and 28, falls on
sloping bank, and deemed unsafe to perpetuate.

- 39.44 Point for the original meander cor. of secs. 27 and 28
for right bank, at proportionate distance falls in the
Virgin River and cannot be perpetuated; there is no
remaining evidence of the original cor.

- 39.94 Point for the cor. of secs. 21, 22, 27 and 28, at propor-
tionate distance falls in Virgin River, and cannot be
perpetuated; there is no remaining evidence of the
original corner.

Point for the witness cor. of secs. 21, 22, 27 and 28,
bears N. 0° 11' W., 2.25 chs. dist., hereinafter
described.

Land, broken desert.

Soil, sandy, exposed sandstone, gypsum.

Undergrowth, sagebrush.

From the cor. of secs. 22, 23, 26 and 27.

S. 89° 52' W., bet. secs. 22 and 27.

Over broken desert land, through sagebrush undergrowth.
Asc. 50 ft. over NE. slope.

- 10.60 Top of ascent, slopes N.; desc. 40 ft. over NW. slope.

- 17.35 Wash, 15 lks. wide, 1 ft. deep, drains N. 1.50 chs.,
thence N. 80° W.; asc. 40 ft. over E. slope.

- 29.60 Spur, slopes N.; thence along N. slope.

- 34.10 Head of small draw, drains N.; desc. 25 ft. over NW.
slope.

- 40.11 The $\frac{1}{4}$ sec. cor. of secs. 22 and 27, monumented with a
limestone, 20x8x8 ins., firmly set 15 ins. in the
ground, and plainly mkd. $\frac{1}{4}$ on the N. face, witnessed
by a mound of stone to N.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivision,

PLANS

T43S R16W

$\frac{S22}{S27}$

1971

Bury original cor. stone alongside iron post, and rebuild mound of stone, 2½ ft. base, 1½ ft. high, N. of cor.

N. 89° 59' W., beginning new measurement.

Desc. 10 ft. over NW. slope.

5.00 Draw, drains N. 50° E.; asc. 80 ft. over SE. slope.

11.70 Spur, slopes N. 55° E.; thence along N. slope.

16.00 Head of draw, drains N. 15° E.

18.00 Spur, slopes N.; desc. 150 ft. over NW. slope.

29.00 Mouth of canyon, drains N.; thence over bottom land.

32.44 Point for the witness meander cor. of secs. 22 and 27.

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T43S R16W

WMC $\frac{S22}{S27}$

1972

35.26 Point for the meander cor. of secs. 22 and 27, on present left bank of Virgin River, bears N. 21° 55' E. and S. 32° 20' W., deemed unsafe to perpetuate.

35.63 Point for the original meander cor. of secs. 22 and 27, for left bank at proportionate distance falls in Virgin River, and cannot be perpetuated; there is no remaining evidence of the original cor.

39.48 Point for the original meander cor. of secs. 22 and 27, for the right bank, at proportionate distance falls in Virgin River and cannot be perpetuated; there is no remaining evidence of the original cor.

40.02 Point for the cor. of secs. 21, 22, 27 and 28.

Land, broken desert E. portion; river bottom W. portion.

Soil, sandy and gypsum.

Undergrowth, sagebrush, with willows along river.

N. 0° 11' W., bet. secs. 21 and 22.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS

Over river bottom land, through willow undergrowth.

0.65 Point for the meander cor. of secs. 21 and 22, on present right bank of Virgin River, bears N. 52° 06' E., and S. 84° 36' W., deemed unsafe to perpetuate.

2.25 Point for the witness cor. of secs. 21, 22, 27 and 28. This point will also function as the witness meander cor. of secs. 21 and 22.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with cedar post, 5 ft. long, alongside, brass cap mkd.

WMC
T43S R16W
S21|S22
S28↓S27

WC
1972

Asc. 70 ft. over gentle S. slope. Leave willows.

23.00 Point of spur, slopes S.; thence along E. slope.

30.00 Small draw, drains S. 50° E.

33.00 Small spur, slopes S. 50° E.; desc. 10 ft. over NE. slope.

35.70 Draw, drains S. 55° E. from N. 75° W.; asc. 20 ft. over SW. slope.

39.94 The ¼ sec. cor. of secs. 21 and 22, monumented with a black lava stone, 16x10x6 ins., firmly set 10 ins. in the ground, plainly mkd. ¼ on W. face, and witnessed by mound of stone, N., S., E. and W. of cor.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T43S R16W
¼
S21|S22
1972

Bury original cor. stone alongside iron post, and rebuild mounds of stone, 2 ft. base, 1 ft high, N., S., E. and W. of cor.

N. 0° 08' W., beginning new measurement.

Asc. 65 ft. over SW. slope.

3.60 Spur, slopes SE.; desc. 15 ft. over NE. slope.

13.10 Draw, drains SE.; asc. 15 ft. over SW. slope.

18.00 Spur, slopes SE.; desc. 25 ft. over NE. slope.

27.00 Ravine, drains S. 80° E.; asc. 15 ft. over gentle S. slope.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS

- 30.80 Spur, slopes S. 80° E.; desc. 35 ft. over gentle N. slope.
- 40.12 The cor. of secs. 15, 16, 21 and 22, monumented with a limestone, 18x8x6 ins., firmly set 15 ins. in the ground, plainly mkd. 3 notches on S. and E. edges.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T43S R16W
S16|S15
S21|S22
 1972

Bury original cor. stone alongside iron post, and raise a mound of stone, 2½ ft. base, 2½ ft. high, W. of cor.

Land, broken desert.

Soil, sand and gypsum.

Undergrowth, sagebrush, with willows along river.

From the true point for the cor. of secs. 14, 15, 22 and 23.

S. 89° 58' W., bet. secs. 15 and 22.

Over river bottom land. By triangulation, over waters of Virgin River.

- 22.58 Point for the original meander cor. of secs. 15 and 22, for left bank, at proportionate distance falls in Virgin River, and cannot be perpetuated.
- 37.56 Point for the original meander cor. of secs. 15 and 22, for the right bank, at proportionate distance falls in Virgin River, and cannot be perpetuated. This point will now function as the meander cor. of sec. 15 only.
- 38.65 Point for the meander cor. of sec. 22 only, on the present right bank of Virgin River, bears N. 33° 37' E. and S. 14° 56' W., deemed unsafe to perpetuate. End triangulation.
- 39.15 Point for the witness meander cor. of sec. 22 only.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T43S R16W
S22 / WMC
 1972

- 40.15 Point for the ¼ sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with cottonwood post, 6 ft. long, alongside brass cap mkd.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS

T43S R16W

$\frac{1}{4}$ $\frac{S15}{S22}$
1972

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Asc. 100 ft. over gently rolling E. slope.

70.10 Spur, slopes SE.; desc. 45 ft. over SW. slope.

78.50 Curly Hollow Wash, 50 lks. wide, 3 ft. deep, drains S. 20° E.; asc. gentle SW. slope.

80.30 The cor. of secs. 15, 16, 21 and 22.

Land, river bottom E. portion; gently rolling W. portion.
Soil, gravelly clay.

Undergrowth, sagebrush and willows.

N. 0° 08' W., bet. secs. 15 and 16.

Over broken desert land through sagebrush undergrowth.
By triangulation; asc. about 40 ft. over general S. slope.

1.50 Curly Hollow Wash, 50 lks. wide, 3 ft. deep, drains irregularly S. 40° E.

21.00 Base of ledges facing SE.; asc. about 160 ft. over broken SE. slope.

26.20 Crest of ledges, bears E. and W., on point, projects E. End triangulation; desc. 50 ft. over NE. slope.

30.50 Ravine, drains E.; asc. 90 ft. over S. slope.

35.60 Spur, slopes E.; desc. 75 ft. over N. slope.

40.00 The $\frac{1}{4}$ sec. cor. of secs. 15 and 16, monumented with a sandstone, 20x14x14 ins., firmly set 6 ins. in the ground, and plainly mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T43S R16W

$\frac{1}{4}$
S16|S15
1972

Place original cor. stone in mound of stone, alongside the iron post.

N. 0° 10' W., beginning new measurement.

By triangulation; desc. about 20 ft. over N. slope.
Topography scaled.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS

- 1.50 Draw, drains E.; asc. about 80 ft. over SE. slope.
- 5.00 Spur, slopes NE.; desc. about 50 ft. over N. slope.
- 9.00 Draw, drains E.; asc. about 120 ft. over S. slope.
- 14.00 Top of ascent, W. side of draw, desc. about 50 ft. over NE. slope.
- 22.00 Draw, drains S. 75° E.; asc. about 50 ft. over S. slope.
- 39.92 The cor. of secs. 9, 10, 15 and 16, monumented with a sandstone, 16x12x4 ins., firmly set 8 ins. in the ground, and plainly mkd. 3 notches on E. and 4 notches on S. edges, and witnessed by a mound of stone to E.
- At the cor. point
- Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
- $$\begin{array}{r} \text{T43S R16W} \\ \text{S9} \mid \text{S10} \\ \hline \text{S16} \mid \text{S15} \end{array}$$
- 1972
- Bury original cor. stone alongside the iron post, and rebuild mound of stone, 3 ft. base, 3 ft. high, E. of cor.
- Land, broken desert.
Soil, gravelly clay.
Undergrowth, sagebrush.
-
- From the cor. of secs. 10, 11, 14 and 15.
- S. 89° 59' W., bet. secs. 10 and 15.
- Over broken desert land through sagebrush undergrowth.
Asc. 115 ft. over NE. slope.
- 34.90 Spur, slopes N.; desc. 55 ft. along N. slope.
- 40.18 Point for the ¼ sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original cor.
- Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.
- $$\begin{array}{r} \text{T43S R16W} \\ \text{¼} \mid \text{S10} \\ \hline \text{S15} \end{array}$$
- 1972
- Desc. 50 ft. over NW. slope.
- 46.75 Ravine, drains S. 20° E., trail road, bears N. 20° W. and S. 20° E.; asc. 50 ft. over NE. slope.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S. R. 16 W. Salt Lake Meridian Utah

CHAINS

66.00 Top of ascent, thence over series of small spurs and washes, draining S.

80.36 The cor. of secs. 9, 10, 15 and 16.

Land, broken desert.

Soil, gravelly white clay.

Undergrowth, sagebrush.

N. 0° 09' W., bet. secs. 9 and 10.

Over broken desert land through sagebrush undergrowth.
Asc. 60 ft. over SW. slope.

1.35 Trail road, bears E. and W.

18.45 Spur, slopes SE.; desc. 30 ft. over NE. slope.

36.35 Wash, 20 lks. wide, 2 ft. deep, drains SE.; asc. gentle SW. slope.

39.95 The $\frac{1}{4}$ sec. cor. of secs. 9 and 10, monumented with a sandstone, 16x16x5 ins., firmly set 10 ins. in the ground, and plainly mkd. $\frac{1}{4}$ on W. face, and witnessed by a mound of stone, E. of cor.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T43S R16W

$\frac{1}{4}$
S9|S10
1972

Bury original cor. stone alongside iron post and rebuild mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.

N. 0° 11' E., beginning new measurement.

By triangulation; asc. about 120 ft. over SW. slope.

30.00 Base of steep ascent, bears NW. and SE.; asc. about 280 ft. over steep and broken SW. slope.

40.02 Point for the cor. of secs. 3, 4, 9 and 10, at proportionate distance; there is no remaining evidence of the original cor. End triangulation.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T43S R16W

S4|S3
S9|S10
1972

Land, broken desert.

Soil, clay.

Undergrowth, sagebrush.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS

From the true point for the cor. of secs. 2, 3, 10 and 11.

N. 89° 50' W., bet. secs. 3 and 10.

Over broken mountain land, through sagebrush undergrowth;
asc. 120 ft. over NE. slope.

12.30 Ravine, drains NE.; asc. 100 ft. over NE. slope.

25.00 Ridge, bears N. and S.; desc. 65 ft. over NW. slope.

37.30 Wash, drains N.; asc. gentle E. slope.

40.31 The $\frac{1}{4}$ sec. cor. of secs. 3 and 10, monumented with a
sandstone, 15x5x4 ins., firmly set, 10 ins. in the ground,
and plainly mkd. $\frac{1}{4}$ on N. face, and witnessed by a
mound of stone alongside.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins.
in the ground to bedrock, and in a mound of stone, 3 ft.
base to top, with brass cap mkd.

T43S R16W

$\frac{1}{4}$ $\frac{S3}{S10}$
1972

Place original cor. stone in mound of stone, alongside
iron post.

Cor. is located about 20 lks. E. of two large boulders
about 10 ft. high.

N. 89° 40' W., beginning new measurement.

sc. 150 ft. over NE. slope.

12.95 Draw, drains N. 60° E.; asc. 240 ft. over steep SE.
slope.

35.00 Top of Red Bluff, bears N. 52° W. and S. 52° E.; desc.
240 ft. over steep and broken SW. slope.

39.96 The cor. of secs. 3, 4, 9 and 10.

and, broken desert mountains.
Soil, sandy clay.
ndergrowth, sagebrush.

. 0° 35' W., bet. secs. 3 and 4.

Over broken desert mountains through sagebrush under-
growth. Asc. 240 ft. over steep and broken SW. slope.

5.25 op of Red Bluff, bears N. 52° W. and S. 52° E.; thence
y triangulation; desc. about 80 ft. over NE. slope.
Topography scaled.

10.00 Draw, drains N. 50° E.; desc. 150 ft. over NE. slope.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS

- 31.00 Draw, drains N. 75° E.; asc. about 120 ft. over S. slope.
- 36.00 Small spur, slopes E.; desc. about 20 ft. over N. slope.
- 38.00 Small draw, drains N. 80° E.; asc. about 10 ft. over S. slope.

40.02 The $\frac{1}{4}$ sec. cor. of secs. 3 and 4, monumented with a sandstone, 16x10x3 ins., firmly set 10 ins. in the ground, plainly mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T43S R16W

$\frac{1}{4}$
S4|S3
1972

Place original cor. stone in mound of stone, alongside the iron post.

N. 0° 14' W., beginning new measurement.

Asc. 10 ft. over SE. slope.

- 5.20 Spur, slopes N. 55° E.; desc. 205 ft. over NW. slope.
- 23.30 Ravine, drains N. 55° E.; asc. 70 ft. over SE. slope.
- 27.70 Spur, slopes N. 50° E.; desc. 60 ft. over NW. slope.
- 35.90 Ravine, drains N. 50° E.; asc. 50 ft. over SE. slope.
- 38.75 The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set in mound of stone, 3½ ft. base 2½ ft. high, with brass cap mkd.

T42S R16W

S33|S34
S4|S3
T43S
1968

Land, broken desert mountains.
Soil, clay, sandy and some gypsum.
Undergrowth, sagebrush.

Reestablishment of the Survey Executed by W. Jenkins and J. A. West, Deputy Surveyors, in 1897, and the Resurvey Executed by A. J. Stewart Jr. and L. A. Snow, Deputy Surveyors, in 1909.

From the cor. of secs. 28, 29, 32 and 33, monumented with a sandstone, 22x12x10 ins., firmly set 10 ins. in the ground, and in a mound of stone, plainly mkd. 4 notches on

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS

E. and 1 on S. edges.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.

T43S R16W
S29|S28
S32|S33
1972

Bury original cor. stone alongside iron post, and raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of cor.

S. 0° 04' E., bet. secs. 32 and 33.

Over broken desert land through sagebrush undergrowth. Along E. slope.

6.23 Drift fence, bears N. 55° W. and S. 55° E.

10.00 Ravine, drains N. 65° E.; asc. 230 ft. over NE. slope.

39.95 The ¼ sec. cor. of secs. 32 and 33, monumented with a sandstone, 16x10x6 ins., firmly set 8 ins. in the ground and witnessed by a mound of stone to E.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

T43S R16W
¼
S32|S33
1972

Bury original cor. stone alongside iron post, and rebuild mound of stone, 3 ft. base, 2 ft. high, E. of cor.

S. 0° 27' E., beginning new measurement.

Asc. 15 ft. over N. slope.

1.10 Low ridge, bears E. and W.; desc. 70 ft. over SE. slope.

7.50 Intersect the Utah-Arizona State Boundary.

Point for the closing cor. of secs. 32 and 33, T. 43 S., R. 16 W.

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

UT
T43S R16W
C C
S32|S33
ARIZ
1972

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS

From this cor., the original closing cor. of secs. 32 and 33, bears S. $0^{\circ} 27'$ E., 0.14 chs. dist., monumented with an iron post, 2 ins. diam., extending 24 ins. above ground, and in a mound of stone, 3 ft. base, with brass cap mkd.

T43S R16W

S32|S33
C|C
—
A

1909

I add "AM" and 1971 to the brass cap markings.

From the same cor., Mile Post 21, on the Utah-Arizona State Boundary, bears N. $89^{\circ} 56'$ W., 37.41 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., herein-before described.

Land, broken desert.
Soil, rocky.
Undergrowth, sagebrush.

From the cor. of secs. 27, 28, 33 and 34.

S. $89^{\circ} 58'$ W., bet. secs. 28 and 33.

Over broken desert land through shadscale undergrowth; asc. 35 ft. along general N. slope.

20.40 Small draw, drains N. 5° E.; asc. 75 ft. along broken N. slope.

33.50 Small gypsum spur, slopes N. 40° E.; thence along N. slope.

37.40 Saddle, on low ridge, bears S. 60° E. and curves W.; thence along S. slope.

39.96 The $\frac{1}{4}$ sec. cor. of secs. 28 and 33, monumented with a sandstone, 16x10x6 ins., firmly set in a mound of gypsum and plainly mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T43S R16W

$\frac{1}{4}$ S28
S33

1972

Place original cor. stone in mound of stone, alongside iron post.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S. R. 16 W. Salt Lake Meridian Utah

CHAINS

N. 89° 57' W., beginning new measurement.

Asc. 45 ft. along S. slope.

- 4.40 Top of ascent, on S. side of gypsum hill, 2.00 chs. diam.; desc. 145 ft. over steep W. slope.
- 10.80 Base of steep descent; thence desc. 45 ft. over gentle NW. slope.
- 18.55 Trail road, bears N. 25° W. and S. 25° E.
- 31.60 Wash, 100 lks. wide, 5 ft. deep, drains N. 10° E.; asc. 50 ft. over E. slope.
- 39.97 The cor. of secs. 28, 29, 32 and 33.

Land, broken desert.
Soil, sandy with some gypsum.
Undergrowth, shadscale and sagebrush.

Reestablishment of the Survey Executed by
W. Jenkins and J. A. West,
Deputy Surveyors, in 1897

N. 0° 04' W., bet. secs. 28 and 29.

Over broken desert land, through shadscale and sagebrush undergrowth, along E. slope.

- 3.00 Spur, slopes N. from S. 40° W.; desc. 35 ft. over N. slope, along spur.
- 12.50 Low saddle on spur, slopes N.; asc. 25 ft. over S. slope.
- 21.75 Top of ascent, on spur, turns N. 40° W.; desc. 60 ft. over NE. slope.
- 25.60 Wash, 50 lks. wide, 5 ft. deep, drains irregularly N. from E.; thence along wash.
- 30.00 Leave wash, drains N. 60° W.; asc. 75 ft. over SW. slope.
- 35.40 Spur, slopes W.; desc. 45 ft. over NW. slope.
- 39.99 The $\frac{1}{4}$ sec. cor. of secs. 28 and 29, in small draw, drains N. 35° W., monumented with a sandstone, 20x14x8 ins., firmly set 12 ins. in the ground, and plainly mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS

T43S R16W

 $\frac{1}{4}$

S29|S28

1972

Bury original cor. stone alongside iron post, and raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.

North, beginning new measurement.

Desc. 70 ft. along gentle W. slope.

- 39.93 Point for the cor. of secs. 20, 21, 28 and 29, at proportionate distance; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with a pine post, 12 ins. diam., 5 ft. long, alongside, brass cap mkd.

T43S R15W

S20|S21

S29|S28

1972

Land, broken desert.

Soil, gypsum clay and sand.

Undergrowth, shadscale and sagebrush.

From true point for the cor. of secs. 21, 22, 27 and 28.

West, bet. secs. 21 and 28.

Over river bottom land, through willows. By triangulation over waters of Virgin River.

- 4.96 Point for the original meander cor. of secs. 21 and 28, for right bank, at proportionate distance falls in river, and cannot be perpetuated; there is no remaining evidence of the original cor.
- 8.54 Point for the original meander cor. of secs. 21 and 28, for left bank, at proportionate distance falls in Virgin River; there is no remaining evidence of the original corner.
- 8.80 Point for the meander cor. of secs. 21 and 28, on present left bank of Virgin River, bears N. $3^{\circ} 40'$ W. and S. $42^{\circ} 42'$ E., falls at base of near vertical ledges, and deemed unsafe to perpetuate.
- Asc. abruptly about 75 ft. over limestone ledges.
- 9.00 Top of limestone ledge, bears S. 40° E. and curves N. End triangulation.
- 9.10 Point for the witness meander cor. of secs. 21 and 28.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W. Salt Lake Meridian Utah

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., over a cross (X) on solid limestone, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T43S R16W
S21
S28 WMC

1972

9.25 Top of ascent; desc. 65 ft. over W. slope.

22.65 Drift fence, bears NW. and SE.

26.55 Point for the witness meander cor. of secs. 21 and 28, for left bank of Virgin River.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T43S R16W
S21
S28 WMC
1972

Enter river bottom land.

29.50 Point for the original meander cor. of secs. 21 and 28, for left bank, at proportionate distance falls in gravelly river bottom; there is no remaining evidence of the original cor. Point not monumented.

29.59 Point for the meander cor. of secs. 21 and 28, on present left bank of Virgin River, bears N. 17° 07' W. and S. 15° 10' E., falls on gravelly bank and deemed unsafe to perpetuate.

31.96 Point for the meander cor. of secs. 21 and 28, on present right bank of Virgin River, bears N. 24° 34' W. and S. 26° 20' E., falls on gravelly bank and deemed unsafe to perpetuate.

32.26 Point for the witness meander cor. of secs. 21 and 28, right bank.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with a cottonwood post, 5 ft. long, alongside, brass cap mkd.

T43S R16W
S21
S28 WMC
1972

Asc. 80 ft. over ledges facing E.

32.29 Point for the original meander cor. of secs. 21 and 28, for right bank, at proportionate distance; there is no remaining evidence of the original corner. Point not monumented.

33.90 Top of ledges, bears N. 25° W. and S. 25° E.; asc. 30 ft. over SE. slope.

37.05 Rocky point of spur; desc. 15 ft. over SW. slope.

39.91 The ¼ sec. cor. of secs. 21 and 28, monumented with a sandstone, 16x10x6 ins., set in a mound of stone, plainly mkd. ¼ on N. face.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T43S R16W
 $\frac{1}{4}$ $\frac{S21}{S28}$
1972

Place original cor. stone in mound of stone, alongside iron post, and raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

N. $89^{\circ} 57'$ W., beginning new measurement.

Desc. 100 ft. over ledgy SW. slope.

- 3.95 Point for the witness meander cor. of secs. 21 and 28, for right bank.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T43S R16W
WMC $\frac{S21}{S28}$
1972

- 4.13 Point for the original meander cor. of secs. 21 and 28, for right bank, at proportionate distance; there is no remaining evidence of the original cor. Point not monumented.

- 6.67 Point for the meander cor. of secs. 21 and 28, on present right bank of Virgin River, bears N. $37^{\circ} 36'$ W. and S. $48^{\circ} 30'$ E., deemed unsafe to perpetuate, thence across river.

- 14.98 The original meander cor. of secs. 21 and 28, on the present left bank of the Virgin River, bears S. $48^{\circ} 06'$ E. and N. $8^{\circ} 17'$ E., monumented with a sandstone, $12 \times 10 \times 8$ ins., firmly set 6 ins. in the ground, and plainly mkd. MC.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T43S R16W
 $\frac{S21}{S28}$ MC
1972

Bury original meander cor. stone alongside the iron post.

Thence over level river bottom land.

- 39.97 The cor. of secs. 20, 21, 28 and 29.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS

Land, river bottom and broken mountains.
Soil, gravelly, rocky.
Undergrowth, willows and shadscale.

N. 0° 07' W., bet. secs. 20 and 21.

Over river bottom land, through willows.

2.60 Point for the original meander cor. of secs. 20 and 21,
left bank, at proportionate distance; there is no re-
maining evidence of the original cor. Point not monu-
mented.

3.49 Point for the witness meander cor. of secs. 20 and 21,
left bank.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T43S R16W
WMC
S20 | S21
1972

3.61 Point for the meander cor. of secs. 20 and 21, on present
left bank of Virgin River, bears N. 71° 55' E. and S. 66°
14' W., deemed unsafe to perpetuated., thence over river.

22.96 Point for the original meander cor. of secs. 20 and 21,
right bank, at proportionate distance; there is no re-
maining evidence of the original cor. Point not monu-
mented.

24.18 Point for the meander cor. of secs. 20 and 21, on
present right bank of Virgin River, bears S. 83° 55'
E. and S. 48° 35' W., deemed unsafe to perpetuate.

24.78 Point for the witness meander cor. of secs. 20 and 21.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T43S R16W
S20 | S21
WMC
1972

Asc. 95 ft. over steep S. slope.

28.90 Saddle on spur, slopes E.; desc. 65 ft. over NE. slope.

34.50 Val Wash, drains E.; asc. 100 ft. over broken SW.
slope.

38.40 Spur, slopes S. 30° W.; thence along W. slope.

39.93 The ¼ sec. cor. of secs. 20 and 21, monumented with a
limestone, 18x12x5 ins., firmly set 10 ins. in the
ground, plainly mkd. ¼ on W. face.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T43S R16W

$\frac{1}{4}$
S20|S21
1972

Bury original cor. stone alongside iron post, and raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

N. $0^{\circ} 04'$ W., beginning new measurement.

Asc. 85 ft. along broken W. slope.

11.90 Spur, slopes S. 50° W.; desc. 85 ft. over NW. slope.

18.15 Ravine, drains S. 60° W., from nearly E.; asc. 130 ft. over SE. slope.

39.93 The cor. of secs. 16, 17, 20 and 21, monumented with a limestone, 18x10x8 ins., firmly set 6 ins. in the ground, and plainly mkd. 3 notches on S., and 4 on E. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

T43S R16W
S17|S16
S20|S21

1972

Place original cor. stone in collar of stone, alongside iron post.

Land, river bottom S. portion; broken desert N. portion. Soil, rocky.

Undergrowth, willows S. portion; shadscale N. portion.

From the cor. of secs. 15, 16, 21 and 22.

S. $89^{\circ} 53'$ W., bet. secs. 16 and 21.

Over broken desert land through shadscale undergrowth. Asc. 110 ft. over NE. slope.

17.40 Spur, slopes S. 55° E. from W.; asc. 25 ft. along S. slope.

39.98 The $\frac{1}{4}$ sec. cor. of secs. 16 and 21, monumented with a sandstone, 16x8x6 ins., firmly set 8 ins. in the ground, and plainly mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS

T43S R16W

$\frac{1}{4}$ $\frac{S16}{S21}$

1972

Bury original cor. stone alongside iron post, and raise
a mound of stone, 2 ft. base, 2 ft. high, N. of cor.

S. 89° 54' W., beginning new measurement.

Asc. 5 ft. along S. slope.

- 5.10 Top of ascent, slopes S.; desc. 30 ft. along general
S. slope.
- 18.25 Wash, drains S. 55° E.; asc. 55 ft. over NE. slope.
- 34.85 Trail road, bears N. 15° W.; and S. 15° E.
- 38.30 Spur, slopes S. 60° E.; desc. 15 ft. over SW. slope.
- 39.84 The cor. of secs. 16, 17, 20 and 21.

Land, broken desert.

Soil, rocky.

Undergrowth, shadscale.

N. 0° 08' W., bet. secs. 16 and 17.

over broken desert land through shadscale undergrowth.
Asc. 15 ft. over SW. slope.

- 2.80 Ridge, bears E. and W.; desc. 125 ft. over general
NE. slope.
- 39.97 The $\frac{1}{4}$ sec. cor. of secs. 16 and 17, monumented with a
limestone, 26x14x6 ins., firmly set 12 ins. in
the ground, and plainly mkd. $\frac{1}{4}$ on W. face, and witnessed
by a mound of stone to W.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T43S R16W

$\frac{1}{4}$
S17|S16

1972

Bury original cor. stone alongside iron post, and raise
a mound of stone, 3 ft. base, 3 ft. high, W. of cor.

N. 0° 05' W., beginning new measurement.

Desc. 20 ft. over gentle NE. slope.

- 10.95 Wash, drains S. 80° E.; asc. 20 ft. over gentle
SE. slope.
- 11.35 Trail road, bears N. 85° E. and N. 72° W.

43

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS

35.65 Wash, 40 lks. wide, 3 ft. deep, drains S. 75° E.

39.96 The cor. of secs. 8, 9, 16 and 17, monumented with a sandstone, 20x10x8 ins., firmly set 10 ins. in the ground, plainly mkd. 4 notches on S. and E. edges.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T43S R16W
S8|S9
S17|S16
1972

Bury original cor. stone alongside iron post, and raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor.

Land, broken desert S. portion; gently rolling N. portion.
Soil, gypsum clay, gravelly.
Undergrowth, shadscale.

From the cor. of secs. 9, 10, 15 and 16.

S. 89° 50' W., bet. secs. 9 and 16.

Over gently rolling desert land, through shadscale undergrowth. Descend 20 ft. over W. slope.

5.00 Wash, drains S.; asc. 15 ft. along gently rolling S. slope.

7.00 Trail road, bears N. 85° E. and S. 85° W.

26.40 Wash, 20 lks. wide, 3 ft. deep, drains nearly E. from NW.; asc. 40 ft. over NE. slope.

35.80 Top of ascent, bears NW. and SE.; desc. 25 ft. over SW. slope.

39.86 The ¼ sec. cor. of secs. 9 and 16, monumented with a limestone, 18x10x6 ins., firmly set 10 ins. in the ground, plainly mkd. ¼ on N. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T43S R16W
S9
¼ S16
1972

Bury original cor. stone alongside iron post, and raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor.

S. 89° 57' W., beginning new measurement.

Desc. 30 ft. over SW. slope.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS

- 9.80 Curly Hollow Wash, drains SE., with trail road, in bottom, bears N. and S. 2.00 chs. to trail road, bearing E. and S. 40° W.; asc. 55 ft. over E. slope.
- 16.20 Low ridge, bears S. and curves W.; desc. 35 ft. along general S. slope.
- 39.86 The cor. of secs. 8, 9, 16 and 17.
- Land, rolling and broken desert.
Soil, gypsum clay, rocky.
Undergrowth, shadscale and sagebrush.
- N. 0° 07' W., bet. secs. 8 and 9.
- Over broken desert land through shadscale and sagebrush undergrowth. Asc. 75 ft. over SW. slope.
- 11.35 Spur, slopes S. 60° E.; desc. 30 ft. over gentle NE. slope.
- 29.90 Curly Hollow Wash, drains irregularly SE.
- 30.10 Trail road, bears S. 47° E. and N. 47° W.; asc. 75 ft. over SW. slope.
- 37.05 Spur, slopes S. 55° E.; desc. 30 ft. over NE. slope.
- 40.03 The $\frac{1}{4}$ sec. cor. of secs. 8 and 9, monumented with a sandstone, 14x12x6 ins., firmly set 5 ins. in the ground and plainly mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T43S R16W

$\frac{1}{4}$
S8|S9
1972

Bury original cor. stone alongside iron post, and raise a mound of stone 3 ft. base, $1\frac{1}{2}$ ft. high, west of cor.

N. 0° 06' W., beginning new measurement.

Desc. 5 ft. over NE. slope.

- 1.00 Draw, drains S. 55° E.; asc. 45 ft. over SW. slope.
- 7.95 Spur, slopes E.; asc. 20 ft. along broken E. slope.
- 12.15 Spur, slopes N. 70° E.; desc. 30 ft. over NW. slope.
- 15.00 Ravine, drains E. about 3.00 chs., thence SE.; asc. 30 ft. over S. slope.
- 18.55 Point of small spur, slopes W.; desc. 30 ft. over NW. slope.
- 23.00 Junction of ravines from E. and W., draining south-westerly; asc. 170 ft. over broken general SE. slope.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS

38.10 Top of ascent, slopes E.; thence along general E. slope.

39.93 The cor. of secs. 4, 5, 8 and 9, monumented with a sandstone, 20x10x5 ins., firmly set in mound of stone, marks have weathered away, but is harmoniously related to existing original cors., and is accepted as the original cor. stone.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

T43S R16W
S5|S4
S8|S9
1972

Bury original cor. stone alongside iron post, and raise a mound of stone, 2 ft. base, 2 ft. high, NW. and SW. of cor.

Land, broken desert.

Soil, gypsum clay.

Undergrowth, sage and blackbrush.

From the cor. of secs. 3, 4, 9 and 10.

S. 89° 47' W., bet. secs. 4 and 9.

Over broken desert land through blackbrush and sagebrush undergrowth. By triangulation; desc. about 300 ft. over steep SW. slope of Red Bluff.

13.00 Base of steep descent, bears NW. and SE.; thence along broken S. slope.

40.01 The ¼ sec. cor. of secs. 4 and 9, monumented with a sandstone, 16x12x5 ins., set 6 ins. in the ground, plainly mkd. ¼ on N. face, and witnessed by a mound of stone to N. End triangulation.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T43S R16W
¼ S4
S9
1972

Bury original cor. stone alongside iron post, and rebuilt mound of stone, 2½ ft. base, 2 ft. high, N. of cor.

S. 89° 55' W., beginning new measurement.

Desc. 50 ft. along broken S. slope.

9.00 Ravine, drains S. 25° E.; asc. 75 ft. over NE. slope.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS

26.65	Top of ascent, slopes S.; desc. 15 ft. along S. slope.
29.15	E. rim of ravine, bears N. and S.; desc. 55 ft. over broken W. slope.
31.65	Ravine, drains S. 3.00 chs., thence SW.; asc. 95 ft. over E. slope.
39.96	The cor. of secs. 4, 5, 8 and 9. Land, broken desert. Soil, rocky clay. Undergrowth, sagebrush, blackbrush and cacti. N. 0° 07' W., bet. secs. 4 and 5. Over broken desert land through sagebrush and blackbrush undergrowth. Desc. 50 ft. over NE. slope.
12.50	Ravine, drains SE.; asc. 50 ft. over SW. slope.
29.00	Spur, slopes S. 40° E.; asc. 50 ft. over SE. slope.
39.93	The $\frac{1}{4}$ sec. cor. of secs. 4 and 5, monumented with a sandstone, 16x9x6 ins., firmly set 6 ins. in the ground, plainly mkd. $\frac{1}{4}$ on W. face, and witnessed by a small mound of gypsum rock, W. of cor. At the cor. point Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T43S R16W $\frac{1}{4}$ S5 S4 1972 Bury original cor. stone alongside iron post, and rebuilt gypsum mound, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.
	<hr/>
	N. 0° 06' W., beginning new measurement.
	Asc. 15 ft. over SE.slope.
2.00	Small spur, slopes S. 65° E.; desc. 10 ft. over gentle NE. slope.
7.00	Small draw, drains S. 60° E.; asc. 35 ft. over SW. slope.
10.90	Small spur, slopes S. 50° E.; asc. 15 ft. over gentle SE. slope.
23.50	Wash, drains S. 50° E.
30.00	Wash, drains S. 55° E., about 3.00 chs., thence E.; asc. 30 ft. over S. slope.
39.26	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., extending 6 ins. above ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W. Salt Lake Meridian, Utah

CHAINS

T42S R16W

S32	S33
S5	S4

T43S
1968

Land, broken desert.
Soil, gypsum clay.
Undergrowth, sagebrush, blackbrush and cacti.

Reestablishment of the Survey Executed by W. Jenkins and J. A. West, Deputy Surveyors, in 1897, and the Resurvey Executed by A. J. Stewart Jr. and L. A. Snow, Deputy Surveyors, in 1909

From the cor. of secs. 29, 30, 31 and 32, monumented with a limestone, 20x12x8 ins., firmly set 10 ins. in the ground, and plainly mkd. 1 notch on S. and 5 on E. edges.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T43S R16W

S30	S29
S31	S32

1972

Bury original cor. stone alongside iron post, and raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.

S. 0° 03' E., bet. secs. 31 and 32.

Over broken desert land through sagebrush undergrowth. Asc. 205 ft. over general N. slope bet. two spurs.

- 26.35 Spur, slopes N. 20° E. and N. 20° W., from S. 20° W.; asc. 20 ft. along E. slope.
- 36.15 Ridge, bears N. 70° W. and S. 70° E.; desc. 50 ft. over S. slope.
- 39.95 The ¼ sec. cor. of secs. 31 and 32, monumented with a limestone, 18x10x5 ins., firmly set 8 ins. in the ground, plainly mkd. ¼ on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T43S R16W

¼
S31|S32
1972

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S. R. 16 W. Salt Lake Meridian Utah

CHAINS

Bury original cor. stone alongside iron post, and raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.

S. $1^{\circ} 01'$ E., beginning new measurement.

Desc. 30 ft. over general S. slope.

7.45 Intersect the Utah-Arizona State Boundary.

Point for the closing cor. of secs. 31 and 32, T. 43 S., R. 16 W.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

UT
T43S R16W
C C
S31|S32
ARIZ
1972

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

From this cor., Mile Post 20, on the Utah-Arizona State Boundary, bears N. $89^{\circ} 58'$ W., 37.33 chs. dist., monumented with an iron post, hereinbefore described.

From the same cor., the original closing cor. of secs. 31 and 32, bears S. $1^{\circ} 01'$ E., 0.08 chs. dist., monumented with an iron post, 2 ins. diam., extending 12 ins. above ground, with brass cap mkd.

U
T43S R16W
S31|S32
C|C
A
1909

I add "AM" and 1971 to the brass cap markings.

Land, broken desert.

Soil, rocky clay.

Undergrowth, sagebrush.

From the cor. of secs. 28, 29, 32 and 33.

S. $89^{\circ} 57'$ W., bet. secs. 29 and 32.

Over broken desert land through sagebrush undergrowth. Asc. 15 ft. along broken N. slope.

6.40 Low rise, bears N. and S.

7.50 Small draw, drains N. 10° E.

8.40 Drift fence, on small spur, bears N. 55° W. and S. 55° E.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS

- 13.00 Draw, drains N. 20° E.; asc. 25 ft. over SE. slope.
17.80 Spur, slopes N.; asc. 65 ft. along broken N. slope.
22.00 Wash, 20 lks. wide, 3 ft. deep, drains N. 20° E.
32.00 Spur, slopes N.; desc. 15 ft. over broken NW. slope.
39.98 The $\frac{1}{4}$ sec. cor. of secs. 29 and 32, monumented with a limestone, 18x8x6 ins., firmly set 5 ins. in the ground, plainly mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 5 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T43S R16W
S29
 $\frac{1}{4}$ S32
1972

Place original cor. stone in mound of stone, alongside iron post.

S. 89° 56' W., beginning new measurement.

Desc. 10 ft. over NW. slope.

- 0.30 Wash, drains NE.; asc. 160 ft. over broken SE. slope.
20.00 Spur, slopes N. 70° E.; desc. 15 ft. over NW. slope.
24.00 Draw, drains N.; asc. 40 ft. over NE. slope.
31.15 Top of ascent, slopes N.; desc. 30 ft. along broken N. slope.
40.02 The cor. of secs. 29, 30, 31 and 32.
Land, broken desert.
Soil, rocky clay.
Undergrowth, sagebrush and blackbrush.

S. 89° 54' W., bet. secs. 30 and 31.

Over broken land through sagebrush and blackbrush undergrowth. By triangulation, asc. about 15 ft. along N. slope.

- 2.10 Spur, slopes N. 20° W.; desc. about 60 ft. along broken N. slope.
13.50 Draw, drains N. 60° E.; asc. about 80 ft. over SE. slope.
21.00 Spur, slopes N. 70° E. from S. 45 W.; desc. about 50 ft. over NW. slope.
25.50 Draw, drains N. 70° E. from S. 35° W.; asc. about 80 ft. over SE. slope.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS

30.90 Spur and rim of Virgin River, bears N. 60° E. and S. 60° W. End triangulation, desc. 115 ft. over ledgy NW. slope.

38.00 Head of ledgy draw, drains N.; asc. 30 ft. over ledgy NE. slope.

38.87 Point for the witness $\frac{1}{4}$ sec. cor. of secs. 30 and 31, on ledgy point.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T43S R16W
W $\frac{1}{4}$ ← $\frac{S30}{S31}$
C
1972

By traverse and triangulation; desc. about 500 ft. over broken, precipitous and ledgy NW. slope.

40.02 Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31, at proportionate distance falls on steep, ledgy slope and cannot be perpetuated; there is no remaining evidence of the original cor.

62.00 Mouth of ledgy draw, at base of broken descent, drains N.; asc. about 100 ft. along broken general N. slope.

78.86 The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described. End triangulation and traverse.

Land, broken mountainous.

Soil, rocky.

Undergrowth, scattered sagebrush.

Reestablishment of the Survey Executed by
W. Jenkins and J. A. West, Deputy Surveyors, in 1897

From the cor. of secs. 29, 30, 31 and 32.

N. 0° 05' W., bet. secs. 29 and 30.

Over broken mountainous land through scattered undergrowth. Desc. 130 ft. over general N. slope.

9.20 Ravine, drains E.; asc. 120 ft. over broken S. slope.

15.80 Ridge, bears N. 70° E. and S. 70° W.; thence by triangulation; desc. about 100 ft. over N. slope.

23.00 Rim of Virgin River, bears N. 75° E. and S. 75° W.; desc. about 400 ft. over broken and precipitous N. slope.

33.50 Virgin River, flows W.; thence over nearly level bottom land.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S. R. W.

CHAINS

40.05 The $\frac{1}{4}$ sec. cor. of secs. 29 and 30, monumented with a limestone, 16x8x6 ins., firmly set 10 ins. in the ground, plainly mkd. $\frac{1}{4}$ on W. face. End triangulation.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T43S R16W

$\frac{1}{4}$

S30|S29

1972

Bury original cor. stone alongside iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

N. $0^{\circ} 03'$ W., beginning new measurement.

Over level bottom land.

- 2.80 Base of broken slope, bears SW. and curves N.; asc. 160 ft. over broken SE. slope.
- 11.40 Rim of canyon, bears N. 35° E. and S. 35° W.; desc. 30 ft. over N. slope.
- 14.00 Draw, drains E. from NW.; asc. 60 ft. over SE. slope.
- 20.80 Spur, slopes E.; thence by triangulation; desc. about 120 ft. over broken NE. slope.
- 33.00 Ledgy draw, drains S. 45° E. from W.; asc. about 80 ft. over broken SW. slope.
- 38.00 Spur, slopes S. 55° E.; desc. 15 ft. over NE. slope.
- 39.96 The cor. of secs. 19, 20, 29 and 30, monumented with a limestone, 16x10x8 ins., firmly set 6 ins. in the ground, and plainly mkd. 2 notches on S. and 5 on E. edges. End triangulation.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T43S R16W

S19|S20

S30|S29

1972

Place original cor. stone in mound of stone, alongside iron post.

Land, broken.

Soil, rocky.

Undergrowth, sagebrush with scattered willows along river.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S. R. 16 W. Salt Lake Meridian Utah

CHAINS

From the cor. of secs. 20, 21, 28 and 29.

N. 89° 57' W., bet. secs. 20 and 29.

Over river bottom land through scattered willows.

1.06 Point for the original meander cor. of secs. 20 and 29, for left bank, at proportionate distance; there is no remaining evidence of the original cor. Point not monumented.

7.95 Point for the witness meander cor. of secs. 20 and 29.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T42S R16W

WMC 

1972


8.20 Point for the meander cor. of secs. 20 and 29, on present left bank of Virgin River, deemed unsafe to perpetuate. Bank bears N. 66° 14' E. and S. 66° 14' W., thence over river.

16.45 Point for the meander cor. of secs. 20 and 29, on present right bank of Virgin River, deemed unsafe to perpetuate. Bank bears N. 28° 50' E. and S. 15° 30' W.

16.77 Point for the witness meander cor. of secs. 20 and 29.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T43S R16W

 WMC

1972

16.79 Point for the original meander cor. of secs. 20 and 29, for right bank, at proportionate distance; there is no remaining evidence of the original cor. Point not monumented.

Asc. 125 ft. over E. slope.

28.00 Spur, slopes S.; thence along S. slope.

36.00 Spur, slopes S. 15° E.; desc. 55 ft. over W. slope.

39.96 The ¼ sec. cor. of secs. 20 and 29, monumented with a limestone, 17x8x6 ins., firmly set 10 ins. in the ground, and plainly mkd. ¼ on N. face, and witnessed by small mounds of stone, N., S., E. and W. of cor.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W., Salt Lake County, Utah.

CHAINS

T43S R16W

$$\frac{1}{4} \frac{S20}{S29}$$

1972

Bury original cor. stone alongside iron post.

S. 89° 59' W., beginning new measurement.

Desc. 60 ft. over W. slope.

- 4.70 Mountain Valley Wash, drains S. 20° E.; asc. 185 ft. over NE. slope.
- 18.33 Drift fence, bears NW. and SE.
- 18.35 Spur, slopes S. 20° E.; desc. 75 ft. over SW. slope.
- 27.10 Ravine, drains S.; asc. 50 ft. over SE. slope.
- 32.25 Point of spur, slopes S.; desc. 20 ft. over SW. slope.
- 36.30 Ravine, drains S. 60° E.; asc. 60 ft. over NE. slope.
- 39.93 The cor. of secs. 19, 20, 29 and 30.

Land, river bottom E. portion; broken desert W. portion.

Soil, sandy clay.

Undergrowth, willows, E. portion; shadscale W. portion.

S. 89° 52' W., bet. secs. 19 and 30.

Over mountainous land, through blackbrush and sagebrush undergrowth. Asc. 10 ft. over NE. slope.

- 3.30 Spur, slopes S. 60° E.; asc. 30 ft. over SE. slope.
- 17.00 Wash, 20 lks. wide, 2 ft. deep, drains S. 25° E. from N. 75° W.; asc. 150 ft. over NE. slope.
- 24.95 Trail road, bears NW. and SW.
- 39.93 The $\frac{1}{4}$ sec. cor. of secs. 19 and 30, monumented with a limestone, 18x12x5 ins., firmly set 10 ins. in the ground, and plainly mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T43S R16W

$$\frac{1}{4} \frac{S19}{S30}$$

1972

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S. R. 16 W. Salt Lake Meridian Utah

CHAINS

Place original cor. stone in mound of stone, alongside iron post.

S. 89° 51' W., beginning new measurement.

Asc. 170 ft. over NE. slope.

17.25 Slope changes; asc. 85 ft. along N. slope.

31.05 Spur, slopes S. 50° E. curving E.; asc. 60 ft. over NE. slope.

36.55 Ridge, bears N. and S.; desc. 20 ft. over W. slope.

38.96 The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described.

Land, mountainous.

Soil, clay

Undergrowth, blackbrush and sagebrush.

From the cor. of secs. 19, 20, 29 and 30.

N. 0° 06' W., bet. secs. 19 and 20.

Over broken desert land through blackbrush and shadscale undergrowth. Descend 20 ft. over NE. slope.

2.15 Ravine, drains S. 70° E.; asc. 85 ft. over SW. slope.

12.50 Trail road, on spur, bears N. 60° W. and S. 60° E.; desc. 10 ft. along general E. slope.

16.00 Small gully, drains E.

20.75 Spur, slopes E.; desc. 45 ft. over NE. slope.

22.53 Drift fence, bears NW. and SE.

27.65 Wash, drains S. 20° E. about 3.00 chs., thence irregularly E.; asc. 45 ft. over SW. slope.

32.65 Spur, slopes SE.; desc. 80 ft. over NE. slope.

39.25 Mountain Valley Wash, 30 lks. wide, 2 ft. deep, drains S. 50° E.; asc. SW. slope.

39.97 The $\frac{1}{4}$ sec. cor. of secs. 19 and 20, monumented with a limestone, 15x8x6 ins., firmly set 6 ins. in the ground, plainly mkd. $\frac{1}{4}$ on W. face, and witnessed by small mound of stone, N., S., E. and W. of cor.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of Portion of the Subdivision,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS

T43S R16W

 $\frac{1}{4}$
S19|S20

1972

Bury original cor. stone alongside iron post.

N. 0° 03' W., beginning new measurement.

Asc. 20 ft. over SW. slope.

8.00 Point of spur, slopes S. 30° E.; desc. 30 ft. over NE. slope.

15.25 Wash, drains SE.; asc. 110 ft. over SW. slope.

39.97 The cor. of secs. 17, 18, 19 and 20, monumented with a limestone, 18x8x4 ins., firmly set 6 ins. in the ground, mkd. 3 notches on S. and 5 on E. edges.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T43S R16W

 $\frac{S18|S17}{S19|S20}$

1972

Place original cor. stone, in mound of stone, alongside iron post.

Land, broken.

Soil, clay.

Undergrowth, blackbrush and shadscale.

From the cor. of secs. 16, 17, 20 and 21.

N. 89° 57' W., bet. secs. 17 and 20.

Over broken desert land through blackbrush and sagebrush undergrowth. Desc. 10 ft. over gentle SW. slope.

10.10 Small wash, drains SE.; asc. 110 ft. over NE. slope.

37.65 Ridge, bears NW. and SE.; desc. 30 ft. over SW. slope.

39.95 The ¼ sec. cor. of secs. 17 and 20, monumented with a limestone, 16x8x5 ins., firmly set 6 ins. in the ground, mkd. ¼ on N. face, and witnessed by mounds of stone, N., S., E. and W. of cor.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivision,
T. 3 S

CHAINS

T43S R16W
 $\frac{1}{4}$ $\frac{S17}{S20}$
1972

Bury original cor. stone alongside iron post.

N. 89° 58' W., beginning new measurement.

Desc. 85 ft. over SW. slope.

- 4.90 Draw, drains SW.; asc. 20 ft. over SE. slope.
10.00 Top of ascent, slopes S.; desc. 60 ft. over SW. slope.
18.00 Val Wash, drains SE.; asc. 145 ft. over NE. slope.
37.20 Ridge, bears NW. and SE.; desc. 25 ft. over SW. slope.
39.88 The cor. of secs. 17, 18, 19 and 20.

Land, broken desert.

Soil, clay.

Undergrowth, sagebrush, blackbrush and shadscale.

S. 89° 51' W., bet. secs. 18 and 19.

Over broken desert land through sagebrush and blackbrush undergrowth. Desc. 65 ft. over SW. slope.

- 2.80 Trail road, bears N. and S.
3.50 Wash, drains S. 10° E.; asc. 80 ft. over SE. slope.
12.00 Point of spur, slopes S.; desc. 15 ft. over SW. slope.
13.50 Draw, drains S.; asc. 15 ft. over SE. slope.
14.90 Point of spur, slopes S.; desc. 30 ft. over SW. slope.
18.00 Draw, drains S.; asc. 35 ft. over E. slope.
19.60 Point of spur, slopes S. 40° E.; desc. 40 ft. over SW. slope.
25.30 Draw, drains S. 65° E., from N.; asc. 220 ft. over general E. slope.
39.50 Ridge, bears E. and curves NW.; thence over top.
39.96 The $\frac{1}{4}$ sec. cor. of secs. 18 and 19, monumented with a limestone, 14x8x6 ins., firmly set 6 ins. in the ground, mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S. R. 16 W., Salt Lake Meridian, Utah

CHAINS

T43S R16W
 $\frac{1}{4}$ $\frac{S18}{S19}$
1972

Place original cor. stone in mound of stone, alongside iron post.

S. 89° 49' W., beginning new measurement.

Desc. 70 ft. over W. slope.

- 4.90 Draw, drains S.; asc. 45 ft. over SE. slope.
- 10.80 Drift fence, bears NW. and SE.
- 11.50 Spur, slopes S.; asc. 10 ft. along S. slope.
- 14.50 Desc. 40 ft. over SW. slope.
- 15.50 Draw, drains S. 15° E.; asc. 105 ft. over NE. slope.
- 28.80 Ridge, bears S. and curves W.; desc. 110 ft. along broken S. slope.
- 38.91 The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described.
- Land, broken desert.
Soil, clay.
Undergrowth, sagebrush and blackbrush.
-
- From the cor. of secs. 17, 18, 19 and 20.
- N. 0° 05' W., bet. secs. 17 and 18.
- Over broken desert land through sagebrush and blackbrush undergrowth. Asc. 25 ft. over SW. slope.
- 1.50 Ridge, bears NW. and SE.; desc. 70 ft. over NE. slope.
- 13.35 Trail road, bears N. 10° E. and S. 10° W.; desc. 15 ft. along gentle E. slope.
- 20.15 Wash, drains S. 80° E.; asc. 100 ft. over SE. slope.
- 21.05 Same trail road, bears NW. and E. about 2.00 chs.; thence S.
- 26.65 Top of ascent, slopes E.; desc. 85 ft. over NE. slope.
- 36.45 Wash, in ravine, drains E. about 3.00 chs. into Val Wash draining S.; asc. 65 ft. over S. slope.
- 39.94 The $\frac{1}{4}$ sec. cor. of secs. 17 and 18, monumented with a limestone, 18x6x6 ins., firmly set in small mound of stone, mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., over a cross (X), on solid stone, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS

T43S R16W

$\frac{1}{4}$
S18|S17
1972

Place original cor. stone, in mound of stone, alongside iron post.

N. 0° 05' W., beginning new measurement.

Asc. 5 ft. over SW. slope.

- 1.40 Point of spur, slopes E.; desc. 20 ft. over gentle NE. slope.
- 5.90 Val Wash, drains SE.; asc. 75 ft. over SW. slope.
- 9.25 Trail road, bears N. 75° W. and S. 75° E.
- 18.75 Ridge, bears N. 80° W. and S. 80° E.; desc. 115 ft. over NW. slope.
- 31.90 Draw, drains N. 50° E.; asc. 85 ft. over SW. slope.
- 39.15 Spur, slopes N. 80° E.; desc. 5 ft. over N. slope.
- 39.93 The cor. of secs. 7, 8, 17 and 18, monumented with a limestone, 18x10x6 ins., firmly set 6 ins. in the ground plainly mkd. 5 notches on E. and 4 on S. edges.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

T43S R16W

S7|S8
S18|S17
1972

Bury original cor. stone alongside iron post, and raise a mound of stone, 2½ ft. base, 1½ ft. high, S. of cor.

Land, broken desert.

Soil, clay.

Undergrowth, sagebrush and blackbrush.

From the cor. of secs. 3, 9, 16 and 17.

S. 89° 58' W., bet. secs. 8 and 17.

Over gently rolling desert land through sagebrush undergrowth. Asc. 15 ft. over gently rolling SE. slope.

- 20.00 Wash, 30 lks. wide, 4 ft. deep, drains S. 60° E.; asc. 40 ft. over gentle NE. slope.
- 40.00 The ¼ sec. cor. of secs. 8 and 17, monumented with a limestone, 16x10x8 ins., firmly set 10 ins. in the ground, and plainly mkd. ¼ on N. face.

At the cor. point

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S. R. 16 W., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, $3\frac{1}{2}$ ft. base to top, with brass cap mkd.

T43S R16W
S8
 $\frac{1}{4}$ $\frac{S17}{S8}$
1972

Bury original cor. stone alongside iron post.

S. $89^{\circ} 56'$ W., beginning new measurement.

Asc. 40 ft. over NE. slope.

18.20 Wash, 100 lks. wide, 6 ft. deep, drains N. 35° E.; asc. 165 ft. over E. slope.

30.70 S. side of pink clay knoll, 1.00 ch. diam.

37.50 Spur, slopes N. 75° E.; thence along N. slope.

39.79 The cor. of secs. 7, 8, 17 and 18.

Land, gently rolling E. portion; broken W. portion.
Soil, clay.

Undergrowth, sagebrush and shadscale.

S. $89^{\circ} 53'$ W., bet. secs. 7 and 18.

Over broken desert land through sagebrush undergrowth.
Asc. 35 ft. along N. slope.

11.90 Spur, slopes E. from N.; desc. 60 ft. over SW. slope.

15.00 Draw, drains S. 35° E.; asc. 30 ft. over NE. slope.

19.00 Point of spur, slopes S. 25° E.; desc. 30 ft. over SW. slope.

23.00 Trail road, in wash, bears NW. and SE., wash drains SE.; asc. 55 ft. over general E. slope.

39.60 Wash, 30 lks. wide, 4 ft. deep, drains N. 85° E.

39.83 The $\frac{1}{4}$ sec. cor. of secs. 7 and 18, which is a cross (X), and $\frac{1}{4}$ on limestone ledge, 4 ft. high, and witnessed by a mound of stone, N. of cor.

Cor. point cannot be perpetuated with an iron post.

Raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor.

S. $89^{\circ} 51'$ W., beginning new measurement.

Asc. 225 ft. over general SE. slope.

23.10 Ridge, bears N. 80° E. from W.; desc. 75 ft. over W. slope, along ridge.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS

31.50	Saddle, bears E. and W.; asc. 100 ft. over SE. slope.
38.97	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described.
	Land, broken desert. Soil, rocky clay. Undergrowth, sagebrush and blackbrush.
	From the cor. of secs. 7, 8, 17 and 18.
	N. 0° 03' W., bet. secs. 7 and 8.
	Over broken desert land through sagebrush undergrowth. Desc. 50 ft. over N. slope.
4.00	Small draw, drains N. 60° E.; asc. 40 ft. over SE. slope.
6.50	Point of spur, slopes E.; desc. 75 ft. over NE. slope.
31.90	Wash, 30 lks. wide, 6 ft. deep, drains S. 70° E.; asc. 30 ft. over S. slope.
36.30	Pink clay spur, slopes S. 75° E.; desc. 55 ft. over NE. slope.
40.01	The $\frac{1}{4}$ sec. cor. of secs. 7 and 8, monumented with a sandstone, 18x10x4 ins., firmly set 10 ins. in the ground, plainly mkd. $\frac{1}{4}$ on W. face.
	At the cor. point
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T43S R16W $\frac{1}{4}$ S7 S8 1972
	Bury original cor. stone alongside iron post.
	N. 0° 06' W., beginning new measurement.
	Desc. 10 ft. over NE. slope.
0.30	Wash, in small ravine, drains S. 75° E.; asc. 60 ft. over SW. slope.
5.20	Spur, slopes S. 75° E.; desc. 50 ft. over NE. slope.
20.20	Curly Hollow Wash, 40 lks. wide, 2 ft. deep, drains irregularly S. 60° E.; asc. 90 ft. over general S. slope.
22.20	Trail road, bears S. 6° E. and N. about 4.00 chs., thence westerly.
39.99	The cor. of secs. 5, 6, 7 and 8, monumented with a sandstone, 18x8x4 ins., firmly set 12 ins. in the ground, mkd. 5 notches on S. and E. edges, and witnessed by a mound of stone to W.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T43S R16W
 $\frac{S6|S5}{S7|S8}$
 1972

Bury original cor. stone alongside iron post, and rebuild mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, broken desert.

Soil, clay.

Undergrowth, sagebrush and blackbrush.

From the cor. of secs. 4, 5, 8 and 9.

S. $89^{\circ} 49'$ W., bet. secs. 5 and 8.

Over broken desert land through sagebrush and blackbrush undergrowth; asc. 20 ft. over NE. slope.

1.60 Ridge, bears NW. and SE.; desc. 70 ft. over SW. slope.

5.00 Base of steep descent, bears N. and SE.; desc. 30 ft. over broken clay hills draining generally S.

13.00 Wash, drains irregularly S.; asc. 100 ft. over broken NE. slope.

33.80 Spur, slopes S. 30° E.; desc. 75 ft. over steep and broken SW. slope.

39.72 The $\frac{1}{4}$ sec. cor. of secs. 5 and 8, monumented with a limestone, $18 \times 8 \times 5$ ins., firmly set 10 ins. in the ground, and mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T43S R16W
 $\frac{1}{4} \frac{S5}{S8}$
 1972

Bury original cor. stone alongside iron post and raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, with cedar post, E. of cor.

N. $89^{\circ} 52'$ W., beginning new measurement.

Desc. 40 ft. over SW. slope.

6.00 Ravine, drains S. 20° E., thence along S. slope.

9.50 Ravine, drains irregularly S. 40° E.; asc. 75 ft. over broken NE. slope.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W. Salt Lake Meridian Utah

CHAINS

- 24.40 Spur, slopes S.; desc. 40 ft. over SW. slope.
- 26.00 Ravine, drains S.; asc. 50 ft. over SE. slope.
- 27.50 Point of spur, slopes S.; desc. 30 ft. over SW. slope.
- 28.50 Ravine, drains S.; asc. 40 ft. over SE. slope.
- 31.40 Spur, slopes S.; desc. 80 ft. over W. slope.
- 34.00 Ravine, drains S.; asc. 50 ft. over E. slope.
- 36.40 Point of spur, slopes S.; desc. 65 ft. over SW. slope.
- 40.02 The cor. of secs. 5, 6, 7 and 8.

Land, broken desert.
Soil, clay.
Undergrowth, sagebrush and blackbrush.

S. 89° 56' W., bet. secs. 6 and 7.

Over broken desert land through sagebrush undergrowth,
along S. slope.

- 4.20 Wash, drains S. 25° E.; asc. 35 ft. over NE. slope.
- 9.60 Pink clay spur, slopes S. 25° E.; desc. 60 ft. over SW.
slope.
- 13.80 Base of descent, bears N. 70° W. and S. 70° E.; thence
along rolling S. slope.
- 39.95 The $\frac{1}{4}$ sec. cor. of secs. 6 and 7, monumented with a
mound of gypsum stones, no remaining evidence, but is
harmoniously related to existing original cors., and
is accepted as the best existing evidence of the
position of the original cor.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T43S R16W
 $\frac{1}{4}$ $\frac{S6}{S7}$
1972

Raise a mound of stone, 2 ft. base, 2 ft. high, N. of
cor.

S. 89° 45' W., beginning new measurement.

Asc. 25 ft. along rolling S. slope.

- 1.29 Drift fence, bears S. 20° W. and N. 20° E. about 2.50 chs.
to end.
- 20.00 Clay knoll, 6 ft. high, 1.00 ch. diam.; asc. 20 ft.
along rolling S. slope.

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS

38.90 The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of
the Tp., hereinbefore described.

Land, broken desert.

Soil, clay and gypsum.

Undergrowth, sagebrush.

From the cor. of secs. 5, 6, 7 and 8.

N. 0° 11' W., bet. secs. 5 and 6.

Over broken desert land through sagebrush undergrowth;
asc. 50 ft. over S. slope.

2.50 Base of irregular clay hills; asc. 150 ft. over general
S. slope.

18.60 Spur, slopes S. 70° E.; desc. 20 ft. over N. slope.

21.00 Ravine, drains E.; asc. 100 ft. over S. slope.

26.85 Spur, slopes E.; desc. 40 ft. over N. slope.

31.00 Ravine, drains E.; asc. 80 ft. over S. slope.

38.20 Crest of ascent, bears E. and W.; thence along E.
slope.

39.96 The $\frac{1}{4}$ sec. cor. of secs. 5 and 6, monumented with a
limestone, 16x14x4 ins., set 10 ins. in the ground, and
mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap mkd.

T43S R16W

$\frac{1}{4}$

S6|S5

1972

Bury original cor. stone alongside iron post, and raise
a mound of stone, 3 ft. base, 3 ft. high, W. of cor.

N. 0° 10' W., beginning new measurement.

Desc. 40 ft. along rolling E. slope.

9.00 Gully, drains N. 50° E.

18.00 Gully, drains irregularly E.; asc. 10 ft. along E.
slope.

33.30 Low spur, slopes E.; desc. 10 ft. over NE. slope.

39.46 The cor. of secs. 5, 6, 31 and 32, on the N. bdy of the
Tp., monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., ex-
tending 6 ins. above ground, with brass cap mkd.

T42S R16W

S31|S32

S6|S5

T43S

1968

Dependent Resurvey of a Portion of the Subdivision,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS

Land, broken desert.
Soil, clay.
Undergrowth, sagebrush.

Partial subdivision of section 22, T. 43 S., R. 16 W., was made for the purpose of marking the boundary lines between public lands and entered lots which border upon the Virgin River. The partition line, on the accretion area, was determined by proportion between the original W. Jenkins and J. A. West (1897) adjusted meander line and the new meanders.

Portion of the Subdivision of Section 22,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

From the $\frac{1}{4}$ sec. cor. of secs. 22 and 27.

N. $0^{\circ} 04'$ W., along the N-S center line of secs. 22.

Over broken desert land, through sagebrush undergrowth.
Desc. 50 ft. over general N. slope.

- 3.00 Small draw, drains N. 55° E.
- 27.00 Mouth of draw, drains N. 25° W.; enter river bottom land and willows.
- 34.00 Atkinsville Wash, drains S. 702° W.
- 48.85 Intersect the W. Jenkins and J. A. West adjusted (1897) original meander line for left bank of Virgin River.

Point for the special meander cor. of sec. 22.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

SMC
C
S 22
C
1972

- 62.79 Present left bank of the Virgin River, bears N. $45^{\circ} 15'$ E. and S. $52^{\circ} 43'$ W., thence across river.

- 74.46 Present right bank of Virgin River, bears N. $14^{\circ} 56'$ E. and S. $55^{\circ} 08'$ W., deemed unsafe to perpetuate.

- 74.81 Point for the witness special meander cor. of sec. 22.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground and in a collar of stone, with brass cap mkd.

C
S 22
C
SMC
1972

Portion of the Subdivision of Section 22,
T. 43 S., R. 16 W., Salt Lake Meridian, Utah

CHAINS

80.06 The $\frac{1}{2}$ sec. cor. of secs. 15 and 22 previously described.

Land, broken desert S. portion; river bottom N. portion.
Soil, gravelly.

Undergrowth, sagebrush and willows.

From the special meander cor. of sec. 22 at 48.85 chs.
on the N-S centerline.

N. $64^{\circ} 48'$ W., on a partition line along the N. boundary
of public land.

5.49 Present left bank of Virgin River, bears N. $2^{\circ} 26'$ E.
and S. $2^{\circ} 26'$ W.

Point for special meander cor. of sec. 22.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

SMC
S | 22
1972

Land, nearly level river bottom.
Soil, gravelly.
Undergrowth, willows.

Present Meanders of the Virgin River through a Portion of
Township 43 South, Range 16 West, Salt Lake Meridian, Utah

Note: Since 1897, the date of the original survey of
this township, the Virgin River has made major shifts in
its position. However, the shift has been erosive and
accretive action rather than by avulsion so the owner-
ship of adjoining lands has changed with the river moves.
A traverse of the present banks of the Virgin River, where
private land borders upon the river, through sections
15 and 22, was made for information purposes only.

Meander of the Present Right Bank
of the Virgin River Through Section 22

From the true point for the meander cor. of sec. 22 only
which is witnessed S. $89^{\circ} 58'$ W., 0.50 chs. dist., pre-
viously described.

Thence with the meanders of the present right bank of
the Virgin River, downstream, through section 22.

S. $14^{\circ} 56'$ W., 5.80 chs.

Intersect the special meander
of sec. 22 on the N-S center-
line previously described.

S. $55^{\circ} 08'$ W., 2.83 chs.

S. $33^{\circ} 48'$ W., 10.14 chs.

S. $20^{\circ} 30'$ W., 12.04 chs.

Meander of the Present Right Bank of the
Virgin River through Section 15

CHAINS

S. 18° 56' E., 18.27 chs.
S. 25° 25' E., 5.89 chs.
S. 35° 14' W., 9.85 chs.
S. 72° 56' W., 7.10 chs.
S. 81° 37' W., 7.12 chs.
S. 66° 08' W., 4.41 chs.
S. 34° 54' W., 18.61 chs.
S. 52° 06' W., 2.60 chs.

Intersect the section line
bet. secs. 21 and 22, at the
true point for the meander
cor. of secs. 21 and 22, at
0.65 chs. on S. half mile
bet. secs. 21 and 22, herei-
before described.

Land, level.
Soil, sandy.
Undergrowth, willows.

Thence with the meanders of the present right bank of the
Virgin River, downstream, through section 21.

S. 84° 36' W., 5.79 chs.
N. 79° 28' W., 1.70 chs.
N. 1° 10' E., 7.52 chs.
N. 7° 40' E., 6.66 chs.
N. 23° 26' W., 3.85 chs.
N. 30° 21' W., 7.67 chs.
N. 46° 48' W., 9.59 chs.
N. 81° 50' W., 3.67 chs.
S. 60° 15' W., 3.10 chs.
S. 32° 38' W., 3.20 chs.
S. 22° 41' W., 10.30 chs.
S. 14° 46' W., 7.51 chs.
S. 20° 10' W., 5.67 chs.
S. 24° 34' E., 6.28 chs.

Intersect the section line
bet. secs. 21 and 28, at
the true point for the
meander cor. of secs. 21 and
28, at 31.96 chs. on E.
half mile bet. secs. 21
and 28, hereinbefore des-
cribed.

Land, nearly level.
Soil, sandy.
Undergrowth, willows.

Meander of the Present Right Bank of the Virgin

CHAINS

Thence with the meanders of the present right bank of the Virgin River, downstream, through section 28.

S. 26° 20' E., 9.00 chs.

S. 52° 15' E., 3.50 chs.

S. 35° 00' E., 7.50 chs.

S. 20° 40' W., 10.00 chs.

S. 37° 15' W., 9.50 chs.

N. 78° 00' W., 3.00 chs.

N. 12° 45' W., 11.50 chs.

N. 45° 15' W., 3.00 chs.

N. 2° 30' W., 3.50 chs.

N. 44° 30' W., 2.00 chs.

N. 5° 00' W., 4.50 chs.

N. 25° 00' E., 3.00 chs.

N. 48° 30' W., 10.85 chs.

Intersect the section line bet. secs. 21 and 28, at the true point for the meander cor. of secs. 21 and 28, at 6.67 chs. on the W. half mile bet. secs. 21 and 28, hereinbefore described.

Land, nearly level.

Soil, sandy.

Undergrowth, willows.

Thence with the meanders of the present right bank of the Virgin River, downstream, through section 21.

N. 37° 36' W., 20.55 chs.

N. 52° 51' W., 10.99 chs.

N. 83° 55' W., 12.15 chs.

Intersect the section line bet secs. 20 and 21, at the true point for the meander cor. of secs. 20 and 21, at 24.18 chs. on the S. half mile bet. secs. 20 and 21, hereinbefore described.

Land, nearly level.

Soil, sandy.

Undergrowth willows.

Thence with the meanders of the present right bank of the Virgin River, downstream, through section 20.

S. 48° 35' W., 8.04 chs.

S. 28° 50' W., 21.51 chs.

Intersect the section line

Meander of the Present Right Bank of the Virgin
River, Through Section 15

CHAINS

bet. secs. 20 and 29, at the
true point for the meander
cor. of secs. 20 and 29, at
16.45 chs. on E. half bet.
secs. 20 and 29, herein-
before described.

Note:

Due to the narrowing of the river about 10.00 chs.
downstream, the meanders are discontinued at this
point.

Land, nearly level.
Soil, sandy.
Undergrowth, willows.

Meander of the Present Left Bank of the Virgin
River, through Section 22

From a point S. 0° 02' E., 0.40 chs. dist., from the true
point for the cor. of secs. 14, 15, 22 and 23, herein-
before described.

Thence with a traverse, downstream, along the present
left bank of the Virgin River, through section 22 for
information purposes only.

S. 89° 57' W., 4.64 chs.

S. 65° 57' W., 7.59 chs.

S. 69° 35' W., 25.01 chs.

At 18.15 chs. on this course,
intersect the calculated
position of the adjusted
original (1897) meander line
bears N. 31° 24' E., 11.51
chs. and S. 31° 24' W., 8.19
chs.

S. 45° 15' W., 7.19 chs.

S. 52° 43' W., 5.80 chs.

S. 2° 26' W., 10.38 chs.

At 8.10 chs. on this course,
intersect the special mean-
der cor. of sec. 22, herein-
before described, at the
NW. terminus of dividing
line bet. private accretion
lands attaching to original
lot 6, sec. 22, and federal-
ly owned accretion lands
attaching to original lot 5,
sec. 22. From this cor.,
point for the special mean-
der cor. on the N-S center
line of sec. 22, and on the
adjusted original (1897)
meander line of sec. 22,
bears S. 64° 48' E., 5.49
chs. dist., hereinbefore
described. From the same
point continue with the

Meander of the Present Left Bank of the Virgin
River Through Section 22

CHAINS

	meander of the present left bank.
S. 14° 37' E., 1.00 chs.	At 3.93 chs. on this course, intersect the calculated position of the adjusted original (1897) meander line, bears N. 36° 54' E., 2.82 chs. and S. 36° 54' E., 3.18 chs.
S. 34° 15' E., 4.05 chs.	
S. 0° 11' E., 5.56 chs.	
S. 39° 49' W., 12.85 chs.	
S. 74° 32' W., 5.74 chs.	
S. 75° 09' W., 9.12 chs.	
S. 49° 39' W., 12.66 chs.	
S. 21° 55' W., 8.00 chs.	Intersect the section line bet. secs. 22 and 27, at the true point for the meander cor. of secs. 22 and 27, at 35.26 chs. on W. half mile bet. secs. 22 and 27, hereinbefore described.
Land, nearly level. Soil, gravelly clay. Undergrowth, willows.	

Thence with the meanders of the present left bank of the Virgin River, downstream, through section 27.

S. 32° 20' W., 1.87 chs.	
S. 65° 25' W., 4.14 chs.	Intersect the section line bet. secs. 27 and 28, at the true point for the meander cor. of secs. 27 and 28, at 36.64 chs. on N. half bet. secs. 27 and 28, hereinbefore described.
Land, level. Soil, gravelly. Undergrowth, willows.	

Thence with the meanders of the present left bank of the Virgin River, downstream, through section 28.

S. 81° 57' W., 2.76 chs.	
N. 71° 39' W., 1.92 chs.	
N. 73° 21' W., 2.05 chs.	
N. 42° 42' W., 3.37 chs.	Intersect the section line bet. secs. 21 and 28, at the

Meander of the Present Left Bank of the Virgin
River Through Section 22

CHAINS

true point for the meander
cor. of secs. 21 and 28, at
8.80 chs. on E. half mile
bet. secs. 21 and 28, herein-
before described.

Land, level.
Soil, sandy.
Undergrowth, willows.

Thence with the meanders of the present left bank of the
Virgin River, downstream, through section 21.

N. 3° 40' W., 16.51 chs.

N. 10° 25' W., 3.03 chs.

N. 26° 01' W., 4.15 chs.

N. 41° 28' W., 6.46 chs.

N. 60° 15' W., 3.77 chs.

N. 76° 00' W., 1.80 chs.

S. 82° 50' W., 2.33 chs.

S. 24° 07' W., 7.16 chs.

S. 9° 53' W., 3.98 chs.

S. 10° 28' W., 9.58 chs.

S. 38° 20' W., 2.25 chs.

S. 1° 19' W., 4.86 chs.

S. 17° 07' E., 3.67 chs.

Intersect the section line
bet. secs. 21 and 28, at
the true point for the mean-
der cor. of secs. 21 and 28,
at 29.59 chs. on E. half bet.
secs. 21 and 28, herein-
before described.

Land, nearly level.
Soil, sandy.
Undergrowth, willows.

Thence with the meanders of the present left bank of the
Virgin River, downstream, through section 28.

S. 15° 10' E., 7.00 chs.

S. 44° 30' E., 2.30 chs.

S. 62° 40' E., 2.50 chs.

S. 34° 55' E., 7.50 chs.

S. 11° 10' E., 4.00 chs.

S. 1° 15' W., 8.00 chs.

S. 14° 00' W., 4.75 chs.

Meander of the Present Left Bank of the Virgin
River, Through Section 22

CHAINS

S. 32° 25' W., 8.00 chs.

S. 61° 30' W., 2.50 chs.

S. 47° 10' W., 13.00 chs.

N. 26° 30' W., 9.30 chs.

N. 14° 45' W., 13.50 chs.

N. 48° 06' W., 14.92 chs.

Intersect the original mean-
der cor. of secs. 21 and 28,
at 14.98 chs. on the W. half
mile bet. secs. 21 and 28,
hereinbefore described.

Land, level.

Soil, sandy.

Undergrowth, willows.

Thence with the meanders of the present left bank of the
Virgin River, downstream, through section 21.

N. 8° 17' E., 1.97 chs.

N. 60° 38' W., 5.30 chs.

N. 82° 09' W., 12.68 chs.

S. 71° 55' W., 8.52 chs.

Intersect the section line
bet. secs. 20 and 21, at
the point for the meander
cor. of secs. 20 and 21,
at 3.61 chs. on S. half bet.
secs. 20 and 21, hereinbefore
described.

Land, level.

Soil, sandy.

Undergrowth, willows.

Thence with the meanders of the present left bank of the
Virgin River, downstream, through section 20.

S. 66° 14' W., 8.96 chs.

Intersect the section line
bet. secs. 20 and 29, at the
true point for the cor. secs.
20 and 29 at 8.20 chs. on
E. half mile bet. secs. 20
and 29, hereinbefore describ-
ed.

Note:

Due to a narrowing of the river, about 10.00 chs.
downstream, the meanders are discontinued at this
point.

Land, level.

Soil, sandy.

Undergrowth, willows.

Adjusted Original Meander of the Left Bank of the
Virgin River, through a Portion of T. 43 S., R. 16 W.,
Salt Lake Meridian, Utah

CHAINS

Adjusted Original Meander of the Left Bank of the
Virgin River, through a Portion of T. 43 S., R. 16 W.,
Salt Lake Meridian, Utah

Note:

The adjusted original (1897) meanders of the left bank of the Virgin River were computed to determine the partition line between private and federally owned accretion lands, through a portion of sec. 22, only.

From the point for the original meander cor. of secs. 15 and 22, at 22.58 chs. on the E. half mile bet. secs. 15 and 22, which point falls in river, hereinbefore described.

Thence with the calculated adjusted original (1897) meanders for left bank of the Virgin River through section 22, across the waters of the river.

S. $31^{\circ} 24'$ W., 19.70 chs. At 11.51 chs. on this course, intersect the present meander line of the left bank of the Virgin River bears N. $69^{\circ} 35'$ E. Thence continue with the adjusted original meanders along the margin of accretion lands attached to non-federal original lots 1 and 6, sec. 22.

S. $13^{\circ} 54'$ W., 12.00 chs.

S. $57^{\circ} 55'$ W., 7.99 chs. At 5.18 chs. on this course, intersect the point for the special meander cor. of sec. 22, on the N-S center line of sec. 22, hereinbefore described. From this point, the dividing partition line between private and federally owned accretion lands bear N. $64^{\circ} 48'$ W., 5.49 chs. dist. to a special meander cor. on the present meander line of Virgin River hereinbefore described. Thence along the margin of accretion lands attaching to federally owned original lot 5, sec. 22.

S. $36^{\circ} 54'$ W., 2.82 chs. Intersect the present meander line of the left bank of the Virgin River, bears N. $14^{\circ} 37'$ W., and S. $14^{\circ} 37'$ E.

Note:

Since the remainder of the land bordering the Virgin River in section 22 is federally owned, the adjusted original meander line has no influence on the accretion lands and is discontinued at this point

Adjusted Original Meander of the Left Bank of the
Virgin River, through a Portion of T. 43 S., R. 16 W.,
St. George, Utah

CHAINS

General Description

Township 43 South, Range 16 West, is located about 2 miles south of St. George, Utah, and borders on the Utah-Arizona State Boundary. It is mostly broken desert land covered with sagebrush, blackbrush, shadscale, cacti creosote bush, with some willows and tamarack along the Virgin River, which flows southwesterly through the township. Timber, in the township consists of scattered cottonwood along the river. Soil is clay and gypsum with sand and gravel along the river bottom. The northwest portion of the township drains southeasterly and the southeast portion drains northwesterly into the Virgin River. The elevation varies from 2,400 ft. above sea level along the river to 3,470 ft. above sea level in the Bloomington Hills, located in section 3, 4 and 10. The Virgin River is the only water noted in the township.

The town of Bloomington is located in sections 13 and 14, and is expanding rapidly into sections 11 and 12. Access to the township is by Interstate Highway 15, presently under construction, and by several trail roads throughout the township.

The mean magnetic declination was read at several places in the township, and the average was found to be 15° 00' East.



CHAINS

Blank Page

[illegible]

CERTIFICATE OF SURVEY


(I) ~~XV2~~, Craig P. Sylvester

, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 15th day of October, 1970, (I) ~~XV2~~ have retraced the Utah-Arizona State Boundary from mile post 19.463 to mile post 24, and dependently resurveyed the west boundary and a portion of the subdivisional lines and surveyed a portion of the subdivision of section 22, and the meanders of a portion of the Virgin River in Township 43 South, Range 16 West

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~XV2~~ and under (my) ~~XV2~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

February 16, 1973
(Date)


(Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date JUN 26 1974

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the retracement of the Utah-Arizona State Boundary from mile post 19.463 to mile post 24, and the dependent resurvey of a portion of the subdivisional lines and the survey of a portion of the subdivision of section 22, and the meanders of a portion of the Virgin River in Township 43 South, Range 16 West, Salt Lake Meridian, Utah

executed by Craig P. Sylvester, Supervisory Cadastral Surveyor
having been critically examined and found correct, are hereby approved.

JUL 31 1975
(Date)


(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in~~
~~, is a true copy of the original field notes.~~

(Date)

(Chief, Division of Cadastral Survey) GPO 840-026